


### 18 CHANNEL CONFLICT MONITOR

#### PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



**NOTES:**

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that the Red Enable is active at all times during normal operation.
- Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.

### NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the signal plan.
- Program controller to start up in phase 2 Green No Walk and 6 Green No Walk.
- If this signal will be managed by an ATMS software, enable controller and detector logging for all detectors used at this location.

### EQUIPMENT INFORMATION

Controller.....2070LX  
 Cabinet.....332 w/ Aux  
 Software.....Q-Free MAXTIME  
 Cabinet Mount.....BASE  
 Output File Positions.....18 With Aux. Output File  
 Load Switches Used.....S2, S7, S8, S11  
 Phases Used.....2, 5, 6, 8  
 Overlap "1".....NOT USED  
 Overlap "2".....NOT USED  
 Overlap "3".....NOT USED  
 Overlap "4".....NOT USED

### SIGNAL HEAD HOOK-UP CHART


LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OL1	OL2	SPARE	OL3	OL4	SPARE
SIGNAL HEAD NO.	NU	21	22	NU	NU	NU	21	61	62	NU	NU	81,82	NU	NU	NU	NU	NU	NU
RED		128	128				*	134	134			107						
YELLOW		129	129						135	135		108						
GREEN		130								136		109						
RED ARROW																		
YELLOW ARROW							132											
GREEN ARROW			130				133	136										

NU = Not Used

\* Denotes install load resistor. See load resistor installation detail this sheet.

### INPUT FILE POSITION LAYOUT

(front view)




### SPECIAL DETECTOR NOTE

Install a video detection system for vehicle detection. Perform installation according to manufacturer's directions and NCDOT engineer-approved mounting locations to accomplish the detection schemes shown on the Signal Design Plans.

### LOAD RESISTOR INSTALLATION DETAIL

(install resistor as shown)

ACCEPTABLE VALUES	
Value (ohms)	Wattage
1.5K - 1.9K	25W (min)
2.0K - 3.0K	10W (min)



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 07-1948T2  
 DESIGNED: Jan 2023  
 SEALED: 3/10/2023  
 REVISED:

Temporary Design 2 (TMP Phase II)  
 Electrical Detail

Prepared for the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

US 158/ NC 14  
 at  
 US 29 Northbound Ramps

Division 7	Rockingham County	Reidsville
PLAN DATE: January 2023	REVIEWED BY: H M Surti	
PREPARED BY: A Ravipti	REVIEWED BY:	
REVISIONS	INIT.	DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL

DocuSigned by:  
 Hwang M. Surti 3/10/2023  
 SIG. INVENTORY NO. 07-1948T2

**AECOM**  
 NC Firm License No.: F-0342  
 5438 Wade Park Boulevard  
 Suite 200, Raleigh, NC 27607  
 Phone: 919-461-1100