COMPUTED BY: N. Moore DATE: 5/15/19 CHECKED BY :N. Roberson DATE: 5/15/19

## SUMMARY OF SUBSURFACE DRAINAGE

	LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
L		CONTIN	SD	200		
					TOTAL LF:	200

\*UD = Underdrain

\*BD = Blind Drain \*SD = Subsurface Drain

## (5-15-18)

## **STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS**

## SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Soil Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
-L-	34+75	42+25	ASU	12"	600	2200	3300		
(		Y	AST					50	
CONTINGENCY			ASU	12"	500				
			TOTAL	CY/TONS/SY:	1100	2200**	3300**	50	0

\*ASU(1/2) = Aggregate Subgrade (Type 1 or 2) \*AST = Aggregate Stabilization \*\*Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Soil Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.

PROJECT NO.	SHEET NO.		
U-5826	3G-1		