

SIGN NUMBER: 7B
TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	50.5	122	36	36
M1_4	270.6	122	36	36
AR_THRU	25.6	12	21	66
AR_THRU_RIGHT	152	12	56	66
AR_RIGHT_ONLY	350.7	12	36.2	45

NO. Z BARS: 6
LENGTH: 454.0

MAT'L: 0.125" (3.2MM) ALUMINUM

DESIGN BY: RRH CHECKED BY: BLW DATE: Apr 06, 2023
PROJECT ID: R-2707D DIV: 12

Spacing Factor is 1 unless specified otherwise

- USE NOTES
- Legend and border (except those that are colored black) shall be direct applied Grade A sheeting.
 - Background shall be Grade C reflective sheeting.
 - Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.
 - Yellow panel shall be Grade C sheeting with direct applied black non-reflective sheeting for legend. RADII: 1.88"

LETTER POSITIONS

Letter spacings are to start of next letter

B	Y	-	P	A	S	S	Series/Size Text Length					
30.7	11	13.1	6.1	10.7	13.6	11.4	9.7	355.7	E 2000	75.6		
	W		E	S	T				E 2000	48.8		
101.5	15.9	2.2	10.7	11	9	311.7			E 2000	48.8		
	W		E	S	T				E 2000	48.8		
321.6	15.9	2.2	10.7	11	9	91.6			E 2000	48.8		
	A	s	h	e	v	i	l	l	e	EM 2000	117.9	
31.6	18.2	15.5	15.5	13.8	17	9.6	9.6	8.2	10.6	312.5	EM 2000	117.9
	S	h	e	l	b	y				EM 2000	85.9	
277.6	17.9	15.5	15.5	9.6	13.8	13.6	98.5		E 2000	85.9		
	E	X	I	T					E 2000	39.2		
286.1	11.4	13.8	5	9	136.7				E 2000	39.2		
	O	N	L	Y					E 2000	47.9		
379.5	12.8	12.8	10	12.2	34.6				E 2000	47.9		

SIGN NUMBER: 9B
TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	50.9	150	36	36
M1_4	247	150	36	36
AR_THRU	23.9	12	21	66
AR_THRU_RIGHT	150.4	12	56	66
AR_RIGHT_ONLY	304.3	12	36.2	45

NO. Z BARS: 6
LENGTH: 406.0

MAT'L: 0.125" (3.2MM) ALUMINUM

DESIGN BY: RRH CHECKED BY: BLW DATE: Mar 10, 2023
PROJECT ID: R-2707D DIV: 12

Spacing Factor is 1 unless specified otherwise

- USE NOTES
- Legend and border (except those that are colored black) shall be direct applied Grade A sheeting.
 - Background shall be Grade C reflective sheeting.
 - Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.
 - Yellow panel shall be Grade C sheeting with direct applied black non-reflective sheeting for legend. RADII: 1.88"

LETTER POSITIONS

Letter spacings are to start of next letter

B	Y	-	P	A	S	S	Series/Size Text Length				
31.1	11	13.1	6.1	10.7	13.6	11.4	9.7	307.3	E 2000	75.6	
	E		A	S	T				E 2000	46.4	
101.9	11.3	1.5	13.6	11	9	265.7			E 2000	46.4	
	E		A	S	T				E 2000	46.4	
298	11.3	1.5	13.6	11	9	69.6			E 2000	46.4	
	G	a	s	t	o	n	i	a	EM 2000	109	
35.2	16.3	15.2	13.9	12	15.8	17	8.2	10.6	269.8	EM 2000	109
	S	h	e	l	b	y			EM 2000	85.9	
252.8	17.9	15.5	15.5	9.6	13.8	13.6	75.3		E 2000	85.9	
	1/2		M	I	L	E			E 2000	70.1	
260.7	22	15	12	4.4	9.2	7.5	83.2		E 2000	70.1	
	E	X	I	T					E 2000	39.2	
239.7	11.4	13.8	5	9	135.1				E 2000	39.2	
	O	N	L	Y					E 2000	47.9	
333.1	12.8	12.8	10	12.2	33				E 2000	47.9	

SIGN NUMBER: 10B
TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White/Black

SYMBOL	X	Y	WID	HT
M1_4	50.9	122	36	36
M1_4	247	122	36	36
AR_THRU	23.9	12	21	66
AR_THRU_RIGHT	150.4	12	56	66
AR_RIGHT_ONLY	304.3	12	36.2	45

NO. Z BARS: 6
LENGTH: 406.0

MAT'L: 0.125" (3.2MM) ALUMINUM

DESIGN BY: RRH CHECKED BY: BLW DATE: Mar 10, 2023
PROJECT ID: R-2707D DIV: 12

Spacing Factor is 1 unless specified otherwise

- USE NOTES
- Legend and border (except those that are colored black) shall be direct applied Grade A sheeting.
 - Background shall be Grade C reflective sheeting.
 - Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.
 - Yellow panel shall be Grade C sheeting with direct applied black non-reflective sheeting for legend. RADII: 1.88"

LETTER POSITIONS

Letter spacings are to start of next letter

B	Y	-	P	A	S	S	Series/Size Text Length				
31.1	11	13.1	6.1	10.7	13.6	11.4	9.7	307.3	E 2000	75.6	
	E		A	S	T				E 2000	46.4	
101.9	11.3	1.5	13.6	11	9	265.7			E 2000	46.4	
	E		A	S	T				E 2000	46.4	
298	11.3	1.5	13.6	11	9	69.6			E 2000	46.4	
	G	a	s	t	o	n	i	a	EM 2000	109	
35.2	16.3	15.2	13.9	12	15.8	17	8.2	10.6	269.8	EM 2000	109
	S	h	e	l	b	y			EM 2000	85.9	
252.8	17.9	15.5	15.5	9.6	13.8	13.6	75.3		E 2000	85.9	
	E	X	I	T					E 2000	39.2	
239.7	11.4	13.8	5	9	135.1				E 2000	39.2	
	O	N	L	Y					E 2000	47.9	
333.1	12.8	12.8	10	12.2	33				E 2000	47.9	

TIP NO. R-2707D SHEET NO. SIGN-4B

APPROVED: *Betsy L. Watson*

DATE: 4/27/2023

SEAL

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$DGN\$\$\$\$\$
\$\$\$\$\$USERNAME\$\$\$\$\$

OVERHEAD SIGNS