DocuSign Envelope ID: 2CBE69AC-BA62-466A-BFD4-8D07A1A379CD

TIP NO.	SHEET NO.
R-2707D	SIGN-4E

APPROVED: Betsy L. Watson (DocuSigned by: 35E67BB34F8743F...)

DATE: 4/27/2023

SEAL

NORTH CAROLINA PROFESSIONAL SEAL 29449 ENGINEER BETSY L. WATSON

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Stantec

SIGN NUMBER: 101
TYPE: A
QUANTITY: 1

SIGN WIDTH: 120″
HEIGHT: 72″
TOTAL AREA: 60.0 Sq.Ft.

BORDER TYPE: FLUSH
RADII: 9″
WIDTH: 2″
RECESS: 0″

NO. Z BARS: 2
LENGTH: 112.0

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT

MAT'L: 0.125″ (3.2MM) ALUMINUM

DESIGN BY: RRH
PROJECT ID: R-2707D
CHECKED BY: BLW
DIV: 12
DATE: Feb 06, 2018

Spacing Factor is 1 unless specified otherwise

USE NOTES

1. Legend and border (except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS

Letter spacings are to start of next letter

																						Series/Size Text Length
	W	a	c	o																		EM 2000
35.1	16.1	12.9	11.7	9	35.1																	49.7
	E	X	I	T		2	0	3														E 2000
16.2	8.9	10.7	3.5	7.5	15	14.7	15.1	12.2	16.2													87.6

SIGN NUMBER: 102A,104A
TYPE: B
QUANTITY: 2

SIGN WIDTH: 132″
HEIGHT: 30″
TOTAL AREA: 27.5 Sq.Ft.

BORDER TYPE: FLUSH
RADII: 3″
WIDTH: 2″
RECESS: 0″

NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT

MAT'L: 0.125″ (3.2MM) ALUMINUM

DESIGN BY: RRH
PROJECT ID: R-2707D
CHECKED BY: BLW
DIV: 12
DATE: Feb 06, 2018

Spacing Factor is 1 unless specified otherwise

USE NOTES

1. Legend and border (except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS

Letter spacings are to start of next letter

																						Series/Size Text Length
	E	X	I	T																		E 2000
21.7	9.2	11.1	3.8	7.5	78.7																	31.6
	2	0	3																			E 2000
68.3	14.7	15.1	12.2	21.7																		42

SIGN NUMBER: 102B
TYPE: A
QUANTITY: 1

SIGN WIDTH: 216″
HEIGHT: 132″
TOTAL AREA: 198.0 Sq.Ft.

BORDER TYPE: FLUSH
RADII: 12″
WIDTH: 2″
RECESS: 0″

NO. Z BARS: 3
LENGTH: 208.0

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
NC243A	56	64.8	36	36
NC243A	124	64.8	36	36

MAT'L: 0.125″ (3.2MM) ALUMINUM

DESIGN BY: RRH
PROJECT ID: R-2707D
CHECKED BY: BLW
DIV: 12
DATE: Mar 28, 2023

Spacing Factor is 1 unless specified otherwise

USE NOTES

1. Legend and border (except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.
3. Shields; A, B, and C type arrows shall be on 0.032″ (0.8mm) aluminum and demountable.

LETTER POSITIONS

Letter spacings are to start of next letter

																						Series/Size Text Length
	T	O																				E 2000
131.6	10.7	10.1	63.6																			20.8
	C	h	e	r	r	y	v	i	l	l	e		R	d								EM 2000
15.9	17.4	15.5	15.5	11.8	10.1	16.5	17	9.6	9.6	8.2	10.6	16	15.8	10.6	15.9							184.2
	3/4		M	I	L	E																E 2000
71.5	25	15	12	4.4	9.2	7.5	71.5															73.1

SIGN NUMBER: 103A,105A
TYPE: B
QUANTITY: 2

SIGN WIDTH: 132″
HEIGHT: 30″
TOTAL AREA: 27.5 Sq.Ft.

BORDER TYPE: FLUSH
RADII: 3″
WIDTH: 2″
RECESS: 0″

NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT

MAT'L: 0.125″ (3.2MM) ALUMINUM

DESIGN BY: RRH
PROJECT ID: R-2707D
CHECKED BY: BLW
DIV: 12
DATE: Feb 05, 2018

Spacing Factor is 1 unless specified otherwise

USE NOTES

1. Legend and border (except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS

Letter spacings are to start of next letter

																						Series/Size Text Length
	E	X	I	T																		E 2000
21.7	9.2	11.1	3.8	7.5	78.7																	31.6
	2	0	8																			E 2000
68.3	14.7	15.2	12.2	21.7																		42

GROUND MOUNTED TYPE 'A' & 'B' SIGNS

$$$$SYSTIME$$$$
$$$$