DocuSign Envelope ID: 1F086052-4F8F-4222-B2F8-F88F2A50EDB2

BEL.AM-NEW

COMPUTED BY: DJS DATE: 04/04/2023

CHECKED BY: BNE DATE: 04/04/2023

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

PROJECT NO.	SHEET NO.
R-2707E	3D-5

Note: Invert Elevations indicated are for Bid Purposes only and shall not be used for project construction stakeout.
See "Standard Specifications For Roads and Structures, Section 300-5".

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 48 INCHES & UNDER)

| LINE & STATION | OFFSET | | STRUCTURE NUMBER FROM | STRUCTURE NUMBER TO | TOP ELEVATION FT. | INVERT ELEVATION FT. | INVERT ELEVATION FT. | MINIMUM REQUIRED SLOPE % | Side Drain Pipe (RCP, CSP, CAAP, HDPE, PVC, or PP PIPE) SIZE 15 | 18 | 24 | 30 | 36 | 42 | Side Drain Pipe THICKNESS OR GAUGE DO NOT USE RCP | DO NOT USE CSP | DO NOT USE HDPE | DO NOT USE PVC | DO NOT USE PP PIPE | C. S. PIPE SIZE 15 | 18 | 24 | 36 | C. S. PIPE THICKNESS OR GAUGE .064 | .064 | .064 | .079 | R. C. PIPE CLASS III SIZE 15 | 18 | 24 | 30 | 36 | 42 | 48 | R. C. PIPE CLASS IV SIZE 15 | 18 | 24 | 30 | 36 | 42 | 48 | R. C. PIPE CLASS V SIZE 30 | 48 | 42" R.C. PIPE CULVERTS, CONTRACTOR DESIGN | 48" R.C. PIPE CULVERTS, CONTRACTOR DESIGN | 16" WELDED STEEL PIPE 0.281" THICK, GRADE B (50% IN SOIL, 50% NOT IN SOIL) | 18" WELDED STEEL PIPE 0.312" THICK, GRADE B (50% IN SOIL, 50% NOT IN SOIL) | 30" WELDED STEEL PIPE 0.500" THICK, GRADE B (50% IN SOIL, 50% NOT IN SOIL) | 42" WELDED STEEL PIPE 0.625" THICK, GRADE B (50% IN SOIL, 50% NOT IN SOIL) | 48" WELDED STEEL PIPE 0.688" THICK, GRADE B (50% IN SOIL, 50% NOT IN SOIL) | ENDWALLS STD. 838.01 OR STD. 838.11 (UNLESS NOTED OTHERWISE) CY | QUANTITIES FOR DRAINAGE STRUCTURES NOTE: TOTAL LIN. FT. FOR PAY QUANTITY SHALL BE A + (1.3 X B) A 0' THRU 5' EACH | A 5' THRU 10' LIN. FT. | A 10' AND ABOVE LIN. FT. | B | C.B. STD. 840.01 OR STD. 840.02 | FRAME, GRATES, AND HOOD STD. 840.03 GRATE TYPE E | F | G | D.I. STD. 840.14 OR STD. 840.15 | D.I. FRAME AND GRATES STD. 840.16 | G.D.I. TYPE "A" STD. 840.17 OR STD. 840.26 | G.D.I. TYPE "B" STD. 840.18 OR STD. 840.27 | G.D.I. TYPE "D" STD. 840.19 OR STD. 840.28 | G.D.I. (W.S. FLAT) FRAME WITH GRATE STD. 840.20 | G.D.I. (W.S. FLAT) FRAME W/ 2 GRATES STD. 840.20 | G.D.I. (W.S. SAG) FRAME W/ GRATE STD. 840.22 | G.D.I. (W.S. SAG) FRAME W/ 2 GRATES STD. 840.22 | G.D.I. (N.S. SAG) FRAME W/ 2 GRATES STD. 840.24 | G.D.I. (N.S. FLAT) FRAME W/ 2 GRATES STD. 840.29 | J.B. STD. 840.31 OR STD. 840.32 | T.B.J.B. STD. 840.34 | T.B.D.I. STD. 840.35 | SPRING BOX STD. 840.41 | M.H. FRAME AND COVER STD. 840.54 | CONVERT EXISTING D.I. TO J.B. w/ MH | ADJUST D.I. | 15" SIDE DRAIN PIPE ELBOW | 18" SIDE DRAIN PIPE ELBOW | 24" SIDE DRAIN PIPE ELBOW | 30" SIDE DRAIN PIPE ELBOW | 36" SIDE DRAIN PIPE ELBOW | 18" SLUICE GATE (25" SIZE SLUICE GATE) | 24" SLUICE GATE (32" SIZE SLUICE GATE) | 30" SLUICE GATE (38.75" SIZE SLUICE GATE) | BERM DITCH OUTLET STD. 850.10 | BERM DITCH OUTLET STD. 850.11 | ENERGY DISSIPATION BASIN | FLOWABLE FILL CY | CONCRETE COLLARS CL. "B" STD. 840.72 CY | CONCRETE AND BRICK PIPE PLUG STD. 840.71 CY | PIPE REMOVAL LIN. FT. | REMARKS |
|---|---|---