COMPUTED BY: DMB DATE: 3/30/23 CHECKED BY: REK DATE: 3/30/23

## SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
	CONTIN	SD	400		
				TOTAL LF:	400

\*UD = Underdrain \*BD = Blind Drain

\*SD = Subsurface Drain

## (2-3-23) **STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS**

## SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Subgrade Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
(	CONTINGENCY		ASU(1)	12	100	200	300		
			TOTAL	CY/TONS/SY:	100	200**	300**	0	0

\*ASU(1/2) = Aggregate Subgrade (Type 1 or 2) \*AST = Aggregate Stabilization

\*\*Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Subgrade Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.

PROJECT NO.	SHEET NO.		
U-5775	3G-1		