

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5808	1	17

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1919 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

ROADWAY
SUBSURFACE INVESTIGATION

COUNTY UNION
PROJECT DESCRIPTION CHESTNUT LANE CONNECTOR
(SR 1362) FROM MATTHEWS INDIAN TRAIL ROAD
(SR 1367) TO GRIBBLE ROAD (SR 1368)

INVENTORY

CONTENTS

LINE	STATION	PLAN	PROFILE
-L1-	41+00 - 43+84	4	8
-L2-	45+30 - 72+00	4-7	8-9
-Y1A-	10+25 - 11+96	4	10
-Y1B-	10+69 - 13+00	4	10
-Y2-	10+40 - 17+40	6	10

CROSS SECTIONS

LINE	STATION	SHEETS
-L1-	41+00 - 43+84	11
-L2-	53+81 - 56+19	12-13
-L2-	59+00	14
-L2-	63+00 - 64+00	15
-Y1B-	10+69 - 13+00	16-17

REFERENCE: U-5808

PROJECT: 44381.1.1

PERSONNEL

P. ZHANG

C. MEATYARD

C. TREMBLAY

INVESTIGATED BY WOOD E&S, INC.

DRAWN BY P. ZHANG

CHECKED BY S. JOHNSON

SUBMITTED BY S. JOHNSON

DATE SEPTEMBER, 2018

NC Engineering F-1253 NC Geology C-247



DocuSigned by:

Shane Johnson 9/25/2018 6:44:05

973FECAA5F84423

SIGNATURE

DATE

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																																									
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																									
SOIL LEGEND AND AASHTO CLASSIFICATION										MINERALOGICAL COMPOSITION										WEATHERING																																																																																																																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-5</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="5"></th> </tr> <tr> <th>SYMBOL</th> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5">[Pattern]</td> <td colspan="5"></td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 30 15</td> <td>25 10 5</td> <td>35 25 10</td> <td>40 30 15</td> <td>45 35 20</td> <td>35 25 10</td> <td>30 20 10</td> <td>25 15 10</td> <td>20 10 5</td> <td>30 20 10</td> <td>25 15 10</td> <td>20 10 5</td> <td>15 10 5</td> <td>10 5 2.5</td> <td colspan="5"></td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td colspan="5">40 30 15</td> <td colspan="5">40 30 15</td> <td colspan="5">40 30 15</td> <td colspan="5"></td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="5">0</td> <td colspan="5">0</td> <td colspan="5">0</td> <td colspan="5"></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="5">FINE SAND</td> <td colspan="5">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="5">SILTY SOILS</td> <td colspan="5">CLAYEY SOILS</td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="5">EXCELLENT TO GOOD</td> <td colspan="5">FAIR TO POOR</td> <td colspan="5">FAIR TO POOR</td> <td colspan="5">POOR UNSUITABLE</td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-5	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7						SYMBOL	[Pattern]					[Pattern]					[Pattern]										% PASSING #10 #40 #200	50 30 15	25 10 5	35 25 10	40 30 15	45 35 20	35 25 10	30 20 10	25 15 10	20 10 5	30 20 10	25 15 10	20 10 5	15 10 5	10 5 2.5						MATERIAL PASSING #40 LL PI	40 30 15					40 30 15					40 30 15										GROUP INDEX	0					0					0										USUAL TYPES OF MAJOR MATERIALS	FINE SAND					SILTY OR CLAYEY GRAVEL AND SAND					SILTY SOILS					CLAYEY SOILS					GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR					POOR UNSUITABLE					<p>MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p>WEATHERING FRESH VERY SLIGHT (V SL.) SLIGHT (SL.) MODERATE (MOD.) MODERATELY SEVERE (MOD. SEV.) SEVERE (SEV.) VERY SEVERE (V SEV.) COMPLETE</p>																			
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																																												
GROUP CLASS.	A-1	A-3	A-2	A-2-5	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																										
SYMBOL	[Pattern]					[Pattern]					[Pattern]																																																																																																																																																																																												
% PASSING #10 #40 #200	50 30 15	25 10 5	35 25 10	40 30 15	45 35 20	35 25 10	30 20 10	25 15 10	20 10 5	30 20 10	25 15 10	20 10 5	15 10 5	10 5 2.5																																																																																																																																																																																									
MATERIAL PASSING #40 LL PI	40 30 15					40 30 15					40 30 15																																																																																																																																																																																												
GROUP INDEX	0					0					0																																																																																																																																																																																												
USUAL TYPES OF MAJOR MATERIALS	FINE SAND					SILTY OR CLAYEY GRAVEL AND SAND					SILTY SOILS					CLAYEY SOILS																																																																																																																																																																																							
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR					POOR UNSUITABLE																																																																																																																																																																																							
CONSISTENCY OR DENSENESS										GROUND WATER										MISCELLANEOUS SYMBOLS										RECOMMENDATION SYMBOLS																																																																																																																																																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p>GROUND WATER </p>										<p>MISCELLANEOUS SYMBOLS ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY DIP & DIP DIRECTION OF ROCK STRUCTURES TEST BORING AUGER BORING CORE BORING MONITORING WELL PIEZOMETER INSTALLATION SLOPE INDICATOR INSTALLATION CONE PENETROMETER TEST SOUNDING ROD TEST BORING WITH CORE SPT N-VALUE</p>										<p>RECOMMENDATION SYMBOLS UNDERCUT SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</p>																																																																																																																																																													
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																																				
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																																				
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																																				
TEXTURE OR GRAIN SIZE										ABBREVIATIONS										FRACTURE SPACING										BEDDING																																																																																																																																																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CS.E. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS.E. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								<p>ABBREVIATIONS AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - COARSE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY VST - VANE SHEAR TEST WEA. - WEATHERED % - UNIT WEIGHT %g - DRY UNIT WEIGHT SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO</p>										<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>										TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET	<p>INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. FRIABLE MODERATELY INDURATED INDURATED EXTREMELY INDURATED RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																																																																								
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																	
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS.E. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																	
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																																				
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																				
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																				
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																				
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																				
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																				
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																				
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT																																																																																																																																																																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT PL - PLASTIC LIMIT</td> <td>- SATURATED - (SAT.) - WET - (W)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT</td> <td>- MOIST - (M) - DRY - (D)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.) - WET - (W)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M) - DRY - (D)	SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>EQUIPMENT USED ON SUBJECT PROJECT DRILL UNITS: <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST <input checked="" type="checkbox"/> CME-550X <input type="checkbox"/></p> <p>ADVANCING TOOLS: <input type="checkbox"/> CLAY BITS <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input checked="" type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG-CARBIDE INSERTS <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB. <input checked="" type="checkbox"/> CORE BIT <input type="checkbox"/></p> <p>HAMMER TYPE: <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input checked="" type="checkbox"/> -N Q HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/></p>																																																																																																																																																																																				
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																					
LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.) - WET - (W)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																					
OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M) - DRY - (D)	SOLID; AT OR NEAR OPTIMUM MOISTURE REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																					
PLASTICITY																																																																																																																																																																																																							
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0-5 6-15 16-25 26 OR MORE</td> <td>VERY LOW SLIGHT MEDIUM HIGH</td> </tr> </table>										NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH					0-5 6-15 16-25 26 OR MORE	VERY LOW SLIGHT MEDIUM HIGH																																																																																																																																																																																		
NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																		
				0-5 6-15 16-25 26 OR MORE	VERY LOW SLIGHT MEDIUM HIGH																																																																																																																																																																																																		
COLOR																																																																																																																																																																																																							
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>																																																																																																																																																																																																							
																				<p>BENCH MARK: BORING ELEVATIONS OBTAINED FROM TIN FILE PROVIDED BY NCDOT (U5808_LS_TIN.tin). ELEVATION: N/A FEET</p>										<p>NOTES:</p>																																																																																																																																																																									

12-SEP-2018 11:24 P:\Transportation\Projects\Road\NC-001\2018\646888045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO\CADD\CADD_GEO\RDWY\CADD_GEO\TECH\Plan\U5808_Plan.dgn
 09/28/2018
 \$\$\$\$\$\$USERNAME\$\$\$\$\$

CONTRACT: TIP PROJECT: U-5808




STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

UNION COUNTY

LOCATION: CHESTNUT LANE CONNECTOR (SR 1362) FROM MATTHEWS INDIAN TRAIL ROAD (SR 1367) TO GRIBBLE ROAD (SR 1368)
TYPE OF WORK: GRADING, DRAINAGE, PAVING, AND STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5808	3	17
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
44381.1.1	N/A	PE	

25% PLANS



CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD ____.
THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF THE TOWN OF INDIAN TRAIL.

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

<p>GRAPHIC SCALES</p> <p>50 25 0 50 100 PLANS</p> <p>50 25 0 50 100 PROFILE (HORIZONTAL)</p> <p>10 5 0 10 20 PROFILE (VERTICAL)</p>	<p>DESIGN DATA</p> <p>ADT 2021 = 21,650 ADT 2041 = 24,650 K = 7 % D = 60 % T = 4 % * V = 40 MPH * TTST = 3% DUAL = 1% FUNC CLASS = MINOR ARTERIAL REGIONAL TIER</p>	<p>PROJECT LENGTH</p> <p>LENGTH ROADWAY TIP PROJECT U-5808 = 0.544 MILES LENGTH STRUCTURE TIP PROJECT U-5808 = 0.043 MILES TOTAL LENGTH TIP PROJECT U-5808 = 0.587 MILES</p>	<p>Prepared for NCDOT Division 10 In the Office of: Mead&Hunt 133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 meadhunt.com NC License No. F-1235</p>	<p>HYDRAULICS ENGINEER</p> <p>SIGNATURE: _____ P.E.</p> <p>ROADWAY DESIGN ENGINEER</p> <p>SIGNATURE: _____ P.E.</p>	

September 25, 2018

WBS Number: 44381.1.1
 TIP Number: U-5808
 COUNTY: Union
 DESCRIPTION: Chestnut Lane Connector (SR 1362) from Matthews Indian Trail Road (SR 1367) to Gribble Road (SR 1368)
 WOOD E&IS Number: 6468188045
 SUBJECT: Geotechnical Inventory Report

Project Description

The project area lies on the north side of the town of Indian Trail, NC between Highway 74 and SR1009. This project consists of approximately 2,000 feet of new location roadway that will extend from Gribble Road to Matthews Indian Trail Road. A potential roundabout is planned at the intersection of the new alignment and Gribble Road. Roadway widening is planned on Gribble Road and Matthews Indian Trail Road near the intersection with the new alignment. A grade separation bridge is planned to carry the new alignment over the existing CSX Railroad.

The geotechnical field investigation was conducted in August, 2018. A CME 550X drill rig mounted on a rubber tracked all-terrain carrier and equipped with an automatic hammer was used to advance borings for the subsurface exploration. Hollow stem auger drilling procedures were used to advance borings to the required depths. Standard Penetration Tests were performed at approximately 2.5-foot to 5.0-foot intervals to termination in selected borings. Representative soil samples were collected for visual classification in the field and selected samples were submitted for laboratory analysis.

The following alignments were explored. Subsurface profiles and/or cross sections of these alignments are included in this report.

<u>Alignment</u>	<u>Station (±)</u>
-L1-	41+00 to 43+84
-L2-	45+30 to 72+00
-Y1A-	10+25 to 11+96
-Y1B-	10+69 to 13+00
-Y2-	10+40 to 17+40

Areas of Special Geotechnical Interest

- 1) **Loose/Soft Soils:** The following sections contain very soft or very loose, compressible soils (n-value < 4) which have the potential to cause embankment/subgrade and/or slope stability problems during construction.

<u>Line</u>	<u>Stations (±)</u>	<u>Offsets (ft.)</u>
-L2-	63+30 – 63+80	LT & RT

- 2) **Fine Grained Soils:** The following sections contain fine grained/cohesive soils which have the potential to cause embankment/subgrade and/or slope stability problems during construction.

<u>Line</u>	<u>Stations (±)</u>	<u>Offsets (ft.)</u>
-L1-	41+00 – 43+84	LT & RT
-Y1B-	10+69 – 13+00	LT & RT

- 3) **Groundwater:** Groundwater was only encountered at two boring locations at depths greater than 20 feet below existing grades.

- 4) **Water wells:** Two existing residential water supply wells were found within or in close proximity to the proposed right of way at the following locations:

<u>Line</u>	<u>Station (±)</u>	<u>Offset (ft.)</u>
-L2-	44+80	15 RT
-Y1B-	15+40	108 RT

- 5) **Ponds:** Several ponds occur on or within close proximity to the right of way on this project at the following locations:

<u>Line</u>	<u>Station (±)</u>	<u>Offset (ft.)</u>
-L2-	60+40 – 63+50	480 RT to 590 RT
-L2-	62+45 – 62+55	200 RT to 215 RT
-L2-	62+30 – 62+60	665 RT to 700 RT
-L2-	83+04 – 83+35	40 RT to 70 RT
-L2-	84+27 – 84+37	49 RT to 62 RT

Physiography and Geology

The project is located in the Piedmont Province. Land use along the project corridor consists of residential, agricultural, commercial businesses and woods. Geologically, the project is located within the Charlotte Belt. metavolcanic rock (CZv) was encountered at the project site. Fourmile Creek and its tributaries and a few ditches drain the project towards south and southeast in general.

Soil Properties

Soils encountered at the project site include roadway embankment, agricultural till, alluvial, residual, weathered metavolcanic rock and crystalline metavolcanic rock.

Roadway Embankment soils are present along existing SR 1368 and SR1362.

Alluvial deposits are located within the floodplains of Fourmile Creek's tributaries, ditches and wetland areas that traverse the project. These soils are primarily brown and gray, very soft to soft, silty clay (A-7).

Residual soils were encountered throughout the project. These soils consist primarily of gray, tan and brown, stiff to hard silt and clay (A-4, A-7) with Liquid Limit ranging from 42 to 59 and Plasticity Indices ranging from 21 to 28.

Rock Properties

Weathered rock was encountered during the roadway investigation at elevations ranging from approximately 697 to 670 feet. It originates from the underlying metavolcanic rock.

Crystalline rock was encountered during the roadway investigation at elevations ranging from approximately 687 to 661 feet, and consists of metavolcanic rock.

Ground Water


Groundwater was encountered in two borings and ranges in elevation from approximately 671 to 675 feet. Groundwater may fluctuate with seasonal precipitation.

Prepared By,

DocuSigned by:
Pu Zhang 9/25/2018 6:46:41 AM PDT
B37087AE5CC74C5...

Pu Zhang, P.E.
Geotechnical Engineer

PROJECT REFERENCE NO. U-5808	SHEET NO. 4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Mead&Hunt	
133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 mead@hunt.com NC License No. F-1235	



BEGIN TIP PROJECT U-5808
-LI- POT STA. 41+00.00

NOTE: TIE TO TOWN OF INDIAN TRAIL PROJECT


OFFSET LEFT ROUNDABOUT
-LI- POT Sta. 44+53.06 (O/S 25')
-L2- POT Sta. 44+53.44 (O/S 25')
-YIA- POT Sta. 12+76.94 (O/S 25')
-YIB- POT Sta. 10+00.00 (O/S 25')

FOR -LI- PROFILE, SEE SHEET 8
FOR -L2- PROFILE, SEE SHEET 8
FOR -YIA- PROFILE, SEE SHEET 10
FOR -YIB- PROFILE, SEE SHEET 10

REVISIONS
 12-SEP-2018 11:24
 P:\Transportation\Projects\Roadway\DOT\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_RDWY\CADD_GEO\TECH\Plan\Prof\U5808_GEO_psh_04.dgn
 \$\$\$USERNAME\$\$\$

8/17/99

PROJECT REFERENCE NO. U-5808	SHEET NO. 5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Mead&Hunt	
133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 mead@meadandhunt.com NC License No. F-1235	



REVISIONS


12-SEP-2018 11:24
 P:\Transportation\Projects\Road\NC\DOT\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_RDWY\CADD_GEO\TECH\Plan\U5808_CEO_psh_05.dgn
 \$\$\$USERNAME\$\$\$

FOR -L2- PROFILE, SEE SHEET 8

BRIDGE APPROACH SLAB

FOR STRUCTURE PLANS, SEE SHEET S-1 THRU S-??

PROJECT REFERENCE NO. U-5808		SHEET NO. 6	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
Mead&Hunt		133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 meadhunt.com NC License No. F-1235	



REVISIONS

12-SEP-2018 11:24
 P:\Transportation\Projects\Road\Connector\6.0 Deliverables\U5808_GEO_RDWY\CADD_GEO\TECH\Plan\U5808_GEO_psh_06.dgn
 \$\$\$USERNAME\$\$\$

★ PROPOSED SIGNAL
 FOR -Y2- PROFILE, SEE SHEET 10
 FOR -L2- PROFILE, SEE SHEETS 8 & 9

8/17/99

12-SEP-2018 11:24 P:\Transportation\Projects\Road\NC\DOT\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_RDWY\CADD_GEO\TECH\Plan\Prof\U5808_GEO_psh_07.dgn

REVISIONS


**THIS SHEET IS INTENTIONALLY BLANK
IT IS INTENDED FOR FUTURE USE**

-L2- CURVE DATA

PI Sta 75+55.62	PI Sta 83+57.76
$\Delta = 27^\circ 45' 51.2" (LT)$	$\Delta = 19^\circ 54' 20.5" (RT)$
$D = 9^\circ 45' 19.9"$	$D = 9^\circ 32' 45.8"$
$L = 284.60'$	$L = 208.52'$
$T = 145.5'$	$T = 105.32'$
$R = 587.32'$	$R = 600.20'$



PROJECT REFERENCE NO. U-5808	SHEET NO. 7
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Mead&Hunt	
133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 mead@meadandhunt.com NC License No. F-1235	





MATCHLINE -L- STA. 76+00 SEE SHEET 6

FOR -L2- PROFILE, SEE SHEET 9

5/28/99

PROJECT REFERENCE NO. U-5808	SHEET NO. 8
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 meadhunt.com NC License No. F-1235	

SAMPLE NO.	STATION	OFFSET	LINE	DEPTH INTERVAL	AASHTO CLASS	L.L.	P.I.	% PASSING SIEVES (SOIL MORTAR)				% PASSING SIEVES			% MOISTURE	% ORGANIC
								C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-31	42+00	68' LT	-L1-	1.0-2.5	A-7-5(30)	59	23	0.3	1.0	64.6	34.1	100	99.9	99.2	19.5	-
SS-32	42+00	68' LT	-L1-	3.5-5.0	A-7-6(24)	43	22	1.8	1.1	63.4	33.7	100	98.4	97.5	8.3	-
SS-36	44+00	26' LT	-L1-	1.0-2.5	A-7-6(26)	46	24	2.0	1.4	47.7	48.8	99.7	98.1	96.8	13.7	-



12-SEP-2018 11:24 AM
 P:\Projects\Road\NC-DOT\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO-RDWY\CADD_GEO\TECH\Plan\Prof_U5808_GEO.pf1.08.dgn
 \$\$\$\$USERNAME\$\$\$\$


5/28/99

PROJECT REFERENCE NO. <i>U-5808</i>	SHEET NO. 9
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 meadhunt.com NC License No. F-1235	

-L2-

SAMPLE NO.	STATION	OFFSET	LINE	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% PASSING SIEVES (SOIL MORTAR)				% PASSING SIEVES			% MOISTURE	% ORGANIC
								C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-63	68+00	24' LT	-L2-	1.0-2.5	A-7-6(22)	46	22	6.8	3.3	57.4	32.5	100	95.4	90.6	17.4	-
SS-67	71+00	31' LT	-L2-	1.0-2.5	A-7-6(21)	45	24	4.5	8.2	59.6	27.7	100	97.4	88.5	22.1	-

- (A) RESIDUAL, STIFF TO HARD, DRY TO MOIST, GRAY AND BROWN, SILTY CLAY (A-7-6)
- (A) RESIDUAL, HARD, DRY, BROWN, CLAYEY SILT (A-4), SAPROLITIC
- (B) WEATHERED ROCK, BROWN AND TAN, METAVOLCANIC



-L2-

INTENTIONALLY BLANK - FOR FUTURE USE

12-SEP-2018 11:24 AM \\projects\road\nc-dot\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_RDWY\CADD_GEO\TECH\Plan\Prof_U5808_GEO.pfl.09.dgn

5/28/99

PROJECT REFERENCE NO. U-5808	SHEET NO. 10
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
<small>133 Fayetteville Street, Suite 210 Raleigh, North Carolina 27601 919-714-8670 meadhunt.com NC License No. F-1235</small>	

-Y1A-



-Y1B-

SAMPLE NO.	STATION	OFFSET	LINE	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.
SS-23	11+45	13' LT	-Y1A-	1.0-2.5	A-7-6(26)	45	24
% PASSING SIEVES (SOIL MORTAR)							
C. SAND	F. SAND	SILT	CLAY	10	40	200	MOISTURE
1.0	1.1	54.9	43.0	100	99.3	98.3	18.4

SAMPLE NO.	STATION	OFFSET	LINE	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% PASSING SIEVES (SOIL MORTAR)				% PASSING SIEVES			%	%
SS-27	10+98	49' LT	-Y1B-	1.0-2.5	A-7-6(28)	46	28	C. SAND	F. SAND	SILT	CLAY	10	40	200	MOISTURE	ORGANIC
3.7	1.7	44.2	50.4	99.3	96.5	94.5	14.5	-								

- (A) RESIDUAL: VERY STIFF TO HARD, MOIST TO DRY, GRAY AND BROWN, SILTY CLAY (A-7-6)
- (A) RESIDUAL: HARD, DRY, BROWN, CLAYEY SILT (A-4), SAPROLITIC
- (B) WEATHERED ROCK: BROWN, METAVOLCANIC

- (A) RESIDUAL: STIFF TO HARD, DRY, GRAY AND BROWN, SILTY CLAY (A-7-6)
- (B) WEATHERED ROCK: BROWN, METAVOLCANIC





NOTE: INFERRED STRATIGRAPHY IS DRAWN AT THE PROFILE CENTERLINE WITH THE BORINGS PROJECTED ONTO THE PROFILE. FOR -Y1A- & -Y1B- PLAN, SEE SHEET 4

-Y2-


SAMPLE NO.	STATION	OFFSET	LINE	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% PASSING SIEVES (SOIL MORTAR)				% PASSING SIEVES			%	%
SS-56	11+56	26' LT	-Y2-	1.0-2.5	A-7-6(21)	44	21	C. SAND	F. SAND	SILT	CLAY	10	40	200	MOISTURE	ORGANIC
4.6	3.8	55.7	35.9	100	96.5	92.7	8.9	-								
SS-71	16+00	19' RT	-Y2-	1.0-2.5	A-7-6(19)	42	21	10.5	2.3	52.8	34.3	99.0	90.4	87.1	6.6	-

- (A) RESIDUAL: VERY STIFF TO HARD, DRY TO MOIST, GRAY AND BROWN, SILTY CLAY (A-7-6)
- (A) RESIDUAL: HARD, MOIST, GRAY AND BROWN, CLAYEY SILT (A-4), SAPROLITIC
- (B) WEATHERED ROCK: GRAY AND BROWN, METAVOLCANIC




NOTE: INFERRED STRATIGRAPHY IS DRAWN AT THE PROFILE CENTERLINE WITH THE BORINGS PROJECTED ONTO THE PROFILE. FOR -Y2- PLAN, SEE SHEET 6

12-SEP-2018 11:24 P:\Projects\Road\NC-DOT\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_RDWY\CADD_GEO\TECH\Plan\Prof_U5808_GEO.pft.10.dgn



I:\SEP-2018\1125
 P:\T\CONSTRUCTION\Projects\Road\NC-001\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808.GEO\RDWY\CADD.GEOTECH\XSC\U5808.GEO_xsl\LI&L2.dgn
 6/23/16




54 + 50.00

53 + 81.99

-L2-

P:\SEP-2018\1125 P:\TERRACON\CONSTRUCTION\Projects\Road\NC-001\2018\6468188045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808.GEO_RDWY\CADD_GEO\TECH\asc\U5808.GEO_xsl\11&L2.dgn 6/23/16




56 + 19.01

55 + 50.00


-L2-

I:\SEP-2018\1125
 P:\PROJECTS\Road\NC-001\2018\6468186045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808.GEO.RDWY\CADD.GEOTECH\XSC\U5808.GEO.XSL\11&L2.dgn
 \$\$\$SUBPROGRAM\$\$\$

6/23/16




I:\2-SEP-2018 11:25 P:\T\CONTRACTS\2018\6468186045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808.GEO.RDW\CADD.GEOTECH\XSC\U5808.GEO.XSL\11.L2.dgn
 \$\$\$SUBPROGRAM\$\$\$



I:\SEP-2018\1125\PROJECTS\Road\NC-001\2018\6468186045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808.GEO.RDWY\CADD.GEOTECH\XSC\U5808.GEO.XSL\1125.L2.dgn

-L2-




SAMPLE NO.	STATION	OFFSET	LINE	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% PASSING SIEVES (SOIL MORTAR)				% PASSING SIEVES			% MOISTURE	% ORGANIC
								C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-27	10+98	49' LT	-Y1B-	1.0-2.5	A-7-6(28)	46	28	3.7	1.7	44.2	50.4	99.3	96.5	94.5	14.5	-

SS-27
 15
 20
 36
 100/.8
 BT
 DRY
 CAVED-IN
 @ 4.1 FT

6/23/16
 12-SEP-2018 11:25
 P:\Transportation\Projects\Road\NC-DOT\2018\6468189045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_ROWY\CADD_GEO\TECH\sec U5808_GEO_xst_Y1B.dgn
 \$\$\$USERNAME\$\$\$

6/23/16

0 2.5 5	PROJ. REFERENCE NO. U-5808	SHEET NO. 17
---------	-------------------------------	-----------------



I:\SEP-2018\1125
 P:\Transportation\Projects\Road\NC-DOT\2018\6468189045 U-5808 Chestnut Drive Connector\6.0 Deliverables\U5808_GEO_ROWY\CADD_GEO_ROWY\GEO_xst_YIB.dgn
 \$\$\$USERNAME\$\$\$

-YIB-