



PAVEMENT SCHEDULE

| | |
|----|---|
| C1 | PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD. |
| C2 | PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. |
| C3 | PROP. APPROX. 2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 224 LBS. PER SQ. YD. |
| D1 | PROP. APPROX. 3" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I-19.0C, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD. |
| E1 | PROP. APPROX. 5.5" ASPHALT CONCRETE BASE COURSE, TYPE B-25.0C, AT AN AVERAGE RATE OF 627 LBS. PER SQ. YD. |
| F1 | PROP. ASPHALT SURFACE TREATMENT, MAT COAT #67 STONE |
| S | AGGREGATE SHOULDER BORROW |
| U | EXISTING PAVEMENT |
| V1 | MILLING 1.5" IN DEPTH |
| V2 | MILLING 5" IN DEPTH |
| V3 | TRENCHING FOR BASE COURSE (SEE S.P.) |