

NOTE: PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE -B AND TEMPORARY ROCK SILT CHECKS TYPE -A AT DRAINAGE OUTLETS.

NOTE: FOR TRENCHLESS PIPE INSTALLATIONS AT JURISDICTIONAL STREAMS, FOLLOW CONSTRUCTION SEQUENCE FOR TRENCHLESS INSTALLATION ON SHEET EC-2A

NOTE: UTILIZE FABRIC INSERT INLET PROTECTION DEVICES IN LIEU OF ROCK INLET SEDIMENT TRAPS TYPE-C AS DIRECTED TO AVOID IMPONDMENT OF RUNOFF IN ROADWAY OPEN TO TRAFFIC.

Place Matting for Erosion Control  
 on Slope as Work Allows.  
 Sta. 67 + 49

76 x 38 x 3  
 1.5 inch Skimmer  
 with 1.5 inch  
 Orifice Diameter  
 11 ft. weir  
 ID 7.1

MATCHLINE -Y- STA 63+00 - SEE SHEET 6

MATCHLINE -Y- STA 75+00 - SEE SHEET 8

8/17/99  
 1/9/2024  
 R:\Environmental\Design\AAAB\_PSH\1-25\3AAAB\_IC\_PSH\_07.dgn  
 Environmental  
 Consulting

REVISIONS

☆ REVISED SIGNAL

