


PERMANENT LOAD FACTORS:

LOAD TYPE	MAX FACTOR	MIN FACTOR
DC	1.25	0.90
DW	1.50	0.65
EV	1.30	0.90
EH	1.35	0.90
ES	1.35	0.90
WA	1.00	--

LOAD AND RESISTANCE FACTOR RATING (LRFR) SUMMARY FOR REINFORCED CONCRETE BOX CULVERT										
	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	STRENGTH I LIMIT STATE							
			MOMENT				SHEAR			
			RATING FACTOR	BOX NO.	ELEMENT TYPE	DISTANCE FROM LEFT END OF ELEMENT (ft)	RATING FACTOR	BOX NO.	ELEMENT TYPE	DISTANCE FROM LEFT END OF SPAN (ft)
PERMANENT LOAD RATING	①	1.02	1.19	1	ROOF SLAB	3.00	1.02	1	ROOF SLAB	4.78

NOTES:

RATING FACTORS ARE BASED ON THE STRENGTH I LIMIT STATE.
 THE EFFECTS OF LIVE LOAD ON DESIGN AND LOAD RATING MAY BE NEGLECTED FOR CULVERTS WITH CERTAIN FILL DEPTHS DESCRIBED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS.
 CULVERTS WITH NEGLIGIBLE LIVE LOAD SHOULD BE LOAD RATED FOR PERMANENT LOADS ONLY IN ACCORDANCE WITH THE AASHTO MANUAL FOR BRIDGE EVALUATION.



LRFR SUMMARY
(LOOKING DOWNSTREAM)

PROJECT NO. I-2513AA/AB
BUNCOMBE COUNTY
 STATION: 24+63.79 -RPC-

SHEET 6 OF 6

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


LRFR SUMMARY FOR
 REINFORCED CONCRETE
 BOX CULVERTS

(DEEP FILLS)



5640 Dillard Drive, Suite 200
 Cary, NC 27518

LICENSURE NO. C-4434



12/14/2023 | 8:58 AM

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:	SHEET NO.
1			3			C2-6
2			4			TOTAL SHEETS 6

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

12/14/2023 11:17:04 AM c:\pwworking\cecom_ds21_na_2020\d0131628\I-2513AA_SMU_CU6_104007.dgn

DRAWN BY : T. BANKOVICH DATE : 4-23
 CHECKED BY : J.A. BATTS DATE : 4-23
 DESIGN ENGINEER OF RECORD: J.A. BATTS DATE : 4-23