


## SEE DETAIL A 6" (TYP.) ELASTOMERIC CONCRETE FOR PRESERVATION (TYP.) EXISTING JOINT PROPOSED FOAM JOINT

—— € EXISTING JOINT

## JOINT INSTALLATION SEQUENCE AT BENTS (SECTION A-A)



## \* FOAM JOINT SEALS FOR PRESERVATION SHALL BE RECESSED AS PER MANUFACTURER'S RECOMMENDATIONS.

JOINT REPAIR QUANTITY						
	FOAM JOI FOR PRES		ELASTOMERIC CONCRETE FOR PRESERVATION			
	ESTIMATED (LIN. FT.)	ACTUAL (LIN.FT.)	ESTIMATED (CU.FT.)	ACTUAL (CU.FT.)		
BENT 1	29.0		7.0			
BENT 2	29.0		7.0			
BENT 3	29.0		7.0			
BENT 4	29.0		7.0			
BENT 5	29.0		7.0			

SAWED JOINT OPENING TABLE						
LOCATION	SKEW ANGLE	PERPENDICULAR JOINT OPENING AT 45°	PERPENDICULAR JOINT OPENING AT 60°	PERPENDICULAR JOINT OPENING AT 90°		
BENT 1	90°00′00″	1 <sup>5</sup> / <sub>8</sub> ′′	1%′′	17/16"		
BENT 2	90°00′00″	1 <sup>11</sup> / <sub>16</sub> "	19/16′′	15/ <sub>16</sub> "		
BENT 3	90°00′00″	1 <sup>5</sup> /8′′	1%6′′	17⁄ <sub>16</sub> "		
BENT 4	90°00′00″	1 <sup>5</sup> /8′′	1%6′′	17/ <sub>16</sub> "		
BENT 5	90°00′00″	15/8′′	1%6′′	17/ <sub>16</sub> "		

## NOTES

THE CONTRACTOR SHALL FIELD VERIFY THE EXISTING JOINT OPENING PRIOR TO ORDER JOINT SEAL MATERIAL. IF THE ACTUAL JOINT OPENING VARIES FROM THE OPENING ALLOWED BY THE JOINT SEAL MATERIAL, NOTIFY THE ENGINEER. REVISION TO THE JOINT SEAL SIZE AND TYPE MIGHT BE NECESSARY.

THE CONTRACTOR WILL NOT BE PERMITTED TO FORM THE JOINTS FOR THE JOINT SEALS IN LIEU OF SAWING THE JOINT.

THE MANUFACTURER IS TO PROVIDE THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE FOAM JOINT SEAL BASED ON JOINT OPENINGS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

FOAM JOINT SEALS FOR PRESERVATION SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATION.

THE INSTALLED FOAM JOINT SEALS FOR PRESERVATION SHALL BE WATER TIGHT.

FOR LOCATION OF SECTION A-A, SEE PLAN OF SPAN SHEETS.

FINAL SURFACE OF THE JOINT DEMOLITION AREA PRIOR TO PLACEMENT OF CONCRETE REPAIR MATERIAL SHOULD BE REASONABLY FLAT AND LEVEL. ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF THE SURFACE PRIOR TO PLACEMENT OF REPAIR CONCRETE.

FOR ELASTOMERIC CONCRETE FOR PRESERVATION, SEE SPECIAL PROVISIONS.

PROJECT NO. 15BPR.130

MOORE county

BRIDGE NO: 620049



DEPARTMENT OF TRANSPORTATION
RALEIGH

JOINT REPAIR
DETAILS AT
BENTS

5430 Wade Park BLVD, Suite 410
Raleigh, NC 27607
Tel. 919-854-0344 Fax. 919-854-0355
NC License No. F-0765

S

DOCUMENT NOT CONSIDERED	N
	2
FINAL UNLESS ALL	I
STGNATURES COMPLETED	9

REVISIONS					SHEET NO	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-100
1			3			TOTAL SHEETS
2			4			156

DRAWN BY : _	D. A. GLADDEN	DATE :	5/23
CHECKED BY	E.E.MURRAY	DATE :	3/24