

REFERENCE: BR-0097

PROJECT: 67097

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STRUCTURE
SUBSURFACE INVESTIGATION

COUNTY ROCKINGHAM
PROJECT DESCRIPTION REPLACE BRIDGE NO. 178
ON SR 1929 (ESTES ROAD) OVER US 29

CONTENTS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	LEGEND (SOIL & ROCK)
3	SITE PLAN
4	PROFILE
5-6	CROSS SECTIONS
7-12	BORE LOGS
13-28	SOIL TEST RESULTS
29	SITE PHOTOGRAPHS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BR-0097	1	29

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
- BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

D. KUBINSKI

TRIGON EXPLORATION

INVESTIGATED BY D. KUBINSKI


DRAWN BY T. WELLS

CHECKED BY X. BARRETT

SUBMITTED BY KLEINFELDER, INC.

DATE JULY 2022

Prepared in the Office of:



DocuSigned by:
Thomas R. Wells 07/06/2022

7DA5D2D056887479 SIGNATURE DATE

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION

SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, *VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6*

SOIL LEGEND AND AASHTO CLASSIFICATION

GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)							SILT-CLAY MATERIALS (> 35% PASSING #200)							ORGANIC MATERIALS		
	A-1	A-1-b	A-1-c	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	
GROUP CLASS.	A-1-a	A-1-b		A-2-4	A-2-5	A-2-6	A-2-7					A-7-5, A-7-6	A-3	A-4, A-5	A-6, A-7		
SYMBOL																	
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX		40 MX 10 MX	41 MX 10 MX	40 MX 35 MX	41 MX 35 MX	40 MX 35 MX	41 MX 35 MX	36 MN 36 MN	36 MN 36 MN						
MATERIAL PASSING #40 LL PI	- 6 MX	- NP		40 MX 10 MX	41 MX 11 MN	40 MX 11 MN	41 MN 11 MN	40 MX 10 MX	41 MN 10 MX	40 MX 11 MN	41 MN 11 MN						
GROUP INDEX	0	0		0	4 MX	8 MX	12 MX	16 MX	NO MX								
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS									
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR			FAIR TO POOR	POOR	UNSATURABLE				

PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30

CONSISTENCY OR DENSENESS

PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4

TEXTURE OR GRAIN SIZE

U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270
	4.76	2.00	0.42	0.25	0.075	0.053
BOULDER (BLDR.)						
COBBLE (COB.)						
GRAVEL (GR.)						
COARSE SAND (CS, SD.)						
FINE SAND (F SD.)						
SILT (SL.)						
CLAY (CL.)						
GRAIN SIZE	305 IN.	75	2.0	0.25	0.05	0.005

SOIL MOISTURE - CORRELATION OF TERMS

SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE
PLASTIC RANGE (PI)	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE

PLASTICITY

	PLASTICITY INDEX (PI)	DRY STRENGTH
NON PLASTIC	0-5	VERY LOW
SLIGHTLY PLASTIC	6-15	SLIGHT
MODERATELY PLASTIC	16-25	MEDIUM
HIGHLY PLASTIC	26 OR MORE	HIGH

COLOR

DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.

GRADATION

WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.
UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.
GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.

ANGULARITY OF GRAINS

THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: **ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.**

MINERALOGICAL COMPOSITION

MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.

COMPRESSIBILITY

SLIGHTLY COMPRESSIBLE LL < 31
MODERATELY COMPRESSIBLE LL = 31 - 50
HIGHLY COMPRESSIBLE LL > 50

PERCENTAGE OF MATERIAL

	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE

GROUND WATER

- WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING
- STATIC WATER LEVEL AFTER 24 HOURS
- PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA
- SPRING OR SEEP

MISCELLANEOUS SYMBOLS

- ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION
- SOIL SYMBOL
- ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT
- INFERRED SOIL BOUNDARY
- INFERRED ROCK LINE
- ALLUVIAL SOIL BOUNDARY
- DIP & DIP DIRECTION OF ROCK STRUCTURES
- SPT TEST BORING
- AUGER BORING
- CORE BORING
- MONITORING WELL
- PIEZOMETER INSTALLATION
- SLOPE INDICATOR INSTALLATION
- CONE PENETROMETER TEST
- SOUNDING ROD
- TEST BORING WITH CORE
- SPT N-VALUE

RECOMMENDATION SYMBOLS

- UNDERCUT
- SHALLOW UNDERCUT
- UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE
- UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK
- UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL

ABBREVIATIONS

- AR - AUGER REFUSAL
- BT - BORING TERMINATED
- CL - CLAY
- CPT - COARSE PENETRATION TEST
- CSE - COARSE
- DMT - DILATOMETER TEST
- DPT - DYNAMIC PENETRATION TEST
- e - VOID RATIO
- F - FINE
- FOSS. - FOSSILIFEROUS
- FRAC. - FRACTURED, FRACTURES
- FRAGS. - FRAGMENTS
- HI. - HIGHLY
- MED. - MEDIUM
- MICA - MICACEOUS
- MOD. - MODERATELY
- NP - NON PLASTIC
- ORG. - ORGANIC
- PMT - PRESSUREMETER TEST
- SAP. - SAPROLITIC
- SD. - SAND, SANDY
- SL. - SILTY, SILTY
- SLI. - SLIGHTLY
- TCR - TRICONE REFUSAL
- w - MOISTURE CONTENT
- V - VERY
- VST - VANE SHEAR TEST
- WEA. - WEATHERED
- W - UNIT WEIGHT
- W_d - DRY UNIT WEIGHT
- S - BULK
- SS - SPLIT SPOON
- ST - SHELBY TUBE
- RS - ROCK
- RT - RECOMPACTED TRIAXIAL
- CBR - CALIFORNIA BEARING RATIO

EQUIPMENT USED ON SUBJECT PROJECT

- DRILL UNITS:
 - CME-45C
 - CME-55
 - CME-550
 - VANE SHEAR TEST
 - PORTABLE HOIST
 - MOBILE B-57
- ADVANCING TOOLS:
 - CLAY BITS
 - 6" CONTINUOUS FLIGHT AUGER
 - 8" HOLLOW AUGERS
 - HARD FACED FINGER BITS
 - TUNG-CARBIDE INSERTS
 - CASING W/ ADVANCER
 - TRICONE STEEL TEETH
 - TRICONE 2-1/2" TUNG-CARB.
 - CORE BIT
- HAMMER TYPE:
 - AUTOMATIC
 - MANUAL
- CORE SIZE:
 - B
 - H
 - N
- HAND TOOLS:
 - POST HOLE DIGGER
 - HAND AUGER
 - SOUNDING ROD
 - VANE SHEAR TEST

ROCK DESCRIPTION

HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:

- WEATHERED ROCK (WR)** - NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.
- CRYSTALLINE ROCK (CR)** - FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.
- NON-CRYSTALLINE ROCK (NCR)** - FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.
- COASTAL PLAIN SEDIMENTARY ROCK (CP)** - COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.

WEATHERING

- FRESH** - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.
- VERY SLIGHT (V SL.)** - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.
- SLIGHT (SL.)** - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.
- MODERATE (MOD.)** - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.
- MODERATELY SEVERE (MOD. SEV.)** - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. *IF TESTED, WOULD YIELD SPT REFUSAL*
- SEVERE (SEV.)** - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. *IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF*
- VERY SEVERE (V SEV.)** - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. *IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF*
- COMPLETE** - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. FABRIC MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.

ROCK HARDNESS

- VERY HARD** - CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.
- HARD** - CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.
- MODERATELY HARD** - CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.
- MEDIUM HARD** - CAN BE GROUDED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.
- SOFT** - CAN BE GROUDED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.
- VERY SOFT** - CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.

FRACTURE SPACING

TERM	SPACING
VERY WIDE	MORE THAN 10 FEET
WIDE	3 TO 10 FEET
MODERATELY CLOSE	1 TO 3 FEET
CLOSE	0.16 TO 1 FOOT
VERY CLOSE	LESS THAN 0.16 FEET

BEDDING

TERM	THICKNESS
VERY THICKLY BEDDED	4 FEET
THICKLY BEDDED	1.5 - 4 FEET
THINLY BEDDED	0.16 - 1.5 FEET
VERY THINLY BEDDED	0.03 - 0.16 FEET
THICKLY LAMINATED	0.008 - 0.03 FEET
THINLY LAMINATED	< 0.008 FEET

INDURATION

- FRIABLE** - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.
- MODERATELY INDURATED** - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.
- INDURATED** - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.
- EXTREMELY INDURATED** - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.

TERMS AND DEFINITIONS


- ALLUVIUM (ALLUV.)** - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
- AQUIFER** - A WATER BEARING FORMATION OR STRATA.
- ARENACEOUS** - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
- ARGILLACEOUS** - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
- ARTESIAN** - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.
- CALCAREOUS (CALC.)** - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
- COLLUVIUM** - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
- CORE RECOVERY (REC.)** - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
- DIKE** - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
- DIP** - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.
- DIP DIRECTION (DIP AZIMUTH)** - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
- FAULT** - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
- FISSILE** - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
- FLOAT** - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL.
- FLOOD PLAIN (FP)** - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
- FORMATION (FM)** - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.
- JOINT** - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
- LEDGE** - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.
- LENS** - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
- MOTTLED (MOT.)** - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
- PERCHED WATER** - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.
- RESIDUAL (RES.) SOIL** - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
- ROCK QUALITY DESIGNATION (ROD)** - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
- SAPROLITE (SAP.)** - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
- SILL** - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
- SLICKENSIDE** - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.
- STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)** - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
- STRATA CORE RECOVERY (SREC.)** - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
- STRATA ROCK QUALITY DESIGNATION (SROD)** - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
- TOPSOIL (TS.)** - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.

BENCH MARK: N/A


ELEVATION: N/A FEET

NOTES:

FIAD - FILLED IMMEDIATELY AFTER DRILLING
THE BORINGS WERE SURVEYED BY SEPIENGINEERING & CONSTRUCTION, INC. USING A SUB CENTIMETER GPS.



PROJECT REFERENCE NO.	SHEET NO.
BR-0097	4
CENTERLINE PROFILE ON BRIDGE NO. 178 ON SR 1929 (-L-) OVER US 29 (-Y-)	




- Ⓐ **RESIDUAL:** MOIST TO SATURATED, SOFT TO VERY STIFF, BROWN, RED, YELLOWISH BROWN, AND OLIVE, SILTY CLAY (A-7) AND CLAYEY SILT (A-5) TO COARSE TO FINE SANDY SILT (A-4) WITH TRACE TO LITTLE MICA
- Ⓑ **RESIDUAL:** SATURATED, MEDIUM DENSE TO VERY DENSE, OLIVE, YELLOWISH BROWN, WHITE, SILTY, COARSE TO FINE SAND (A-2-4) WITH TRACE ROCK FRAGMENTS AND MICA
- Ⓒ **RESIDUAL:** SATURATED, MEDIUM DENSE TO VERY DENSE, OLIVE TO GREENISH BLACK SILTY, COARSE TO FINE SAND (A-2-4) WITH TRACE ROCK FRAGMENTS

NOTES:

GROUNDLINE TAKEN FROM PROJECT ROADWAY FILES DATED FEBRUARY 18, 2022

INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE PROFILE


WEATHERED ROCK:
OLIVE, YELLOWISH BROWN, GRAY AND GREENISH BLACK SCHIST AND GNEISS




- (A) RESIDUAL: MOIST TO SATURATED, SOFT TO VERY STIFF, BROWN TO YELLOWISH BROWN TO OLIVE, SILTY CLAY (A-7-5) TO COARSE TO FINE SANDY SILT (A-4) WITH TRACE TO LITTLE MICA
- (B) RESIDUAL: SATURATED, MEDIUM DENSE TO VERY DENSE, OLIVE TO YELLOWISH BROWN AND WHITE, SILTY, COARSE TO FINE SAND (A-2-4) WITH TRACE MICA
- (C) RESIDUAL: SATURATED, MEDIUM DENSE, YELLOWISH, BROWN, SILTY, FINE TO COARSE SAND (A-2-4)

WEATHERED ROCK: YELLOWISH BROWN, OLIVE GRAY GNEISS

NOTES:
 GROUNDLINE TAKEN FROM PROJECT TIN FILE BRO097_LS_TIN.TIN DATED FEBRUARY 2, 2022.
 INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE CROSS SECTIONS.
 SKEW: 120°33'37"




CROSS SECTION ALONG END BENT NO. 1 AT STA. 29+18




- (A) RESIDUAL: MOIST TO SATURATED, SOFT TO HARD, YELLOWISH BROWN AND OLIVE, CLAYEY SILT (A-5) AND COARSE TO FINE SANDY SILT (A-4) WITH TRACE TO LITTLE MICA
- (B) RESIDUAL: SATURATED, MEDIUM DENSE TO VERY DENSE, OLIVE, SILTY, COARSE TO FINE SAND (A-2-4) WITH TRACE MICA
- (C) RESIDUAL: SATURATED, VERY DENSE, GREENISH, BLACK AND OLIVE, SILTY, COARSE TO FINE SAND (A-2-4) WITH TRACE ROCK FRAGMENTS

WEATHERED ROCK: GRAY, OLIVE, YELLOW, AND BROWN SCHIST


NOTES:
 GROUNDLINE TAKEN FROM PROJECT TIN FILE BRO097_LS_TIN.TIN DATED FEBRUARY 2, 2022.
 INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE CROSS SECTIONS.
 SKEW: 120°33'37"



CROSS SECTION ALONG BENT NO. 1 AT STA. 30+18



**THIS PAGE
INTENTIONALLY
LEFT BLANK**



VE = 1

**CROSS SECTION ALONG
END BENT NO. 2 AT STA. 31+34**

LABORATORY SUMMARY SHEET FOR SOIL SAMPLES

SHEET 13

WBS NO. (TIP NO.): 67097.1.1 (BR-0097)

PROJECT ID: 39271

COUNTY: ROCKINGHAM

DESCRIPTION: REPLACE BRIDGE NO. 178 ON SR 1929 (ESTES ROAD) OVER US 29

Sample No.	Boring Number	Alignment	Station	Offset	Sample Depth (ft.)	Natural Moisture Content (%)	AASHTO Class.	N-Value (blows/ ft.)	Atterberg Limits			Gradation Results							
									L.L.	P.L.	P.I.	Retained #4 Sieve	Pass #10 Sieve	Pass #40 Sieve	Pass #200 Sieve	Coarse Sand (%)	Fine Sand (%)	Silt (%)	Clay (%)
SS-5	B1-A	-L-	30+33	4' LT	13.3 - 14.8	--	A-4	6	NP	NP	NP	0.0	99.0	97.4	62.7	4.9	62.3	18.4	14.3
SS-6	B1-A	-L-	30+33	4' LT	28.3 - 29.8	--	A-4	17	NP	NP	NP	1.0	96.0	89.1	55.0	17.3	38.6	31.8	12.4
SS-7	B1-B	-L-	30+17	25' RT	18.5 - 20.0	--	A-4	7	NP	NP	NP	1.0	98.0	96.1	64.5	7.2	42.4	38.2	12.1
SS-8	B1-B	-L-	30+17	25' RT	38.5 - 40.0	--	A-4	72	NP	NP	NP	3.0	89.0	82.8	42.7	22.4	48.0	19.6	10.0
SS-9	EB2-A	-L-	31+91	9' LT	28.2 - 29.7	--	A-4	7	NP	NP	NP	0.0	98.0	96.3	50.0	9.6	67.5	8.6	14.2
SS-10	EB2-B	-L-	31+75	12' RT	13.4 - 14.9	--	A-4	5	NP	NP	NP	1.0	97.0	96.3	72.6	6.0	33.9	42.0	18.2
ST-1	EB1-A	-L-	28+83	7' LT	31.0 - 33.0	53.8	A-4	--	NP	NP	NP	0.0	99.9	97.0	49.0	7.9	52.0	23.3	16.8
ST-2	EB1-B	-L-	28+62	20' RT	21.0 - 23.0	50.5	A-7-5	--	64	46	18	0.2	99.8	97.0	70.5	5.4	31.7	39.5	23.4


**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS
AASHTO T-297**

Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001


**MOHR TOTAL STRENGTH ENVELOPE
AASHTO T-297**

Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001
 Visual Description: Orange Clayey Silt (UNDISTURBED)

Consolidated Undrained Triaxial Test with Pore Pressure



a	=	0.00	\overline{C}	=	0.00
α	=	25.0	$\overline{\Phi}$	=	27.82



Failure Based on Maximum Effective Principal Stress Ratio

NOTE: GRAPH NOT TO SCALE

Tested By: 129-07-0411 Date: 4/27/22 Approved By: MPS Date: 5/5/22

Tested By: 129-07-0411 Date: 4/27/22 Approved By: MPS Date: 5/5/22

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS**
AASHTO T-297



Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001

Visual Description: Orange Clayey Silt (UNDISTURBED)

Stage No.	0
Test No.	1

INITIAL SAMPLE DIMENSIONS (in)			
Length 1:	5.962	Diameter 1:	2.833
Length 2:	5.971	Diameter 2:	2.836
Length 3:	5.994	Diameter 3:	2.846
Length 4:	5.999	Diameter 4:	2.848
Avg. Length:	5.982	Avg. Diam.:	2.841

PRESSURES (psi)	
Cell Pressure (psi)	63.89
Back Pressure (psi)	50.0
Eff. Conf. Pressure (psi)	13.9
Pore Pressure Response (%)	99

VOLUME CHANGE	
Initial Burette Reading (ml)	46.7
Final Burette Reading (ml)	26.7
Final Change (ml)	20.0

MAXIMUM OBLIQUITY POINTS	
\bar{P} =	8.97
Q =	4.18

Initial Dial Reading (mil)	308
Dial Reading After Saturation (mil)	308
Dial Reading After Consolidation (mil)	389

LOAD (LB)	DEFORMATION (IN)	PORE PRESSURE (PSI)
6.3	0.000	50.0
10.0	0.001	50.5
12.6	0.003	50.9
20.0	0.009	52.4
24.9	0.014	53.5
28.8	0.020	54.4
33.4	0.030	55.3
37.0	0.039	56.0
41.0	0.051	56.7
46.4	0.072	57.5
51.7	0.103	58.2
55.4	0.140	58.6
57.5	0.175	58.9
58.9	0.217	59.1
59.6	0.246	59.1
60.4	0.289	59.1
61.6	0.346	59.1
62.4	0.407	59.1
63.0	0.451	59.1
63.8	0.512	59.0
64.4	0.558	59.0
64.6	0.603	59.0
65.1	0.649	58.9
65.3	0.678	58.9
65.3	0.708	58.9
65.2	0.738	58.9
65.3	0.768	58.8
65.4	0.813	58.8
65.1	0.858	58.7
64.9	0.888	58.4
64.4	0.918	58.3

Tested By: 129-07-0411 Date: 4/27/22 Input Checked By: GEM Date: 5/5/22



**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS**
AASHTO T-297

Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001

Visual Description: Orange Clayey Silt (UNDISTURBED)

Effective Confining Pressure (psi)	13.9	Stage No.	0
		Test No.	1

INITIAL DIMENSIONS		VOLUME CHANGE	
Initial Sample Length (in)	5.98	Volume After Consolidation (in ³)	36.69
Initial Sample Diameter (in)	2.84	Length After Consolidation (in)	5.90
Initial Sample Area (in ²)	6.34	Area After Consolidation (in ²)	6.218
Initial Sample Volume (in ³)	37.91		

Strain (%)	Deviator Stress PSI	ΔU	$\bar{\sigma}_1$	$\bar{\sigma}_3$	Effective Principal Stress Ratio	\bar{A}	\bar{P}	Q
------------	---------------------	------------	------------------	------------------	----------------------------------	-----------	-----------	---

0.03	0.60	0.50	13.99	13.4	1.045	0.84	13.69	0.30
0.06	1.02	0.94	13.97	13.0	1.079	0.93	13.46	0.51
0.15	2.20	2.44	13.65	11.5	1.192	1.12	12.55	1.10
0.24	3.00	3.54	13.34	10.3	1.289	1.19	11.85	1.50
0.34	3.61	4.38	13.13	9.5	1.380	1.22	11.32	1.81
0.50	4.34	5.28	12.95	8.6	1.504	1.23	10.78	2.17
0.66	4.91	5.96	12.84	7.9	1.619	1.23	10.39	2.45
0.87	5.53	6.66	12.76	7.2	1.764	1.22	10.00	2.76
1.22	6.37	7.50	12.77	6.4	1.997	1.19	9.58	3.19
1.74	7.18	8.21	12.86	5.7	2.263	1.15	9.27	3.59
2.37	7.72	8.64	12.97	5.3	2.470	1.13	9.11	3.86
2.97	7.99	8.93	12.95	5.0	2.610	1.13	8.96	3.99
3.68	8.15	9.06	12.98	4.8	2.686	1.12	8.91	4.07
4.18	8.22	9.11	13.01	4.8	2.720	1.12	8.89	4.11
4.89	8.28	9.08	13.10	4.8	2.720	1.11	8.96	4.14
5.87	8.37	9.11	13.15	4.8	2.750	1.10	8.97	4.18
6.89	8.40	9.08	13.22	4.8	2.746	1.09	9.01	4.20
7.65	8.43	9.06	13.26	4.8	2.746	1.09	9.04	4.21
8.68	8.44	9.01	13.32	4.9	2.730	1.08	9.10	4.22
9.45	8.47	8.98	13.37	4.9	2.726	1.07	9.14	4.23
10.22	8.43	8.96	13.36	4.9	2.708	1.07	9.15	4.21
10.99	8.42	8.92	13.39	5.0	2.692	1.07	9.18	4.21
11.50	8.39	8.91	13.38	5.0	2.684	1.07	9.18	4.20
12.00	8.35	8.88	13.37	5.0	2.665	1.07	9.19	4.18
12.51	8.30	8.85	13.33	5.0	2.648	1.08	9.19	4.15
13.02	8.26	8.82	13.33	5.1	2.628	1.08	9.20	4.13
13.78	8.19	8.78	13.31	5.1	2.603	1.08	9.21	4.10
14.55	8.08	8.66	13.32	5.2	2.545	1.08	9.27	4.04
15.06	8.01	8.40	13.49	5.5	2.460	1.06	9.49	4.00
15.57	7.89	8.31	13.47	5.6	2.414	1.06	9.52	3.94

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS
AASHTO T-297**



Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001

Visual Description: Orange Clayey Silt (UNDISTURBED)

Stage No.	0
Test No.	2

INITIAL SAMPLE DIMENSIONS (in)

Length 1:	6.228	Diameter 1:	2.851
Length 2:	6.143	Diameter 2:	2.857
Length 3:	6.228	Diameter 3:	2.853
Length 4:	6.195	Diameter 4:	2.836
Avg. Length	6.199	Avg. Diam.:	2.849

PRESSURES (psi)

Cell Pressure (psi)	77.89
Back Pressure (psi)	50.0
Eff. Conf. Pressure (psi)	27.9
Pore Pressure Response (%)	97

VOLUME CHANGE

Initial Burette Reading (ml)	46.0
Final Burette Reading (ml)	15.6
Final Change (ml)	30.4

MAXIMUM OBLIQUITY POINTS

\bar{P}	=	25.52
Q	=	14.80

Initial Dial Reading (mil)	365
Dial Reading After Saturation (mil)	375
Dial Reading After Consolidation (mil)	528

LOAD (LB)	DEFORMATION (IN)	PORE PRESSURE (PSI)
12.2	0.000	50.0
14.1	0.001	50.5
15.7	0.003	50.7
17.6	0.009	51.0
39.0	0.014	51.3
56.2	0.020	53.0
76.5	0.029	55.4
92.8	0.038	57.0
109.1	0.052	58.9
130.7	0.073	61.1
152.3	0.104	63.3
171.6	0.142	64.7
184.1	0.179	65.6
192.0	0.222	66.3
195.8	0.253	66.5
199.2	0.297	66.9
204.3	0.357	67.0
209.7	0.418	67.2
210.4	0.465	67.0
211.0	0.527	67.2
213.2	0.574	67.1
215.8	0.621	66.9
218.2	0.667	67.0
218.3	0.698	66.8
216.6	0.729	66.9
213.9	0.760	66.9
209.6	0.791	66.9
200.5	0.838	66.8
191.2	0.885	66.5
182.9	0.917	66.6
175.9	0.948	66.5

Tested By: 129-07-0411 Date: 4/27/22 Input Checked By: GEM Date: 5/5/22

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS
AASHTO T-297**



Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001

Visual Description: Orange Clayey Silt (UNDISTURBED)

Effective Confining Pressure (psi)	27.9	Stage No.	0
		Test No.	2

INITIAL DIMENSIONS

Initial Sample Length (in)	6.20
Initial Sample Diameter (in)	2.85
Initial Sample Area (in ²)	6.38
Initial Sample Volume (in ³)	39.52

VOLUME CHANGE

Volume After Consolidation (in ³)	37.48
Length After Consolidation (in)	6.04
Area After Consolidation (in ²)	6.209

Strain (%)	Deviator Stress PSI	ΔU	$\bar{\sigma}_1$	$\bar{\sigma}_3$	Effective Principal Stress Ratio	\bar{A}	\bar{P}	Q
------------	---------------------	------------	------------------	------------------	----------------------------------	-----------	-----------	---

0.02	0.30	0.50	27.69	27.4	1.011	1.72	27.54	0.15
0.05	0.56	0.70	27.75	27.2	1.021	1.28	27.47	0.28
0.15	0.86	1.00	27.75	26.9	1.032	1.20	27.32	0.43
0.24	4.30	1.27	30.92	26.6	1.162	0.30	28.77	2.15
0.34	7.06	2.96	31.99	24.9	1.283	0.43	28.46	3.53
0.48	10.30	5.35	32.84	22.5	1.457	0.54	27.69	5.15
0.64	12.90	7.04	33.75	20.8	1.619	0.56	27.30	6.45
0.86	15.47	8.94	34.42	19.0	1.816	0.60	26.69	7.73
1.21	18.85	11.07	35.67	16.8	2.121	0.61	26.24	9.43
1.73	22.17	13.28	36.79	14.6	2.517	0.62	25.70	11.09
2.34	25.07	14.72	38.24	13.2	2.903	0.61	25.71	12.53
2.97	26.86	15.62	39.13	12.3	3.189	0.60	25.70	13.43
3.69	27.89	16.33	39.44	11.6	3.413	0.60	25.50	13.94
4.19	28.32	16.55	39.66	11.3	3.497	0.60	25.50	14.16
4.92	28.63	16.94	39.59	11.0	3.614	0.61	25.27	14.32
5.91	29.10	17.01	39.98	10.9	3.676	0.60	25.43	14.55
6.93	29.60	17.17	40.31	10.7	3.762	0.60	25.52	14.80
7.71	29.46	17.04	40.31	10.9	3.714	0.60	25.58	14.73
8.73	29.21	17.17	39.93	10.7	3.724	0.61	25.33	14.61
9.51	29.30	17.06	40.13	10.8	3.704	0.60	25.48	14.65
10.28	29.42	16.91	40.39	11.0	3.679	0.59	25.69	14.71
11.05	29.51	16.96	40.44	10.9	3.701	0.59	25.68	14.76
11.57	29.35	16.82	40.42	11.1	3.650	0.59	25.75	14.67
12.08	28.94	16.88	39.96	11.0	3.628	0.60	25.48	14.47
12.59	28.39	16.91	39.37	11.0	3.586	0.61	25.17	14.20
13.11	27.62	16.92	38.58	11.0	3.518	0.63	24.78	13.81
13.89	26.11	16.85	37.15	11.0	3.364	0.67	24.10	13.05
14.66	24.60	16.54	35.95	11.3	3.168	0.69	23.65	12.30
15.19	23.31	16.62	34.58	11.3	3.069	0.74	22.92	11.65
15.70	22.23	16.52	33.59	11.4	2.955	0.77	22.48	11.11

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS**
AASHTO T-297

Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001

Visual Description: Orange Clayey Silt (UNDISTURBED)

Stage No.	0
Test No.	3

INITIAL SAMPLE DIMENSIONS (in)			
Length 1:	6.113	Diameter 1:	2.811
Length 2:	6.133	Diameter 2:	2.840
Length 3:	6.132	Diameter 3:	2.835
Length 4:	6.164	Diameter 4:	2.827
Avg. Length:	6.136	Avg. Diam.:	2.828

PRESSURES (psi)

Cell Pressure (psi)	105.6
Back Pressure (psi)	50.0
Eff. Conf. Pressure (psi)	55.6
Pore Pressure Response (%)	97

VOLUME CHANGE	
Initial Burette Reading (ml)	92.8
Final Burette Reading (ml)	21.7
Final Change (ml)	71.1

MAXIMUM OBLIQUITY POINTS

\bar{P}	=	35.93
\bar{Q}	=	21.22

Initial Dial Reading (mil)	240
Dial Reading After Saturation (mil)	248
Dial Reading After Consolidation (mil)	534

LOAD (LB)	DEFORMATION (IN)	PORE PRESSURE (PSI)
18.4	0.000	50.0
19.6	0.001	50.1
24.2	0.002	50.4
75.0	0.008	55.6
110.6	0.014	61.1
135.6	0.020	65.6
161.7	0.030	70.6
180.1	0.039	74.2
196.7	0.051	77.9
215.8	0.072	82.0
232.3	0.102	85.4
245.0	0.140	87.7
254.1	0.177	89.1
261.8	0.220	89.9
266.9	0.251	90.4
272.6	0.294	90.6
278.9	0.353	90.9
284.3	0.414	90.9
287.0	0.460	90.9
288.7	0.522	90.8
290.2	0.568	90.7
292.0	0.614	90.7
293.5	0.660	90.5
294.3	0.691	90.6
295.7	0.722	90.6
296.6	0.753	90.5
297.5	0.783	90.5
299.3	0.830	90.4
301.4	0.876	90.4
302.0	0.908	90.3
302.7	0.938	90.3

Tested By: 129-07-0411 Date: 4/27/22 Input Checked By: GEM Date: 5/5/22

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS**
AASHTO T-297

Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001

Visual Description: Orange Clayey Silt (UNDISTURBED)

Effective Confining Pressure (psi)	55.6	Stage No.	0
		Test No.	3

INITIAL DIMENSIONS

Initial Sample Length (in)	6.14
Initial Sample Diameter (in)	2.83
Initial Sample Area (in ²)	6.28
Initial Sample Volume (in ³)	38.55


VOLUME CHANGE

Volume After Consolidation (in ³)	34.06
Length After Consolidation (in)	5.84
Area After Consolidation (in ²)	5.830

Strain (%)	Deviator Stress PSI	ΔU	$\bar{\sigma}_1$	$\bar{\sigma}_3$	Effective Principal Stress Ratio	\bar{A}	\bar{P}	\bar{Q}
0.02	0.20	0.09	55.71	55.5	1.004	0.48	55.61	0.10
0.04	0.99	0.45	56.14	55.2	1.018	0.47	55.65	0.49
0.14	9.69	5.64	59.65	50.0	1.194	0.60	54.80	4.84
0.24	15.77	11.10	60.27	44.5	1.354	0.73	52.39	7.88
0.34	20.03	15.58	60.05	40.0	1.501	0.80	50.03	10.01
0.51	24.45	20.60	59.45	35.0	1.699	0.87	47.22	12.23
0.66	27.54	24.22	58.92	31.4	1.878	0.91	45.15	13.77
0.87	30.32	27.88	58.04	27.7	2.094	0.95	42.88	15.16
1.23	33.43	32.02	57.01	23.6	2.418	0.99	40.29	16.71
1.75	36.04	35.45	56.19	20.2	2.788	1.01	38.17	18.02
2.40	37.93	37.69	55.84	17.9	3.117	1.02	36.88	18.96
3.03	39.20	39.08	55.72	16.5	3.373	1.03	36.12	19.60
3.76	40.17	39.88	55.90	15.7	3.555	1.02	35.81	20.09
4.29	40.78	40.35	56.03	15.2	3.675	1.02	35.64	20.39
5.03	41.40	40.63	56.37	15.0	3.765	1.01	35.67	20.70
6.04	41.98	40.85	56.73	14.7	3.846	1.00	35.74	20.99
7.09	42.37	40.90	57.07	14.7	3.884	1.00	35.88	21.19
7.88	42.44	40.89	57.15	14.7	3.886	0.99	35.93	21.22
8.93	42.23	40.76	57.07	14.8	3.845	1.00	35.96	21.11
9.73	42.08	40.73	56.96	14.9	3.829	1.00	35.92	21.04
10.51	42.00	40.67	56.93	14.9	3.814	1.00	35.93	21.00
11.31	41.84	40.52	56.92	15.1	3.775	1.00	36.00	20.92
11.83	41.72	40.60	56.73	15.0	3.781	1.00	35.86	20.86
12.35	41.69	40.59	56.70	15.0	3.778	1.00	35.85	20.85
12.89	41.56	40.53	56.63	15.1	3.758	1.01	35.85	20.78
13.41	41.45	40.47	56.58	15.1	3.740	1.01	35.86	20.73
14.21	41.34	40.45	56.49	15.2	3.729	1.01	35.82	20.67
15.00	41.26	40.38	56.47	15.2	3.711	1.01	35.85	20.63
15.54	41.09	40.32	56.36	15.3	3.689	1.01	35.82	20.54
16.06	40.93	40.28	56.26	15.3	3.672	1.01	35.79	20.47

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS
AASHTO T-297**

Client: Kleinfelder Boring No.: EB1-B
 Client Reference: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001
 Visual Description: Orange Clayey Silt (UNDISTURBED)



Tested By: 129-07-0411 Date: 4/27/22 Approved By: MPS Date: 5/5/22

**CONSOLIDATED UNDRAINED TRIAXIAL TEST
WITH PORE PRESSURE READINGS
ASTM D4767-11**

Client: Kleinfelder
 Client Reference: BR-0097
 Project No.: R-2022-091-002
 Lab ID: R-2022-091-002-001 Specific Gravity (assumed) 2.68
 Visual Description: Orange Clayey Silt (UNDISTURBED)

SAMPLE CONDITION SUMMARY

	EB1-B 21.0-23.0 ST-1	EB1-B 21.0-23.0 ST-1	EB1-B 21.0-23.0 ST-1
Boring No.:	EB1-B	EB1-B	EB1-B
Depth (ft):	21.0-23.0	21.0-23.0	21.0-23.0
Sample No.:	ST-1	ST-1	ST-1
Test No.	T1	T2	T3
Deformation Rate (in/min)	0.002	0.002	0.002
Back Pressure (psi)	50.0	50.0	50.0
Consolidation Time (days)	1	1	1
Moisture Content (%) (INITIAL)	47.8	47.8	47.8
Total Unit Weight (pcf)	100.6	103.9	108.5
Dry Unit Weight (pcf)	68.0	70.3	73.4
Moisture Content (%) (FINAL)	58.9	45.6	42.6
Initial State Void Ratio, e	1.459	1.381	1.279
Void Ratio at Shear, e	1.380	1.258	1.014



Tested By: 129-07-0411 Date: 4/27/22 Input Checked By: GEM Date: 5/5/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder
Client Project: BR-0097
Project No.: R-2022-091-002
Lab ID: R-2022-091-002-001

Boring No.: EB1-B
Depth (ft): 21.0-23.0
Sample No.: ST-1
Visual Description: Orange Elastic Silt


Client: Kleinfelder
Client Project: BR-0097
Project No.: R-2022-091-002
Lab ID: R-2022-091-002-001

Boring No.: EB1-B
Depth (ft): 21.0-23.0
Sample No.: ST-1
Visual Description: Orange Elastic Silt

Sample Conditions: Undisturbed, Inundated, Double Drained

Sample Conditions: Undisturbed, Inundated, Double Drained

Consolidometer No. R-409
1 Division = 0.0001 (in.)



Sample Properties

	Initial	Final
Water Content		
Tare Number	485	473
Wt. of Tare & WS (g)	412.41	222.53
Wt. of Tare & DS (g)	311.15	189.13
Wt. of Water (g)	101.26	33.40
Wt. of Tare (g)	99.33	97.81
Wt. of DS (g)	211.82	91.32
Water Content (%)	47.80	36.57

	Initial	Final
Sample Parameters		
Sample Diameter (in)	2.5	2.5
Sample Height (in)	1.0000	0.8286
Sample Volume (cm ³)	80.44	66.65
Wt. of Wet Sample + Ring (g)	347.89	337.77
Wt. of Ring (g)	214.67	214.67
Wt. of Wet Sample (g)	133.22	123.10
Wet Density (pcf)	103.34	115.24
Wet Density (g/cm ³)	1.66	1.85
Water Content (%)	47.80	36.57
Wt. of Dry Sample (g)	90.13	90.13
Dry Density (pcf)	69.92	84.38
Dry Density (g/cm ³)	1.12	1.35
Void Ratio	1.3918	0.9819
Saturation (%)	92.05	99.83
Specific Gravity	2.68	Assumed

Test Data Summary

Applied Pressure (tsf)	Final Dial Reading (div)	Machine Deflection (div)	Corrected Reading (div)	Height of Sample (mm)	Volume (cm ³)	Dry Density (g/cm ³)	Void Ratio
Seating	0	0	0	25.400	80.440	1.12050	1.39180
0.25	106.2	49.4	56.8	25.256	79.983	1.12689	1.37822
0.5	208.6	67.4	141.2	25.041	79.304	1.13655	1.35802
1	385.6	84.9	300.7	24.636	78.021	1.15523	1.31988
1.25	437.7	92.9	344.8	24.524	77.666	1.16051	1.30933
1	435.2	91.7	343.5	24.528	77.677	1.16035	1.30965
0.25	313.4	73.2	240.2	24.790	78.507	1.14808	1.33434
0.5	341.4	79.5	261.9	24.735	78.333	1.15063	1.32915
1	420.8	89.0	331.8	24.557	77.771	1.15895	1.31244
2	612.9	114.4	498.5	24.134	76.430	1.17929	1.27256
4	1033.5	148.1	885.5	23.151	73.317	1.22935	1.18001
8	1742.6	188.0	1554.6	21.451	67.934	1.32676	1.01996
16	2520.6	234.8	2285.7	19.594	62.053	1.45250	0.84510
4	2314.8	175.5	2139.3	19.966	63.232	1.42543	0.88013
1	2054.7	142.1	1912.6	20.542	65.055	1.38549	0.93434
0.25	1823.7	109.9	1713.8	21.047	66.654	1.35225	0.98188

Tested By MY Date 4/27/22 Approved By MPS Date 5/6/22

Tested By MY Date 4/27/22 Checked By MPS Date 5/6/22


ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216



Client: Kleinfelder
Client Project: BR-0097
Project No.: R-2022-091-002
Lab ID: R-2022-091-002-001

Boring No.: EB1-B
Depth (ft): 21.0-25.0
Sample No.: ST-1 & ST-2
Visual Description: Orange Elastic Silt

Sample Conditions: Undisturbed, Inundated, Double Drained



Tested By MY Date 4/27/22 Checked By MPS Date 5/6/22

ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216



Client: Kleinfelder
Client Project: BR-0097
Project No.: R-2022-091-002
Lab ID: R-2022-091-002-001

Boring No.: EB1-B
Depth (ft): 21.0-23.0
Sample No.: ST-1
Visual Description: Orange Elastic Silt

Sample Conditions: Undisturbed, Inundated, Double Drained
Consolidometer No. R-409
1 Division = 0.0001 (in.)

Sample Properties	Initial	Final
Water Content		
Tare Number	485	473
Wt. of Tare & WS (g)	412.41	222.53
Wt. of Tare & DS (g)	311.15	189.13
Wt. of Water (g)	101.26	33.40
Wt. of Tare (g)	99.33	97.81
Wt. of DS (g)	211.82	91.32
Water Content (%)	47.80	36.57
Sample Parameters		
Sample Diameter (in)	2.5	2.5
Sample Height (in)	1.0000	0.8286
Sample Volume (cm ³)	80.44	66.65
Wt. of Wet Sample + Ring (g)	347.89	337.77
Wt. of Ring (g)	214.67	214.67
Wt. of Wet Sample (g)	133.22	123.10
Wet Density (pcf)	103.34	115.24
Wet Density (g/cm ³)	1.66	1.85
Water Content (%)	47.80	36.57
Wt. of Dry Sample (g)	90.13	90.13
Dry Density (pcf)	69.92	84.38
Dry Density (g/cm ³)	1.12	1.35
Void Ratio	1.3918	0.9819
Saturation (%)	92.05	99.83
Specific Gravity	2.68	Assumed

C_v Test Data Summary


Load Increment (tsf)	Dial Reading @ t ₅₀ (div)	Machine Deflection (div)	Corrected Dial Reading @ t ₅₀ (div)	Sample Height @ t ₅₀ (cm)	Time t ₅₀ (min.)	C _v (cm ² /sec)
0 - 0.25	77.9	49.4	28.5	2.533	0.17	0.0310
0.25 - 0.5	176.6	67.4	109.1	2.512	0.14	0.0370
0.5 - 1	314.6	84.9	229.7	2.482	0.19	0.0266
1 - 1.25	421.6	92.9	328.7	2.457	1.10	0.0045
1.25 - 1	NA	91.7	NA	NA	NA	NA
1 - 0.25	NA	NA	NA	NA	NA	NA
0.25 - 0.5	NA	NA	NA	NA	NA	NA
0.5 - 1	405.7	89.0	316.7	2.460	0.19	0.0261
1 - 2	573.0	114.4	458.6	2.424	0.27	0.0179
2 - 4	899.1	148.1	751.0	2.349	0.15	0.0302
4 - 8	1532.2	188.0	1344.2	2.199	0.19	0.0209
8 - 16	2247.9	234.8	2013.1	2.029	0.16	0.0211
16 - 4	NA	175.5	NA	NA	NA	NA
4 - 1	NA	NA	NA	NA	NA	NA
1 - 0.25	NA	NA	NA	NA	NA	NA
0.25 - 0	NA	NA	NA	NA	NA	NA

Tested By MY Date 4/27/22 Checked By MPS Date 5/6/22

ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) **0 - 0.25**
 Final Reading (div) **106.2**
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 4/27/22
 Start Time 10:41:22

Elapsed Time (min)	Dial Reading (div)
Initial	0.0
0.10	70.1
0.20	81.6
0.23	83.8
0.27	86.4
0.32	87.3
0.37	87.4
0.43	88.4
0.52	89.4
0.63	89.9
1.42	92.4
2.67	94.5
5.18	97.2
12.78	100.5
20.15	102.1
31.83	102.8
40.02	102.4
63.32	103.9
79.65	104.5
100.23	105.1
126.13	106.0
158.72	106.0
199.77	106.5
251.43	107.3
316.47	107.6
398.35	107.7
501.43	107.3
631.22	106.7
720.17	106.2




Tested By 129-07-0411 Date 4/27/22 Checked By MPS Date 5/6/22

ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) **0.25 - 0.5**
 Final Reading (div) **208.6**
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 4/27/22
 Start Time 22:41:32

Elapsed Time (min)	Dial Reading (div)
Initial	106.2
0.10	169.4
0.20	185.8
0.23	186.0
0.27	186.1
0.32	185.6
0.37	186.0
0.43	186.2
0.52	186.4
1.13	190.2
2.15	193.4
4.15	195.0
10.18	197.6
16.05	198.5
25.32	200.3
31.83	200.7
50.33	201.4
63.32	201.6
79.67	202.5
100.23	202.3
126.13	202.9
158.73	203.4
199.78	203.9
251.45	204.3
316.48	205.5
398.37	206.5
501.45	206.7
627.53	208.6




Tested By 129-07-0411 Date 4/27/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 0.5 - 1
 Final Reading (div) 385.6
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/28/22
 Start Time 9:09:05

Elapsed Time (min)	Dial Reading (div)
Initial	208.6
0.10	324.7
0.20	342.7
0.22	342.7
0.27	343.1
0.30	346.4
0.37	348.1
0.43	349.2
0.52	350.7
1.13	353.4
2.15	355.7
4.15	358.3
10.17	361.1
16.03	363.1
25.30	366.1
31.82	366.5
50.32	370.1
63.30	370.3
79.63	371.3
100.22	371.6
126.12	374.0
158.72	374.4
199.75	377.1
251.42	379.1
316.47	381.9
398.35	385.2
501.43	385.8
631.20	385.3
720.37	385.6




Tested By '29-07-041' Date 4/28/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 1 - 1.25
 Final Reading (div) 437.7
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/28/22
 Start Time 21:09:27

Elapsed Time (min)	Dial Reading (div)
Initial	385.6
0.10	413.1
0.20	417.7
0.23	418.4
0.28	419.0
0.32	419.4
0.38	419.7
0.45	420.3
0.53	420.6
1.15	421.9
2.15	423.5
4.15	424.5
10.18	426.8
16.05	428.2
25.32	429.8
31.83	430.0
50.33	431.6
63.32	432.1
79.65	433.0
100.23	433.9
126.13	434.7
158.73	435.6
199.77	436.4
251.43	437.6
316.48	437.8
398.37	437.8
501.45	437.7




Tested By '29-07-041' Date 4/28/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 1.25 - 1
 Final Reading (div) 435.2
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/29/22
 Start Time 8:56:26

Elapsed Time (min)	Dial Reading (div)
Initial	437.7
0.10	431.8
0.20	431.6
0.23	431.7
0.27	431.1
0.32	430.9
0.37	431.1
0.43	430.9
0.52	431.0
1.13	430.8
2.15	431.1
4.15	431.1
10.18	430.7
16.05	430.6
25.32	430.7
31.83	430.7
50.33	430.8
63.32	430.8
79.65	430.8
100.23	430.7
126.13	430.8
158.73	431.2
199.77	433.5
251.43	434.8
279.33	435.2




Tested By '29-07-041' Date 4/29/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 1 - 0.25
 Final Reading (div) 313.4
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/29/22
 Start Time 13:35:47

Elapsed Time (min)	Dial Reading (div)
Initial	435.2
0.10	362.0
0.20	341.9
0.23	339.9
0.27	338.3
0.30	337.9
0.37	336.2
0.43	335.3
0.52	334.3
1.13	331.1
2.15	328.8
4.15	326.3
10.18	323.8
16.03	322.7
25.32	322.1
31.82	321.8
50.33	319.4
63.32	319.2
79.65	318.7
100.23	318.2
126.13	317.4
158.73	317.4
199.77	317.2
251.43	316.3
316.48	316.0
398.37	314.9
501.45	315.1
631.22	313.9
720.48	313.4




Tested By '29-07-041' Date 4/29/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 0.25 - 0.5
 Final Reading (div) 341.4
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/30/22
 Start Time 1:36:16

Elapsed Time (min)	Dial Reading (div)
Initial	313.4
0.10	334.7
0.20	337.5
0.23	337.8
0.28	337.7
0.32	338.0
0.38	337.8
0.45	338.3
0.53	338.0
1.15	338.8
2.17	339.0
4.17	339.4
10.20	340.0
16.05	339.9
25.33	340.1
31.83	340.4
50.33	340.9
63.32	341.2
79.67	341.1
100.23	341.4
126.13	341.4
158.73	340.9
199.78	341.8
251.45	341.4
316.48	341.2
398.37	341.3
420.42	341.4




Tested By '29-07-041' Date 4/30/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 0.5 - 1
 Final Reading (div) 420.8
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/30/22
 Start Time 8:36:42

Elapsed Time (min)	Dial Reading (div)
Initial	341.4
0.10	400.3
0.20	406.0
0.23	406.9
0.27	407.3
0.30	407.7
0.37	408.1
0.43	408.4
0.52	408.8
1.13	410.1
2.13	410.5
4.15	411.7
10.18	412.8
16.03	413.4
25.32	414.1
31.82	414.2
50.32	414.7
63.30	415.3
79.65	415.9
100.22	416.6
126.12	417.5
158.72	417.7
199.77	418.9
251.43	419.8
316.47	420.2
398.35	420.9
420.50	420.8



Tested By '29-07-041' Date 4/30/22 Checked By MPS Date 5/6/22




ONE DIMENSIONAL CONSOLIDATION

AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 1 - 2
 Final Reading (div) 612.9
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/30/22
 Start Time 15:37:13

Elapsed Time (min)	Dial Reading (div)
Initial	420.8
0.12	557.6
0.22	570.1
0.25	572.6
0.28	574.1
0.32	575.7
0.38	579.2
0.45	580.3
0.53	582.0
1.15	587.0
2.15	589.3
4.15	590.6
10.18	593.7
16.05	595.3
25.32	598.2
31.83	599.0
63.30	601.2
79.65	602.6
100.22	603.1
126.12	604.6
158.72	605.8
199.75	608.1
251.42	610.9
316.47	610.9
398.35	612.7
420.48	612.9



Tested By '29-07-041' Date 4/30/22 Checked By MPS Date 5/6/22




ONE DIMENSIONAL CONSOLIDATION

AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 2 - 4
 Final Reading (div) 1033.5
 Consolidometer No. R-409
 1 Division (in) 0.0001

Start Date 4/30/22
 Start Time 22:37:41

Elapsed Time (min)	Dial Reading (div)
Initial	612.9
0.10	876.4
0.20	927.3
0.23	934.1
0.27	938.1
0.30	944.0
0.37	948.8
0.43	951.6
0.52	955.9
1.13	972.5
2.15	979.1
4.15	986.0
10.18	995.9
16.05	1001.9
25.32	1006.4
31.83	1009.5
50.33	1013.2
63.32	1014.7
79.65	1016.2
100.23	1019.8
126.13	1021.5
158.73	1023.9
199.77	1026.4
251.43	1029.0
316.48	1033.5




Tested By '29-07-041' Date 4/30/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) **4 - 8**
 Final Reading (div) **1742.6**
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 5/1/22
 Start Time 5:38:00

Elapsed Time (min)	Dial Reading (div)
Initial	1033.5
0.10	1469.7
0.22	1549.8
0.25	1558.6
0.28	1565.7
0.32	1576.8
0.38	1590.1
0.45	1594.6
0.53	1600.5
1.15	1622.4
2.17	1640.3
4.17	1650.1
10.20	1662.4
16.05	1668.7
25.33	1676.4
31.85	1680.9
50.35	1690.2
63.33	1694.7
79.67	1696.7
100.25	1701.2
126.15	1703.1
158.75	1707.5
199.78	1712.5
251.45	1718.2
316.50	1726.2
398.38	1731.7
501.47	1736.4
631.23	1743.5
720.22	1742.6




Tested By '29-07-041' Date 5/1/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) **8 - 16**
 Final Reading (div) **2520.6**
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 5/1/22
 Start Time 17:38:13

Elapsed Time (min)	Dial Reading (div)
Initial	1742.6
0.10	2188.6
0.20	2285.9
0.23	2309.2
0.27	2325.1
0.32	2335.8
0.37	2352.4
0.43	2361.4
0.52	2373.7
1.13	2408.3
2.15	2425.5
4.15	2431.6
10.18	2451.2
16.05	2458.9
25.32	2465.9
31.83	2469.3
50.33	2475.5
63.32	2481.3
79.67	2487.6
100.23	2490.8
126.13	2493.4
158.73	2496.2
199.78	2498.5
251.45	2502.4
316.48	2507.3
398.37	2510.9
501.45	2516.8
631.23	2519.4
720.37	2520.6




Tested By '29-07-041' Date 5/1/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) **16 - 4**
 Final Reading (div) **2314.8**
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 5/2/22
 Start Time 5:38:36

Elapsed Time (min)	Dial Reading (div)
Initial	2520.6
0.10	2358.2
0.20	2346.8
0.23	2344.9
0.27	2342.7
0.32	2340.8
0.37	2338.6
0.45	2335.6
0.53	2333.1
1.15	2328.1
2.15	2325.0
4.15	2323.7
10.18	2321.9
16.05	2321.6
25.32	2319.8
31.83	2319.3
50.33	2317.5
63.32	2316.1
79.65	2316.0
100.23	2315.4
126.13	2314.8
158.73	2314.2
199.77	2311.7
251.43	2312.3
316.48	2312.4
398.37	2312.3
501.45	2314.5
533.77	2314.8




Tested By '29-07-041' Date 5/2/22 Checked By MPS Date 5/6/22



ONE DIMENSIONAL CONSOLIDATION
AASHTO T-216

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) **4 - 1**
 Final Reading (div) **2054.7**
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 5/2/22
 Start Time 14:32:23

Elapsed Time (min)	Dial Reading (div)
Initial	2314.8
0.12	2196.7
0.22	2168.5
0.25	2161.7
0.28	2157.7
0.32	2153.3
0.38	2141.3
0.45	2133.5
0.53	2127.7
1.15	2104.0
2.17	2095.4
4.17	2093.0
10.20	2087.1
16.05	2081.8
25.33	2075.1
31.83	2073.4
50.35	2069.9
63.33	2068.3
79.67	2067.2
100.25	2065.5
126.15	2065.1
158.75	2063.6
199.78	2061.4
251.45	2059.3
316.50	2055.7
398.38	2055.1
501.47	2054.5
631.23	2054.5
720.35	2054.7



Tested By '29-07-041' Date 5/2/22 Checked By MPS Date 5/6/22




ONE DIMENSIONAL CONSOLIDATION

ASTM D 2435-96 (SOP-S24A)

Client: Kleinfelder Boring No.: EB1-B
 Client Project: BR-0097 Depth (ft): 21.0-23.0
 Project No.: R-2022-091-002 Sample No.: ST-1
 Lab ID: R-2022-091-002-001 Visual Description: Orange Elastic Silt


Sample Conditions: Undisturbed, Inundated, Double Drained



Test Load (tsf) 1 - 0.25
Final Reading (div) 1823.7
 Consolidometer No. **R-409**
 1 Division (in) 0.0001

Start Date 5/3/22
 Start Time 2:32:43


Elapsed Time (min)	Dial Reading (div)
Initial	2054.7
0.10	2001.0
0.20	1974.8
0.23	1966.2
0.27	1958.5
0.30	1954.1
0.37	1950.6
0.43	1943.0
0.52	1935.7
1.13	1905.0
2.15	1888.4
4.15	1875.5
10.18	1861.2
16.05	1857.1
25.32	1854.9
31.83	1852.9
50.33	1846.4
63.32	1843.7
79.65	1837.2
100.23	1836.3
126.12	1834.9
158.72	1832.7
199.77	1831.0
251.43	1829.2
316.48	1828.0
398.35	1824.9
501.43	1823.6
631.22	1823.7



Tested By '29-07-041' Date 5/3/22 Checked By MPS Date 5/6/22

SITE PHOTOGRAPH

Bridge No. 178 on -L- (SR 1929) over US 29



Looking Southwest Towards Bent No. 1 at Bridge No. 178