	-	TRAFFIC WILL BE MAINTA	INED THROUGH	LANE CLOSURES			
	-	LOCAL ACCESS TO ALL RE AT ALL TIMES DURING CO		BUSINESSES WILL	. BE MAINT		
	-	CONTACT THE CENTURY CE (919)707-7370 TO COORD PROJECT TIP NO HL-0008	INATE THE PRO		-		
		GEN	ERAL	NOTES			
DRAN MEE ⁻ OF I	NING T F: DEV:	S MAY BE REQUIRED WHEN GS, STANDARD DETAILS, A IELD CONDITIONS OR RESU ICES. MODIFICATION MAY NG, OR REMOVAL OF DEVIC	ND ROADWAY DI ILT IN DUPLIC / INCLUDE: MO	ETAILS ARE NOT A ATE OR UNDESIRED /ING, SUPPLEMENT	ATTAINABLE D OVERLAPF TING,		
THE	COI	LLOWING GENERAL NOTES A NSTRUCTION PROJECT EXCE ED BY THE ENGINEER.					
TIMI	E RI	ESTRICTIONS					
A)	DO	NOT CLOSE OR NARROW TR	AVEL LANES AS	S FOLLOWS:			
		AD NAME 42		TIME RESTRICTIO FRIDAY 7:00 AM T 4:00 PM T			
3)		NOT CLOSE OR NARROW TF ENTS AS FOLLOWS:	AVEL LANES DU	JRING HOLIDAYS A	ND SPECIA		
	ROAD NAME: NC 42						
	HOI	LIDAY					
	1.	FOR ANY UNEXPECTED OCC TRAFFIC VOLUMES, AS DI			LY HIGH		
	2.	FOR NEW YEAR'S, BETWEE TO 6:00 P.M. JANUARY 2 SATURDAY, SUNDAY, OR M TUESDAY.	ND. IF NEW	YEAR'S DAY IS ON	A FRIDAY		
	3.	FOR EASTER, BETWEEN TH 6:00 P.M. MONDAY.	IE HOURS OF 7	:00 A.M. THURSDA	AY AND		
	4.	FOR MEMORIAL DAY, BETW 6:00 P.M. TUESDAY.	EEN THE HOUR	S OF 7:00 A.M. F	RIDAY TO		
	5.	FOR INDEPENDENCE DAY, BEFORE INDEPENDENCE DA INDEPENDENCE DAY.					
		IF INDEPENDENCE DAY IS MONDAY THEN BETWEEN TH INDEPENDENCE DAY AND 6 DAY.	IE HOURS OF 7	:00 A.M. THE THU	JRSDAY BEF		
	6.	FOR LABOR DAY, BETWEEN 6:00 P.M. TUESDAY.	I THE HOURS OI	F 7:00 A.M. FRID)ay and		
	7.	FOR THANKSGIVING DAY, TO 6:00 P.M. MONDAY.	BETWEEN THE H	HOURS OF 7:00 A.	M. TUESDA		
	8.	FOR CHRISTMAS, BETWEEN BEFORE THE WEEK OF CHP TUESDAY AFTER THE WEEK	ISTMAS DAY A	ND 6:00 P.M. THE			
LANI	E Al	ND SHOULDER CLOSURE REG	UIREMENTS				
C)		MOVE LANE CLOSURE DEVIC RFORMED BEHIND THE LANE					

9/4/2024 X:\2016\TRI6.008.00 W-5601\W-5601EX\TMP\W5601EX TMP-1B.dgn

TAINED	D)	WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROAD STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECT BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.	WAY		OI PI T\ DI M/
Η	E)	WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWA STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECT BARRIER OR GUARDRAIL.	Y		
E TO PING		WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN T LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STAND DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BAR OR GUARDRAIL.	ARD		II L UI TI
F OR	F)	WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRA OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL L	WINGS,	M)	PI AI E TI PI
	G)	DO NOT WORK SIMULTANEOUSLY WITHIN 15 FT ON BOTH SIDES OF AN TRAVELWAY, RAMP, OR LOOP WITHIN THE SAME LOCATION UNLESS PROTECTED WITH GUARDRAIL OR BARRIER.	OPEN		OI TI FI (
M	PAV	EMENT EDGE DROP OFF REQUIREMENTS			P
AL	H)	BACKFILL AT A 6:1 SLOPE UP TO THE EDGE AND ELEVATION OF EXIS PAVEMENT IN AREAS ADJACENT TO AN OPENED TRAVEL LANE THAT HAS EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:			
		BACKFILL DROP-OFFS THAT EXCEED 2 INCHES ON ROADWAYS WITH POS SPEED LIMITS OF 45 MPH OR GREATER.	TED	TRA	
		BACKFILL DROP-OFFS THAT EXCEED 3 INCHES ON ROADWAYS WITH POS SPEED LIMITS LESS THAN 45 MPH.	TED	N)	II L E
SТ ′,		BACKFILL WITH SUITABLE COMPACTED MATERIAL, AS APPROVED BY TH ENGINEER, AT NO EXPENSE TO THE DEPARTMENT.	E		R((
WING	TRA	FFIC PATTERN ALTERATIONS		PAV	EMI
	I)	NOTIFY THE ENGINEER THIRTY (30) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.		0)	II M/
	SIG	NING			R(N(
AY	J)	INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.		P)	T L
	K)	ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING A TRAFFIC PATTERN.	NY	Q)	RI M/
FORE NCE	TRA	FFIC BARRIER			
AY	L)	INSTALL TEMPORARY BARRIER ACCORDING TO THE TRANSPORTATION MANAGEMENT PLANS A MAXIMUM OF TWO (2) WEEKS PRIOR TO BEGINNI WORK IN ANY LOCATION. ONCE TEMPORARY BARRIER IS INSTALLED AT LOCATION PROCEED IN A CONTINUOUS MANNER TO COMPLETE THE PROP WORK IN THAT LOCATION UNLESS OTHERWISE STATED IN THE TRANSPORTATION MANAGEMENT PLANS OR AS DIRECTED BY THE ENGINE	ANY OSED		
NG		DO NOT PLACE BARRIER DIRECTLY ON ANY SURFACE OTHER THAN ASPH CONCRETE.	ALT OR		
					:
			APPROVED:	Steve Mille 9FBC6C15CEEB	
ING O			DATE:		ALL
				SEAL	5



1 Glenwood Avenue Raleigh, NC 27603 Tel:919.789.9977 Fax:919.789.9591 License: F-0453

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SHEET NO.	PROJ. REFERENCE NO.
TMP-1B	W-5601EX

ONCE TEMPORARY BARRIER IS INSTALLED AT ANY LOCATION AND NO WORK IS PERFORMED BEHIND THE TEMPORARY BARRIER FOR A PERIOD LONGER THAN TWO (2) MONTHS, REMOVE / RESET TEMPORARY BARRIER AT NO COST TO THE DEPARTMENT UNLESS OTHERWISE STATED IN THE TRANSPORTATION MANAGEMENT PLANS, TEMPORARY BARRIER IS PROTECTING A HAZARD, OR AS DIRECTED BY THE ENGINEER.

INSTALL TEMPORARY BARRIER WITH THE TRAFFIC FLOW BEGINNING WITH THE UPSTREAM SIDE OF TRAFFIC. REMOVE TEMPORARY BARRIER AGAINST THE TRAFFIC FLOW BEGINNING WITH THE DOWNSTREAM SIDE OF TRAFFIC.

INSTALL AND SPACE DRUMS NO GREATER THAN TWICE THE POSTED SPEED LIMIT (55 MPH) TO CLOSE OR KEEP THE SECTION OF THE ROADWAY CLOSED JNTIL THE TEMPORARY BARRIER CAN BE PLACED OR AFTER THE TEMPORARY BARRIER IS REMOVED.

PROTECT THE APPROACH END OF MOVABLE/PORTABLE CONCRETE BARRIER AT ALL TIMES DURING THE INSTALLATION AND REMOVAL OF THE BARRIER BY EITHER A TRUCK MOUNTED ATTENUATOR (MAXIMUM 72 HOURS) OR A TEMPORARY CRASH CUSHION.

PROTECT THE APPROACH END OF MOVABLE/PORTABLE CONCRETE BARRIER FROM ONCOMING TRAFFIC AT ALL TIMES BY A TEMPORARY CRASH CUSHION UNLESS THE APPROACH END OF MOVABLE/PORTABLE CONCRETE BARRIER IS OFFSET FROM ONCOMING TRAFFIC AS FOLLOWS OR AS SHOWN IN THE PLANS: (SEE ALSO 1101.05)

OSTED SPEED LIMIT	MINIMUM OFFSET
40 OR LESS	15 FT
45 - 50	20 FT
55	25 FT
60 MPH OR HIGHER	30 FT

FIC CONTROL DEVICES

WHEN LANE CLOSURES ARE NOT IN EFFECT SPACE CHANNELIZING DEVICES IN WORK AREAS NO GREATER IN FEET THAN TWICE THE POSTED SPEED _IMIT (55 MPH) EXCEPT, 10 FT ON-CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN TRAVELWAY. REFER TO STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES SECTIONS 1130 (DRUMS), 1135 (CONES), AND 1180 (SKINNY DRUMS) FOR ADDITIONAL REQUIREMENTS.


MENT MARKINGS AND MARKERS

INSTALL TEMPORARY PAVEMENT MARKINGS AND TEMPORARY PAVEMENT MARKERS ON INTERIM LAYERS OF PAVEMENT AS FOLLOWS:

ROAD NAME	MARKING	MARKER
IC 42	PAINT	TEMPORARY RAISED

TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING _INES.

REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS BY THE END OF EACH DAY'S OPERATION.



TRANSPORTATION OPERATIONS PLAN