SHEET NUM	BER	SHEET
1 1-A 1-B 2A-1 THRU 2B-1 THRU 2C-1 THRU 2D-1 3B-1 3D-1 THRU 3G-1 3P-1 4-9 4A THRU 9 10-15 RW-01 THRU 4-9 4A THRU 9 10-15 RW-01 THRU EC-1 THRU EC-1 THRU EC-1 THRU SIGN-1 THRU UO-1 THRU W-1 THRU	2A-7 2B-8 2C-8 3D-7 A U RW-06 U TMP-24 U PMP-7 E-6 EC-15 RU SIGN-14 UC-21 UO-7 X-73 W-10	TITLE SHEET INDEX OF SHEETS, GENERAL NOTES AND STANDARD DF CONVENTIONAL SYMBOLS PAVEMENT SCHEDULE AND TYPICAL SECTIONS ROUNDABOUT AND INTERSECTION DETAIL SHEETS ROADWAY DETAIL SHEETS DRAINAGE DETAIL SHEET ROADWAY SUMMARIES DRAINAGE SUMMARIES GEOTECHNICAL SUMMARIES PARCEL INDEX SHEET PLAN SHEETS ROW PLAN SHEETS PROFILE SHEETS RIGHT OF WAY PLANS TRANSPORTATION MANAGEMENT PLANS PAVEMENT MARKING PLANS ELECTRICAL PLANS SIGNING PLANS UTILITY CONSTRUCTION PLANS UTILITY CONSTRUCTION PLANS CROSS-SECTION INDEX SHEET, CROSS-SECTION SUMMARE
		EFF. 01-16-2024 REV.
2024 ROAD	WAY ENGLISH ST	ANDARD DRAWINGS
The follo N. C. Dep and by re	wing Roadway S artment of Tro ference hereby	tandards as appear in "Roadway Standard Drawing Insportation - Raleigh, N. C., Dated January 16, are considered a part of these plans:
225.02 225.04 225.06 DIVISION 300.01 310.10 DIVISION 560.01 DIVISION 654.01 DIVISION 700.01 DIVISION 806.01	Guide for Gro Method of Obt Method of Gro 3 - PIPE CULVE Method of Pip Driveway Pipe 5 - SUBGRADE, Method of Sho 6 - ASPHALT BA Pavement Repo 7 - CONCRETE P Concrete Pave 8 - INCIDENTAL	ading Subgrade - Secondary and Local aining Superelevation - Two Lane Pavement ading Sight Distance at Intersections RTS e Installation Construction BASES AND SHOULDERS pulder Construction - High Side of Superelevated SES AND PAVEMENTS airs AVEMENTS AND SHOULDERS ment Joints - Construction and Contraction Joints
806.02	Granite Right	-of-Way Marker -of-Way Marker
806.02 815.02 840.00 840.01 840.02 840.03 840.14 840.15 840.16 840.31	Granite Right Granite Right Subsurface Dr Concrete Base Brick Catch B Concrete Catc Frame, Grates Concrete Drop Brick Drop In Drop Inlet Fr Concrete Junc	-of-Way Marker -of-Way Marker ain Pad for Drainage Structures asin - 12" thru 54" Pipe A Basin - 12" thru 54" Pipe and Hood - for Use on Standard Catch Basin Inlet - 12" thru 30" Pipe ame and Grates - for use with Std. Dwg 840.14 of tion Box - 12" thru 66" Pipe D Box - 12" thru 66" Pipe
806.02 815.02 840.00 840.01 840.02 840.03 840.14 840.15 840.16 840.31 840.32 840.34 840.34 840.45 840.45 840.46 840.54 840.66 840.71 840.72 846.01	Granite Right Granite Right Subsurface Dr Concrete Base Brick Catch B Concrete Catc Frame, Grates Concrete Drop Brick Drop In Drop Inlet Fr Concrete Junc Brick Junctic Traffic Beari Precast Drain Traffic Beari Manhole Frame Drainage Stru Concrete and Pipe Collar	<ul> <li>it-of-Way Marker</li> <li>-of-Way Marker</li> <li>ain</li> <li>Pad for Drainage Structures</li> <li>asin - 12" thru 54" Pipe</li> <li>th Basin - 12" thru 54" Pipe</li> <li>and Hood - for Use on Standard Catch Basin</li> <li>Inlet - 12" thru 30" Pipe</li> <li>ame and Grates - for use with Std. Dwg 840.14 dettion Box - 12" thru 66" Pipe</li> <li>ng Junction Box - for Use with Pipes 42" and Ur</li> <li>age Structure</li> <li>ng Precast Drainage Structure</li> <li>and Cover</li> <li>and Cover</li></ul>

NU5536\_Rdy\_psh\_1A.dgn

Docusign Envelope ID: 7AF58538-C391-4448-800A-F881A0DE61EF

PROJECT REFERENCE NO. SHEET NO. U-5536 /-A GENERAL NOTES: 2024 SPECIFICATIONS DOCUMENT NOT CONSIDERED FINAL **UNLESS ALL SIGNATURES COMPLETED** EFFECTIVE: 01-16-2024 ROADWAY DESIGN REVISED: ENGINEER TANDARD DRAWINGS "TH CARD GRADING AND SURFACING OR RESURFACING AND WIDENING: ×12/19/2024 SEAL THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED 033400 SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE Davide & ZhetsE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN. CDM Smith Inc. 5400 Glenwood Aver Smith Smith Raleigh, NC 27612-: NC COA No. F-1255 CLEARING: CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II. SUPERELEVATION: ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. ION SUMMARY, AND CROSS-SECTIONS SHOULDER CONSTRUCTION: ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01 SIDE ROADS: rd Drawings" Contracts Standards and Development Unit -THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE anuary 16, 2024 are applicable to this project SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED. SUBSURFACE DRAINS: SUBSURFACE DRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD, NO, 815,02 AT LOCATIONS DIRECTED BY THE ENGINEER. DRIVEWAYS: DRIVEWAYS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. 848.03 AT LOCATIONS SHOWN IN THE PLANS OR AS DIRECTED BY THE ENGINEER. erelevated Curve - Method I STREET TURNOUT: STREET RETURNS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD, NO, 848,04 USING THE RADII NOTED ON PLANS. ction Joints TEMPORARY SHORING: SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK" IN ACCORDANCE WITH SECTION 104-7. UTILITIES: UTILITY OWNERS ON THIS PROJECT ARE: DUKE ENERGY 840.14 and 840.15 THE CITY OF WINSTON SALEM PIEDMONT NATURAL GAS AT&T 42" and Under WINDSTREAM YADTEL SPECTRUM VERIZON ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS, EXCEPT AS SHOWN ON THE PLANS. RIGHT-OF-WAY MARKERS: ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY CONTRACT. CURB RAMPS: lexible Pavement CURB RAMPS ARE SHOWN ON THE PLANS AT APPROXIMATE LOCATIONS.

CURB RAMPS ARE SHOWN ON THE PLANS AT APPROXIMATE LOCATIONS. CONSTRUCT ALL CURB RAMPS ACCORDANCE WITH STD 848.06.