

SIGN NUMBER: 102	BACKG COLOR: Green	DESIGN BY: VHS	CHECKED BY:
TYPE: D	COPY COLOR: White	PROJECT ID: I-5979	LOCATION:
QUANTITY: 1			Nov 07, 2024
SIGN WIDTH: 7'-0"			DIV: 08
HEIGHT: 3'-0"			
TOTAL AREA: 21.0 Sq.Ft.			
BORDER TYPE: FLUSH			
RECESS: 0"			
WIDTH: 0.75"			
RADII: 2.75"			
NO. Z BARS:			
LENGTH:			

SYMBOL	X	Y	WID	HT
AR_FISHOOK	6	18.6	9.9	10.8
AR_Type D	69	3	6	9

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES:	
1. Legend and border (except those that are colored black) shall be direct applied Grade C sheeting. 2. Background shall be Grade C reflective sheeting. 3. Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.	

[illegible]

SIGN NUMBER: 304 TYPE: D QUANTITY: 2 SIGN WIDTH: 3'-6" HEIGHT: 1'-6" TOTAL AREA: 10.5 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 0.75" RADII: 1.5" NO. Z BARS: LENGTH:	BACKG COLOR: Green COPY COLOR: White <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>SYMBOL</th> <th>X</th> <th>Y</th> <th>WID</th> <th>HT</th> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table> MAT'L: 0.125" (3.2 mm) ALUMINUM	SYMBOL	X	Y	WID	HT																																														DESIGN BY: YHB PROJECT ID: I-5979 CHECKED BY: LOCATION: Jun 22, 2022 DIR: 08
SYMBOL	X	Y	WID	HT																																																

USE NOTES:

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.

BORDER
R=1.5"
TH=0.75"

Spacing Factor is 1 unless specified otherwise

[illegible]

SIGN DESIGNS