

REFERENCE: B-5895

PROJECT: 48088

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STRUCTURE
SUBSURFACE INVESTIGATION

COUNTY MADISON
PROJECT DESCRIPTION REPLACE BRDG #0067 ON
US-25/70 OVER THE FRENCH BROAD RIVER

CONTENTS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2-2A	LEGEND (SOIL & ROCK)
3	SITE PLAN
4-5	PROFILES
6-10	CROSS SECTIONS
11-22	BORE & CORE LOGS
23-33	CORE PHOTOGRAPHS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5895	1	33

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

-NCDOT-

DC CHEEK

CJ COFFEY

CD JOHNSON

DC ELLIOTT

INVESTIGATED BY NCDOT GEU /DCE

DRAWN BY DC ELLIOTT

CHECKED BY JC KUHNE

SUBMITTED BY JC KUHNE

DATE _____



DocuSigned by:
D. Clayton Elliott

FD421F60CB0E40E...
SIGNATURE DATE


10/26/2020
DATE

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																										
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (ASTM T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i>										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.										HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:										ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																										
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS										WEATHERING										WEATHERING																																																																																																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>% PASSING #10 #200</th> <td>50 MX</td> <td>30 MX</td> <td>15 MX</td> <td>25 MX</td> <td>50 MX</td> <td>10 MN</td> <td>35 MX</td> <td>35 MX</td> <td>35 MX</td> <td>35 MX</td> <td>35 MX</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> <td>36 MN</td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td>-</td> <td>6 MX</td> <td>-</td> <td>NP</td> <td>40 MX</td> <td>41 MN</td> <td>10 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> <td>40 MX</td> <td>41 MN</td> </tr> <tr> <th>GROUP INDEX</th> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>4 MX</td> <td>0</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>NO MX</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td>STONE FRAGS. GRAVEL, AND SAND</td> <td>FINE SAND</td> <td>SILTY OR CLAYEY GRAVEL AND SAND</td> <td>SILTY SOILS</td> <td>CLAYEY SOILS</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="5">EXCELLENT TO GOOD</td> <td colspan="5">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td>UNSATURABLE</td> </tr> </table>										GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	SYMBOL																% PASSING #10 #200	50 MX	30 MX	15 MX	25 MX	50 MX	10 MN	35 MX	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN	MATERIAL PASSING #40 LL PI	-	6 MX	-	NP	40 MX	41 MN	10 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	GROUP INDEX	0	0	0	0	0	4 MX	0	8 MX	12 MX	16 MX	NO MX	0	0	0	0	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE	<p style="text-align: center;">MINERALOGICAL COMPOSITION</p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p style="text-align: center;">COMPRESSION</p> <p>SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50</p>										<p style="text-align: center;">PERCENTAGE OF MATERIAL</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE
GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																														
GROUP CLASS.	A-1	A-3	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																									
SYMBOL																																																																																																																																																																																								
% PASSING #10 #200	50 MX	30 MX	15 MX	25 MX	50 MX	10 MN	35 MX	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	36 MN																																																																																																																																																																									
MATERIAL PASSING #40 LL PI	-	6 MX	-	NP	40 MX	41 MN	10 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN	40 MX	41 MN																																																																																																																																																																									
GROUP INDEX	0	0	0	0	0	4 MX	0	8 MX	12 MX	16 MX	NO MX	0	0	0	0																																																																																																																																																																									
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER																																																																																																																																																																									
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD					FAIR TO POOR					FAIR TO POOR	POOR	UNSATURABLE																																																																																																																																																																											
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																					
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																																																																																																					
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																																																																																																					
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																																																																																																					
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																																																																																																					
TEXTURE OR GRAIN SIZE										MISCELLANEOUS SYMBOLS										ROCK HARDNESS										RECOMMENDATION SYMBOLS																																																																																																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> <tr> <td></td> <td>IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005		IN.	12	3															<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>VERY HARD</th> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> </tr> <tr> <th>HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> </tr> <tr> <th>MODERATELY HARD</th> <td>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> </tr> <tr> <th>MEDIUM HARD</th> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> </tr> <tr> <th>SOFT</th> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> </tr> <tr> <th>VERY SOFT</th> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> </tr> <tr> <th>COMPLETE</th> <td>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</td> </tr> </table>										VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.	COMPLETE	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.	<p style="text-align: center;">ABBREVIATIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>AR - AUGER REFUSAL</td> <td>MED. - MEDIUM</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>MICA - MICACEOUS</td> <td>WEA. - WEATHERED</td> </tr> <tr> <td>CL. - CLAY</td> <td>MOD. - MODERATELY</td> <td>UW - UNIT WEIGHT</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>NP - NON PLASTIC</td> <td>DW - DRY UNIT WEIGHT</td> </tr> <tr> <td>CSE. - COARSE</td> <td>ORG. - ORGANIC</td> <td>SAMPLE ABBREVIATIONS</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>PMT - PRESSUREMETER TEST</td> <td>S - BULK</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>SAP. - SAPROLITIC</td> <td>SS - SPLIT SPOON</td> </tr> <tr> <td>e - VOID RATIO</td> <td>SD. - SAND, SANDY</td> <td>ST - SHELBY TUBE</td> </tr> <tr> <td>F - FINE</td> <td>SL. - SILTY, SILTY</td> <td>RS - ROCK</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>SLI. - SLIGHTLY</td> <td>RT - RECOMPACTED TRIAXIAL</td> </tr> <tr> <td>FRAC. - FRACTURED, FRACTURES</td> <td>TCR - TRICONE REFUSAL</td> <td>CBR - CALIFORNIA BEARING RATIO</td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td>w - MOISTURE CONTENT</td> <td></td> </tr> <tr> <td>HI. - HIGHLY</td> <td>V - VERY</td> <td></td> </tr> </table>										AR - AUGER REFUSAL	MED. - MEDIUM	VST - VANE SHEAR TEST	BT - BORING TERMINATED	MICA - MICACEOUS	WEA. - WEATHERED	CL. - CLAY	MOD. - MODERATELY	UW - UNIT WEIGHT	CPT - CONE PENETRATION TEST	NP - NON PLASTIC	DW - DRY UNIT WEIGHT	CSE. - COARSE	ORG. - ORGANIC	SAMPLE ABBREVIATIONS	DMT - DILATOMETER TEST	PMT - PRESSUREMETER TEST	S - BULK	DPT - DYNAMIC PENETRATION TEST	SAP. - SAPROLITIC	SS - SPLIT SPOON	e - VOID RATIO	SD. - SAND, SANDY	ST - SHELBY TUBE	F - FINE	SL. - SILTY, SILTY	RS - ROCK	FOSS. - FOSSILIFEROUS	SLI. - SLIGHTLY	RT - RECOMPACTED TRIAXIAL	FRAC. - FRACTURED, FRACTURES	TCR - TRICONE REFUSAL	CBR - CALIFORNIA BEARING RATIO	FRAGS. - FRAGMENTS	w - MOISTURE CONTENT		HI. - HIGHLY	V - VERY																																																	
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																		
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																		
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																		
GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005																																																																																																																																																																																	
	IN.	12	3																																																																																																																																																																																					
VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.																																																																																																																																																																																							
HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.																																																																																																																																																																																							
MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.																																																																																																																																																																																							
MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.																																																																																																																																																																																							
SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.																																																																																																																																																																																							
VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																																																																																																																																																							
COMPLETE	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.																																																																																																																																																																																							
AR - AUGER REFUSAL	MED. - MEDIUM	VST - VANE SHEAR TEST																																																																																																																																																																																						
BT - BORING TERMINATED	MICA - MICACEOUS	WEA. - WEATHERED																																																																																																																																																																																						
CL. - CLAY	MOD. - MODERATELY	UW - UNIT WEIGHT																																																																																																																																																																																						
CPT - CONE PENETRATION TEST	NP - NON PLASTIC	DW - DRY UNIT WEIGHT																																																																																																																																																																																						
CSE. - COARSE	ORG. - ORGANIC	SAMPLE ABBREVIATIONS																																																																																																																																																																																						
DMT - DILATOMETER TEST	PMT - PRESSUREMETER TEST	S - BULK																																																																																																																																																																																						
DPT - DYNAMIC PENETRATION TEST	SAP. - SAPROLITIC	SS - SPLIT SPOON																																																																																																																																																																																						
e - VOID RATIO	SD. - SAND, SANDY	ST - SHELBY TUBE																																																																																																																																																																																						
F - FINE	SL. - SILTY, SILTY	RS - ROCK																																																																																																																																																																																						
FOSS. - FOSSILIFEROUS	SLI. - SLIGHTLY	RT - RECOMPACTED TRIAXIAL																																																																																																																																																																																						
FRAC. - FRACTURED, FRACTURES	TCR - TRICONE REFUSAL	CBR - CALIFORNIA BEARING RATIO																																																																																																																																																																																						
FRAGS. - FRAGMENTS	w - MOISTURE CONTENT																																																																																																																																																																																							
HI. - HIGHLY	V - VERY																																																																																																																																																																																							
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT										FRACTURE SPACING										BEDDING																																																																																																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td></td> </tr> <tr> <td></td> <td><input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE *STEEL TEETH</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE *TUNG-CARB.</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </table>										DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER		<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS		<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS			<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER			<input type="checkbox"/> TRICONE *STEEL TEETH			<input type="checkbox"/> TRICONE *TUNG-CARB.			<input type="checkbox"/> CORE BIT					<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>										TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET	<p style="text-align: center;">INDURATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>FRAGILE</th> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <th>MODERATELY INDURATED</th> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <th>INDURATED</th> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <th>EXTREMELY INDURATED</th> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										FRAGILE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																													
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																						
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																						
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																						
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																						
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																						
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																																						
<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																																						
<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER																																																																																																																																																																																							
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS																																																																																																																																																																																							
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS																																																																																																																																																																																							
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS																																																																																																																																																																																							
	<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER																																																																																																																																																																																							
	<input type="checkbox"/> TRICONE *STEEL TEETH																																																																																																																																																																																							
	<input type="checkbox"/> TRICONE *TUNG-CARB.																																																																																																																																																																																							
	<input type="checkbox"/> CORE BIT																																																																																																																																																																																							
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																					
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																					
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																					
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																					
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																					
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																					
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																					
FRAGILE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																																							
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																							
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																							
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																							
PLASTICITY										NOTES:										FRAC. SPACING										BEDDING																																																																																																																																																										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> </tr> <tr> <td>0-5</td> <td>6-15</td> <td>16-25</td> <td>26 OR MORE</td> </tr> <tr> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> <td></td> <td></td> </tr> <tr> <td></td> <td>VERY LOW</td> <td>SLIGHT</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td></td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC	0-5	6-15	16-25	26 OR MORE	PLASTICITY INDEX (PI)	DRY STRENGTH				VERY LOW	SLIGHT	MEDIUM				HIGH	<p>-BL-1- : N--801995.4316, E--867684.6623, ELEV=1333.17, -BL-STA II+63.14</p> <p>-BL-2- : N--801969.6447, E--868231.0760, ELEV=1343.52, -BL-STA I7+10.16</p> <p>-BY-5- : N--801930.6311, E--868178.8087, ELEV=1317.72, -BY-STA 6+85.50</p> <p>FIAD - FILLED IMMEDIATELY AFTER DRILLING</p>										<p>TERM SPACING</p> <p>VERY WIDE MORE THAN 10 FEET</p> <p>WIDE 3 TO 10 FEET</p> <p>MODERATELY CLOSE 1 TO 3 FEET</p> <p>CLOSE 0.16 TO 1 FOOT</p> <p>VERY CLOSE LESS THAN 0.16 FEET</p>										<p>TERM THICKNESS</p> <p>VERY THICKLY BEDDED 4 FEET</p> <p>THICKLY BEDDED 1.5 - 4 FEET</p> <p>THINLY BEDDED 0.16 - 1.5 FEET</p> <p>VERY THINLY BEDDED 0.03 - 0.16 FEET</p> <p>THICKLY LAMINATED 0.008 - 0.03 FEET</p> <p>THINLY LAMINATED < 0.008 FEET</p>																																																																																																																																						
NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC																																																																																																																																																																																					
0-5	6-15	16-25	26 OR MORE																																																																																																																																																																																					
PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																							
	VERY LOW	SLIGHT	MEDIUM																																																																																																																																																																																					
			HIGH																																																																																																																																																																																					
COLOR										RECOMMENDATION SYMBOLS										FRAC. SPACING										BEDDING																																																																																																																																																										
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>																				<p>TERM SPACING</p> <p>VERY WIDE MORE THAN 10 FEET</p> <p>WIDE 3 TO 10 FEET</p> <p>MODERATELY CLOSE 1 TO 3 FEET</p> <p>CLOSE 0.16 TO 1 FOOT</p> <p>VERY CLOSE LESS THAN 0.16 FEET</p>										<p>TERM THICKNESS</p> <p>VERY THICKLY BEDDED 4 FEET</p> <p>THICKLY BEDDED 1.5 - 4 FEET</p> <p>THINLY BEDDED 0.16 - 1.5 FEET</p> <p>VERY THINLY BEDDED 0.03 - 0.16 FEET</p> <p>THICKLY LAMINATED 0.008 - 0.03 FEET</p> <p>THINLY LAMINATED < 0.008 FEET</p>																																																																																																																																																										
PLASTICITY										RECOMMENDATION SYMBOLS										FRAC. SPACING										BEDDING																																																																																																																																																										
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>																				<p>TERM SPACING</p> <p>VERY WIDE MORE THAN 10 FEET</p> <p>WIDE 3 TO 10 FEET</p> <p>MODERATELY CLOSE 1 TO 3 FEET</p> <p>CLOSE 0.16 TO 1 FOOT</p> <p>VERY CLOSE LESS THAN 0.16 FEET</p>										<p>TERM THICKNESS</p> <p>VERY THICKLY BEDDED 4 FEET</p> <p>THICKLY BEDDED 1.5 - 4 FEET</p> <p>THINLY BEDDED 0.16 - 1.5 FEET</p> <p>VERY THINLY BEDDED 0.03 - 0.16 FEET</p> <p>THICKLY LAMINATED 0.008 - 0.03 FEET</p> <p>THINLY LAMINATED < 0.008 FEET</p>																																																																																																																																																										

SKEW : 65 DEGREES




NAD 83/NA 2011

17

20


20


22



PROJECT REFERENCE NO.	SHEET NO.
B-5895	4
-L- BRDG 0067 : STA 17+50 - 20+40	

- (A) ARTIFICIAL FILL: LOOSE SANDY-SILT, w/ a little PEBBLES/GRAVELS/COBBLES & trace of ORG'S
- (B) SAPROLITE: DENSE SANDY-SILT






PROJECT REFERENCE NO.	SHEET NO.
B-5895	5
-L- BRDG 0067 : STA 20+40 - 23+30	

- (A) SAPROLITE: DENSE CLAYEY-SILT, w/ ROCK FRAGS
- (B) WEATHERED ROCK: BLUE-GRAY SHADY DOLOMITE
- (C) ROADWAY EMBANKMENT: SOFT SANDY-SILT, w/ trace CLAY & some COBBLES


EB2-A
23+13
34' RT




6/23/16
I2-SEP-2019 10:41
C:\PROJECTS\STRUCTURES\B5895.GEO\BROD0067_MADISON\CAADD.GEOTECH\XSC\B5895.GEO_r.dwg_xsc.dgn
\$\$\$\$\$USERNAME\$\$\$\$\$

SKEW = 65 DEG.

- (A) ROADWAY EMBANKMENT: LOOSE SILTY, FINE to COURSE SAND
w/ a few PEBBLES/GRAVELS & trace of CLAY
- (B) ARTIFICIAL FILL: LOOSE SANDY-SILT,
w/ a little PEBBLES/GRAVELS/COBBLES & trace of ORG'S




SKEW = 65 DEG.



I2-SEP-2019 10:09 C:\PROJECTS\STRUCTURES\B5895.GEO_BROD0067_MADISON\CADD\GEO\TECH\XSC\B5895.GEO_r.dwg_xsc.dgn \$\$\$USERNAME\$\$\$

6/23/16
I2-SEP-2019 10:44
C:\PROJECTS\STRUCTURES\B5895.GEO_BROD0067_MADISON\CADD\GEO\TECH\XSC\B5895.GEO_r.dwg_xsc.dgn
\$\$\$\$\$USERNAME\$\$\$\$\$

SKEW = 65 DEG.




B.T. @
33.6'
IN
NON-CRYSTALLINE
ROCK

SECTION THRU BENT # 2

SKEW = 65 DEG.



SKEW = 65 DEG.



ALLUVIUM: MED DENSE to DENSE SILTY, FINE to COURSE SAND, GRAVELS & COBBLES & BOULDERS (AI)

ALLUVIUM: MED DENSE to DENSE (AI)




ALLUVIUM: MED DENSE to DENSE SILTY, FINE to COURSE SAND, GRAVELS & COBBLES & BOULDERS (AI)

EXISTING GROUND

AS-STAKED B3-A
B3-A
21+68
23' LT

B3-C
21+82
0.0' CL

AS-STAKED B3-B
B3-B (ALT)
21+88
19' RT




SECTION THRU BENT # 3
SKEW = 65 DEG.



- (A) SAPROLITE: STIFF to HARD SANDY-SILT w/ trace of a little CLAY, some ROCK FRAGMENTS
- (B) WEATHERED ROCK: DARK GRAY/BLUISH-GRAY, RIBBONED
- (C) RESIDUAL: IN-SITU, VERY SOFT to MED STIFF CLAY, w/ VARYING AMOUNTS of SILT, SAND, some ROCK FRAGMENTS
- (D) NON-CRYSTALLINE ROCK: GRAY/BLUISH-GRAY, RIBBONED; FRACTURED (SHADY DOLOMITE)

6/23/16
I:\2-SEP-2019 10:25
C:\PROJECTS\STRUCTURES\B5895.GEO\BROD0067_MADISON\CAADD.GEOTECH\XSC\B5895.GEO_r.dwg_xsc.dgn
\$\$\$\$\$USERNAME\$\$\$\$\$

SKEW = 65 DEG.



GEOTECHNICAL BORING REPORT BORE LOG

GEOTECHNICAL BORING REPORT CORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.									
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)								
BORING NO. B1-A		STATION 18+98		OFFSET 38 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 1,302.8 ft		TOTAL DEPTH 35.9 ft		NORTHING 801,992		EASTING 867,827									
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017			DRILL METHOD NW Casing WSPT & Core			HAMMER TYPE Automatic									
DRILLER Cheek, D. O.		START DATE 07/29/19		COMP. DATE 07/29/19		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
1305															
														1,302.8	0.0
1300															
1295	1,296.5	6.3	3	5	22										
1290	1,291.5	11.3	25	24	76/0.4										
	1,289.7	13.1												1,289.7	13.1
1285															
1280															
1275															
1270															
														1,266.9	35.9
Boring Terminated at Elevation 1,266.9 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE)															

NCDOT BORE DOUBLE B5895_BRDG0067_MADISON_BOREHOLES_UPDATED FALL 2020.GPJ NC_DOT.GDT 10/12/20

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.						
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)					
BORING NO. B1-A		STATION 18+98		OFFSET 38 ft LT		ALIGNMENT -L-						
COLLAR ELEV. 1,302.8 ft		TOTAL DEPTH 35.9 ft		NORTHING 801,992		EASTING 867,827						
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017			DRILL METHOD NW Casing WSPT & Core			HAMMER TYPE Automatic						
DRILLER Cheek, D. O.		START DATE 07/29/19		COMP. DATE 07/29/19		SURFACE WATER DEPTH N/A						
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		SAMP. NO.	STRATA		LOG	DESCRIPTION AND REMARKS	DEPTH (ft)
					REC. (%)	RQD (%)		REC. (%)	RQD (%)			
1289.65												
	1,289.7	13.1	2.8	N=60/0.0 1:41/0.8 1:28/1.0 1:51/1.0	(1.2) 43%	(0.7) 25%					Continued from previous page	
1285	1,286.9	15.9	5.0	2:13/1.0 1:21/1.0 2:02/1.0 0:51/1.0 1:23/1.0	(1.5) 30%	W.R. (0.8) 16%					NON-CRYSTALLINE ROCK	13.1
1280	1,281.9	20.9	5.0	1:44/1.0 1:28/1.0 NA/1.0 2:06/1.0 1:02/1.0	(2.5) 50%	(1.2) 24%						
1275	1,276.9	25.9	5.0	0:32/1.0 0:45/1.0 1:37/1.0 1:29/1.0 2:31/1.0	(1.6) 32%	(1.1) 22%						
1270	1,271.9	30.9	5.0	1:27/1.0 NA/1.0 NA/1.0 NA/1.0	(1.5) 30%	(0.0) 0%					GSI : 10-20	
	1,266.9	35.9										
Boring Terminated at Elevation 1,266.9 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE)												

NCDOT CORE DOUBLE B5895_BRDG0067_MADISON_BOREHOLES_UPDATED FALL 2020.GPJ NC_DOT.GDT 10/12/20

GEOTECHNICAL BORING REPORT BORE LOG

GEOTECHNICAL BORING REPORT CORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.								
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)							
BORING NO. B2-A		STATION 20+38		OFFSET 38 ft LT		ALIGNMENT -L-								
COLLAR ELEV. 1,303.0 ft		TOTAL DEPTH 33.6 ft		NORTHING 801,977		EASTING 867,966								
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017		DRILL METHOD NW Casing W/SPT & Core		HAMMER TYPE Automatic										
DRILLER Cheek, D. O.		START DATE 07/30/19		COMP. DATE 07/30/19		SURFACE WATER DEPTH N/A								
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				
1305														1,303.0 GROUND SURFACE 0.0
1300														1,301.7 ALLUVIAL BROWN/TAN/GRAY, LOOSE, SILTY, FINE-TO-COURSE SAND, w/ trace of GRAVELS & COBBLES 1.3
1295														1,299.0 ALLUVIAL GRAY/BLuish GRAY/BROWN, SILTY, FINE-TO-COURSE SAND, w/ several BOULDERS 4.0
1290	1,294.0	9.0												1,294.0 ALLUVIAL BROWN/TAN/GRAY, LOOSE, SILTY, FINE-TO-COURSE SAND, w/ trace of GRAVELS & COBBLES 9.0
1285														NON-CRYSTALLINE ROCK GREY/BLuish-GREY HIGHLY FRACTURED (DOLOMITE), **with ZONES OF CLAY IN-FILL, ROCK FRAGMENTS, THROUGH-OUT RECOVERY **
1280														
1275														
1270														1,269.4 Boring Terminated at Elevation 1,269.4 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE) 33.6

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.	
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)
BORING NO. B2-A		STATION 20+38		OFFSET 38 ft LT		ALIGNMENT -L-	
COLLAR ELEV. 1,303.0 ft		TOTAL DEPTH 33.6 ft		NORTHING 801,977		EASTING 867,966	
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017		DRILL METHOD NW Casing W/SPT & Core		HAMMER TYPE Automatic			
DRILLER Cheek, D. O.		START DATE 07/30/19		COMP. DATE 07/30/19		SURFACE WATER DEPTH N/A	
CORE SIZE NXWL			TOTAL RUN 23.9 ft				
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (%)	RQD (%)	STRATA REC. (%)
1293.27	1,293.3	9.7	3.9	2:22/0.9 1:58/1.0	(1.9) 49%	(1.2) 31%	
1290	1,289.4	13.6	5.0	1:24/1.0 3:26/1.0	(4.2) 84%	(2.4) 48%	
1285	1,284.4	18.6	5.0	1:53/1.0 2:10/1.0 1:44/1.0 1:43/1.0 2:32/1.0	(2.7) 54%	(1.4) 28%	
1280	1,279.4	23.6	5.0	1:08/1.0 1:06/1.0 2:29/1.0 1:26/1.0 2:49/1.0	(3.0) 60%	(1.1) 22%	
1275	1,274.4	28.6	5.0	1:45/1.0 1:52/1.0 1:32/1.0 1:43/1.0 2:02/1.0	(4.0) 80%	(2.6) 52%	
1270	1,269.4	33.6		1:51/1.0 1:49/1.0 1:32/1.0 1:44/1.0 2:10/1.0			
GSI : 9.7' - 23.6' : 20 - 30 23.6' - 33.6' : 15 - 25 *w/ CLAY IN-FILL ZONES							
Boring Terminated at Elevation 1,269.4 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE)							

GEOTECHNICAL BORING REPORT

CORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.					
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)				
BORING NO. B3-A		STATION 21+68		OFFSET 23 ft LT		ALIGNMENT -L-					
COLLAR ELEV. 1,309.0 ft		TOTAL DEPTH 89.3 ft		NORTHING 801,947		EASTING 868,094					
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017				DRILL METHOD NW Casing WSPT & Core		HAMMER TYPE Automatic					
DRILLER Cheek, D. O.		START DATE 07/25/19		COMP. DATE 07/26/19		SURFACE WATER DEPTH N/A					
CORE SIZE NXWL		TOTAL RUN 62.9 ft									
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		STRATA		LOG	DESCRIPTION AND REMARKS	DEPTH (ft)
					REC. (%)	RQD (%)	REC. (%)	RQD (%)			
282.6										Continued from previous page	
1280	1,282.6	26.4	2.9	0:30/0.9 2:37/1.0 2:40/1.0	(1.5) 52%	(1.1) 38%				NON-CRYSTALLINE ROCK (continued)	
1275	1,279.7	29.3	5.0	1:35/1.0 2:54/1.0 2:04/1.0 1:14/1.0 2:04/1.0	(4.3) 86%	(3.8) 76%					
1270	1,274.7	34.3	5.0	0:45/1.0 1:22/1.0 NA/1.0 1:36/1.0 1:49/1.0	(2.9) 58%	(2.0) 40%				RESIDUAL NON-CRYSTALLINE ROCK	35.3 36.3
1265	1,269.7	39.3	5.0	0:30/1.0 0:28/1.0 4:32/1.0 2:11/1.0 2:17/1.0	(2.0) 40%	(1.1) 22%				RESIDUAL NON-CRYSTALLINE ROCK	39.3 41.3
1260	1,264.7	44.3	5.0	1:57/1.0 0:21/1.0 1:00/1.0 1:32/1.0 1:58/1.0	(3.8) 76%	(2.7) 54%				RESIDUAL NON-CRYSTALLINE ROCK	45.4 46.3
1255	1,259.7	49.3	5.0	1:40/1.0 1:09/1.0 1:39/1.0 1:33/1.0 2:06/1.0	(4.1) 82%	(2.5) 50%				RESIDUAL NON-CRYSTALLINE ROCK	54.3 55.8
1250	1,254.7	54.3	5.0	NA/1.0 NA/1.0 NA/1.0 NA/1.0 NA/1.0	(2.3) 46%	(1.4) 28%				RESIDUAL NON-CRYSTALLINE ROCK	59.3 59.3
1245	1,249.7	59.3	5.0	NA/1.0 NA/1.0 NA/1.0 NA/1.0 NA/1.0	(1.4) 28%	(0.9) 18%				RESIDUAL NON-CRYSTALLINE ROCK	62.8 64.3 65.3
1240	1,244.7	64.3	5.0	4:02/1.0 1:47/1.0 1:41/1.0 0:25/1.0 0:49/1.0	(2.7) 54%	(1.8) 36%				RESIDUAL NON-CRYSTALLINE ROCK	68.3 68.3
1235	1,239.7	69.3	5.0	1:11/1.0 1:14/1.0 2:03/1.0 1:15/1.0 1:25/1.0	(3.4) 68%	(0.8) 16%				RESIDUAL NON-CRYSTALLINE ROCK	71.8 71.8
1230	1,234.7	74.3	5.0	1:35/1.0 3:45/1.0 1:56/1.0 1:34/1.0 2:14/1.0	(3.5) 70%	(2.7) 54%					
1225	1,229.7	79.3	5.0	1:54/1.0 2:49/1.0 2:24/1.0 1:46/1.0 2:56/1.0	(4.4) 88%	(3.9) 78%					
1220	1,224.7	84.3	5.0	2:43/1.0 3:09/1.0 1:23/1.0 1:49/1.0 1:35/1.0	(5.0) 100%	(4.7) 94%					
	1,219.7	89.3								Boring Terminated at Elevation 1,219.7 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE)	89.3
<p style="text-align: center;">GSI : 26.4' - 39.3' : 30-40 39.3' - 47.4' : 15-25 *CLAY IN-FILL 46.3' - 47.3' 47.4' - 52.5' : 30-40 52.5' - 54.3' : 45-55 54.3' - 75.0' : 10-15 *N.C.R. w/ SEVRL CLAY IN-FILL ZONES 75.0' - 89.3' : 40-50</p>											

NCDOT CORE DOUBLE B6895_BRD0067 MADISON BOREHOLES_UPDATED FALL 2020.GPJ_NC_DOT_GDT 10/12/20


GEOTECHNICAL BORING REPORT

BORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.									
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)								
BORING NO. B3-C		STATION 21+82		OFFSET CL		ALIGNMENT -L-									
COLLAR ELEV. 1,310.0 ft		TOTAL DEPTH 129.8 ft		NORTHING 801,923		EASTING 868,105									
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 94% 04/08/2019		DRILL METHOD NW Casing WSPT & Core		HAMMER TYPE Automatic											
DRILLER Cheek, D. O.		START DATE 09/25/20		COMP. DATE 09/28/20		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
1315															
1310														1,310.0	0.0
1305	1,305.5	4.5	14	15	15										
1300	1,300.5	9.5	6	7	4										
1295	1,295.5	14.5	2	30	54										
1290	1,290.5	19.5	6	6	10										
1285	1,287.0	23.0	4	5	5										
1280	1,280.5	29.5	1	11	17										
1275	1,275.5	34.5	2	4	5										
1270	1,270.5	39.5	17	20	63										
1265	1,265.5	44.5	25	7	10										
1260	1,260.5	49.5	37	63/0.3											
1255	1,255.5	54.5	28	10	11										
1250	1,250.5	59.5	96	10	14										
1245	1,245.5	64.5	10	16	22										
1240	1,240.5	69.5	53	47/0.1											
1235															

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.									
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)								
BORING NO. B3-C		STATION 21+82		OFFSET CL		ALIGNMENT -L-									
COLLAR ELEV. 1,310.0 ft		TOTAL DEPTH 129.8 ft		NORTHING 801,923		EASTING 868,105									
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 94% 04/08/2019		DRILL METHOD NW Casing WSPT & Core		HAMMER TYPE Automatic											
DRILLER Cheek, D. O.		START DATE 09/25/20		COMP. DATE 09/28/20		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
1235															
1230															
1225															
1220															
1215															
1210															
1205															
1200															
1195															
1190															
1185															

NCDOT BORE DOUBLE B5895_BRD0067_MADISON_BOREHOLES_UPDATED FALL 2020.GPJ NC_DOT_GDT_10/12/20



GEOTECHNICAL BORING REPORT

CORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.						
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)					
BORING NO. B3-C		STATION 21+82		OFFSET CL		ALIGNMENT -L-						
COLLAR ELEV. 1,310.0 ft		TOTAL DEPTH 129.8 ft		NORTHING 801,923		EASTING 868,105						
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 94% 04/08/2019				DRILL METHOD NW Casing W/SPT & Core		HAMMER TYPE Automatic						
DRILLER Cheek, D. O.		START DATE 09/25/20		COMP. DATE 09/28/20		SURFACE WATER DEPTH N/A						
CORE SIZE NXWL		TOTAL RUN 59.6 ft										
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		SAMP. NO.	STRATA		LOG	DESCRIPTION AND REMARKS	DEPTH (ft)
					REC. (%)	RQD (%)		REC. (%)	RQD (%)			
1239.84	1,239.8	70.2	4.6	0:35/0.6 0:59/1.0 0:48/1.0	(1.8)	(0.0)					Begin Coring @ 70.2 ft	70.2
					39%	0%					NON-CRYSTALLINE ROCK	71.7
											RESIDUAL	
1235	1,235.2	74.8		0:09/1.0 1:04/1.0								74.4
			5.0	1:32/1.0 0:24/1.0 0:12/1.0	(2.3)	(1.7)					NON-CRYSTALLINE ROCK	75.7
				1:25/1.0 3:13/1.0	46%	34%					RESIDUAL	
1230	1,230.2	79.8		2:18/1.0 1:16/1.0 1:21/1.0	(3.6)	(2.3)					NON-CRYSTALLINE ROCK	80.2
			5.0	2:23/1.0 2:56/1.0	72%	46%					RESIDUAL	82.4
1225	1,225.2	84.8		1:24/1.0 2:13/1.0 0:56/1.0	(4.4)	(3.4)					NON-CRYSTALLINE ROCK	86.8
			5.0	2:16/1.0 3:11/1.0	88%	68%					RESIDUAL	87.8
1220	1,220.2	89.8		2:13/1.0 2:31/1.0 1:05/1.0	(4.8)	(1.7)					NON-CRYSTALLINE ROCK	
			5.0	1:51/1.0 2:05/1.0	96%	34%					RESIDUAL	
1215	1,215.2	94.8		2:15/1.0 1:54/1.0 1:45/1.0	(4.4)	(3.1)						99.4
			5.0	2:23/1.0 0:33/1.0	88%	62%					RESIDUAL	100.3
1210	1,210.2	99.8		0:42/1.0 0:50/1.0 2:40/1.0	(3.5)	(1.4)					NON-CRYSTALLINE ROCK	
			5.0	1:30/1.0 2:06/1.0	70%	28%					RESIDUAL	
1205	1,205.2	104.8		2:11/1.0 2:01/1.0 1:15/1.0	(4.7)	(2.9)						108.5
			5.0	2:11/1.0 1:30/1.0	94%	58%					RESIDUAL	108.9
1200	1,200.2	109.8		3:24/1.0 0:47/1.0 0:03/1.0	(2.6)	(1.0)					NON-CRYSTALLINE ROCK	111.4
			5.0	0:08/1.0 2:26/1.0	52%	20%					RESIDUAL	
1195	1,195.2	114.8		0:38/1.0 1:00/1.0 0:46/1.0	(0.9)	(0.4)					NON-CRYSTALLINE ROCK	113.8
			5.0	0:03/1.0 0:09/1.0	18%	8%					RESIDUAL	114.8
1190	1,190.2	119.8		0:15/1.0 0:17/1.0 0:06/1.0	(0.0)	(0.0)					NON-CRYSTALLINE ROCK	116.0
			5.0	0:07/1.0 0:18/1.0	0%	0%					RESIDUAL	117.1
1185	1,185.2	124.8		0:07/1.0 1:02/1.0 1:27/1.0	(3.9)	(2.5)						125.3
			5.0	1:49/1.0 1:56/1.0	78%	50%					NON-CRYSTALLINE ROCK	127.4
											RESIDUAL	128.4
	1,180.2	129.8									NON-CRYSTALLINE ROCK	129.8
Boring Terminated at Elevation 1,180.2 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE)												
GSI : 70.2' - 78.4' : 10-20 * w/ CLAY IN-FILL ZONES 78.4' - 95.8' : 30-40 * w/ CLAY IN-FILL ZONES 95.8' - 109.8' : 35-45 109.8' - 117.1' : 10-20 *LOW RECOVERY 117.1' - 125.3' : CLAY IN-FILL, NO RECOVERY 125.3' - 129.8' : 30-40												

GEOTECHNICAL BORING REPORT

CORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.						
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)					
BORING NO. B3-B (ALT.)		STATION 21+88		OFFSET 19 ft RT		ALIGNMENT -L-						
COLLAR ELEV. 1,310.0 ft		TOTAL DEPTH 119.8 ft		NORTHING 801,903		EASTING 868,108						
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 94% 04/08/2019				DRILL METHOD NW Casing W/SPT & Core		HAMMER TYPE Automatic						
DRILLER Cheek, D. O.		START DATE 09/30/20		COMP. DATE 09/30/20		SURFACE WATER DEPTH N/A						
CORE SIZE NXWL		TOTAL RUN 91.5 ft										
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) %	RUN RQD (ft) %	SAMP. NO.	STRATA REC. (ft) %	RQD (ft) %	LOG	DESCRIPTION AND REMARKS	DEPTH (ft)
1281.69	1,281.7	28.3	1.5	N=60/0.0 2:51/1.5	(1.5) 100%	(0.5) 33%					Begin Coring @ 28.3 ft	28.3
1280	1,280.2	29.8	5.0	1:37/1.0 1:27/1.0 0:55/1.0 1:49/1.0	(4.7) 94%	(2.7) 54%					CRYSTALLINE ROCK	
1275	1,275.2	34.8	5.0	1:25/1.0 0:15/1.0 0:15/1.0 0:43/1.0	(3.3) 66%	(0.9) 18%					RESIDUAL	35.9
1270	1,270.2	39.8	5.0	0:59/1.0 0:09/1.0 1:27/1.0 0:48/1.0 0:26/1.0	(2.3) 46%	(1.5) 30%					CRYSTALLINE ROCK	40.5
1265	1,265.2	44.8	5.0	NA/1.0 0:18/1.0 0:17/1.0 0:31/1.0 0:20/1.0	(0.7) 14%	(0.0) 0%					RESIDUAL	41.8
1260	1,260.2	49.8	5.0	0:15/1.0 0:11/1.0 1:42/1.0 0:40/1.0 1:12/1.0	(1.5) 30%	(0.7) 14%					CRYSTALLINE ROCK	43.4
1255	1,255.2	54.8	5.0	1:36/1.0 1:55/1.0 1:40/1.0 2:10/1.0 0:10/1.0	(4.5) 90%	(0.4) 8%					RESIDUAL	51.8
1250	1,250.2	59.8	5.0	NA/1.0 NA/1.0 NA/1.0 0:54/1.0 0:02/1.0	(0.0) 0%	(0.0) 0%					CRYSTALLINE ROCK	55.2
1245	1,245.2	64.8	5.0	0:09/1.0 0:58/1.0 0:16/1.0 0:07/1.0 0:11/1.0	(0.3) 6%	(0.0) 0%					RESIDUAL	55.7
1240	1,240.2	69.8	5.0	0:27/1.0 0:47/1.0 1:22/1.0 1:08/1.0 2:09/1.0	(3.5) 70%	(0.4) 8%					CRYSTALLINE ROCK	59.8
1235	1,235.2	74.8	5.0	1:47/1.0 2:18/1.0 2:51/1.0 2:21/1.0 NA/1.0	(1.1) 22%	(0.4) 8%					RESIDUAL	71.3
1230	1,230.2	79.8	5.0	NA/1.0 NA/1.0 NA/1.0 NA/1.0 NA/1.0	(1.9) 38%	(0.9) 18%					CRYSTALLINE ROCK	74.8
1225	1,225.2	84.8	5.0	1:56/1.0 1:38/1.0 1:28/1.0 1:10/1.0 0:49/1.0	(4.2) 84%	(1.0) 20%					RESIDUAL	78.7
1220	1,220.2	89.8	5.0	1:47/1.0 1:39/1.0 2:08/1.0 2:15/1.0 0:45/1.0	(5.0) 100%	(1.8) 36%					CRYSTALLINE ROCK	85.1
1215	1,215.2	94.8	5.0	1:12/1.0 1:39/1.0 1:43/1.0 2:14/1.0 2:06/1.0	(4.4) 88%	(2.8) 56%					RESIDUAL	87.3
1210	1,210.2	99.8	5.0	1:09/1.0 1:22/1.0 1:50/1.0 1:52/1.0 2:07/1.0	(4.5) 90%	(3.6) 72%					CRYSTALLINE ROCK	90.1
1205	1,205.2	104.8	5.0	0:58/1.0 1:31/1.0 0:32/1.0	(2.6) 52%	(2.6) 52%					RESIDUAL	90.9
											CRYSTALLINE ROCK	107.5

NCDOT CORE DOUBLE B5895_BRDG067_MADISON_BOREHOLES_UPDATED FALL 2020.GPJ NC_DOT_GDT 10/13/20

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.						
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)					
BORING NO. B3-B (ALT.)		STATION 21+88		OFFSET 19 ft RT		ALIGNMENT -L-						
COLLAR ELEV. 1,310.0 ft		TOTAL DEPTH 119.8 ft		NORTHING 801,903		EASTING 868,108						
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 94% 04/08/2019				DRILL METHOD NW Casing W/SPT & Core		HAMMER TYPE Automatic						
DRILLER Cheek, D. O.		START DATE 09/30/20		COMP. DATE 09/30/20		SURFACE WATER DEPTH N/A						
CORE SIZE NXWL		TOTAL RUN 91.5 ft										
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) %	RUN RQD (ft) %	SAMP. NO.	STRATA REC. (ft) %	RQD (ft) %	LOG	DESCRIPTION AND REMARKS	DEPTH (ft)
1201.69											Continued from previous page	
1200	1,200.2	109.8	5.0	0:07/1.0 0:08/1.0 0:06/1.0 1:15/1.0 1:02/1.0 2:04/1.0 1:42/1.0	(5.0) 100%	(3.9) 78%					RESIDUAL (continued)	111.0
1195	1,195.2	114.8	5.0	1:02/1.0 1:50/1.0 0:24/1.0 0:50/1.0 1:59/1.0	(3.6) 72%	(2.8) 56%					CRYSTALLINE ROCK	
	1,190.2	119.8									Boring Terminated at Elevation 1,190.2 ft IN NON-CRYSTALLINE ROCK (SHADY DOLOMITE)	119.8
											GSI : 28.3' - 35.9' : 20-30 35.9' - 39.5' : CLAY IN-FILL, SOME RECOVERY 39.5' - 59.8' : 5-10 *MULTI ZONES OF CLAY 59.8' - 71.3' : CLAY IN-FILL, NO RECOVERY 71.3' - 90.9' : 15-20 *w/ CLAY IN-FILL ZONES, 90.9' - 107.5' : 30-40 107.5' - 111.0' : *CLAY IN-FILL, LITTLE RECOVERY 111.0' - 119.8' : 30-40	

GEOTECHNICAL BORING REPORT

BORE LOG

GEOTECHNICAL BORING REPORT

CORE LOG

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.										
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)									
BORING NO. B3-B		STATION 21+90		OFFSET 23 ft RT		ALIGNMENT -L-										
COLLAR ELEV. 1,309.6 ft		TOTAL DEPTH 44.9 ft		NORTHING 801,899		EASTING 868,110										
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017				DRILL METHOD NW Casing WSPT & Core		HAMMER TYPE Automatic										
DRILLER Cheek, D. O.		START DATE 07/24/19		COMP. DATE 07/25/19		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
1310														1,309.6	GROUND SURFACE	0.0
1305	1,304.6	5.0	72	28/0.3											ALLUVIAL GRAY/BLUISH-GRAY/BROWN, MED DENSE to VERY DENSE, SILTY, FINE-to-COURSE SAND, GRAVELS/COBBLES & BOULDERS	
1300															100/0.8 BLDRS : BEGIN CORE @ 6.5'	
1295																
1290														1,294.7	WEATHERED ROCK	14.9
1285														1,292.8	NO RECOVERY : ASSUMED DARK GRAY W.R.	16.8
1280														1,290.7	NON-CRYSTALLINE ROCK GREY/BLUISH-GREY HIGHLY FRACTURED (DOLOMITE), **with ZONES OF CLAY IN-FILL, ROCK FRAGMENTS, THROUGH-OUT RECOVERY **	18.9
1275															RESIDUAL NO RECOVERY : CLAY IN-FILL MATERIALS	
1270														1,281.3	NON-CRYSTALLINE ROCK GREY/BLUISH-GREY FRACTURED	28.3
1265														1,279.7	RESIDUAL NO RECOVERY : CLAY IN-FILL MATERIALS	29.9
														1,277.7	NON-CRYSTALLINE ROCK GREY/BLUISH-GREY FRACTURED	31.9
														1,275.7	RESIDUAL NO RECOVERY : CLAY IN-FILL MATERIALS	33.9
														1,271.7	NON-CRYSTALLINE ROCK GREY/BLUISH-GREY FRACTURED	37.9
														1,268.7	RESIDUAL NO RECOVERY : CLAY IN-FILL MATERIALS	40.9
														1,264.7	Boring Terminated at Elevation 1,264.7 ft IN RESIDUAL CLAY-IN-FILL MATERIALS (IN-SITU)	44.9

WBS 48088.1.1		TIP B-5895		COUNTY MADISON		GEOLOGIST Johnson, C. D.						
SITE DESCRIPTION Replace Bridge No. 67 on US 25/70 over French Broad River and Private Drive							GROUND WTR (ft)					
BORING NO. B3-B		STATION 21+90		OFFSET 23 ft RT		ALIGNMENT -L-						
COLLAR ELEV. 1,309.6 ft		TOTAL DEPTH 44.9 ft		NORTHING 801,899		EASTING 868,110						
DRILL RIG/HAMMER EFF./DATE AFO8963 CME-550X 77% 07/31/2017				DRILL METHOD NW Casing WSPT & Core		HAMMER TYPE Automatic						
DRILLER Cheek, D. O.		START DATE 07/24/19		COMP. DATE 07/25/19		SURFACE WATER DEPTH N/A						
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		SAMP. NO.	STRATA		LOG	DESCRIPTION AND REMARKS	DEPTH (ft)
					REC. (%)	RQD (%)		REC. (%)	RQD (%)			
1303.12	1,303.1	6.5	3.4	3:35/1.0 0:23/1.0 0:33/1.4	(0.8) 24%	(0.6) 18%					Continued from previous page ALLUVIAL (continued)	
1300	1,299.7	9.9	5.0	0:20/1.0 0:35/1.0 1:13/1.0 2:11/1.0 0:32/1.0	(0.9) 18%	(0.0) 0%						
1295	1,294.7	14.9	5.0	0:50/1.0 0:50/1.0 1:43/1.0 2:27/1.0 0:42/1.0	(2.1) 42%	(1.5) 30%					WEATHERED ROCK	14.9
1290	1,289.7	19.9	5.0	0:55/1.0 0:09/1.0 0:35/1.0 0:20/1.0 0:32/1.0	(0.0) 0%	(0.0) 0%					NON-CRYSTALLINE ROCK	16.8
1285	1,284.7	24.9	5.0	0:15/1.0 0:15/1.0 0:55/1.0 2:09/1.0 1:15/1.0	(1.6) 32%	(0.4) 8%					RESIDUAL	18.9
1280	1,279.7	29.9	5.0	0:18/1.0 0:14/1.0 2:16/1.0 1:10/1.0 0:07/1.0	(0.9) 18%	(0.0) 0%					NON-CRYSTALLINE ROCK	28.3
1275	1,274.7	34.9	5.0	0:16/1.0 0:14/1.0 0:17/1.0 1:42/1.0 1:05/1.0	(1.1) 22%	(0.0) 0%					RESIDUAL	29.9
1270	1,269.7	39.9	5.0	1:19/1.0 0:07/1.0 0:09/1.0 0:11/1.0 0:28/1.0	(0.4) 8%	(0.0) 0%					NON-CRYSTALLINE ROCK	31.9
1265	1,264.7	44.9									RESIDUAL	33.9
											Boring Terminated at Elevation 1,264.7 ft IN RESIDUAL CLAY-IN-FILL MATERIALS (IN-SITU)	37.9
											GSI : 6.5; - 14.9' : ALLUVIUM 14.9' - 16.8' : WEATHERED ROCK, NO REC. 16.8' - 18.9' : 15-25 18.9' - 28.3' : CLAY IN-FILL, NO RECOVERY 28.3' - 44.9' : 10-15 (N.C.R. w/ CLAY IN-FILL)	40.9
												44.9


NCDOT BORE DOUBLE B5895_BRDG0067_MADISON_BOREHOLES_UPDATED FALL 2020.GPJ NC_DOT_GDT 10/12/20

NCDOT CORE DOUBLE B5895_BRDG0067_MADISON_BOREHOLES_UPDATED FALL 2020.GPJ NC_DOT_GDT 10/12/20

CORE PHOTOGRAPHS

B1-A

BOX 1 of 1 : 13.1 - 35.9 FEET



GEOLOGICAL STRENGTH INDEX: GSI
13.1' - 35.9' : 10 - 20

B2-A

BOX 1 of 2 : 9.7 - 23.6 FEET



GEOLOGICAL STRENGTH INDEX: GSI
9.7' - 23.6' : 20 - 30

CORE PHOTOGRAPHS

B2-A

BOX 2 of 2 : 23.6 - 33.6 FEET



GEOLOGICAL STRENGTH INDEX: GSI
23.6' - 33.6' : 15 - 25

CORE PHOTOGRAPHS

B3-A

BOX 1 of 5 : 26.4 - 39.3 FEET



GEOLOGICAL STRENGTH INDEX: GSI
26.4' - 39.3' : 35 - 45

B3-A

BOX 2 of 5 : 39.3 - 52.5 FEET



GEOLOGICAL STRENGTH INDEX: GSI
39.3' - 47.4' : 15 - 25 *CLAY IN-FILL 46.3'-47.3'
47.4' - 52.5' : 30 - 40

CORE PHOTOGRAPHS

B3-A


BOX 3 of 5 : 52.5 - 69.3 FEET



GEOLOGICAL STRENGTH INDEX: GSI
52.5' - 54.3' : 45 - 55
54.3' - 69.3' : 15 - 25*
*N.C.R. w/ CLAY IN-FILL ZONES

B3-A

BOX 4 of 5 : 69.3 - 82.6 FEET



GEOLOGICAL STRENGTH INDEX: GSI
69.3' - 75.0' : 10 - 20 *N.C.R. w/ CLAY IN-FILL ZONES
75.0' - 82.6' : 40 - 50

CORE PHOTOGRAPHS

B3-A

BOX 5 of 5 : 82.6 - 89.3 FEET




GEOLOGICAL STRENGTH INDEX: GSI
82.6' - 89.3' : 40 - 50

CORE PHOTOGRAPHS

B3-C


BOX 1 of 4 : 70.2' - 85.9' FEET



GEOLOGICAL STRENGTH INDEX: GSI
70.2' - 78.4' : 10-20 *w/ CLAY IN-FILL ZONES
78.4' - 85.9' : 30-40 *w/ CLAY IN-FILL ZONES

B3-C

BOX 2 of 4 : 85.9' - 95.8' FEET




GEOLOGICAL STRENGTH INDEX: GSI
85.9' - 95.8' : 30-40 *w/ CLAY IN-FILL ZONES

CORE PHOTOGRAPHS

B3-C


BOX 3 of 4 : 95.8' - 107.2' FEET



GEOLOGICAL STRENGTH INDEX: GSI
 95.8 - 107.2' : 35-45

B3-C


BOX 4 of 4 : 107.2' - 129.8' FEET



GEOLOGICAL STRENGTH INDEX: GSI
 107.2' - 109.8' : 35-45
 109.8' - 117.1' : 10-20 * LOW RECOVERY
 117.1 - 125.3' : CLAY IN-FILL, NO RECOVERY (SOME FROM 124.8' to 125.3')
 125.3' - 129.8' : 30-40


CORE PHOTOGRAPHS

B3-B ALT
BOX 1 of 6 : 28.3' - 39.8' FEET



GEOLOGICAL STRENGTH INDEX: GSI
28.3' - 35.9' : 20-30
35.9' - 39.5' : CLAY IN-FILL, SOME RECOVERY

B3-B ALT
BOX 2 of 6 : 39.8' - 69.8' FEET




GEOLOGICAL STRENGTH INDEX: GSI
39.8' - 59.8' : 5-15 *ZONES OF FRACTURED N.C.R. w/ CLAY IN-FILL, LOW to MOD RECOVERY
59.8' - 69.8' : CLAY IN-FILL, NO RECOVERY (TRACE of REC. 64.8-69.8)

CORE PHOTOGRAPHS

B3-B ALT


BOX 3 of 6 : 69.8' - 88.6" FEET



GEOLOGICAL STRENGTH INDEX: GSI
69.8' - 71.3' : CLAY IN-FILL, SOME RECOVERY
71.3' - 88.6' : 15-20 *w/ CLAY IN-FILL ZONES

B3-B ALT

BOX 4 of 6 : 88.6' - 98.6' FEET




GEOLOGICAL STRENGTH INDEX: GSI
88.6' - 90.9' : 15-20 *w/ CLAY IN-FILL ZONES
90.9' - 98.6' : 30-40

CORE PHOTOGRAPHS

B3-B ALT


BOX 5 of 6 : 98.6'- 110.4' FEET



GEOLOGICAL STRENGTH INDEX: GSI
98.6' - 107.5' : 30-40
107.5' - 110.4' : CLAY IN-FILL, SOME RECOVERY

B3-B ALT

BOX 6 of 6 : 110.4' - 119.8' FEET




GEOLOGICAL STRENGTH INDEX: GSI
110.4' - 111.0' : CLAY IN-FILL
111.0' - 119.8' : 30-40

CORE PHOTOGRAPHS

B3-B


BOX 1 of 1 : 6.5 - 44.9 FEET



GEOLOGICAL STRENGTH INDEX: GSI
 16.8' - 19.9' : 30 - 40
 19.9' - 24.9' : Barrel had NO RECOVERY
 24.9' - 44.9' : 10 - 15

EB2-B

BOX 1 of 1 : 18.4 - 30.5 FEET



GEOLOGICAL STRENGTH INDEX: GSI
 21.0' - 30.5' : 45-55

REFERENCE: B-5895

PROJECT: 48088

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5895	1	9

STRUCTURE
SUBSURFACE INVESTIGATION

CONTENTS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	LEGEND
3	SITE PLAN
4	PROFILE
5-7	CROSS SECTIONS
8-9	BORE & CORE LOGS

COUNTY MADISON

PROJECT DESCRIPTION REPLACE BRIDGE # 0067 ON
US-25/70 OVER FRENCH BROAD RIVER

SITE DESCRIPTION RETAINING WALL 1
STATION 23+90 TO 27+50 RT

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

-NCDOT-

DC CHEEK

CJ COFFEY

CD JOHNSON

DC ELLIOTT


INVESTIGATED BY DC ELLIOTT

DRAWN BY DC ELLIOTT

CHECKED BY JC KUHNE

SUBMITTED BY JC KUHNE

DATE _____



DocuSigned by:
D. Clayton Elliott 6/4/2019

FD421F60081478E DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION		GRADATION		ROCK DESCRIPTION		TERMS AND DEFINITIONS																																																																																																																																																																																								
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</p>		<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>		<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>		<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																								
<p>SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">GENERAL CLASS.</th> <th colspan="6">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="6">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>A-1</th> <th>A-1-a</th> <th>A-1-b</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> </thead> <tbody> <tr> <td>GROUP CLASS.</td> <td colspan="2">A-1-a</td> <td colspan="2">A-1-b</td> <td colspan="2">A-2</td> <td colspan="2">A-4</td> <td colspan="2">A-5</td> <td colspan="2">A-7</td> <td colspan="3">A-1, A-2</td> <td colspan="3">A-3</td> </tr> <tr> <td>SYMBOL</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="3">[Symbol]</td> <td colspan="3">[Symbol]</td> </tr> <tr> <td>% PASSING #10 #40 #200</td> <td colspan="2">50 MX 30 MX 15 MX</td> <td colspan="2">50 MX 25 MX</td> <td colspan="2">51 MN 35 MX 35 MX</td> <td colspan="2">35 MX 35 MX</td> <td colspan="2">36 MN 36 MN</td> <td colspan="2">36 MN 36 MN</td> <td colspan="3">GRANULAR SOILS</td> <td colspan="3">SILT-CLAY SOILS</td> </tr> <tr> <td>MATERIAL PASSING #40 LL PI</td> <td colspan="2">-</td> <td colspan="2">-</td> <td colspan="2">40 MX 41 MN</td> <td colspan="2">40 MX 41 MN</td> <td colspan="2">40 MX 41 MN</td> <td colspan="2">40 MX 41 MN</td> <td colspan="3">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="3">HIGHLY ORGANIC SOILS</td> </tr> <tr> <td>GROUP INDEX</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">4 MX</td> <td colspan="2">8 MX</td> <td colspan="2">12 MX</td> <td colspan="3">FAIR TO POOR</td> <td colspan="3">POOR</td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td colspan="2">STONE FRAGS. GRAVEL, AND SAND</td> <td colspan="2">FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="3"></td> <td colspan="3"></td> </tr> <tr> <td>GEN. RATING AS SUBGRADE</td> <td colspan="6">EXCELLENT TO GOOD</td> <td colspan="6">FAIR TO POOR</td> <td colspan="3">FAIR TO POOR</td> <td colspan="3">POOR</td> </tr> </tbody> </table>		GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)						ORGANIC MATERIALS			A-1	A-1-a	A-1-b	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	GROUP CLASS.	A-1-a		A-1-b		A-2		A-4		A-5		A-7		A-1, A-2			A-3			SYMBOL	[Symbol]		[Symbol]		[Symbol]		[Symbol]		[Symbol]		[Symbol]		[Symbol]			[Symbol]			% PASSING #10 #40 #200	50 MX 30 MX 15 MX		50 MX 25 MX		51 MN 35 MX 35 MX		35 MX 35 MX		36 MN 36 MN		36 MN 36 MN		GRANULAR SOILS			SILT-CLAY SOILS			MATERIAL PASSING #40 LL PI	-		-		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER			HIGHLY ORGANIC SOILS			GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		FAIR TO POOR			POOR			USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS								GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD						FAIR TO POOR						FAIR TO POOR			POOR			<p>MINERALOGICAL COMPOSITION</p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p>WEATHERING</p> <p>FRESH: ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p>VERY SLIGHT (V SL.): ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p>SLIGHT (SL.): ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p>MODERATE (MOD.): SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p>MODERATELY SEVERE (MOD. SEV.): ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL.</p> <p>SEVERE (SEV.): ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF.</p> <p>VERY SEVERE (V SEV.): ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF.</p> <p>COMPLETE: ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>		<p>PERCENTAGE OF MATERIAL</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> </thead> <tbody> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </tbody> </table>		ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)						ORGANIC MATERIALS																																																																																																																																																																																	
	A-1	A-1-a	A-1-b	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																														
GROUP CLASS.	A-1-a		A-1-b		A-2		A-4		A-5		A-7		A-1, A-2			A-3																																																																																																																																																																														
SYMBOL	[Symbol]		[Symbol]		[Symbol]		[Symbol]		[Symbol]		[Symbol]		[Symbol]			[Symbol]																																																																																																																																																																														
% PASSING #10 #40 #200	50 MX 30 MX 15 MX		50 MX 25 MX		51 MN 35 MX 35 MX		35 MX 35 MX		36 MN 36 MN		36 MN 36 MN		GRANULAR SOILS			SILT-CLAY SOILS																																																																																																																																																																														
MATERIAL PASSING #40 LL PI	-		-		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER			HIGHLY ORGANIC SOILS																																																																																																																																																																														
GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		FAIR TO POOR			POOR																																																																																																																																																																														
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS																																																																																																																																																																																					
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD						FAIR TO POOR						FAIR TO POOR			POOR																																																																																																																																																																														
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																											
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																																																																																																											
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																																																																																																											
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																																																																																																											
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																																																																																																											
<p>TEXTURE OR GRAIN SIZE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <td>BOULDER (BLDR.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>COBBLE (COB.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>GRAVEL (GR.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>COARSE SAND (CS, SD.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>FINE SAND (F SD.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>SILT (SL.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>CLAY (CL.)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)							COBBLE (COB.)							GRAVEL (GR.)							COARSE SAND (CS, SD.)							FINE SAND (F SD.)							SILT (SL.)							CLAY (CL.)							<p>MISCELLANEOUS SYMBOLS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>[Symbol] ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td>[Symbol] DIP & DIP DIRECTION OF ROCK STRUCTURES</td> <td>[Symbol] SLOPE INDICATOR INSTALLATION</td> </tr> <tr> <td>[Symbol] SOIL SYMBOL</td> <td>[Symbol] TEST BORING</td> <td>[Symbol] CONE PENETROMETER TEST</td> </tr> <tr> <td>[Symbol] ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td>[Symbol] AUGER BORING</td> <td>[Symbol] SOUNDING ROD</td> </tr> <tr> <td>[Symbol] INFERRED SOIL BOUNDARY</td> <td>[Symbol] CORE BORING</td> <td>[Symbol] TEST BORING WITH CORE</td> </tr> <tr> <td>[Symbol] INFERRED ROCK LINE</td> <td>[Symbol] MONITORING WELL</td> <td>[Symbol] SPT N-VALUE</td> </tr> <tr> <td>[Symbol] ALLUVIAL SOIL BOUNDARY</td> <td>[Symbol] PIEZOMETER INSTALLATION</td> <td></td> </tr> </tbody> </table>		[Symbol] ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	[Symbol] DIP & DIP DIRECTION OF ROCK STRUCTURES	[Symbol] SLOPE INDICATOR INSTALLATION	[Symbol] SOIL SYMBOL	[Symbol] TEST BORING	[Symbol] CONE PENETROMETER TEST	[Symbol] ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	[Symbol] AUGER BORING	[Symbol] SOUNDING ROD	[Symbol] INFERRED SOIL BOUNDARY	[Symbol] CORE BORING	[Symbol] TEST BORING WITH CORE	[Symbol] INFERRED ROCK LINE	[Symbol] MONITORING WELL	[Symbol] SPT N-VALUE	[Symbol] ALLUVIAL SOIL BOUNDARY	[Symbol] PIEZOMETER INSTALLATION		<p>RECOMMENDATION SYMBOLS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>[Symbol] UNDERCUT</td> <td>[Symbol] UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td>[Symbol] UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> </tr> <tr> <td>[Symbol] SHALLOW UNDERCUT</td> <td>[Symbol] UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td></td> </tr> </tbody> </table>		[Symbol] UNDERCUT	[Symbol] UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	[Symbol] UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	[Symbol] SHALLOW UNDERCUT	[Symbol] UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK																																																																																																			
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																								
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																								
BOULDER (BLDR.)																																																																																																																																																																																														
COBBLE (COB.)																																																																																																																																																																																														
GRAVEL (GR.)																																																																																																																																																																																														
COARSE SAND (CS, SD.)																																																																																																																																																																																														
FINE SAND (F SD.)																																																																																																																																																																																														
SILT (SL.)																																																																																																																																																																																														
CLAY (CL.)																																																																																																																																																																																														
[Symbol] ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	[Symbol] DIP & DIP DIRECTION OF ROCK STRUCTURES	[Symbol] SLOPE INDICATOR INSTALLATION																																																																																																																																																																																												
[Symbol] SOIL SYMBOL	[Symbol] TEST BORING	[Symbol] CONE PENETROMETER TEST																																																																																																																																																																																												
[Symbol] ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	[Symbol] AUGER BORING	[Symbol] SOUNDING ROD																																																																																																																																																																																												
[Symbol] INFERRED SOIL BOUNDARY	[Symbol] CORE BORING	[Symbol] TEST BORING WITH CORE																																																																																																																																																																																												
[Symbol] INFERRED ROCK LINE	[Symbol] MONITORING WELL	[Symbol] SPT N-VALUE																																																																																																																																																																																												
[Symbol] ALLUVIAL SOIL BOUNDARY	[Symbol] PIEZOMETER INSTALLATION																																																																																																																																																																																													
[Symbol] UNDERCUT	[Symbol] UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	[Symbol] UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL																																																																																																																																																																																												
[Symbol] SHALLOW UNDERCUT	[Symbol] UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK																																																																																																																																																																																													
<p>SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </tbody> </table>		SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>ABBREVIATIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>AR - AUGER REFUSAL</td> <td>MED. - MEDIUM</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>MICA - MICACEOUS</td> <td>WEA. - WEATHERED</td> </tr> <tr> <td>CL - CLAY</td> <td>MOD. - MODERATELY</td> <td>UNIT WEIGHT</td> </tr> <tr> <td>CPT - CORE PENETRATION TEST</td> <td>NP - NON PLASTIC</td> <td>DRY UNIT WEIGHT</td> </tr> <tr> <td>CSE - COARSE</td> <td>ORG. - ORGANIC</td> <td>SAMPLE ABBREVIATIONS</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>PMT - PRESSUREMETER TEST</td> <td>S - BULK</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>SAP. - SAPROLITIC</td> <td>SS - SPLIT SPOON</td> </tr> <tr> <td>e - VOID RATIO</td> <td>SD. - SAND, SANDY</td> <td>ST - SHELBY TUBE</td> </tr> <tr> <td>F - FINE</td> <td>SL. - SILTY, SILTY</td> <td>RS - ROCK</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>SLI. - SLIGHTLY</td> <td>RT - RECOMPACTED TRIAXIAL</td> </tr> <tr> <td>FRAC. - FRACTURED, FRACTURES</td> <td>TCR - TRICONE REFUSAL</td> <td>CBR - CALIFORNIA BEARING RATIO</td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td>w - MOISTURE CONTENT</td> <td></td> </tr> <tr> <td>HI. - HIGHLY</td> <td>V - VERY</td> <td></td> </tr> </tbody> </table>		AR - AUGER REFUSAL	MED. - MEDIUM	VST - VANE SHEAR TEST	BT - BORING TERMINATED	MICA - MICACEOUS	WEA. - WEATHERED	CL - CLAY	MOD. - MODERATELY	UNIT WEIGHT	CPT - CORE PENETRATION TEST	NP - NON PLASTIC	DRY UNIT WEIGHT	CSE - COARSE	ORG. - ORGANIC	SAMPLE ABBREVIATIONS	DMT - DILATOMETER TEST	PMT - PRESSUREMETER TEST	S - BULK	DPT - DYNAMIC PENETRATION TEST	SAP. - SAPROLITIC	SS - SPLIT SPOON	e - VOID RATIO	SD. - SAND, SANDY	ST - SHELBY TUBE	F - FINE	SL. - SILTY, SILTY	RS - ROCK	FOSS. - FOSSILIFEROUS	SLI. - SLIGHTLY	RT - RECOMPACTED TRIAXIAL	FRAC. - FRACTURED, FRACTURES	TCR - TRICONE REFUSAL	CBR - CALIFORNIA BEARING RATIO	FRAGS. - FRAGMENTS	w - MOISTURE CONTENT		HI. - HIGHLY	V - VERY		<p>FRACATURE SPACING</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>TERM</th> <th>SPACING</th> </tr> </thead> <tbody> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </tbody> </table>		TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p>BEDDING</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> </thead> <tbody> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </tbody> </table>		TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET																																																																																																							
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																												
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																												
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																												
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																												
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																												
AR - AUGER REFUSAL	MED. - MEDIUM	VST - VANE SHEAR TEST																																																																																																																																																																																												
BT - BORING TERMINATED	MICA - MICACEOUS	WEA. - WEATHERED																																																																																																																																																																																												
CL - CLAY	MOD. - MODERATELY	UNIT WEIGHT																																																																																																																																																																																												
CPT - CORE PENETRATION TEST	NP - NON PLASTIC	DRY UNIT WEIGHT																																																																																																																																																																																												
CSE - COARSE	ORG. - ORGANIC	SAMPLE ABBREVIATIONS																																																																																																																																																																																												
DMT - DILATOMETER TEST	PMT - PRESSUREMETER TEST	S - BULK																																																																																																																																																																																												
DPT - DYNAMIC PENETRATION TEST	SAP. - SAPROLITIC	SS - SPLIT SPOON																																																																																																																																																																																												
e - VOID RATIO	SD. - SAND, SANDY	ST - SHELBY TUBE																																																																																																																																																																																												
F - FINE	SL. - SILTY, SILTY	RS - ROCK																																																																																																																																																																																												
FOSS. - FOSSILIFEROUS	SLI. - SLIGHTLY	RT - RECOMPACTED TRIAXIAL																																																																																																																																																																																												
FRAC. - FRACTURED, FRACTURES	TCR - TRICONE REFUSAL	CBR - CALIFORNIA BEARING RATIO																																																																																																																																																																																												
FRAGS. - FRAGMENTS	w - MOISTURE CONTENT																																																																																																																																																																																													
HI. - HIGHLY	V - VERY																																																																																																																																																																																													
TERM	SPACING																																																																																																																																																																																													
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																													
WIDE	3 TO 10 FEET																																																																																																																																																																																													
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																													
CLOSE	0.16 TO 1 FOOT																																																																																																																																																																																													
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																													
TERM	THICKNESS																																																																																																																																																																																													
VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																													
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																													
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																													
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																													
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																													
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																													
<p>PLASTICITY</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>NON PLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td>SLIGHTLY PLASTIC</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table>		NON PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	SLIGHTLY PLASTIC	0-5	VERY LOW	MODERATELY PLASTIC	6-15	SLIGHT	HIGHLY PLASTIC	16-25	MEDIUM		26 OR MORE	HIGH	<p>EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>DRILL UNITS:</td> <td>ADVANCING TOOLS:</td> <td>HAMMER TYPE:</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B <input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input checked="" type="checkbox"/> -N NXWL</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td>HAND TOOLS:</td> </tr> <tr> <td></td> <td><input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE _____ * STEEL TEETH</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE _____ * TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> </tbody> </table>		DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input checked="" type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B <input type="checkbox"/> -H	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input checked="" type="checkbox"/> -N NXWL	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:		<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER		<input type="checkbox"/> TRICONE _____ * TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD		<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST	<p>INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>FRIABLE</td> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </tbody> </table>		FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																				
NON PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																												
SLIGHTLY PLASTIC	0-5	VERY LOW																																																																																																																																																																																												
MODERATELY PLASTIC	6-15	SLIGHT																																																																																																																																																																																												
HIGHLY PLASTIC	16-25	MEDIUM																																																																																																																																																																																												
	26 OR MORE	HIGH																																																																																																																																																																																												
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																																												
<input checked="" type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																																												
<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																																																																																												
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B <input type="checkbox"/> -H																																																																																																																																																																																												
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input checked="" type="checkbox"/> -N NXWL																																																																																																																																																																																												
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:																																																																																																																																																																																												
	<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																																												
	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER																																																																																																																																																																																												
	<input type="checkbox"/> TRICONE _____ * TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																																												
	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																																												
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																																													
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																													
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																													
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																													
<p>COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p>FRANCH MARK: ELEVATIONS TAKEN FROM CROSS-SECTIONS, FROM FILE FROM NCDOT CONNECT: "B-5895 Electronic Files", "b5895_rdy_xsc"</p> <p style="text-align: right;">ELEVATION: FEET</p>		<p>NOTES:</p> <p>FIAD - FILLED IMMEDIATELY AFTER DRILLING</p>																																																																																																																																																																																										

PROJECT REFERENCE NO.	SHEET NO.
B-5895	3
SITE PLAN	
 0 50 100 FEET	

NAD 83/NSRS 2007


END BRIDGE
-L- STA. 23+17.09

END CONSTRUCTION
-Y- STA 11+80.00

STAIRS-TRAIL

STAIRS-TRAIL

25



EB2-B
(RW-1)
23+12
35' RT

RW-2
24+18
28' RT

RW-3
25+00
32' RT


US 70/US 25

PC Sta. 27+93.51


-Y- POT Sta. 10+00.00=
-L- STA. 25+52.38

END TIP PROJECT B-5895
-L- STA 28+75.00
S 79° 50' 52.45" E

APPROXIMATE WALL FACE AREA = 7280 SQ.FT.




PROJECT REFERENCE NO.	SHEET NO.
B-5895	4
REPLACE BRDG No. 0067 ON US-2770 over FRENCH BROAD RIVER	




WALL PROFILE ALONG -L-

THE WALL ENVELOPE DOES NOT ACCURATELY
DEPICT THE ACTUAL FACE OF THE WALL



23 + 25.00

-L-



24 + 25.00

-L-

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	#10	#40	#200		
SS-1	32.0' RT	25+00	20.2' - 21.7'	A-7-6(18)	53	29	9.1	10.3	27.6	53	99.8	95.4	80.6	NA	-

