Docusign Envelope ID: 94D9E2A4-7916-493B-A008-320B33FDF579

PROJECT REFERENCE NO. U-4758 PMP-01C PLAN VIEW SECTION VIEW MARKER SPACING WIDTH OF MARKER +0.50" ANGLE = 1.042.00" TOP OF **PAVEMENT** NOTES: 6.00''THE PAVEMENT SHALL BE SAW CUT TO THE DIMENSIONS SHOWN. THE SAW CUT AREA MUST BE DRY AND FREE OF DUST. DIRT OR ANY ADHESIVE MATERIAL WHICH WILL ADVERSELY AFFECT THE BOND OF THE ADHESIVE. INSTALL MARKERS WITH APPROVED ADHESIVE. ADHESIVE SHOULD NOT BE ALLOWED TO BUILD UP IN FRONT OF 42.00" MARKER LENS. THE MARKER AND THE ADHESIVE PAD SHALL NOT EXCEED THE TOP OF THE PAVEMENT SURFACE. DEPTH = 0.75" MINIMUM. RECESSED MARKERS INSTALLED ON CONCRETE PAVEMENT SHOULD BE INSTALLED A MINIMUM OF 2" FROM 0.75" MINIMUM THE PAVEMENT JOINT OR EDGE

CONTRACTS STANDARDS
AND DEVELOPMENT UNIT
Office 919-707-8950 FAX 919-250-4119

DETAIL OF INLAID RAISED PAVEMENT MARKER

ORIGINAL BY: rgwatson DATE: 02-06-2024

MODIFIED BY: DATE: DATE: FILE SPEC.: