

REFERENCE: U-4758

PROJECT: 40251

CONTENTS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	LEGEND (SOIL & ROCK)
2A	SUPPLEMENTAL LEGEND (GSI)
3	SITE PLAN
4	PROFILE
5-8	CROSS SECTIONS
9-25	BORE LOGS & CORE REPORTS
26-27	LABORATORY TEST RESULTS
28	SITE PHOTOGRAPH

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

**STRUCTURE  
SUBSURFACE INVESTIGATION**

COUNTY GUILFORD

PROJECT DESCRIPTION SR 1818 (JOHNSON ST)/  
SR 1850 (SANDY RIDGE RD) FROM  
SR 1820 (SKEET CLUB RD) TO I-40

SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-)  
OVER WEST FORK DEEP RIVER

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-4758	1	29

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

S&ME PERSONNEL

GEU/ERO PERSONNEL

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_


INVESTIGATED BY S&M/ENC DOT GEU


DRAWN BY C. BRUINSMA, LG

CHECKED BY C. YOUNGBLOOD, LG

SUBMITTED BY C. YOUNGBLOOD, LG

DATE APRIL 2021



DocuSigned by:  4/30/2021

C6DB1CBA0D0F44A... SIGNATURE DATE

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL ENGINEERING UNIT**  
**SUBSURFACE INVESTIGATION**  
**SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																																																																																																																																																																																																																																				
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</p>										<p><b>WELL GRADED</b> - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. <b>UNIFORMLY GRADED</b> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. <b>GAP-GRADED</b> - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p><b>ALLUVIUM (ALLUV.)</b> - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. <b>AQUIFER</b> - A WATER BEARING FORMATION OR STRATA. <b>ARENACEOUS</b> - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. <b>ARGILLACEOUS</b> - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. <b>ARTESIAN</b> - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. <b>CALCAREOUS (CALC.)</b> - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. <b>COLLUVIUM</b> - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. <b>CORE RECOVERY (REC.)</b> - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <b>DIKE</b> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. <b>DIP</b> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. <b>DIP DIRECTION (DIP AZIMUTH)</b> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. <b>FAULT</b> - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. <b>FISSILE</b> - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. <b>FLOAT</b> - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. <b>FLOOD PLAIN (FP)</b> - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. <b>FORMATION (FM)</b> - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. <b>JOINT</b> - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. <b>LEDGE</b> - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. <b>LENS</b> - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. <b>MOTTLED (MOT.)</b> - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. <b>PERCHED WATER</b> - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. <b>RESIDUAL (RESJ) SOIL</b> - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. <b>ROCK QUALITY DESIGNATION (RQD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <b>SAPROLITE (SAP.)</b> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. <b>SILL</b> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. <b>SLICKENSIDE</b> - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. <b>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)</b> - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. <b>STRATA CORE RECOVERY (SREC.)</b> - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. <b>STRATA ROCK QUALITY DESIGNATION (SRQD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. <b>TOPSOIL (TSJ)</b> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																																																																																																																																																																																																				
<p><b>SOIL LEGEND AND AASHTO CLASSIFICATION</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>GENERAL CLASS.</th><th colspan="4">GRANULAR MATERIALS (≤ 35% PASSING #200)</th><th colspan="4">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th><th colspan="2">ORGANIC MATERIALS</th></tr><tr><th>GROUP CLASS.</th><th>A-1</th><th>A-3</th><th>A-2</th><th>A-4</th><th>A-5</th><th>A-6</th><th>A-7</th><th>A-1, A-2</th><th>A-4, A-5</th><th></th></tr><tr><th>SYMBOL</th><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></thead><tbody><tr><td>Z PASSING #10</td><td>50 MX</td><td>30 MX</td><td>50 MX</td><td>51 MN</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>36 MN</td><td>36 MN</td><td>36 MN</td></tr><tr><td>*40</td><td>15 MX</td><td>25 MX</td><td>10 MX</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>35 MX</td><td>36 MN</td><td>36 MN</td><td>36 MN</td></tr><tr><td>*200</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>MATERIAL PASSING #40 LL PI</td><td colspan="4"></td><td colspan="4"></td><td colspan="2"></td></tr><tr><td>GROUP INDEX</td><td colspan="4">0</td><td colspan="4">4 MX</td><td colspan="2">8 MX</td></tr><tr><td>USUAL TYPES OF MAJOR MATERIALS</td><td colspan="4">STONE FRAGS, GRAVEL, AND SAND</td><td colspan="4">FINE SAND</td><td colspan="4">SILTY OR CLAYEY GRAVEL AND SAND</td></tr><tr><td>GEN. RATING AS SUBGRADE</td><td colspan="4">EXCELLENT TO GOOD</td><td colspan="4">FAIR TO POOR</td><td colspan="2">FAIR TO POOR</td><td>POOR</td></tr></tbody></table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)				SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS		GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5		SYMBOL											Z PASSING #10	50 MX	30 MX	50 MX	51 MN	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	*40	15 MX	25 MX	10 MX	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN	*200											MATERIAL PASSING #40 LL PI											GROUP INDEX	0				4 MX				8 MX		USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL, AND SAND				FINE SAND				SILTY OR CLAYEY GRAVEL AND SAND				GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR		POOR	<p><b>MINERALOGICAL COMPOSITION</b></p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p><b>COMPRESSIBILITY</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>ORGANIC MATERIAL</th><th>GRANULAR SOILS</th><th>SILT - CLAY SOILS</th><th>OTHER MATERIAL</th></tr></thead><tbody><tr><td>TRACE OF ORGANIC MATTER</td><td>2 - 3%</td><td>3 - 5%</td><td>TRACE</td></tr><tr><td>LITTLE ORGANIC MATTER</td><td>3 - 5%</td><td>5 - 12%</td><td>LITTLE</td></tr><tr><td>MODERATELY ORGANIC</td><td>5 - 10%</td><td>12 - 20%</td><td>SOME</td></tr><tr><td>HIGHLY ORGANIC</td><td>&gt; 10%</td><td>&gt; 20%</td><td>HIGHLY</td></tr></tbody></table> <p><b>PERCENTAGE OF MATERIAL</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>ORGANIC MATERIAL</th><th>GRANULAR SOILS</th><th>SILT - CLAY SOILS</th><th>OTHER MATERIAL</th></tr></thead><tbody><tr><td>TRACE OF ORGANIC MATTER</td><td>2 - 3%</td><td>3 - 5%</td><td>TRACE</td></tr><tr><td>LITTLE ORGANIC MATTER</td><td>3 - 5%</td><td>5 - 12%</td><td>LITTLE</td></tr><tr><td>MODERATELY ORGANIC</td><td>5 - 10%</td><td>12 - 20%</td><td>SOME</td></tr><tr><td>HIGHLY ORGANIC</td><td>&gt; 10%</td><td>&gt; 20%</td><td>HIGHLY</td></tr></tbody></table> <p><b>GROUND WATER</b></p> <p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING</p> <p>STATIC WATER LEVEL AFTER 24 HOURS</p> <p>PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA</p> <p>SPRING OR SEEP</p> <p><b>MISCELLANEOUS SYMBOLS</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>SYMBOL</th><th>DESCRIPTION</th></tr></thead><tbody><tr><td></td><td>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td></tr><tr><td></td><td>SOIL SYMBOL</td></tr><tr><td></td><td>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td></tr><tr><td></td><td>INFERRED SOIL BOUNDARY</td></tr><tr><td></td><td>INFERRED ROCK LINE</td></tr><tr><td></td><td>ALLUVIAL SOIL BOUNDARY</td></tr><tr><td></td><td>DIP &amp; DIP DIRECTION OF ROCK STRUCTURES</td></tr><tr><td></td><td>TEST BORING</td></tr><tr><td></td><td>SLOPE INDICATOR INSTALLATION</td></tr><tr><td></td><td>CONE PENETROMETER TEST</td></tr><tr><td></td><td>SOUNDING ROD</td></tr><tr><td></td><td>TEST BORING WITH CORE</td></tr><tr><td></td><td>SPT N-VALUE</td></tr></tbody></table> <p><b>RECOMMENDATION SYMBOLS</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>SYMBOL</th><th>DESCRIPTION</th></tr></thead><tbody><tr><td></td><td>UNDERCUT</td></tr><tr><td></td><td>SHALLOW UNDERCUT</td></tr><tr><td></td><td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td></tr><tr><td></td><td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td></tr></tbody></table> <p><b>ABBREVIATIONS</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>MEQ. - MEDIUM</th><th>VST - VANE SHEAR TEST</th></tr></thead><tbody><tr><td>BT - BORING TERMINATED</td><td>WEA. - WEATHERED</td></tr><tr><td>CL - CLAY</td><td>W - UNIT WEIGHT</td></tr><tr><td>CPT - CONE PENETRATION TEST</td><td>W<sub>d</sub> - DRY UNIT WEIGHT</td></tr><tr><td>CSE. - COARSE</td><td></td></tr><tr><td>DMT - OILATOMETER TEST</td><td></td></tr><tr><td>OPT - DYNAMIC PENETRATION TEST</td><td></td></tr><tr><td>e - VOID RATIO</td><td></td></tr><tr><td>F - FINE</td><td></td></tr><tr><td>FOSS. - FOSSILIFEROUS</td><td></td></tr><tr><td>FRAC. - FRACTURED, FRACTURES</td><td></td></tr><tr><td>FRAGS. - FRAGMENTS</td><td></td></tr><tr><td>HL - HIGHLY</td><td></td></tr><tr><td>MO. - MODERATELY</td><td></td></tr><tr><td>NP - NON PLASTIC</td><td></td></tr><tr><td>ORG. - ORGANIC</td><td></td></tr><tr><td>PMT - PRESSUREMETER TEST</td><td></td></tr><tr><td>SAP. - SAPROLITIC</td><td></td></tr><tr><td>SD. - SAND, SANDY</td><td></td></tr><tr><td>SL. - SILT, SILTY</td><td></td></tr><tr><td>SLI. - SLIGHTLY</td><td></td></tr><tr><td>TCR - TRICONE REFUSAL</td><td></td></tr><tr><td>W - MOISTURE CONTENT</td><td></td></tr><tr><td>V - VERY</td><td></td></tr></tbody></table> <p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>DRILL UNITS:</th><th>ADVANCING TOOLS:</th><th>HAMMER TYPE:</th></tr></thead><tbody><tr><td><input type="checkbox"/> CME-45C</td><td><input checked="" type="checkbox"/> CLAY BITS</td><td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td></tr><tr><td><input checked="" type="checkbox"/> CME-55</td><td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td><td></td></tr><tr><td></td><td><input checked="" type="checkbox"/> 8" HOLLOW AUGERS</td><td></td></tr><tr><td><input checked="" type="checkbox"/> CME-550</td><td><input type="checkbox"/> HARD FACED FINGER BITS</td><td></td></tr><tr><td></td><td><input type="checkbox"/> TUNG.-CARBIDE INSERTS</td><td></td></tr><tr><td><input type="checkbox"/> VANE SHEAR TEST</td><td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td><td></td></tr><tr><td><input type="checkbox"/> PORTABLE HOIST</td><td><input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH</td><td></td></tr><tr><td><input checked="" type="checkbox"/> BK-51 (1993)</td><td><input checked="" type="checkbox"/> TRICONE <input type="checkbox"/> TUNG.-CARB.</td><td></td></tr><tr><td></td><td><input type="checkbox"/> CORE BIT</td><td></td></tr></tbody></table> <p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th><th>FIELD MOISTURE DESCRIPTION</th><th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th></tr></thead><tbody><tr><td rowspan="2">LL - LIQUID LIMIT PL - PLASTIC LIMIT</td><td>- SATURATED - (SAT.)</td><td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td></tr><tr><td>- WET - (W)</td><td>SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td></tr><tr><td>OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT</td><td>- MOIST - (M)</td><td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td></tr><tr><td></td><td>- DRY - (D)</td><td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td></tr></tbody></table> <p><b>PLASTICITY</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>PLASTICITY INDEX (PI)</th><th>DRY STRENGTH</th></tr></thead><tbody><tr><td>0-5</td><td>VERY LOW</td></tr><tr><td>6-15</td><td>SLIGHT</td></tr><tr><td>16-25</td><td>MEDIUM</td></tr><tr><td>26 OR MORE</td><td>HIGH</td></tr></tbody></table> <p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY	ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY	SYMBOL	DESCRIPTION		ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION		SOIL SYMBOL		ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT		INFERRED SOIL BOUNDARY		INFERRED ROCK LINE		ALLUVIAL SOIL BOUNDARY		DIP & DIP DIRECTION OF ROCK STRUCTURES		TEST BORING		SLOPE INDICATOR INSTALLATION		CONE PENETROMETER TEST		SOUNDING ROD		TEST BORING WITH CORE		SPT N-VALUE	SYMBOL	DESCRIPTION		UNDERCUT		SHALLOW UNDERCUT		UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE		UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK	MEQ. - MEDIUM	VST - VANE SHEAR TEST	BT - BORING TERMINATED	WEA. - WEATHERED	CL - CLAY	W - UNIT WEIGHT	CPT - CONE PENETRATION TEST	W <sub>d</sub> - DRY UNIT WEIGHT	CSE. - COARSE		DMT - OILATOMETER TEST		OPT - DYNAMIC PENETRATION TEST		e - VOID RATIO		F - FINE		FOSS. - FOSSILIFEROUS		FRAC. - FRACTURED, FRACTURES		FRAGS. - FRAGMENTS		HL - HIGHLY		MO. - MODERATELY		NP - NON PLASTIC		ORG. - ORGANIC		PMT - PRESSUREMETER TEST		SAP. - SAPROLITIC		SD. - SAND, SANDY		SL. - SILT, SILTY		SLI. - SLIGHTLY		TCR - TRICONE REFUSAL		W - MOISTURE CONTENT		V - VERY		DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-45C	<input checked="" type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input checked="" type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER			<input checked="" type="checkbox"/> 8" HOLLOW AUGERS		<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS			<input type="checkbox"/> TUNG.-CARBIDE INSERTS		<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH		<input checked="" type="checkbox"/> BK-51 (1993)	<input checked="" type="checkbox"/> TRICONE <input type="checkbox"/> TUNG.-CARB.			<input type="checkbox"/> CORE BIT		SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE		- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	PLASTICITY INDEX (PI)	DRY STRENGTH	0-5	VERY LOW	6-15	SLIGHT	16-25	MEDIUM	26 OR MORE	HIGH	<p><b>ROCK HARDNESS</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>TERM</th><th>SPACING</th><th>THICKNESS</th></tr></thead><tbody><tr><td>VERY WIDE</td><td>MORE THAN 10 FEET</td><td>4 FEET</td></tr><tr><td>WIDE</td><td>3 TO 10 FEET</td><td>1.5 - 4 FEET</td></tr><tr><td>MODERATELY CLOSE</td><td>1 TO 3 FEET</td><td>0.16 - 1.5 FEET</td></tr><tr><td>CLOSE</td><td>0.16 TO 1 FOOT</td><td>0.03 - 0.16 FEET</td></tr><tr><td>VERY CLOSE</td><td>LESS THAN 0.16 FEET</td><td>0.008 - 0.03 FEET</td></tr></tbody></table> <p><b>BEDDING</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>TERM</th><th>THICKNESS</th></tr></thead><tbody><tr><td>VERY THICKLY BEDDED</td><td>4 FEET</td></tr><tr><td>THICKLY BEDDED</td><td>1.5 - 4 FEET</td></tr><tr><td>THINLY BEDDED</td><td>0.16 - 1.5 FEET</td></tr><tr><td>VERY THINLY BEDDED</td><td>0.03 - 0.16 FEET</td></tr><tr><td>THICKLY LAMINATED</td><td>0.008 - 0.03 FEET</td></tr><tr><td>THINLY LAMINATED</td><td>&lt; 0.008 FEET</td></tr></tbody></table> <p><b>FRACTURE SPACING</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>TERM</th><th>SPACING</th></tr></thead><tbody><tr><td>VERY WIDE</td><td>MORE THAN 10 FEET</td></tr><tr><td>WIDE</td><td>3 TO 10 FEET</td></tr><tr><td>MODERATELY CLOSE</td><td>1 TO 3 FEET</td></tr><tr><td>CLOSE</td><td>0.16 TO 1 FOOT</td></tr><tr><td>VERY CLOSE</td><td>LESS THAN 0.16 FEET</td></tr></tbody></table> <p><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th>TERM</th><th>DESCRIPTION</th></tr></thead><tbody><tr><td>FRIABLE</td><td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td></tr><tr><td>MODERATELY INDURATED</td><td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td></tr><tr><td>INDURATED</td><td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td></tr><tr><td>EXTREMELY INDURATED</td><td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td></tr></tbody></table>										TERM	SPACING	THICKNESS	VERY WIDE	MORE THAN 10 FEET	4 FEET	WIDE	3 TO 10 FEET	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	0.008 - 0.03 FEET	TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	TERM	DESCRIPTION	FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<p><b>NOTES:</b></p> <p>F.I.A.D. - FILLED IMMEDIATELY AFTER DRILLING</p>									
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)				SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS																																																																																																																																																																																																																																																																																																																																																																																									
GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5																																																																																																																																																																																																																																																																																																																																																																																									
SYMBOL																																																																																																																																																																																																																																																																																																																																																																																																		
Z PASSING #10	50 MX	30 MX	50 MX	51 MN	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN																																																																																																																																																																																																																																																																																																																																																																																								
*40	15 MX	25 MX	10 MX	35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN																																																																																																																																																																																																																																																																																																																																																																																								
*200																																																																																																																																																																																																																																																																																																																																																																																																		
MATERIAL PASSING #40 LL PI																																																																																																																																																																																																																																																																																																																																																																																																		
GROUP INDEX	0				4 MX				8 MX																																																																																																																																																																																																																																																																																																																																																																																									
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL, AND SAND				FINE SAND				SILTY OR CLAYEY GRAVEL AND SAND																																																																																																																																																																																																																																																																																																																																																																																									
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR		POOR																																																																																																																																																																																																																																																																																																																																																																																							
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																																																																																																																																																																																																																															
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																																																																																																																																																																																																																																																																																															
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																																																																																																																																																																																																																																																																																															
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																																																																																																																																																																																																																																																																																															
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																																																																																																																																																																																																																																																																																																															
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																																																																																																																																																																																																																															
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																																																																																																																																																																																																																																																																																															
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																																																																																																																																																																																																																																																																																															
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																																																																																																																																																																																																																																																																																															
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																																																																																																																																																																																																																																																																																																															
SYMBOL	DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																	
	ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																	
	SOIL SYMBOL																																																																																																																																																																																																																																																																																																																																																																																																	
	ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT																																																																																																																																																																																																																																																																																																																																																																																																	
	INFERRED SOIL BOUNDARY																																																																																																																																																																																																																																																																																																																																																																																																	
	INFERRED ROCK LINE																																																																																																																																																																																																																																																																																																																																																																																																	
	ALLUVIAL SOIL BOUNDARY																																																																																																																																																																																																																																																																																																																																																																																																	
	DIP & DIP DIRECTION OF ROCK STRUCTURES																																																																																																																																																																																																																																																																																																																																																																																																	
	TEST BORING																																																																																																																																																																																																																																																																																																																																																																																																	
	SLOPE INDICATOR INSTALLATION																																																																																																																																																																																																																																																																																																																																																																																																	
	CONE PENETROMETER TEST																																																																																																																																																																																																																																																																																																																																																																																																	
	SOUNDING ROD																																																																																																																																																																																																																																																																																																																																																																																																	
	TEST BORING WITH CORE																																																																																																																																																																																																																																																																																																																																																																																																	
	SPT N-VALUE																																																																																																																																																																																																																																																																																																																																																																																																	
SYMBOL	DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																	
	UNDERCUT																																																																																																																																																																																																																																																																																																																																																																																																	
	SHALLOW UNDERCUT																																																																																																																																																																																																																																																																																																																																																																																																	
	UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE																																																																																																																																																																																																																																																																																																																																																																																																	
	UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK																																																																																																																																																																																																																																																																																																																																																																																																	
MEQ. - MEDIUM	VST - VANE SHEAR TEST																																																																																																																																																																																																																																																																																																																																																																																																	
BT - BORING TERMINATED	WEA. - WEATHERED																																																																																																																																																																																																																																																																																																																																																																																																	
CL - CLAY	W - UNIT WEIGHT																																																																																																																																																																																																																																																																																																																																																																																																	
CPT - CONE PENETRATION TEST	W <sub>d</sub> - DRY UNIT WEIGHT																																																																																																																																																																																																																																																																																																																																																																																																	
CSE. - COARSE																																																																																																																																																																																																																																																																																																																																																																																																		
DMT - OILATOMETER TEST																																																																																																																																																																																																																																																																																																																																																																																																		
OPT - DYNAMIC PENETRATION TEST																																																																																																																																																																																																																																																																																																																																																																																																		
e - VOID RATIO																																																																																																																																																																																																																																																																																																																																																																																																		
F - FINE																																																																																																																																																																																																																																																																																																																																																																																																		
FOSS. - FOSSILIFEROUS																																																																																																																																																																																																																																																																																																																																																																																																		
FRAC. - FRACTURED, FRACTURES																																																																																																																																																																																																																																																																																																																																																																																																		
FRAGS. - FRAGMENTS																																																																																																																																																																																																																																																																																																																																																																																																		
HL - HIGHLY																																																																																																																																																																																																																																																																																																																																																																																																		
MO. - MODERATELY																																																																																																																																																																																																																																																																																																																																																																																																		
NP - NON PLASTIC																																																																																																																																																																																																																																																																																																																																																																																																		
ORG. - ORGANIC																																																																																																																																																																																																																																																																																																																																																																																																		
PMT - PRESSUREMETER TEST																																																																																																																																																																																																																																																																																																																																																																																																		
SAP. - SAPROLITIC																																																																																																																																																																																																																																																																																																																																																																																																		
SD. - SAND, SANDY																																																																																																																																																																																																																																																																																																																																																																																																		
SL. - SILT, SILTY																																																																																																																																																																																																																																																																																																																																																																																																		
SLI. - SLIGHTLY																																																																																																																																																																																																																																																																																																																																																																																																		
TCR - TRICONE REFUSAL																																																																																																																																																																																																																																																																																																																																																																																																		
W - MOISTURE CONTENT																																																																																																																																																																																																																																																																																																																																																																																																		
V - VERY																																																																																																																																																																																																																																																																																																																																																																																																		
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																																																																																																																																																																																																																																																
<input type="checkbox"/> CME-45C	<input checked="" type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																																																																																																																																																																																																																																																
<input checked="" type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER																																																																																																																																																																																																																																																																																																																																																																																																	
	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS																																																																																																																																																																																																																																																																																																																																																																																																	
<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS																																																																																																																																																																																																																																																																																																																																																																																																	
	<input type="checkbox"/> TUNG.-CARBIDE INSERTS																																																																																																																																																																																																																																																																																																																																																																																																	
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER																																																																																																																																																																																																																																																																																																																																																																																																	
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH																																																																																																																																																																																																																																																																																																																																																																																																	
<input checked="" type="checkbox"/> BK-51 (1993)	<input checked="" type="checkbox"/> TRICONE <input type="checkbox"/> TUNG.-CARB.																																																																																																																																																																																																																																																																																																																																																																																																	
	<input type="checkbox"/> CORE BIT																																																																																																																																																																																																																																																																																																																																																																																																	
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																
LL - LIQUID LIMIT PL - PLASTIC LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																																																																																																																																																																																																																
	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																
OM - OPTIMUM MOISTURE SL - SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																
	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																
PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																																																																																																																																																																																																																	
0-5	VERY LOW																																																																																																																																																																																																																																																																																																																																																																																																	
6-15	SLIGHT																																																																																																																																																																																																																																																																																																																																																																																																	
16-25	MEDIUM																																																																																																																																																																																																																																																																																																																																																																																																	
26 OR MORE	HIGH																																																																																																																																																																																																																																																																																																																																																																																																	
TERM	SPACING	THICKNESS																																																																																																																																																																																																																																																																																																																																																																																																
VERY WIDE	MORE THAN 10 FEET	4 FEET																																																																																																																																																																																																																																																																																																																																																																																																
WIDE	3 TO 10 FEET	1.5 - 4 FEET																																																																																																																																																																																																																																																																																																																																																																																																
MODERATELY CLOSE	1 TO 3 FEET	0.16 - 1.5 FEET																																																																																																																																																																																																																																																																																																																																																																																																
CLOSE	0.16 TO 1 FOOT	0.03 - 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																
VERY CLOSE	LESS THAN 0.16 FEET	0.008 - 0.03 FEET																																																																																																																																																																																																																																																																																																																																																																																																
TERM	THICKNESS																																																																																																																																																																																																																																																																																																																																																																																																	
VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
TERM	SPACING																																																																																																																																																																																																																																																																																																																																																																																																	
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
WIDE	3 TO 10 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
CLOSE	0.16 TO 1 FOOT																																																																																																																																																																																																																																																																																																																																																																																																	
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																	
TERM	DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																	
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																																																																																																																																																																																																																																																	
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																																																																																																																																																																																																																																	
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																																																																																																																																																																																																																																	
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																																																																																																																																																																																																																	

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION

SUPPLEMENTAL LEGEND, GEOLOGICAL STRENGTH INDEX (GSI) TABLES  
FROM AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS

AASHTO LRFD Figure 10.4.6.4-1 — Determination of GSI for Jointed Rock Mass (Marinos and Hoek, 2000)

AASHTO LRFD Figure 10.4.6.4-2 — Determination of GSI for Tectonically Deformed Heterogeneous Rock Masses (Marinos and Hoek, 2000)

GEOLOGICAL STRENGTH INDEX (GSI) FOR  
JOINTED ROCKS (Hoek and Marinos, 2000)

From the lithology, structure and surface conditions of the discontinuities, estimate the average value of GSI. Do not try to be too precise. Quoting a range from 33 to 37 is more realistic than stating that GSI = 35. Note that the table does not apply to structurally controlled failures. Where weak planar structural planes are present in an unfavorable orientation with respect to the excavation face, these will dominate the rock mass behaviour. The shear strength of surfaces in rocks that are prone to deterioration as a result of changes in moisture content will be reduced if water is present. When working with rocks in the fair to very poor categories, a shift to the right may be made for wet conditions. Water pressure is dealt with by effective stress analysis.

SURFACE CONDITIONS

VERY GOOD  
Very rough, fresh unweathered surfaces

GOOD  
Rough, slightly weathered, iron stained surfaces


FAIR  
Smooth, moderately weathered and altered surfaces

POOR  
Slickensided, highly weathered surfaces with compact coatings or fillings or angular fragments


VERY POOR  
Slickensided, highly weathered surfaces with soft clay coatings or fillings

DECREASING SURFACE QUALITY →


STRUCTURE



INTACT OR MASSIVE - intact rock specimens or massive in situ rock with few widely spaced discontinuities




BLOCKY - well interlocked undisturbed rock mass consisting of cubical blocks formed by three intersecting discontinuity sets



VERY BLOCKY - interlocked, partially disturbed mass with multi-faceted angular blocks formed by 4 or more joint sets



BLOCKY/DISTURBED/SEAMY - folded with angular blocks formed by many intersecting discontinuity sets. Persistence of bedding planes or schistosity




DISINTEGRATED - poorly interlocked, heavily broken rock mass with mixture of angular and rounded rock pieces



LAMINATED/SHEARED - Lack of blockiness due to close spacing of weak schistosity or shear planes

DECREASING INTERLOCKING OF ROCK PIECES  
↓



GSI FOR HETEROGENEOUS ROCK MASSES SUCH  
AS FLYSCH (Marinos, P and Hoek E., 2000)

From a description of the lithology, structure and surface conditions (particularly of the bedding planes), choose a box in the chart. Locate the position in the box that corresponds to the condition of the discontinuities and estimate the average value of GSI from the contours. Do not attempt to be too precise. Quoting a range from 33 to 37 is more realistic than giving GSI = 35. Note that the Hoek-Brown criterion does not apply to structurally controlled failures. Where unfavourably oriented continuous weak planar discontinuities are present, these will dominate the behaviour of the rock mass. The strength of some rock masses is reduced by the presence of groundwater and this can be allowed for by a slight shift to the right in the columns for fair, poor and very poor conditions. Water pressure does not change the value of GSI and it is dealt with by using effective stress analysis.

SURFACE CONDITIONS OF  
DISCONTINUITIES  
(Predominantly bedding planes)

VERY GOOD - Very Rough, fresh unweathered surfaces

GOOD - Rough, slightly weathered surfaces

FAIR - Smooth, moderately weathered and altered surfaces

POOR - Very smooth, occasionally slickensided surfaces with compact coatings or fillings with angular fragments

VERY POOR - Very smooth, slickensided or highly weathered surfaces with soft clay coatings or fillings

COMPOSITION AND STRUCTURE



A. Thick bedded, very blocky sandstone  
The effect of pelitic coatings on the bedding planes is minimized by the confinement of the rock mass. In shallow tunnels or slopes these bedding planes may cause structurally controlled instability.



B. Sandstone with thin inter-layers of siltstone



C. Sandstone and siltstone in similar amounts



D. Siltstone or silty shale with sandstone layers



E. Weak siltstone or clayey shale with sandstone layers

C, D, E, and G - may be more or less folded than illustrated but this does not change the strength. Tectonic deformation, faulting and loss of continuity moves these categories to F and H.



F. Tectonically deformed, intensively folded/faulted, sheared clayey shale or siltstone with broken and deformed sandstone layers forming an almost chaotic structure




G. Undisturbed silty or clayey shale with or without a few very thin sandstone layers




H. Tectonically deformed silty or clayey shale forming a chaotic structure with pockets of clay. Thin layers of sandstone are transformed into small rock pieces.


→ Means deformation after tectonic disturbance


PROJECT REFERENCE NO.	SHEET NO.
U-4758	3
<b>SITE PLAN</b>	
0 60 120 FEET	
















WBS 40251.1.1			TIP U-4758			COUNTY GUILFORD			GEOLOGIST Bhuiyan, A.							
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER									GROUND WTR (ft)							
BORING NO. EB1-A			STATION 54+50			OFFSET 45 ft LT			ALIGNMENT -L-			0 HR. N/A				
COLLAR ELEV. 814.9 ft			TOTAL DEPTH 22.0 ft			NORTHING 837,278			EASTING 1,700,054			24 HR. FIAD				
DRILL RIG/HAMMER EFF./DATE SME9978 CME-750 74% 12/19/2018						DRILL METHOD Mud Rotary			HAMMER TYPE Automatic							
DRILLER Marlowe, J.			START DATE 12/12/18			COMP. DATE 12/12/18			SURFACE WATER DEPTH N/A							
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
			0.5ft	0.5ft	0.5ft	0	25	50	75	100			ELEV. (ft)	DEPTH (ft)		
815													814.9	GROUND SURFACE	0.0	
													814.2	ROADWAY EMBANKMENT (PAVEMENT)	0.7	
810	811.4	3.5		7	6	5							M	LOOSE TO MED. DENSE, GRAY AND BROWN, SILTY FINE TO COARSE SAND, A-2-4		
805	806.4	8.5		2	3	2							M			
800	801.4	13.5											W	ALLUVIAL		
														STIFF, GRAY AND BLACK, SANDY CLAY, A-6		
			1	6	9									802.9		12.0
													</			

NCDOT BORE DOUBLE U4758\_GEO\_BRDG0308.GPJ NC\_DOT.GDT 4/22/21

# GEOTECHNICAL BORING REPORT


## CORE LOG

NCDOT CORE SINGLE U4758 GEO BRDG0308.GPJ NC DOT.GDT 3/25/21

WBS 40251.1.1					TIP U-4758					COUNTY GUILFORD					GEOLOGIST Bhuiyan, A.											
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER															GROUND WTR (ft)											
BORING NO. EB1-C					STATION 54+50					OFFSET CL					ALIGNMENT -L-					0 HR. N/A						
COLLAR ELEV. 809.6 ft					TOTAL DEPTH 26.5 ft					NORTHING 837,245					EASTING 1,700,085					24 HR. 1.0						
DRILL RIG/HAMMER EFF./DATE SIME0593 CME-550X 86% 05/01/2019										DRILL METHOD Mud Rotary					HAMMER TYPE Automatic											
DRILLER Marlowe, J.					START DATE 12/18/18					COMP. DATE 12/18/18					SURFACE WATER DEPTH N/A											
CORE SIZE NQ					TOTAL RUN 13.0 ft																					
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) %		RQD (ft) %	SAMP. NO.	STRATA REC. (ft) %		RQD (ft) %	L O G	DESCRIPTION AND REMARKS													
													ELEV. (ft) DEPTH (ft)													
796.1													Begin Coring @ 13.5 ft													
795	796.1	13.5	3.0	3:56/1.0 2:32/1.0 2:41/1.0	(2.6) 87%	(1.1) 37%			(11.9) 92%	(7.0) 54%			796.1	CRYSTALLINE ROCK 13.5												
790	793.1	16.5		2:15/1.0 1:57/1.0 2:25/1.0	(4.8) 96%	(1.7) 34%								TAN AND GRAY, SEVERE TO MODERATELY WEATHERED, VERY CLOSE TO CLOSE FRACTURE SPACING, MEDIUM HARD, META-GABBRO												
			5.0	2:18/1.0 2:01/1.0										REC = 92% RQD = 54% GSI = 47-52												
	788.1	21.5		2:01/1.0 2:42/1.0 2:02/1.0	(4.5) 90%	(4.2) 84%																				
785	783.1	26.5		2:14/1.0 2:25/1.0									783.1	26.5												
															Boring Terminated at Elevation 783.1 ft IN CRYSTALLINE ROCK (META-GABBRO)											

## CORE PHOTOGRAPHS

### EB1-C BOXES 1 & 2: 13.5 - 26.5 FEET



# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS 40251.1.1		TIP U-4758		COUNTY GUILFORD		GEOLOGIST Bhuiyan, A.								
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER								GROUND WTR (ft)						
BORING NO. EB1-B		STATION 54+50		OFFSET 40 ft RT		ALIGNMENT -L-		0 HR.	N/A					
COLLAR ELEV. 808.2 ft		TOTAL DEPTH 9.8 ft		NORTHING 837,216		EASTING 1,700,112		24 HR.	1.0					
DRILL RIGHAMMER EFF./DATE SME0593 CME-550X 86% 05/01/2019				DRILL METHOD H.S. Augers			HAMMER TYPE Automatic							
DRILLER Marlowe, J.		START DATE 12/19/18		COMP. DATE 12/19/18		SURFACE WATER DEPTH N/A								
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT				SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100			ELEV. (ft)	DEPTH (ft)
810														
805	804.5	3.7	1	3	5								808.2	GROUND SURFACE 0.0
800	799.5	8.7	12	11	89/0.2								801.2	ALLUVIAL 7.0
													799.0	LOOSE, GRAY AND BROWN, SILTY FINE TO COARSE SAND, A-2-4 9.2
													798.3	RESIDUAL 9.9
														WEATHERED ROCK (META-GABBRO) Boring Terminated at Elevation 798.4 ft IN WEATHERED ROCK (META-GABBRO)

NCDOT BORE DOUBLE U4758 GEO BRDG0308.GPJ NC DOT GDT 3/25/21

GEOTECHNICAL BORING REPORT  
BORE LOG

WBS 40251.1.1			TIP U-4758			COUNTY GUILFORD			GEOLOGIST Sanderson, A.						
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER									GROUND WTR (ft)						
BORING NO. B1-A			STATION 55+08			OFFSET 44 ft LT			ALIGNMENT -L-			0 HR. N/A			
COLLAR ELEV. 800.7 ft			TOTAL DEPTH 15.3 ft			NORTHING 837,317			EASTING 1,700,098			24 HR. N/A			
DRILL RIGHAMMER EFF./DATE GEUBK-51 1993						DRILL METHOD Mud Rotary			HAMMERTYPE Automatic						
DRILLER Conley, H			START DATE 02/03/93			COMP. DATE 02/03/93			SURFACE WATER DEPTH N/A						
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				ELEV. (ft)	DEPTH (ft)
805															
800	800.7	0.0												800.7	0.0
			1	0	1									GROUND SURFACE	
														ALLUVIAL	
														BROWN TO GRAY, COARSE SAND WITH SOME GRAVEL	
795	795.9	4.8	13	15	25										
	794.1	6.6	14	29	71/0.3										
790	790.9	9.8	100/0.3											793.0	7.7
														WEATHERED ROCK	
														GRAY AND WHITE DIORITE	
	785.9	14.8	100/0.5											785.4	15.3
														Boring Terminated at Elevation 785.4 ft IN WEATHERED ROCK (DIORITE)	
														INFORMATION BASED ON 1993 INVESTIGATIONS. ALL ELEVATIONS ARE ESTIMATES BASED ON ROAD FINISHED BRIDGE ELEVATION/AS BUILD PLANS	

NCDOT BORE DOUBLE U4758\_GEO\_BRDG0308.GPJ NC DOT.GDT 3/25/21

# GEOTECHNICAL BORING REPORT

## BORE LOG

[illegible]

# GEOTECHNICAL BORING REPORT

## CORE LOG


WBS 40251.1.1		TIP U-4758		COUNTY GUILFORD		GEOLOGIST Jones, A. N.						
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER								GROUND WTR (ft)				
BORING NO. B1-C		STATION 54+95		OFFSET 10 ft RT		ALIGNMENT -L-		0 HR.	N/A			
COLLAR ELEV. 808.4 ft		TOTAL DEPTH 41.4 ft		NORTHING 387,268		EASTING 1,700,125		24 HR.	3.8			
DRILL RIG/HAMMER EFF./DATE RFC0074 CME-55 80% 03/08/2019				DRILL METHOD Wash Boring			HAMMER TYPE Automatic					
DRILLER Pinter, D. G.		START DATE 09/03/20		COMP. DATE 09/30/20		SURFACE WATER DEPTH N/A						
CORE SIZE NQ		TOTAL RUN 27.7 ft										
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) % RQD (ft) %		SAMP. NO.	STRATA REC. (ft) % RQD (ft) %		L O G	DESCRIPTION AND REMARKS	DEPTH (ft)
794.66	794.7	13.7	2.7	N=60/0.0 1:32/0.7 2:01/1.0 1:44/1.0	(2.7) 100%	(2.2) 81%		(27.7) 100%	(6.1) 22%		Begin Coring @ 13.7 ft	13.7
	792.0	16.4	5.0	2:15/1.0 2:10/1.0 2:25/1.0 2:22/1.0 2:48/1.0	(5.0) 100%	(0.0) 0%					GRAY AND WHITE, V. SLI. WEATHERING TO FRESH, HARD TO V. HARD,V. CLOSE TO MOD. CLOSELY FRACTURED, META-GABBRO	
790											LOW RQD FROM 16.4 TO 26.4 FT DUE TO HORIZONTAL EXPANSION CRACKING	
	787.0	21.4	5.0	2:00/1.0 2:32/1.0 2:28/1.0 2:36/1.0 2:26/1.0	(5.0) 100%	(0.0) 0%					GSI = 55	
785												
	782.0	26.4	5.0	2:06/1.0 2:19/1.0 2:17/1.0 2:28/1.0 2:14/1.0	(5.0) 100%	(0.0) 0%						
780												
	777.0	31.4	5.0	2:06/1.0 2:18/1.0 1:48/1.0 1:46/1.0 2:14/1.0	(5.0) 100%	(0.0) 0%						
775												
	772.0	36.4	5.0	2:18/1.0 1:49/1.0 2:09/1.0 2:30/1.0 2:18/1.0	(5.0) 100%	(4.1) 82%						
770												
	767.0	41.4									Boring Terminated at Elevation 767.0 ft IN CRYSTALLINE ROCK (META-GABBRO)	41.4
	</											



CORE PHOTOGRAPHS


B1-C

BOXES 1 & 2: 13.7 - 31.9 FEET



B1-C

BOXES 3: 31.9 - 41.4 FEET






[illegible]

WBS 40251.1.1				TIP U-4758				COUNTY GUILFORD				GEOLOGIST Jones, A. N.										
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER												GROUND WTR (ft)										
BORING NO. B1-B				STATION 54+78				OFFSET 41 ft RT				ALIGNMENT -L-				0 HR. N/A						
COLLAR ELEV. 807.9 ft				TOTAL DEPTH 31.5 ft				NORTHING 837,234				EASTING 1,700,134				24 HR. 2.8						
DRILL RIG/HAMMER EFF./DATE RFC0074 QME-55 80% 03/08/2019								DRILL METHOD Wash Boring				HAMMER TYPE Automatic										
DRILLER Pinter, D. G.				START DATE 09/02/20				COMP. DATE 09/03/20				SURFACE WATER DEPTH N/A										
CORE SIZE NQ				TOTAL RUN 17.8 ft																		
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) %RQD (ft) %		SAMP. NO.	STRATA REC. (ft) %RQD (ft) %		L O G	DESCRIPTION AND REMARKS ELEV. (ft) DEPTH (ft)											
794.08	794.1	13.8	2.8	N=60/0.0 0:55/0.8 1:17/1.0 1:36/1.0	(2.6) 93%	(2.0) 71%		(17.0) 96%	(12.7) 71%		Begin Coring @ 13.8 ft											
790	791.3	16.6	5.0	1:25/1.0 1:58/1.0 1:50/1.0 1:39/1.0 1:43/1.0	(4.4) 88%	(2.0) 40%					GRAY, BLACK, WHITE, V. SLIGHT WEATHERING TO FRESH, HARD TO VERY HARD, CLOSE TO MOD. CLOSELY FRACTURED, META-GABBRO W/ WEATHERED ZONE FROM 20.5-21.5 FEET GSI=70											
785	786.3	21.6	5.0	1:24/1.0 2:29/1.0 1:31/1.0 1:59/1.0 1:37/1.0	(5.0) 100%	(4.6) 92%	RS-1															
780	781.3	26.6	5.0	2:35/1.0 2:13/1.0 2:16/1.0 2:32/1.0 2:41/1.0	(5.0) 100%	(4.1) 82%																
	776.3	31.6									Boring Terminated at Elevation 776.4 ft IN CRYSTALLINE ROCK (GNEISS)											

## CORE PHOTOGRAPHS

### B1-B

BOXES 1 & 2: 13.8 - 31.5 FEET



## **GEOTECHNICAL BORING REPORT**

### **BORE LOG**

WBS 40251.1.1			TIP U-4758			COUNTY GUILFORD			GEOLOGIST Sanderson, A.					
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER									GROUND WTR (ft)					
BORING NO. B2-A			STATION 55+43			OFFSET 31 ft LT			ALIGNMENT -L-			0 HR. N/A		
COLLAR ELEV. 803.2 ft			TOTAL DEPTH 25.4 ft			NORTHING 837,331			EASTING 1,700,132			24 HR. N/A		
DRILL RIG/HAMMER EFF./DATE GEUBK-51 1993						DRILL METHOD Mud Rotary			HAMMER TYPE Automatic					
DRILLER Conley, H			START DATE 02/09/93			COMP. DATE 02/09/93			SURFACE WATER DEPTH N/A					
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				
805														
	803.2	0.0	1	0	0	1							803.2	GROUND SURFACE 0.0
800	800.1	3.1	WOH	1	1	2						M	800.2	ALLUVIAL BROWN, SANDY SILT WITH TRACE MICA AND ORGANICS (A-4) 3.0
	798.4	4.8		3	1	2						W	798.2	BROWN, SANDY SILTY CLAY WITH TRACE MICA AND ORGANICS (A-7) 5.0
	795.9	7.3		15	33	21						W	796.2	BROWN COARSE SAND WITH SOME GRAVEL (A-1-a) 7.0
795	793.4	9.8		8	11	52						M		RESIDUAL GRAY, SANDY SILT (A-4), SAPROLITIC (QUARTZ VEIN AT 10.7 FT)
	791.0	12.2	100/0.2									M	791.2	12.0
790														CRYSTALLINE ROCK GRAY AND WHITE CRYSTALLINE ROCK WITH WEATHERED ROCK LAYERS (CORE LOG AND CORE PHOTOS NOT AVAILABLE) 18.0
785													785.2	
														RESIDUAL GRAY, SANDY SILT (A-4)
780													778.6	24.6
													777.8	25.4
														CRYSTALLINE ROCK (DIORITE) Boring Terminated at Elevation 777.8 ft IN CRYSTALLINE ROCK (DIORITE)
														INFORMATION BASED ON 1993 INVESTIGATIONS. ALL ELEVATIONS ARE ESTIMATES BASED ON ROAD FINISHED BRIDGE ELEVATION/AS BUILD PLANS

# GEOTECHNICAL BORING REPORT


## CORE LOG

NCDOT BORE DOUBLE U4758\_GEO\_BRDG0308.GPJ NC\_DOT.GDT 4/29/21



CORE PHOTOGRAPHS

B2-C  
BOXES 1 & 2: 18.7 - 36.5 FEET




GEOTECHNICAL BORING REPORT  
BORE LOG

WBS 40251.1.1				TIP U-4758				COUNTY GUILFORD				GEOLOGIST Jones, A. N.					
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER												GROUND WTR (ft)					
BORING NO. B2-B				STATION 55+43				OFFSET 26 ft RT				ALIGNMENT -L-				0 HR. N/A	
COLLAR ELEV. 807.9 ft				TOTAL DEPTH 32.1 ft				NORTHING 837,289				EASTING 1,700,171				24 HR. 3.4	
DRILL RIGHAMMER EFF./DATE RFC0074 CME-55 80% 03/08/2019								DRILL METHOD Wash Boring				HAMMER TYPE Automatic					
DRILLER Pinter, D. G.				START DATE 09/09/20				COMP. DATE 09/09/20				SURFACE WATER DEPTH N/A					
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION				
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					ELEV. (ft)	DEPTH (ft)	
810																	
805	803.8	4.1									M	W	GROUND SURFACE 0.0				
													806.9 ALLUVIAL 1.0				
800	798.8	9.1	2	2	3						W		BROWN, V. SOFT, SANDY SILT (A-4) (TOPSOIL)				
													GRAY, LOOSE TO V. LOOSE, SILTY SAND (A-2-4) W/ TRACE MICA AND ORGANICS				
795	793.8	14.1	WOH	1	1								794.4 13.5				
790			60/0.0										793.8 14.1				
785											RS-2		CRYSTALLINE ROCK 13.5				
													GRAY AND WHITE, GNEISS				
780													GRAY AND WHITE, META-GABBRO				
											STRATA REC = 99% STRATA RQD = 76% GSI = 60						
													775.8 32.1				
													Boring Terminated at Elevation 775.8 ft IN CRYSTALLINE ROCK (META-GABBRO)				

GEOTECHNICAL BORING REPORT  
CORE LOG

SHEET 21


WBS 40251.1.1					TIP U-4758			COUNTY GUILFORD			GEOLOGIST Jones, A. N.			
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER											GROUND WTR (ft)			
BORING NO. B2-B					STATION 55+43			OFFSET 26 ft RT			ALIGNMENT -L-		0 HR. N/A	
COLLAR ELEV. 807.9 ft					TOTAL DEPTH 32.1 ft			NORTHING 837,289			EASTING 1,700,171		24 HR. 3.4	
DRILL RIGHAMMER EFF./DATE RFC0074 CME-55 80% 03/08/2019								DRILL METHOD Wash Boring				HAMMER TYPE Automatic		
DRILLER Pinter, D. G.					START DATE 09/09/20			COMP. DATE 09/09/20			SURFACE WATER DEPTH N/A			
CORE SIZE NQ					TOTAL RUN 18.0 ft									
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		SAMP. NO.	STRATA		LOG	DESCRIPTION AND REMARKS			
					REC. (ft) %	RQD (ft) %		REC. (ft) %	RQD (ft) %					
793.82														
790	793.8	14.1	3.0	1:33/1.0 N=60/0.0	(2.8) 93%	(1.8) 60%		(17.8) 99%	(13.7) 76%		793.8	GRAY, WHITE AND GREEN, V. SLI. WEATHERED TO FRESH, V. HARD, V. CLOSE TO MOC. CLOSELY FRACTURED, META-GABBRO	14.1	
	790.8	17.1		1:33/1.0 1:08/1.0 1:36/1.0	(5.0) 100%	(3.0) 60%								
785	785.8	22.1	5.0	1:09/1.0 1:09/1.0 1:18/1.0 1:33/1.0 1:14/1.0			RS-2					GSI = 60		
780	780.8	27.1	5.0	1:22/1.0 1:16/1.0 1:02/1.0 1:09/1.0 1:13/1.0	(5.0) 100%	(3.9) 78%								
	775.8	32.1		1:33/1.0 2:06/1.0 2:11/1.0 2:14/1.0 2:03/1.0	(5.0) 100%	(5.0) 100%						Boring Terminated at Elevation 775.8 ft IN CRYSTALLINE ROCK (META-GABBRO)	32.1	

NCDOT BORE DOUBLE U4758\_GEO\_BRDG0308.GPJ NC\_DOT.GDT 4/29/21

NCDOT CORE SINGLE U4758\_GEO\_BRDG0308.GPJ NC\_DOT.GDT 3/25/21



**B2-B**  
BOXES 1 & 2: 14.1 - 32.1 FEET



GEOTECHNICAL BORING REPORT  
BORE LOG

WBS 40251.1.1			TIP U-4758			COUNTY GUILFORD			GEOLOGIST Bhuiyan, A.					
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER									GROUND WTR (ft)					
BORING NO. EB2-A			STATION 56+00			OFFSET 45 ft LT			ALIGNMENT -L-			0 HR. N/A		
COLLAR ELEV. 814.1 ft			TOTAL DEPTH 38.1 ft			NORTHING 837,380			EASTING 1,700,164			24 HR. FIAD		
DRILL RIGHAMMER EFF./DATE SME0593 CME-550X 86% 05/01/2019						DRILL METHOD Mud Rotary			HAMMER TYPE Automatic					
DRILLER Marlowe, J.			START DATE 12/13/19			COMP. DATE 12/13/19			SURFACE WATER DEPTH N/A					
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100			ELEV. (ft)	DEPTH (ft)
815														
810	811.1	3.0	3	2	3								814.1 GROUND SURFACE 0.0	
805	806.1	8.0	1	1	1								813.4 ROADWAY EMBANKMENT (PAVEMENT) 0.7	
800	801.1	13.0	1	4	2								ROADWAY EMBANKMENT MEDIUM STIFF, GRAY AND RED, SANDY CLAY, A-6	
795	796.1	18.0	3	11	18								806.6 ALLUVIAL 7.5	
790	791.1	23.0	26	40	33								VERY SOFT TO MEDIUM STIFF, SANDY CLAY WITH TRACE ORGANIC MATTER, A-6	
785	786.1	28.0	52	48/0.4									798.1 MEDIUM DENSE, GRAY, CLAYEY FINE TO COARSE SAND, TRACE GRAVEL, TRACE ORGANIC MATTER, A-2-6 16.0	
780	781.1	33.0	24	17	22								792.1 RESIDUAL 22.0	
	776.1	38.0	60/0.1										VERY DENSE, GRAY, FINE TO COARSE SAND WITH TRACE ROCK FRAG., A-3	
													787.1 WEATHERED ROCK (META-GABBRO) 27.0	
													784.6 RESIDUAL 29.5	
													DENSE, GRAY, SILTY FINE TO COARSE SAND WITH TRACE ROCK FRAG., A-2-4	
													776.1 CRYSTALLINE ROCK 38.0	
													776.0 CRYSTALLINE ROCK (META-GABBRO) 38.0	
													Boring Terminated at Elevation 776.0 ft IN CRYSTALLINE ROCK (META-GABBRO)	

WBS 40251.1.1			TIP U-4758			COUNTY GUILFORD			GEOLOGIST Bhuiyan, A.				
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER									GROUND WTR (ft)				
BORING NO. EB2-C			STATION 55+92			OFFSET 3 ft RT			ALIGNMENT -L-			0 HR. N/A	
COLLAR ELEV. 806.3 ft			TOTAL DEPTH 17.2 ft			NORTHING 837,340			EASTING 1,700,191			24 HR. 0.5	
DRILL RIGHAMMER EFF./DATE SME0593 CME-550X 86% 05/01/2019						DRILL METHOD H.S. Augers			HAMMER TYPE Automatic				
DRILLER Marlowe, J.			START DATE 12/19/18			COMP. DATE 12/19/18			SURFACE WATER DEPTH N/A				
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
			0.5ft	0.5ft	0.5ft	0	25	50	75	100		MOI	
810													
805													
800	802.8	3.5	1	1	1						S-5	33%	806.3 GROUND SURFACE 0.0
	797.8	8.5	WOH	WOH	1							W	ALLUVIAL VERY SOFT, GRAY, SILTY CLAY, A-7-6
795	792.8	13.5	100/0.5										798.3 VERY LOOSE, GRAY, CLAYEY FINE TO COARSE SAND, A-2-6 8.0
790	789.1	17.2	60/0.0										793.3 WEATHERED ROCK (META-GABBRO) 13.0
													789.1 Boring Terminated WITH STANDARD PENETRATION TEST REFUSAL at Elevation 789.1 ft ON CRYSTALLINE ROCK (META-GABBRO) 17.2

NCDOT BORE DOUBLE U4758\_GEO\_BRDG0308.GPJ NC\_DOT.GDT 3/25/21




WBS 40251.1.1						TIP U-4758				COUNTY GUILFORD				GEOLOGIST Bhuiyan, A.					
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER														GROUND WTR (ft)					
BORING NO. EB2-B						STATION 56+00				OFFSET 40 ft RT				ALIGNMENT -L-				0 HR. N/A	
COLLAR ELEV. 805.8 ft						TOTAL DEPTH 22.5 ft				NORTHING 837,318				EASTING 1,700,222				24 HR. 1.0	
DRILL RIG/HAMMER EFF./DATE SIME0593 CME-550X 86% 05/01/2019										DRILL METHOD H.S. Augers				HAMMER TYPE Automatic					
DRILLER Marlowe, J.						START DATE 12/19/18				COMP. DATE 12/19/18				SURFACE WATER DEPTH N/A					
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	L O G	SOIL AND ROCK DESCRIPTION					
			0.5ft	0.5ft	0.5ft	0	25	50	75	100				ELEV. (ft)	DEPTH (ft)				
810																			
805														805.8	GROUND SURFACE 0.0				
	802.3	3.5	1	1	1						S-4	37%			ALLUVIAL VERY SOFT, GRAY, SILTY CLAY, A-7-6				
800																			
	797.3	8.5	WOH	WOH	WOH									797.8	8.0 VERY LOOSE, GRAY, CLAYEY FINE TO COARSE SAND, A-2-6				
795																			
	792.9	12.9	60/0.1											792.9 792.8	12.9 13.0 CRYSTALLINE ROCK TAN AND GRAY, META-GABBRO				
790																			
785																			
														783.3	22.5 Boring Terminated at Elevation 783.3 ft IN CRYSTALLINE ROCK (META-GABBRO)				

WBS 40251.1.1				TIP U-4758				COUNTY GUILFORD				GEOLOGIST Bhuiyan, A.					
SITE DESCRIPTION BRIDGE NO. 308 ON SR 1818 (-L-) OVER WEST FORK DEEP RIVER												GROUND WTR (ft)					
BORING NO. EB2-B				STATION 56+00				OFFSET 40 ft RT				ALIGNMENT -L-				0 HR. N/A	
COLLAR ELEV. 805.8 ft				TOTAL DEPTH 22.5 ft				NORTHING 837,318				EASTING 1,700,222				24 HR. 1.0	
DRILL RIG/HAMMER EFF./DATE SME0593 CME-550X 86% 05/01/2019								DRILL METHOD H.S. Augers				HAMMER TYPE Automatic					
DRILLER Marlowe, J.				START DATE 12/19/18				COMP. DATE 12/19/18				SURFACE WATER DEPTH N/A					
CORE SIZE NQ				TOTAL RUN 9.5 ft													
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. (ft) %		ROD (ft) %	SAMP. NO.	STRATA REC. (ft) %		ROD (ft) %	L O G	DESCRIPTION AND REMARKS			DEPTH (ft)	
792.8	792.8	13.0	4.5	1:15/0.5 2:50/1.0 3:29/1.0 3:56/1.0 2:29/1.0	(3.6) 80%	(2.2) 49%			(8.6) 91%	(6.8) 72%			Begin Coring @ 13.0 ft				
790													CRYSTALLINE ROCK			13.0	
	788.3	17.5		4:49/1.0 6:16/1.0 4:26/1.0 4:28/1.0 6:25/1.0	(5.0) 100%	(4.6) 92%							TAN AND GRAY, SLIGHTLY TO MODERTELY WEATHERED, CLOSE TO MODERATELY CLOSE FRACTURE SPACING, MEDIUM HARD, META-GABBRO				
785			5.0										REC = 91% RQD = 72% GSI = 49-54				
	783.3	22.5											Boring Terminated at Elevation 783.3 ft IN CRYSTALLINE ROCK (META-GABBRO)			22.5	

# CORE PHOTOGRAPHS


**EB2-B**

BOX 1: 13.0 - 22.5 FEET



SUMMARY OF LABORATORY TEST DATA  
Soil Classification and Gradation



S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616																													
S&ME Project #:					6235-18-015										Date Report:					2/26/2019									
State Project No.:					40251.1.1					County:					Guilford					Date Tested:					2/5-2/19				
Federal ID No.:					N/A					TIP No.:					U-4758														
Project Name:					Bridge No. 308 on SR 1818 (Johnson St.) over West Fork Deep River																								
Client Name:					ATKINS										Client Address:					Raleigh, NC									
Sample No.	Station	Offset	Alignment	Sample Depth (ft)	AASHTO Classification		Total % Passing Sieve #					Total Mortar Fraction (%)				LL	PL	PI	Moist. %										
							10	40	60	200	270	Coarse Sand	Fine Sand	Silt	Clay														
S-3	54+50	CL	-L-	2.0-3.0	A-6	(5)	98	89	83	60	-	15	34	31	20	32	19	13	26.8										
S-4	56+00	40' RT	-L-	2.0-3.0	A-7-6	(24)	100	99	98	90	-	2	12	41	45	51	28	23	36.7										
S-5	55+92	3' RT	-L-	2.0-3.0	A-7-6	(14)	100	96	93	80	-	7	19	35	39	42	25	17	33.2										
References / Comments / Deviations: ND=Not Detemined. NP=Non-Plastic.																													
AASHTO T88: Particle Size Analysis of Soils as Modified by the NCDOT										AASHTO T89: Determining the Liquid Limit of Soils																			
AASHTO T90: Determining the Plastic Limit & Plasticity Index of Soils										AASHTO T265: Laboratory Determination of Moisture Content of Soils																			
AASHTO M145: The Classification of Soils and Soil Aggregate Mixtures for Highway Construction Purposes																													
Mal Krajan, ET										104-01-0703					Stacie Mitchell, PE					Project Manager									
Technician Name:					Signature					Certification #					Technical Responsibility:					Position									
This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.																													

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAY  
MATERIALS & TESTS UNIT  
PHYSICAL TESTING LABORATORY

T. I. P. No. U-4758

REPORT ON SAMPLES OF ROCK COMPRESSION

Project	40251.1.1	County	Guilford	Owner	C.M. Bruinsma
Date: Sampled	9/23/2020	Received	10/1/2020	Reported	11/5/2020
Sampled from	BR#308 onSR 1818 over West Fork Deep R.		By	C. M. Bruinsma	
Submitted by	C. M. Bruinsma			Standard Specifications	
Tested By	Michael Dubeau		Date Tested	11/5/2020	

TEST RESULTS

Proj. Sample No.	RS-1	RS-2	RS-3			
Boring Sample No.	B1-B	B2-B	B2-C			
Diameter in	1.984	1.984	1.984			
Specimen Height in	3.681	3.564	3.681			
Area in <sup>2</sup>	3.092	3.092	3.092			
H/D Ratio	1.86	1.80	1.86			
Weight lbf	1.21	1.08	1.23			
Unit Weight lbf/ft <sup>3</sup>	183.7	169.4	186.8			
Ultimate lbf	50100	26400	18610			
Ultimate ksi	16.20	8.55	6.02			
Ultimate Corrected ksi	16.05	8.43	5.97			
Sec Mod @ 40% Mpsi	11.43	8.52	11.86			
Station						
Offset						
Alignment						
Depth (ft)	22.30	22.10	31.50			
to	22.90	23.40	32.30			

cc:

Joshua Law  
Physical Testing Engineer

North Carolina Dept. of Transportation  
Division of Highways  
Materials and Tests  
Physical Testing Laboratory

Rock Compression

Lab Number:  
Project #:  
County:  
Tip ID:

0  
40251.1.1  
Guilford  
U-4758

Structure Description:  
Test Date:

Br No 308 SR 1818 over.  
11/05/2020

Sample No.	Diameter in	Specimen Height in	Area in <sup>2</sup>	H/D Ratio	Weight lbf	Unit Weight lbf/ft <sup>3</sup>	Ultimate lbf	Ultimate ksi	Ultimate (corrected) ksi	40% Ult. Load lbf	Sec Mod @ 40% Mpsi
RS-1	1.9840	3.681	3.0915	1.855	1.21	183.7	50100	16.2	16.05	20000	11.43
RS-2	1.9840	3.564	3.0915	1.796	1.08	169.4	26400	8.55	8.43	10570	8.52
RS-3	1.9840	3.721	3.0915	1.876	1.23	184.8	18610	6.02	5.97	7450	11.86



**SITE PHOTOGRAPH**

Bridge No. 308 on –L– (SR 1818) over West Fork Deep River



Looking Northeast towards End Bent 2