0600-8 REFERENCE

Ó

SEE SHEET 3 FOR PLAN SHEET LAYOUT AT TIME OF INVESTIGATION

CONTENTS

<u>LINE</u>

STATION 12+15 TO 20+95 <u>PLAN</u>

SHEET 5-6

BORE LOGS

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

ROADWAY SUBSURFACE INVESTIGATION

COUNTY NASH

PROJECT DESCRIPTION REPLACE BRIDGE NO. 36 OVER FISHING CREEK ON NC 561

INVENTORY

STATE PROJECT REFERENCE NO. **BR-0090** 6

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-8850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE OR INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION, THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.


THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED OF AN PREASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:

 1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N.C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL A. N. JONES D. G. PINTER N. O. MOORE INVESTIGATED BY A. N. JONES DRAWN BY A. N. JONES CHECKED BY N. T. ROBERSON SUBMITTED BY N. T. ROBERSON DATE MARCH 2022



UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. SHEET NO.

BR-0090
2

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED	TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT	<u>WELL GRADED</u> - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. <u>UNIFORMLY GRADED</u> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.	ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION	GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN	AQUIFER - A WATER BEARING FORMATION OR STRATA.
IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH	ANGULARITY OF GRAINS	REPRESENTED BY A ZONE OF WEATHERED ROCK.	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF.GRAY.SULTY CLAY.MOIST WITH INTERBEDDED FINE SAND LAYERS.HIGHLY PLASTIC.A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
SOIL LEGEND AND AASHTO CLASSIFICATION	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED VIOLEN NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.	ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT
CENEDAL CRANIII AR MATERIALS SILT-CLAY MATERIALS	MINERALOGICAL COMPOSITION	FINE TO COARSE CRAIN ICNEOUS AND METAMORPHIC POCK THAT	WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND
CLASS. (≤ 35% PASSING *200) (> 35% PASSING *200) ORGANIC MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAQLIN, ETC.	WOULD YIELD SPT REFUSAL IF TESTED, ROCK TYPE INCLUDES GRANITE,	SURFACE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	SINE TO COARSE CRAIN METAMORPHIC AND NON-COASTAL PLAIN	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
CLASS. A-1-a A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-7-5 A-3 A-6, A-7	COMPRESSIBILITY	NON-CRISTRELINE SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM
SYMBOL 000000000000000000000000000000000000	SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	OF SLOPE.
7. PASSING	HIGHLY COMPRESSIBLE LL > 50	SEDIMENTARY ROCK SPT REFUSAL ROCK TYPE INCLUDES LIMESTONE SANDSTONE CEMENTED	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
■10 50 MX GRANULAR SIL1- MUCK,	PERCENTAGE OF MATERIAL	CP) SHELL BEDS, ETC. WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT
*40 30 MX 50 MX 51 MN PEAT ** *200 15 MX 25 MX 10 MX 35 MX 35 MX 35 MX 35 MX 36 MN 36 MN 36 MN 36 MN 36 MN \$ SOILS ** ** ** ** ** ** ** ** ** **	GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER	ROCKS OR CUTS MASSIVE ROCK.
MATERIAL	TRACE OF ORGANIC MATTER 2 - 3%, 3 - 5%, TRACE 1 - 10%	HAMMER IF CRYSTALLINE.	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.
PASSING *40 SOILS WITH	LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20% MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN,	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE
LL	HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	(V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY, ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
GROUP INDEX 0 0 0 4 MY 8 MY 12 MY 16 MY NO MY AMOUNTS OF ORGANIC	GROUND WATER	SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE
USIAL TYPE STAME FRACE	✓ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	(SLI.) 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
OF MAJOR GRAVEL, AND SAMP CAMP SOUR SOUR SOUR SOUR		CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
MATERIALS SAND SAND STATE HAW SAND SOLES SOLES	STATIC WATER LEVEL AFTER <u>24</u> HOURS	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN (MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.
GEN. RATING EXCELLENT TO GOOD FAIR TO POOR FAIR TO POOR UNSUITABL		DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ;PI OF A-7-6 SUBGROUP IS > LL - 30	─ SPRING OR SEEP	WITH FRESH ROCK.	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE
CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH	FIELD.
PANCE OF CTANDARD PANCE OF UNICONSTINED	The same of the sa	(MOD.SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK.	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
PRIMARY SOIL TYPE COMPACINESS UN PENETRATION RESISTENCE COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION WITH SOIL DESCRIPTION OF ROCK STRUCTURES	IF TESTED, WOULD YIELD SPT REFUSAL	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
	SPT CLORE INDICATOR	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT (SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED	ITS LATERAL EXTENT.
GENERALLY LOOSE 4 TO 10	SOIL SYMBOL OPT DAT TEST BORING INSTALLATION SCORE INDICATOR INSTALLATION	TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
GRANULAR MEDIUM DENSE 10 TO 30 N/A MATERIAL DENSE 30 TO 50	ARTIFICIAL FILL (AF) OTHER AUGER BORING CONE PENETROMETER THAN ROADWAY EMBANKMENT TEST	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
(NON-COHESIVE) VERY DENSE > 50	THAN ROADWAY EMBANKMENT TEST	VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK	PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE
VERY SOFT < 2 < 0.25	──── INFERRED SOIL BOUNDARY -()- CORE BORING ● SOUNDING ROD	(V SEV.) REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR	OF AN INTERVENING IMPERVIOUS STRATUM.
GENERALLY SOFT 2 TO 4 0.25 TO 0.5 SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0	INFERRED ROCK LINE MAN MONITORING WELL TEST BORING	VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
MATERIAL STIFF 8 TO 15 1 TO 2	with cone	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS	ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE
(COHESIVE) VERY STIFF 15 TO 30 2 TO 4 HARD > 30 > 4	→ → → → ← ALLUVIAL SOIL BOUNDARY ALLUVIAL SO	ALSO AN EXAMPLE.	RUN AND EXPRESSED AS A PERCENTAGE.
HARD > 30 > 4 TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	ROCK HARDNESS	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT
		VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	ROCK,
U.S. STD. SIEVE SIZE 4 10 40 60 200 270 OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	UNDERCUT UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE	SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO
COARSE FINE	SHALLOW UNCLASSIFIED EXCAVATION - USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
BUDLDER CUBBLE GRAVEL SAND SAND (SL) (CL)		MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT
(CSE. SD.) (F SD.)	ABBREVIATIONS	HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED	OR SLIP PLANE.
GRAIN MM 305 75 2.0 0.25 0.05 0.005 SIZE IN. 12 3	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED	BY MODERATE BLOWS. MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL
	CL CLAY MOD MODERATELY γ - UNIT WEIGHT	HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL
SOIL MOISTURE - CORRELATION OF TERMS	CPT - CONE PENETRATION TEST NP - NON PLASTIC 7 _d - DRY UNIT WEIGHT	POINT OF A GEOLOGIST'S PICK.	TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
SOIL MOISTURE SCALE FIELD MOISTURE (ATTERBERG LIMITS) DESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	CSE COARSE ORG ORGANIC DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST SAMPLE ABBREVIATIONS	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
• 1 CATURATED 100101 VERY VET 100101 V		PIECES CAN BE BROKEN BY FINGER PRESSURE.	
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY (SAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH	STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERGENTAGE.
(SAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS, - FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
LL LIOUID LIMIT PLASTIC RANGE - WFT - (W) SEMISOLID: REQUIRES DRYING TO	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE - FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK FRAC FRACTURED, FRACTURES TER - TRICOME REFUSAL RT - RECOMPACTED TRIAXIAL	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. <u>TOPSOIL (TS.)</u> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
LL LIOUID LIMIT PLASTIC RANGE - WFT - (W) SEMISOLID: REQUIRES DRYING TO	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS, - FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	VERY SOFT CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE, CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING BEDDING	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
PLASTIC RANGE (PI) PL PLASTIC LIMIT (SAT.) FROM BELOW THE GROUND WATER TABLE (SAT.) FROM BELOW THE GROUND WATER TABLE SEMISOLID: REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SILINGTY RS - ROCK FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL FRAGS FRAGMENTS W - MOISTURE CONTENT CBR - CALIFORNIA BEARING	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A
PLASTIC RANGE (PI) PL OPTIMUM MOISTURE (SAT.) FROM BELOW THE GROUND WATER TABLE - WET - (W) SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE - WET - (W) SOLID; AT OR NEAR OPTIMUM MOISTURE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SILTY RS - ROCK FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL FRAGS FRAGMENTS W - MOISTURE CONTENT CBR - CALIFORNIA BEARING HI HIGHLY V - VERY RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING VERY WIDE MORE THAN 10 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET
PLASTIC RANGE (PI) PL OPTIMUM MOISTURE SHRINKAGE LIMIT (SAT.) FROM BELOW THE GROUND WATER TABLE (SAT.) FROM BELOW THE GROUND WATER TABLE - WET - (W) SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE - WET - (W) SOLID; AT OR NEAR OPTIMUM MOISTURE SHRINKAGE LIMIT	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING TERM THICKNESS VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.23 - 0.16 FEET	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES:
PLASTIC RANGE (PI) PL OPTIMUM MOISTURE (SAT.) FROM BELOW THE GROUND WATER TABLE - WET - (W) SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE - WET - (W) SOLID; AT OR NEAR OPTIMUM MOISTURE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL FRAGS FRAGMENTS W - MOISTURE CONTENT CBR - CALIFORNIA BEARING HI HIGHLY V - VERY RATIO BOULDMENT USED ON SUBJECT PROJECT DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE: CME-45C CLAY BITS AUTOMATIC MANUAL	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.003 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.003 FEET	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
LL LIQUID LIMIT PLASTIC RANGE (PI) PL OPTIMUM MOISTURE SL OPTIMUM MOISTURE SHRINKAGE LIMIT ON OPTIMUM MOISTURE SHRINKAGE LIMIT OR OPTIMUM MOISTURE TO ATTAIN OPTIMUM MOISTURE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING IERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.20 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.0008 - 0.03 FEET	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES:
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINKLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINKLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINKLY LAMINATED 0.008 FEET	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
LL LIQUID LIMIT PLASTIC RANGE (PI) PL OM OPTIMUM MOISTURE SL SHRINKAGE LIMIT OPTIMUM MOISTURE SHRINKAGE LIMIT ORY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE PLASTICITY PLASTICITY PLASTICITY PLASTICITY INDEX (PI) ORY STRENGTH	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE, CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING IERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THICKLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.20 - 0.16 FEET THINLY LAMINATED 0.000 FEET THINLY LAMINATED 0.000 FEET THINLY LAMINATED 0.000 FEET INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING IERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY BEDDED 0.008 - 0.03 FEET THICKLY BEDDED 0.008 - 0.03 FEET THICKLY LAMINATED 0.008 FEET THINLY LAMINATED 0.008 FEET THINLY LAMINATED 0.008 FEET THINLY LAMINATED TO 0.008 FEET THINLY LAMINATED 0.008 FEET THINLY BEDDED 0.008 FEET THINLY LAMINATED 0.008 F	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING IERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINKLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINKLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY MINDERDED 0.080 8 - 0.03 FEET THICKLY LAMINATED < 0.000 FEET THINKLY LAMINATED < 0.000 FEET THINKLY LAMINATED < 0.000 FEET INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. RUBBING WITH FINGER FREES NUMBEROUS GRAINS: GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINKLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINKLY BEDDED 0.008 - 0.03 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY MINDERD 0.008 - 0.03 FEET THICKLY LAMINATED 0.008 FEET THINKLY LAMINATED 0.008 FEET INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. RUBBING WITH FINGER FREES NUMBEROUS GRAINS: GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE: BREAKS EASILY WHEN HIT WITH HAMMER.	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO F - FINE SL SILT, SILTY F - FINE SL SILT, SILTY F - ST - SHELBY TUBE SS FOSSILIFEROUS SILT - SILGHTLY FRAC FRACTURED, FRACTURES FRACTOR - GROWN - FRACTURE FRACTOR - GROWN - G	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED 0.008 FEET 0.008	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING IERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET WIDE 1.5 - 4 FEET THICKLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.23 - 0.16 FEET THICKLY BEDDED 0.26 - 0.03 FEET THINLY BEDDED 0.008 - 0.03 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THICKLY LAMINATED 0.008 FEET T	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE
CSAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL. FRACTURE SPACING TERM SPACING VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED 0.008 FEET 0.008	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. BENCH MARK: N/A ELEVATION: N/A FEET NOTES: BORING ELEVATIONS TAKEN FROM TIN FILE

See Sheet 1B For Conventional Symbols WARREN! VICINITY MAP


See Sheet 1A For Index of Sheets


STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS


HALIFAX & NASH COUNTIES

LOCATION: BRIDGE NO. 36 OVER FISHING CREEK ON NC 561

TYPE OF WORK: GRADING, DRAINAGE, PAVING AND STRUCTURE








NTR

BR.

IE

PRO

GRAPHIC SCALES



DESIGN DATA ADT 2023 = 1555

ADT 2043 = 1780

T = 15 % * V = 60 MPH* TTST = 10 DUAL 5 FUNC CLASS =

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT BR-0090 = 0.127 MILES LENGTH STRUCTURE TIP PROJECT BR-0090 = 0.040 MILES TOTAL LENGTH TIP PROJECT BR-0090 = 0.167 MILES

Prepared in the Office of: **DIVISION OF HIGHWAYS**

1000 Birch Ridge Dr., Raleigh NC, 27610 2018 STANDARD SPECIFICATIONS

KRISTY ALFORD, PE PROJECT MANAGER RIGHT OF WAY DATE JORDAN WOODARD, PE JANUARY 12, 2022 LETTING DATE:

JANUARY 17, 2023

PROJECT ENGINEER DOUG KRETCHMAN, PE

HYDRAULICS ENGINEER

SIGNATURE:

ROADWAY DESIGN **ENGINEER**



INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

ROY COOPER

March 22, 2022

J. ERIC BOYETTE

SECRETARY

STATE PROJECT: 67090.1.1 (BR-0090)

FEDERAL PROJECT: N/A COUNTY: **NASH**

GOVERNOR

DESCRIPTION: Replace Bridge no. 36 over Fishing Creek on NC 561

SUBJECT: Geotechnical Report – Inventory

The Geotechnical Engineering Unit has completed a subsurface investigation for this project and presents the following inventory.

Project Description

This project consists of replacing bridge no. 36 over Fishing Creek on NC 561 and improvement to approaches.

A geotechnical investigation was conducted during March of 2022. Four hand-auger borings were performed by the Geotechnical Engineering Unit. Representative soil samples were collected for visual classification in the field.

The following alignment, totaling 0.167 miles, was investigated.

Line **Stations** -L-12+15 to 20+95

Physiography and Geology

The project is located North of the city of Nashville and within the Piedmont physiographic province of North Carolina. Soils consist of Roadway Embankment and Residual derived from underlying crystalline rock of the Raleigh Belt. The topography is gently rolling hills. The widening project consists of wooded areas.

Mailing Address: NC DEPARTMENT OF TRANSPORTATION GEOTECHNICAL ENGINEERING UNIT 1589 MAIL SERVICE CENTER RALEIGH NC 27699-1589

Telephone: (984) 920-8900

3301 JONES SAUSAGE RD, SUITE 100 Customer Service: 1-877-368-4968

Website: www.ncdot.gov

Soils Properties

Soils encountered during this investigation are Roadway Embankment, Alluvial, and Residual.

Roadway Embankment soils are present throughout the entire project. These soils primarily consist of orange, red, and tan, moist, very soft to medium stiff, sandy clay(A-6).


Alluvial soils are present in areas adjacent to Fishing Creek. These soils are characterized by tan, wet, very soft to soft, sandy silt with trace organics (A-4).

Residual soils are present throughout the entire project. These soils are characterized by orange and tan mottled, moist to wet, very soft to medium stiff, sandy clay and sandy silt (A-4, A-5) and loose to medium dense, clayey sand (A-2-6).

Groundwater

Groundwater measurements were taken during February of 2022 during average rainfall conditions. Groundwater was found to be between 1.0 to 3.7 feet below existing grade.

Sheet 3A



GEOTECHNICAL BORING REPORT BORE LOG

_													3(Jh	<u>'E</u>	<u></u>		7																	_																																			
'	VBS	670	90.1.1				TIP	3R-00	90		C	OUN	ΙΤΥ	N/	ASH							GE	OLO	GIST	٦ Jo	ones	s, A	. N.							W	/BS	6709	0.1.1	1					TIP	BR-	0090)		C	ראטכ	TY N	IASH	1						GEO	LOG	SIST	Jor	nes, /	۹. N.						
;	ITE I	DESC	RIPTIC	N RE	EPLA	CE BR	DGE N	IO. 36	OVE	R FIS	SHIN	G CF	REE	K C	N N	C 56	31													G	ROL	JND	WTF	R (ft)	s	ITE DI	ESCF	RIPTI	ION	REF	PLAC	CE E	BRID	OGE	NO.	36 C	OVEF	RFIS	HING	G CR	EEK	NO	NC 5	61												GF	OUN	ID W	TR ((ft)
I	BORI	NG N) . L_^	1300			STAT	ION	13+0	0			(OFF	SET	4	5 ft L	T				ALI	GNN	IENT	Г -L	-				() HR			1.0	В	ORING	g no	. L	_150	0				STA	TION	l 15	5+00				OF	FSE	T 5	0 ft F	RT				ALIG	MM	ENT	-L-				0	HR.		Г	Ory
-	OLL	AR E	LEV.	155.21	ft		TOTA	L DEF	TH	5.0 ft	t		Ī	NOF	RTHI	NG	893	3,30	0			EA	STIN	G 2	2,293	3,62	25			24	4 HR			1.0	С	OLLA	R EL	EV.	153	3.1 ft			-	тот	AL D	EPT	Ή 5	5.0 ft			NC	RTH	IING	893	3,396	6			EAS	TING	3 2	,293,	824			24	HR.		3	3.0
П	RILL	RIG/H	AMMER	EFF/D/	ATE	VΑ											DRIL	L ME	TH	OD	Han	d Aug	er					Н	AMN	/ER	TYPE	AL	ıtoma	tic	D	RILLR	IG/HA	MME	R EFF	/DAT	TE I	NΑ												DRIL	L ME	THC	D I	Hand.	Auger	-				Н	IAMIV	ERT	/PE	Auto	matic	;
I	RILL	.ER	Pinter,	D. G.			STAF	T DA	E C	3/01/	/22		T	CON	/IP. [AT	E ()3/0	1/22	2		SUI	RFA	CE W	VATI	ER I	DEF	РΤН	l N	/A					D	RILLE	ER F	Pinte	r, D.	G.				STA	RT D	ATE	03	3/01/2	22		CC	MP.	DAT	E 0	3/01	1/22			SURF	FAC	EW	ATE	R DE	PTH	l N	A				
E	LEV (ft)	DRIV ELE\ (ft)	E DEP (ft)	TH BI 0.5	LOW (COUN 5ft 0.	- 5ft 0		BI 25	LOWS	50	RFO		'5 	1	00	SAN	.	/	- 1 (0	ELEV	. (ft)	S	OIL A	AND	RO	CK	DES	SCR	PTIC		DEP	TH (ft)	EL (.EV E	ORIVE ELEV (ft)	DEI (†	PTH ft)	BL0 0.5ft	OW (COL .5ft	JNT 0.5f	ft (0	2	BL0 25	ows	PER 50	FOC	75	,	100	SAM	.	MC	L O II G				SC	OIL AI	ND R	ЭСК	DES	CRIP	TION			
	160		_																																1	55		<u> </u>																								0	DOLL	ND 0	N IDE	^ C F				
	155		<u> </u>																10		-	155.2						ID S						0.0	1	50		 							: :		1			: :						M			53.1 52.6	1	N-O	ROA	SE, S SAI	Y EM OFT NDY	TO I	KME //EDII /	TV	TIFF,	\int	<u>-0:5</u>
DWY_BH.GPJ NC_DOT.GDT 3/18/22	155								-		: :		:	-		-			W W		3	155.2 154.4 153.7 150.2	Т	AN, \	/ERY WI GE-1	ADV REI S Y SO TH	D, V SAN AL OFT TRA RE , SC SAN ated	/EM/ /ER\ IDY (LUV TO: ACE SIDI OFT IDY (Y SC CLA /IAL SOF ORC UAL TO CLA	FT, S GAN MED	ENT TO S SAND ICS	STIF	 _T F,	0.0 0.8 1.5 5.0		50		+++++++++++++++++++++++++++++++++++++									ŀ		ļ.		- -								48.1	\ \	ORA	NGE DE	SE, S SAI RI TAN NSE, ninate	OFT NDY ESID , LOO CLA d at I	TO I CLA' UAL OSE YEY Eleva	TO M	JM ST IEDIU 148.1	IM] 	5.0
DOUBLE BR0090_GEO_			+ + + + + + + + + + + + + + + + + + + +																																			+ + + + + + + + +																																
ACDOL BORE			+																		-																	+																				-												

GEOTECHNICAL BORING REPORT BORE LOG

		BORE LOG	T				T
WBS 67090.1.1		NTY NASH	GEOLOGIST Jones, A. N.	WBS 67090.1.1		NTY NASH	GEOLOGIST Jones, A. N.
	BRIDGE NO. 36 OVER FISHING C		GROUND WTR (ft	´ 	E BRIDGE NO. 36 OVER FISHING C		GROUND WTR (f
BORING NO. L_1800	STATION 18+00	OFFSET 50 ft LT	ALIGNMENT -L- 0 HR. Dry	´ 	STATION 20+00	OFFSET 45 ft RT	ALIGNMENT -L- 0 HR. Dr
COLLAR ELEV. 154.7 ft DRILL RIG/HAMMER EFF/DATE N/A	TOTAL DEPTH 5.0 ft	NORTHING 893,692 DRILL METHOD H	EASTING 2,293,935 24 HR. 3.7 and Auger HAMMER TYPE Automatic	7 COLLAR ELEV. 155.7 ft DRILL RIG/HAMMER EFF/DATE N/A	TOTAL DEPTH 5.0 ft	NORTHING 893,788 DRILL METHOD H	EASTING 2,294,134 24 HR. Do and Auger HAMMER TYPE Automatic
DRILLER Pinter, D. G.	START DATE 03/01/22	COMP. DATE 03/01/22	SURFACE WATER DEPTH N/A	DRILLER Pinter, D. G.	START DATE 03/01/22	COMP. DATE 03/01/22	SURFACE WATER DEPTH N/A
ELEV DRIVE DEPTH BLOW COL		OOT SAMP.		ELEV DRIVE DEPTH BLOW CO			
(ft) ELEV (ft) 0.5ft 0.5ft	0.5ft 0 25 50	400	SOIL AND ROCK DESCRIPTION ELEV. (ft) DEPTH (0.5ft 0 25 50	75 100 NO. MOI G	SOIL AND ROCK DESCRIPTION
155			154.7 GROUND SURFACE 0	160			
<u> </u>		M M	154.0 RESIDUAL 0 - 152.7 BROWN, VERY SOFT, SANDY SILT WITH 2	☑ 			
450		🙀 🚫	TRACE ORGANICS (TOPSOIL) ORANGE-TAN, LOOSE TO MEDIUM	7 +			155.7 GROUND SURFACE
150			DENSE, CLAYEY SAND ORANGE AND GRAY MOTTLED, SOFT	.0 155		M	RESIDUAL BROWN, VERY SOFT, SANDY SILT WITH
			TO MEDIUM STIFF, SANDY CLAY			M	LITTLE ORGANICS (TOPSOIL) ORANGE-TAN, SOFT TO MEDIUM STIFF,
			Boring Terminated at Elevation 149.7 ft IN RESIDUAL (SANDY CLAY)			• • • • • • • • • • • • • • • • • • • •	SANDY CLAY Boring Terminated at Elevation 150.7 ft IN
, ‡			- -				RESIDUAL (SANDY CLAY)
			- - -				_
			<u>-</u> -				_
			 -				-
			- -				- -
			- -				- -
			- -				- -
			- -				-
			- -				-
			- -				F
			- -				<u> </u>
			-				-
							E
							E
			<u>-</u> -				_
			_ -				<u>-</u> -
			- -				- -
			<u>-</u>				-
			- -				-
			- -				-
			 -				F
			- -				F
			- 				_
			- - -				_
			- -				<u>-</u>
			- -				_
			- -				ţ
			 -				<u> </u>
, ‡			- -				‡
, ‡			- -				<u> </u>
‡			- -				-
			- -				‡
	i	1 1 1			1 1	1 1 1	I .