

10'-30'/SP SKIP LINE

10'
WHITE
SKIP

15'

15'

80'

REFER TO SPACING CHART
FOR SPACING REDUCTIONS

3'-9'/SP MINI-SKIP LINE

24'

MARKER CENTERED
BETWEEN MINI-SKIP LINES

LEGEND

CRYSTAL/RED PAVEMENT MARKER

YELLOW/YELLOW PAVEMENT MARKER

DIRECTION OF TRAFFIC FLOW

GORE LINES

20'

MARKERS OFFSET 2"
FROM GORE LINES

YELLOW CENTER LINES

80'

80'

15'

15'

15'

15'

15'

15'

REFER TO SPACING CHART
FOR SPACING REDUCTIONS

MARKERS CENTERED
BETWEEN DOUBLE CENTER LINES

CENTER LINES FOR -

TWO-LANE, TWO-WAY ROADWAYS

UNDIVIDED ROADWAYS

TWO-WAY LEFT TURN LANES

DETAIL OF PAVEMENT MARKER PLACEMENT

RAISED REFLECTIVE PAVEMENT MARKERS

6"

MARKERS CENTERED BETWEEN
DOUBLE CENTER LINES

MARKERS CENTERED
BETWEEN SKIP LINES

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR
RAISED PAVEMENT MARKERS
INSTALLATION SPACING

SHEET 2 OF 3
1250D01

CONTRACTS STANDARDS
AND DEVELOPMENT UNIT

Office 919-707-8950 FAX 919-250-4119

SEE TITLE BLOCK

ORIGINAL BY: M.V. SPRINGER DATE: 2-15-24

MODIFIED BY: DATE:

CHECKED BY: DATE:

FILE SPEC.: