



Design Loading for Existing METAL POLE NO. 2
(Formerly NO. 11 Proj. No. W00117)



Elevation View

Design Loading for Existing METAL POLE NO. 3
(Formerly NO. 12 Proj. No. W00117)




Elevation View

SPECIAL NOTE


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

Elevation Data for Mast Arm Attachment (H1)

Elevation Differences for:	Pole 2	Pole 3
Baseline reference point at ϕ Foundation @ ground level	Exist.	Exist.
Elevation difference at High point of roadway surface	Exist.	Exist.
Elevation difference at Edge of travelway or face of curb	Exist.	Exist.




POLE RADIAL ORIENTATION



8 BOLT BASE PLATE DETAIL

See Note 5



BASE PLATE TEMPLATE & ANCHOR BOLT
LOCK PLATE DETAIL
For 8 Bolt Base Plate

METAL POLE No. 2 and 3

PROJECT REFERENCE NO.	SHEET NO.
U-5906	Sig. 4.3

MAST ARM LOADING SCHEDULE

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	POLYCARBONATE RIGID MOUNTED SIGNAL HEAD 12\"~4 SECTION-NO BACKPLATE	5.6 S.F.	14.0\" W x 56.0\" L	62.5 LBS
	POLYCARBONATE RIGID MOUNTED SIGNAL HEAD 12\"~3 SECTION-NO BACKPLATE	4.2 S.F.	14.0\" W x 43.0\" L	38 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0\" W x 36.0\" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	16.0 S.F.	24.0\" W x 96.0\" L	36 LBS

NOTES

DESIGN REFERENCE MATERIAL

- Design the traffic signal structure and foundation in accordance with:
 - The 1st Edition 2015 AASHTO LRFD "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
 - The 2024 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
 - The 2024 NCDOT Roadway Standard Drawings.
 - The traffic signal project plans and special provisions.
 - The NCDOT "Metal Pole Standards" located at the following NCDOT website:
<https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

DESIGN REQUIREMENTS

- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using force ratios that do not exceed 0.9.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
 - Nominal vertical rise in mast arm is 5 feet as measured from the centerline of the arm base to the centerline of the free end of the arm.
 - Signal heads are rigidly mounted and vertically centered on the mast arm.
 - The roadway clearance height for design is as shown in the elevation views.
 - The top of the pole base plate is 0.75 feet above the ground elevation.
 - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
 - Provide horizontal distance from the proposed centerline of the foundation to the edge of travelway. Refer to the Elevation Data Chart for elevation difference between the proposed foundation ground level and the edge of travelway. This information is necessary to ensure that the roadway clearance is maintained at the edge of the travelway and to aid in the camber design of the arm.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
 - Mast arm attachment height (H1) plus 2 feet, or
 - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 814-5000.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The contractor is responsible for providing soil penetration testing data (SPT) to the pole manufacturer so site specific foundations can be designed.

NCDOT Wind Zone 5 (110 mph)

	SR 5544 (West Catawba Avenue) at SR 2195 (Torrence Chapel Road)/ Liverpool Parkway Division 10 Mecklenburg County Cornelius PLAN DATE: July 2025 PREPARED BY: A.M. Kollar	REVIEWED BY: S.G. Haynie REVIEWED BY:
	REVISIONS	
0 N/A		INIT. DATE
N/A		

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
SEAL	SEAL
Steve Haynie	7/30/2025
SIG. INVENTORY NO.	10-0939