Docusign Envelope ID: 110CCD88-A958-4669-BD0D-20131993975E

SHEET NO. TIP NO. SIGN-1B L-5898 DATE: 10/20/2025 SEAL

> DOCUMENT NOT CONSIDERED FINAL **UNLESS ALL SIGNATURES COMPLETED**

Posted: 7/5/2023 Version: 3.2

																														FOOTINGS		
SIGN				NUME	BER		SUPPORT				HORIZONTAL			LENGTH	(ft)										SUPPORT	WEIGHTS					FIELD VERIFIED	
		SIZE (in.)		ROADWA	ROADWAY OF		BEAM	TYPE	OMNI	ATTACHMENT MOUNTING		CLEARANCE*	CLEARANCE* SUPPORT SNS HT		MTG HT EMBED-		LEF	LEFT SUPPORT (ft)			CENTER SUPPORT (ft)			RIGHT SUPPORT (ft)			SIMPLE	DIAMETER	DEPTH R	REINFORCED	PLAIN	SEE NOTE 2
NUMBER	TYPE	w	x h	STATION	SUPPO	ORTS	SECTION	BA or S	COUPLER	METHOD	METHOD	(ft.)	SPACING	"H"	"C"	MENT	S	L	LENGTH	S	L	LENGTH	S	L	LENGTH	(lbs.)	(lbs.)	(ft.)	(ft.)	(c.y.)	(c.y.)	(mm/dd/yy)
901	В	72	x 48	RP A 10+4	7 2	2	S3x5.7	BA	N/A	N/A	N/A	18.00	3.52	4.00	7.00	2.5	4.37	15.37	17.87	0.00	0.00	0.00	2.22	13.22	15.72	227.46	0	1.0	3	0.00	0.17	
902	Α	72	x 60	RP A 11+4	7 2	<u> </u>	S3x5.7	BA	N/A	N/A	N/A	18.00	3.52	5.00	7.00	2.5	1.72	13.72	16.22	0.00	0.00	0.00	2.30	14.30	16.80	224.21	0	1.0	3	0.00	0.17	
903	В	72	x 48	RP A 12+4	7 2	2.	S3x5.7	BA	N/A	N/A	N/A	18.00	3.52	4.00	7.00	2.0	1.72	12.72	14.72	0.00	0.00	0.00	2.30	13.30	15.30	207.11	0	1.0	2.5	0.00	0.15	
904	В	72	x 48	RP C 12+4	3 2	2	S3x5.7	ВА	N/A	N/A	N/A	18.00	3.52	4.00	7.00	2.0	2.22	13.22	15.22	0.00	0.00	0.00	2.65	13.65	15.65	211.96	0	1.0	2.5	0.00	0.15	
905	Α	72	x 60	RP C 13+4	3 2	2	S3x5.7	ВА	N/A	N/A	N/A	18.00	3.52	5.00	7.00	2.5	2.22	14.22	16.72	0.00	0.00	0.00	3.13	15.13	17.63	231.80	0	1.0	3	0.00	0.17	
906	В	72	x 48	RP C 14+9	3 2	2	S3x5.7	ВА	N/A	N/A	N/A	18.00	3.52	4.00	7.00	2.5	2.22	13.22	15.72	0.00	0.00	0.00	3.13	14.13	16.63	220.39	0	1.0	3	0.00	0.17	
			•	•	•		•		•	•	•	•	•	•	•	•	•	•	•		•	•		•	•	TOTAL	TOTAL		•	TOTAL	TOTAL	

1102.55 0.00

1103.00 0.00

0.00 0.81

0.00 1.00

NOTES

- 1. DIMENSION "S" REPRESENTS AN INCREASE (+), OR A DECREASE (-) IN POLE LENGTH, RELATIVE TO THE ELEVATION OF THE EDGE OF TRAVEL LANE.
- 2.FIELD VERIFICATIONS SHALL BE REQUIRED FOR ALL SUPPORTS, SEE (*) ARTICLE 903-3.
 FABRICATORS SHALL BE AISC CERTIFIED IN CATEGORY 1, SEE (*) ARTICLE 1072-1.
 (*) = N.C.D.O.T. STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES
- 3. PLAN LOCATIONS FOR EXISTING UTILITIES ARE BASED ON THE BEST AVAILABLE INFORMATION AND, THEREFORE MAY NOT BE PRECISELY ACCURATE. THEREFORE, IT IS INCUMBENT UPON THE CONTRACTOR TO DETERMINE THE EXACT LOCATION OF UTILITIES BEFORE BEGINNING WORK IN A LOCATION.



