



Telephone: (252) 623-2083 Fax: (252) 623-2062

www.catlinusa.com

January 31, 2025

MEMORANDUM TO: Cheryl Youngblood, LG, CPG

Assistant State Geotechnical Engineer

FROM: Yinhui Liu, PhD, PE

Geotechnical Engineer

CATLIN Engineers and Scientists

STATE PROJECT: 67173.1.1 (BR-0173)

F.A. NUMBER: Not Applicable

COUNTY: Pamlico

DESCRIPTION: Replace Bridge 680078 on NC306 Ferry over Neuse River

SUBJECT: Geotechnical Report for Pavement and Subgrade Investigation

Richard Catlin and Associates (DBA: CATLIN Engineers and Scientists) (CATLIN) have completed the evaluation of the pavement and subgrade investigation for this project and presents the following.

The proposed work consists of constructing a bridge on NC306 Ferry over Neuse River. A bridge replacement with approach roadways is proposed along the existing alignment and minor paving is proposed to widen the turn radius of the entrance to the parking lot.

The subgrade beneath the existing roadway and parking lots consists of undivided coastal plain fine sands (A-3).

Anticipated borrow will likely consist of common borrow material conforming to coastal area criteria 1018-2 (B) of the Standard Specification.

The length of this project is 180 feet.

The existing pavement is in fair condition with moderate severity, transverse and longitudinal cracking. The cracks are approximately 0.25" wide, and the cracks span throughout the whole parking area and the inner wheel along the roadway.

AREA OF SPECIAL GEOTECHNICAL INTEREST

A. Highly Plastic Clays

Highly plastic clays were not encountered during this investigation.

B. Trapped Water Within the Pavement

Trapped water was not encountered during this investigation.

C. Soils with a High Moisture Content

Soils at the project site were classified as moist to saturated.

D. Groundwater

Groundwater was encountered from 3.1' to 5.2' below ground surface at the project site.

Prepared By:



Yinhui Liu, PhD, P.E. CATLIN Senior Geotechnical Engineer

DocuSigned by:

Yinhui Liu

673A8A76BCF14BE...

02/06/2025

10 8 REFERE **CONTENTS**

DESCRIPTION TITLE SHEET

LEGEND

PLAN SHEET

LABORATORY SUMMARY SHEET

4 PAVEMENT INVESTIGATION DATA SHEET DUAL MASS DCP DATA SHEETS DUAL MASS DCP GRAPHS PAVEMENT CORE PHOTOS

IO PAVEMENT CORE EVALUATION SHEET

SHEET NO.

0

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

ROADWAY SUBSURFACE INVESTIGATION

COUNTY <u>PAMLICO</u>

PROJECT DESCRIPTION REPLACE BRIDGE 680078

ON NC306 FERRY OVER NEUSE RIVER

PAVEMENT AND SUBGRADE INVESTIGATION

STATE PROJECT REFERENCE NO. BR-0173

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANGING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FELD BORING LOGS, ROCK CORES AND SOL TEST DATA AVAILABLE MAY BE REVEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGREENING UNIT AT 1999 TOT-6850, THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARLY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORRIGS OR BETWEEN SAMPLED STRATA WITHIN THE BORRIGHGE. THE LABORATORY SAMPLE DATA AND THE M STU UN-PLACE ITEST DATA CAN BE RELED ON ONLY TO THE DEGREE OF RELIABILITY INVERENT IN THE STANDARD TEST METHOD THE OBSERVED WATER LEVELS OR SOIL MOSTURE CONDITIONS ANDICATED IN THE SUBSURFACE INVESTIGATION, THESE WATER LEVELS OR SOIL MOSTURE CONDITIONS MAY VARY CONSIDERABLY WITH THE ACCORDING TO CLIMATIC CONDITIONS MAY VARY CONSIDERABLY WITH THE ACCORDING TO CLIMATIC CONDITIONS MAY VARY CONSIDERABLY WITH THE ACCORDING TO CLIMATIC CONDITIONS MAY VARY CONSIDERABLY WITH THE ACCORDING TO CLIMATIC CONDITIONS MAY VARY CONSIDERABLY WITH THE ACCORDING TO CLIMATIC CONDITIONS MAY VARY CONSIDERABLY WITH THE ACCORDING TO CLIMATIC CONDITIONS

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELAMMARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DEFERENT, FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN MFORMATION ON THES PROJECT, THE DEPARTMENT DOES NOT WARRANT OR GUIDENEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPPINON OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO PERFORM INDEPENDENT SUBSURFACE INVESTIGATIONS AND MAKE INTERPRETATIONS AS NECESSARY TO CONFIRM CONDITIONS ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAMFOR ADDITIONAL COMPENSATION OF FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DEFERRING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

L. THE REFORMATION CONTAINED HEREIN IS NOT IMPLED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRAINSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECETICATIONS OR CONTRACT FOR THE PROJECT.

BY HAVING REQUESTED THIS MORMATION, THE CONTRACTOR SPECETICALLY WAIVES ANY CLAMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DEFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL	
T. PARK	

INVESTIGATED	BY <u>CATLIN</u>
DRAWN BY Y	
CHECKED BY _	J. STONE, LG
	J. STONE, LG
DATE JANU	





Yinhui Liu

02/06/2025

73A8A76BCF14BE SIGNATURE

DOCUMENT NOT CONSIDERED FINAL

UNLESS ALL SIGNATURES COMPLETED

BR-0173 2


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS

GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND VIELD LESS HANN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST MASKITO T 286, ASTM DISSON, SOIL CLASSIFICATION IS BASED ON THE ANSHTO SYSTEM, BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING CONSISTENCY, COLOR, TEXTURE, MOISTURE, ANSHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALGOICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE.	WELL CRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES. ANGULARITY OF GRAINS THE ANGULARITY OR ROUMDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	MARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN BLIFOOT PER 68 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK, ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ALLUYIUM MALLUYJ - SOILS THAT HAVE BEEN TRAMSPORTED BY WATER, AQUIFER - A WATER BEARING FORMATION OR STRATA, ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND, ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING
VERY STIFF,GRAY,SUTY CLAY,MOST WITH INTERBEDDED FINE SAND LIVERS,HIGHLY PLASTIC,A-7-6	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > ROCK (WR) 188 BLOWS PER FOOT IF TESTED.	A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
SOIL LEGEND AND AASHTO CLASSIFICATION GENERAL CAMALAR MATERIALS LASS. LASS. (S 302 PASSING 2000) STREET 2000 STRE	MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAQLIN, ETC.	CRYSTALLINE FINE TO COARSE CRAIN ICNEOUS AND METAMORPHIC ROCK THAT	ARTESIAN - CROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SUFFACE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	CAEISS, CABBRO, SCHIST, ETC.	CALCAREOUS ICALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
(LASS. A-1-o A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-2-5 A-2-6 A-2-7 SW80.	COMPRESSIBILITY SLIGHTLY COMPRESSIBLE LL < 31	ROCK (NCR) SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED.	COLLUVIUM - ROCK FRACMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
2 PASSING Sh 1-	MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SEDIMENTARY ROCK SPT REFUSAL, ROCK TYPE INCLUDES LIMESTONE, SANOSTONE, CEMENTED CP) SMELL BEDS, ETC.	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
10 56 MZ	PERCENTAGE OF MATERIAL GRANLIAR SILT - CLAY	WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
MATERIAL 13 MZ 23 MZ 13	ORGANIC MATERIAL GRANLLAR SOLS OTHER MATERIAL TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 18% LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 18 - 20%	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.
PASSING *40 LL 40 MXX 41 MM 50 MX 41 MM 50 MX 41 MM 50 MX 41 MM 50 MX 41 MM 61 M 50 MX 41 MM 61 M 64 MX 41 MM 61 MX 41 MX 41 MM 61 MX 41 MX 41 MM 61 MX 41	MODERATELY ORGANIC 5 - 18% 12 - 28% SOME 28 - 35% HIGHLY ORGANIC > 18% > 28% HIGHLY 35% AND ABOVE	VERY SLIGHT ROCK CENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, IV SLIJ. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY, ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	<u>DIP DIRECTION (DIP AZIMUTH)</u> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH,
CROUP INDEX 0 0 0 4 MX 8 MX 12 MX 16 MX MD MX MOUNTS OF SOILS	GROUND WATER	SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO INCH, OPEN JOINTS MAY CONTAIN CLAY, IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
USUAL TYPES STORE FRACS. OF MAJOR GRAVEL, AND SAND SILTY OR CLAYEY SILTY CLAYEY MATTER SAND GRAVEL AND SAND SOILS SOILS	▼ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS	CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
CEN, RATING SWELL TO COOR SAID TO DOOD FAIR TO DOOD INSCRITABLE	▼PW PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND MEATHERING EFFECTS. IN HOD.J GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOCKED FROM PARENT MATERIAL.
AS SUBGRADE E-ELECTION 10 0000 FINANTIN FOUN POUR FOUN OFFICIAL	- O-M⊶ SPRING OR SEEP	WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM, FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE
CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, IN GRANITOID ROCKS, ALL FELDSPARS DULL SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION, ROCK SHOWS SEVERE LOSS OF STRENGTH	FIELD.
PRIMARY SOIL TYPE COMPACTNESS OR RANGE OF STANDARD RANGE OF UNCONFINED COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) 25/825 DIP & DIP DIRECTION	(MOD. SEV.) AND CAN BE EXCAVATED WITH A CEOLOGIST'S PICK. ROCK GIVES "CLUMK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL.	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
CONSISTENCE (N-VALUE) (TONS/FT ²)	WITH SOIL DESCRIPTION → OF ROCK STRUCTURES	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT (SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAQLINIZED	ITS LATERAL EXTENT.
GENERALLY VERY LOOSE 4 4 TO 10 GRANULAR MEDIUM DENSE 10 TO 30 N/A	SOIL SYMBOL SIMBOL SLOPE INDICATOR INSTALLATION ARTIFICIAL FILL (AF) OTHER AUTER POPULAT. ARTIFICIAL FILL (AF) OTHER AUTER POPULAT.	TO SOME EXTENT. SOME FRACMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED. WOULD YIELD SPT N VALUES > 180 BPF	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED CHOT.1 - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS
	ARTIFICIAL FILL (AF) OTHER AUGER BORING COME PENETROMETER	VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK	USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL CROUND WATER LEVEL BY THE PRESENCE
VERY SOFT < 2 < 8.25 GENERALLY SOFT 2 TO 4 8.25 TO 8.5	- INFERRED SOIL BOUNDARY - CORE BORING SOUNDING ROD TEST BORING TEST BORING	IV SEV.) REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOLLD YIELD SPT IN VALUES (180 BPF	OF AN INTERVENING IMPERVIOUS STRATUM, RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE MEATHERING OF ROCK.
SILT-CLAY MEDIUM STIFF 4 TO 8 9.5 TO 1.0 MATERIAL STIFF 8 TO 15 1 TO 2 (CO-ESIVE) VERY STIFF 15 TO 30 2 TO 4	WITH CORE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS, QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS, SAPROLITE IS ALSO AN EXAMPLE.	ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE
HARD > 39 > 4	IND DEED ION	ROCK HARDNESS	RUN AND EXPRESSED AS A PERCENTAGE. SAPPOLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT
TEXTURE OR CRAIN SIZE	RECOMMENDATION SYMBOLS XX MARKEDOLY	VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	ROCK.
U.S. STD. SIEVE SIZE 4 10 40 60 200 270 OPENING (MH) 4.76 2.80 0.42 0.25 0.053 COARSE FINE	UNSUITABLE WASTE SHALLOW UNCLASSIFIED EXCAVATION - USED IN THE TOP 3 FEET OF	SEVERAL MARD BLOWS OF THE CEOLOGIST'S PICK. MARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY, MARD MAMMER BLOWS REQUIRED TO DETACH MAND SPECIMEN.	SILL - AN INTRUSIVE BODY OF ICHEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUCED ROCKS.
BOULDER COBBLE GRAVEL COARSE FINE SILT CLAY (BLDR.) (COB.) (GR.) (CSE.) (CS.) (CS.) (CL.)	ACCEPTABLE DEGRADABLE ROCK EMBANGENT OR BACKFILL ABBREVIATIONS	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 8.25 INCHES DEEP CAN BE MARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.
GRAIN MM 385 75 2.8 8.25 8.85 8.865 SIZE IN. 12 3	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST BT - BORING TERMINATED MICA, - MICACEOUS WEA, - WEATHERED	BY MODERATE BLOWS. MEDIUM CAN BE GROOVED OR COUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - MUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL
SOIL MOISTURE - CORRELATION OF TERMS	CL CLAY ODL - MODERATELY CPT - COME PENETRATION TEST MP - NON PLASTIC GET - COMPRES ODL - MODERATELY ODL - MODERATELY ODL - MODERATELY ODL - MODERATELY O	HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 8.1 FOOT PER 68 BLOWS.
SOIL MOISTURE SCALE FIELD MOISTURE GUIDE FOR FIELD MOISTURE DESCRIPTION	CSE COARSE ORG ORGANIC DNT - DILATOMETER TEST PMT - PRESSUREMETER TEST SAMPLE ABBREVIATIONS DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK	SOFT CAN BE GROVED OR COUGED READILY BY KNIFE OR PICK, CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCRES IN SIZE BY MODERATE BLOWS OF A PICK POINT, SMALL, THIN DIFFER CAN BE BORDEN BY ENVISED RESCENSE.	STRATA CORE RECOVERY ISRECT - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY (SAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SLICHTLY RS - ROCK	PIECES CAN BE BROKEN BY FINGER PRESSURE. VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SECNEM'S WITHIN A STRATUM EQUAL TO OR CREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
PLASTIC SEMISOLID: REQUIRES DRYING TO	FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL	FINGERMAIL. FRACTURE SPACING BEDDING	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
PL PLASTIC LIMIT ATTAIN OPTIMUM MOISTURE	FRAGS FRAGMENTS	TERM SPACING TERM THICKNESS	BENCH MARK: BORINGS LOCATED WITH REAL TIME KINEMATIC (RTK) GLOBAL POSITIONING SYSTEM (GPS) TO NORTH CAROLINA STATE PLANE
OM OPTIMUM NOISTURE - MOIST - (NO SOLID) AT OR NEAR OPTIMUM MOISTURE	EQUIPMENT USED ON SUBJECT PROJECT	VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET	ELEVATION: FEET
SL _ SHRIMKAGE LIMIT	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE: CME-45C CLAY BITS AUTOMATIC MANUAL	MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 8.16 - 1.5 FEET VERY THINLY BEDDED 8.83 - 8.16 FEET	NOTES:
- DRY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	G. CONTINUOUS FLIGHT AUGER	VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET	
PLASTICITY	X CME-95	INDURATION	
PLASTICITY INDEX (P)) DRY STRENGTH	CME-550 HARD FACED FINGER BITS	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	
NON PLASTIC 9-5 VERY LOW SLIGHTLY PLASTIC 6-15 SLIGHT	VANE SHEAR TEST LING,-CARBIDE INSERTS HAND TOOLS.	FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS: CENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	
MODERATELY PLASTIC 16-25 MEDIUM HIGHLY PLASTIC 26 OR MORE HIGH	CASING W/ ADVANCER POST HOLE DIGGER	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE:	
COLOR	PORTABLE HOIST TRICONE	BREAKS EASILY WHEN MIT WITH MAMMER,	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-CRAY),	CORE BIT VANE SHEAR TEST	DIFFICULT TO BREAK WITH HAMMER,	
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.	UAL MASS DCP	EXTREMELY INDURATED SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1-



Engineers and Scientists 224219 CATLIN #:

ROUTE:

PAVEMENT INVESTIGATION DATA SHEET

NC 306 over the Neuse River

BR-0173 TIP#: 67173.1.1 WBS: Pamlico COUNTY:

GATERAN.					,														OCCIVIT:		
Boring Identification	(s	WIDTH		s (Feet)				IICKNE (Inches						SUBGRADE					ASPHALT NOTES		PS DINATES
and Position (Station, Lane, Shoulder)	Cut/Fill (Inches) (Est. Amount)	Lane(s) ft	Shoulder(s) ft	Offset Distances ((See Notes)	Crown "C" or Super "S"	Gross to Top of Soil	ASPHALT	CONCRETE	ABC	Stabilized Soil / Other	PAVEMENT LAYERING	Depth (Feet)	Origin (See Notes)	Material Description	Sample Number	AASHTO Classification	Soil Moisture	Probe / Bore Depth (Feet)		NORTHING	EASTING
CS-01	Grade	66.0	N/A	N/A	N/A	7.50"		N/A	5.0"	N/A		0.6 - 5.0	СР	Tan fine SAND	CS-01	A-3	6%	5.0	Moderate severity longitudal and transverse cracks. Cracks are ~1/4" wide, and the cracks span the whole parking area.	450,398	2,657,403
CS-02	Grade	18.5	N/A	N/A	N/A	8.00"	2.75"	N/A	5.25"	N/A	Asphalt ABC	0.7 - 5.0	СР	Tan fine SAND	CS-02	A-3	12%	5.0	Moderate Inner wheel longitudal and adjacent transverse cracking. Cracks are ~ 1/4" wide, and most likely sealed.	450,388	2,657,255
CS-03	Grade	92.1	N/A	N/A	N/A	15.00"	10.0"	N/A	5.0"	N/A	Asphalt ABC	1.3 - 5.0	СР	Tan fine SAND		A-3		5.0	Moderate to severe longitudinal and lateral cracking throughout parking lot	450,502	2,657,325
																		-			
																		_			
																		-			
																		-			
																		-			

OSL = Outside Lane Notes:

CTL = Center Turn Lane ISL = Inside Lane

LTL = Left Turn Lane PS = Paved Shoulder OSS = Outside Shoulder

ACCEL = Acceleration Lane

ISS = Inside Shoulder

DECEL = Deceleration Lane IGM = Inside Grass Median

OGS = Outside Grass Median

COL = Collector Lane

RT = Right

I = Inside

Origin: RE = Roadway Embankment

FW = From White LT = Left C&G = Curb and Gutter AF = Artificial Fill CF = Curb Face CP = Coastal Plain FY = From Yellow O = Outside


RTL = Right Lane

						WBS	NO.		PROJEC	T TIP I.D.	ROUTE					
DUAL	MASS DY	NAMIC	CONE PE	NETROME	TER	6717	3.1.1		B-0	173		NC 306 over the Neuse River				
		DATA :	SHEET			COU	INTY		FIELD PRO	FESSIONAL			FIELD	CREW		
		T41				Pan			Thoma	as Park			CA	TLIN	- B	
	CS-01 - Par		ocation N 450398 I	E 2657403		Date 10/28		C2-0	2 - Ferry Q	Test Lo ueuing Lane		388 E 265	7255	Date Run 10/28/2024		
Type	T	est Interv	al	Datum		Cut,	/Fill	Type		Test Interva		Da	tum		/Fill	
9.1	113.5	ative cm p	er blow	Subgrad	de	Gra	ade	DCP 10.6	62.0	lative cm pe 124.1	r blow	Sub	grade	Gr	ade	
12.1	114.3							13.5	63.1	126.4						
13.9	114.9							15.5	63.7	128.3						
15.4 16.8	117.9 119.0							17.1 18.5	64.6 64.8	130.4 133.2						
18.3	120.6							19.9	65.3							
19.6 20.8	122.5 124.3							21.0 22.2	66.0 66.6							
22.1	125.5							23.4	67.2							
23.3	127.6							24.4	67.8							
24.3 25.5	129.5 131.3							25.4 26.2	68.4 69.0							
26.6	133.3							27.1	69.6							
27.7								28.0	70.2							
28.8 30.0								28.8 29.6	70.8 71.3							
31.2								30.6	71.7							
31.6								31.3	72.5							
32.9 34.4								32.1 32.8	73.0 73.8							
35.8								33.5	74.4							
37.0 38.4								35.0 36.1	75.4 76.0							
39.4								36.6	76.6							
41.0								37.6	77.1							
42.8 44.2								38.0 39.0	78.1 78.8					_		
46.2								39.4	79.5							
48.0								40.2	80.3							
50.2 53.5								40.8 41.2	80.9 81.6							
57.3								41.9	82.1							
60.5								42.6	82.6							
63.3 68.8								43.1 44.0	83.6 84.5							
71.5								44.6	85.3							
73.1								45.3	86.1							
74.1 75.0								46.0 46.5	87.0 87.8							
77.8								47.1	88.6							
79.1 80.7								47.7 48.2	89.6 90.5							
81.8								48.2	90.5							
83.0								49.3	92.1							
84.5 85.7								50.1 50.7	93.0 93.8	\vdash						
86.9								51.4	94.7							
88.1								51.9	95.7							
89.3 90.4								52.5 52.9	96.4 97.7							
91.7								53.4	99.7							
93.2								53.8	100.8							
94.1 95.5								54.7 55.2	101.7 103.0							
96.7								55.8	104.6							
98.3 99.8								56.4	105.1	\square				_		
101.4								57.0 57.5	106.6 108.2							
102.8								58.0	109.7							
104.1 105.6								58.5 59.1	110.8 114.0							
105.6								59.1	114.0							
108.6								60.2	118.1							
110.2 111.6								60.8 61.4	120.1 122.1							
111.0								01.4	122.1			L				

						WBS	S NO.			ROUTE					
DUAL I	MASS D	YNAMIC	CONE PE	ENETROME	ETER	6717	3.1.1		B-0	173	NC 306 over the Neuse River				
		DATA	SHEET			COL	JNTY		FIELD PRO	FESSIONA		FIELD	CREW		
							Pamlico			s Park				LIN	
			ocation				Run			Test Lo	ocation			Date	Run
Type		ueuing Lan Test Interv		502 E 26573: Datun			10/28/2024 Cut/Fill		1	est Interva	al	Dat	um	Cut/Fill	
DCP		lative cm p		Subgra			ade	Type		oot iiitoi ii				ouç	
11.7	104.5														
13.0 15.2	105.6 106.6														
16.3	107.6														
17.8	108.5														
18.7 20.3	109.9 110.9														
21.6	111.8														
22.5	112.6														
23.8	113.6														
25.4 26.7	114.4 115.2							1							
27.8	116.8														
29.8															
31.2 35.2															
50.5															
53.3															
54.4 55.7															
56.7															
58.3															
59.7															
60.6 61.8															
62.7															
63.5															
65.1 65.6															
66.2															
68.2															
68.8 69.2															
69.7															
70.1															
70.6 67.9															
71.4															
72.2															
73.3 75.7															
76.6												<u> </u>			
77.5															
78.1 79.0															
80.0															
81.1															
82.1 83.5															
84.8															
86.5															
88.4 90.0															
90.0															
93.0															
94.0															
95.4 96.2															
97.5															
98.6															
99.6															

99.6 100.6

101.6 102.6 103.5 Sheet 5



Notes:


SG = Subgrade

SS = Stabilized Soil

CTBC = Cement-Treated Base Course

ABC = Aggregate Base Course

ESG = Estimated Subgrade (Approximately 1 foot below the existing ground surface)



Notes:


SG = Subgrade

SS = Stabilized Soil

CTBC = Cement-Treated Base Course

ABC = Aggregate Base Course

ESG = Estimated Subgrade (Approximately 1 foot below the existing ground surface)



Notes:

SG = Subgrade


SS = Stabilized Soil

CTBC = Cement-Treated Base Course

ABC = Aggregate Base Course

ESG = Estimated Subgrade (Approximately 1 foot below the existing ground surface)


CATIIN	PROJECT DESCRIPTION:	TIP NUMBER:	BR-0173
Engineers and Scientists	Replace Bridge 680078 on NC306 Ferry over Neuse River	WBS NUMBER:	67173.1.1
CATLIN PROJECT NUMBER: 224219	PAVEMENT CORE PHOTOGRAPHS	COUNTY:	Pamlico







CS-01 CS-02 CS-03



PAVEMENT CORES FOR 67173.1.1, BR-0173, Pamlico County

		ABC	LAYER THICKNESS			
LINE	STATION			LIFTS	REMARKS	
CS-01 2.5" Asphalt		5.00	2.50	S	2	low stripping, low severity oxidation, vuggy limestone aggregate
CS-02	2 2.75" Asphalt	5.25	2.75	S	2	low stripping, low severity oxidation, vuggy limestone aggregate
			3.00	S	2	low stripping, low severity oxidation, vuggy limestone aggregate
CS-03 10" Asphalt		5.00	7.00	В	E 6	low severity oxidation, moderate stripping, delaminated in lift 1, possible mechanical break, vuggy limestone aggregate

CATLIN Engineers and Scientists

PROJECT REFERENCE BR-0173

SHEET 11

LABORATORY **SUMMARY SHEET**

AASHTO Standard Specifications

(As modified by NCDOT, Material and Tests Unit, 2000.)

						TEST RES	ULTS				
Proj. Sample Number	CS-01	CS-02									
Lab Sample Number	CS-01	CS-02									
Retained #4 Sieve %	0.5	1.5									
Passing #10 Sieve %	98.0	96.6									
Passing #40 Sieve %	88	61									
Passing #200 Sieve %	8	5									
					MINU	S NUMBER 1	0 FRACTIO	J			
SOIL MORTAR - 100%											
Coarse Sand Ret#60 %	31.9	76.9									
Fine Sand Ret#270 %	60.8	17.8									
Silt 0.05 - 0.005mm %	1.9	0.9									
Clay <0.005mm %	5.4	4.4									
			,								
Liquid Limit (LL)	NP	NP									
Plasticity Index (PI)	NP	NP									
AASHTO Classification /Group Index	A-3(0)	A-3(0)									
Organic Content %	N/A	N/A									
Station											
Offset											
Alignment											
Boring Identification	CS-01	CS-02									
Depth (FT)	0.6	1.3									
to	5.0	5.0									
Depth (FT) to Field Moist. Content % Tested By Submitted By Date Submitted	6	12									
Tested By	MDMASON	MDMASON									
Submitted By	LSTONE	LSTONE									
Date Submitted	12/11/24	12/11/24									

NP = Non-Plastic

NEM = Not Enough Material for Analysis

N/A = Not Applicable / Not Analyzed

Laboratory Manager

Report Date: __12/26/2024 Laboratory Report Page 1 of 1