

NOTES:

1. MOUNT SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE.
2. FIELD VERIFICATION SHALL BE REQUIRED FOR ALL FOOTING ELEVATIONS, PER THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES. PROVIDE FIELD VERIFICATION TO THE SIGNING SECTION.
3. REMOVE THE EXISTING OVERHEAD LIGHTING.
4. CUT AND REMOVE EXISTING SIGN HANGERS.
5. SIGN HANGERS AND ATTACHMENT HARDWARE SHALL BE PROVIDED AND INSTALLED ON THE ASSEMBLY TO ACCOMODATE ALL SIGNS SHOWN IN THIS PLAN SHEET.

6. MAXIMUM VERTICAL CLEARANCE SHALL BE 18' AND MEASURED FROM THE BOTTOM OF THE LOWEST WIND LOAD AREA TO THE SURFACE OF THE ROADWAY.
7. SEE STANDARD 904-3(B)(3) FOR REQUIREMENTS OF NEW STRUCTURAL MEMBERS, MOUNTING HARDWARE FOR NEW SIGNS, SHOP DRAWINGS, BRACING, AND ACCESSORY HARDWARE FOR ATTACHMENTS.

OVERHEAD SIGN ASSEMBLY

