

EMERGENCY VEHICLE PREEMPTION
PROGRAMMING DETAIL

(program controller as shown below)

From Main Menu press 'A' (Preemption), then '1' (Standard Preemptions). Press 'NEXT' as needed to advance to Preempts 3 and 5.

PREEMPTION #3			SETTINGS (NEXT:1-10)									
INTERVAL/TIMING			CLEAR/DWELL PHASES									
GRN	YEL	RED	1	2	3	4	5	6	7	8	9	10
1	255	0.0	0.0									
2	0	0.0	0.0									
3	0	0.0	0.0									
4	0	0.0	0.0									
5	1	0.0	0.0									
EXIT CALLS			OPTIONS									
			PRIORITY (Y/N TO SELECT)MED									
			DELAY TIMER (0-255 SEC)0									
			MIN GREEN BEFORE PRE (0= DEFAULT)....1									
			PED CLEAR BEFORE PRE (0= DEFAULT)....0									
			YELLOW CLEAR BEFORE PRE (0= DEFAULT).0.0									
			RED CLEAR BEFORE PRE (0= DEFAULT)....0.0									
			DWELL MIN TIMER (0-255 SEC)12									
			DWELL MAX TIMER (0=OFF,1-255MIN)0									
			DWELL HOLD-OVER TIMER (0-255)0									
			LATCH CALL?N									
			LINK TO NEXT PREEMPT?N									
			ENABLE BACKUP PROTECTION?N									
			HOLD CLEAR 1 PHASES DURING DELAY? ...N									
			FAST GREEN FLASH DWELL PHASES?N									
			PED CLEARANCE THROUGH YELLOW?Y									
			INHIBIT OVERLAP GREEN EXTENSION?N									
			SERVICE DURING SOFTWARE FLASH?N									
			REST IN RED DURING DWELL INTERVAL? ..N									
			FLASH DWELL INTERVAL?N									
			ALLOW PEDS IN DWELL INTERVAL?N									
			RE-TIME DWELL INTERVAL?N									
			OVERLAPS: ABCDEFGHIJKLMNOP									
			DWELL INT FLASH YELLOW									
			OMIT OVERLAPS:									

PRESS 'NEXT' TWICE

PREEMPTION #5			SETTINGS (NEXT:1-10)									
INTERVAL/TIMING			CLEAR/DWELL PHASES									
GRN	YEL	RED	1	2	3	4	5	6	7	8	9	10
1	255	0.0	0.0									
2	0	0.0	0.0									
3	0	0.0	0.0									
4	0	0.0	0.0									
5	1	0.0	0.0									
EXIT CALLS			OPTIONS									
			PRIORITY (Y/N TO SELECT)MED									
			DELAY TIMER (0-255 SEC)0									
			MIN GREEN BEFORE PRE (0= DEFAULT)....1									
			PED CLEAR BEFORE PRE (0= DEFAULT)....0									
			YELLOW CLEAR BEFORE PRE (0= DEFAULT).0.0									
			RED CLEAR BEFORE PRE (0= DEFAULT)....0.0									
			DWELL MIN TIMER (0-255 SEC)12									
			DWELL MAX TIMER (0=OFF,1-255MIN)0									
			DWELL HOLD-OVER TIMER (0-255)0									
			LATCH CALL?N									
			LINK TO NEXT PREEMPT?N									
			ENABLE BACKUP PROTECTION?N									
			HOLD CLEAR 1 PHASES DURING DELAY? ...N									
			FAST GREEN FLASH DWELL PHASES?N									
			PED CLEARANCE THROUGH YELLOW?Y									
			INHIBIT OVERLAP GREEN EXTENSION?N									
			SERVICE DURING SOFTWARE FLASH?N									
			REST IN RED DURING DWELL INTERVAL? ..N									
			FLASH DWELL INTERVAL?N									
			ALLOW PEDS IN DWELL INTERVAL?N									
			RE-TIME DWELL INTERVAL?N									
			OVERLAPS: ABCDEFGHIJKLMNOP									
			DWELL INT FLASH YELLOW									
			OMIT OVERLAPS:									

PROGRAMMING COMPLETE

Program extend time
on optical detector
unit for 2.0 seconds.

ACCESSIBLE PEDESTRIAN SIGNAL (APS)
INSTALLATION NOTES

1. Install push buttons and APS equipment per manufacturer's instructions.
2. Provide a dedicated cable to each push button per manufacturer's instructions.
3. If APS equipment is mounted in cabinet, use filtered power (i.e., Controller Receptacle) to power APS equipment. Do not use Equipment Receptacle, which is a GFCI outlet.
4. Never attempt to operate a standard contact closure push button with the APS system unless cabinet is re-wired for standard button operation or unless explicitly allowed by the manufacturer.
5. Place manufacturer's instructions in cabinet with cabinet prints, signal plans, and electrical details.
6. An APS push button station that is designed to work without the need for interfacing with a pedestrian signal head shall be installed for applications where a push button is installed in a median without a pedestrian signal head.
7. A push button with a single tactile arrow that point in both directions of travel shall be installed if the median separates two parallel crosswalks.

COUNTDOWN PEDESTRIAN SIGNAL OPERATION

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

FLASHER CIRCUIT MODIFICATION DETAIL

IN ORDER TO INSURE THAT SIGNALS FLASH CONCURRENTLY ON THE SAME APPROACH, MAKE THE FOLLOWING FLASHER CIRCUIT CHANGES:


1. ON REAR OF PDA - REMOVE WIRE FROM TERM. T2-4 AND TERMINATE ON T2-2.
2. ON REAR OF PDA - REMOVE WIRE FROM TERM. T2-5 AND TERMINATE ON T2-3.
3. REMOVE FLASHER UNIT 2.

THE CHANGES LISTED ABOVE TIES ALL PHASES AND OVERLAPS TO FLASHER UNIT 1.

PROJECT REFERENCE NO.	SHEET NO.
U-5728	Sig. 3.4

THIS ELECTRICAL DETAIL IS FOR
THE SIGNAL DESIGN: 03-0090
DESIGNED: July 2026
SEALED: 7-21-2026
REVISED: N/A

Project #: 230906



DAVENPORT
HOME OFFICE:
119 BROOKSTOWN AVENUE, SUITE PH1
WINSTON-SALEM, NC 27101
336.744.1636 www.davenportworld.com
NCBELS FIRM LICENSE NO. C-2522

Temporary Design 2 (TMP Phase 5-Step1)
Electrical Detail - Sheet 3 of 3

Prepared for:



750 N. Greenfield Pkwy, Garner, NC 27529

7/22/2026

7/22/2026

US 17 Bus. (Marine Boulevard)
at
SR 1308 (Gum Branch Road/
Bell Fork Road)

Division 03

Onslow County

Jacksonville

PLAN DATE: July 2026

REVIEWED BY: D. Bennett

PREPARED BY: B. Dowell

REVIEWED BY:

REVISIONS

INIT.

DATE

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

SEAL



Signed by: Donald R. Bennett II

2CEB3701D4084FC...

7/22/2026

SIGNATURE

DATE

SIG. INVENTORY NO. 03-0090T2