

MATCHLINE -Y3- STA 34+00.00 - SEE SHEET 10

**120 x 35 x 3
2.0 inch Skimmer
with 1.75 inch
Orifice Diameter
16 ft. weir
ID 10A.1**

NOTE: POTENTIAL BMPSCM IN PROPOSED DITCH AREA

**BASE DITCH W/
VEGETATED BENCH
AND CLASS B RIP RAP
EST 130 TONS
EST 345 SY GEOTEXTILE
EST 405 CY DDE
SLOPE=0.2%
SEE DETAIL 56**

**STANDARD BASE DITCH
W/CLASS B RIP RAP
EST 625 TONS
EST 1490
SY GEOTEXTILE
EST 910 CY DDE
SLOPE=0.2%
SEE DETAIL 57**

**CITY OF ASHEVILLE
DB 2053 PG 438
PB 72 PG 53**

**DEBORAH A GERHARDT
DB 1928 PG 310
PB 21 PG 43**

**WEST ASHEVILLE HOUSE
OF PRAYER INC
DB 5270 PG 752
PB 21 PG 43**

**CADDOVA STREET LLC
DB 4521 PG 989
PB 21 PG 43**

**FRANK E GOODSON
CHRIST FELLOWSHIP
CENTER
DB 2324 PG 218
PB 21 PG 43**

**PROGRESS ENERGY OF
THE CAROLINAS FKA
CAROLINA POWER & LIGHT
DB 600 PG 600**

**RIVER FRONT STUDIO LLC
DB 4235 PG 803
PB 14 PG 173**

CITY LIMITS = EDGE OF RIVER

-Y3- POT Sta. 37+71.38

NOTE: POTENTIAL BMP/SCM IN PROPOSED DITCH AREA

STANDARD BASE DITCH
W/CLASS B RIP RAP
EST 625 TONS
EST 1490
SY GEOTEXTILE
EST 910 CY DDE
SLOPE = 0.2%
SEE DETAIL 57

NOTE: POTENTIAL BMP/SCM IN PROPOSED DITCH AREA SEE

CITY OF ASHEVILLE
DB 2053 PG 438
PB 72 PG 53

RIVER FRONT STUDIO I
DB 4235 PG 803
PB 14 PG 73

NOTE:	PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.
NOTE:	ALL EROSION CONTROL DEVICES SHOWN ARE LOCATED WITHIN EXISTING RW OR EASEMENT.
NOTE:	PERMETER EROSION CONTROL MEASURES SHALL BE INSTALLED DURING CLEARING AND GRUBBING PHASE.
NOTE:	CONTRACTOR SHALL PROVIDE GROUND COVER ON EXPOSED SLOPES IN ACCORDANCE WITH THE "SOIL STABILIZATION TIMEFRAMES," SEE EC-3C.
NOTE:	PRIOR TO INSTALLATION OF EROSION CONTROL DEVICES, CONTRACTOR SHALL VERIFY BOUNDARIES OF JURISDICTIONAL AREAS AND DELINEATE WITH SAFETY FENCE OR FLAGGING.