

8/17/99

CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 10

NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
DRAINAGE OUTLETS.

NOTE:
UTILIZE FABRIC INSERT INLET PROTECTION DEVICE IN LIEU OF
ROCK INLET SEDIMENT TRAP, TYPE-C, AS DIRECTED TO AVOID
IMPOUNDMENT OF RUNOFF IN ROADWAY OPEN TO TRAFFIC.

HNTB

HNTB NORTH CAROLINA, P.C.
4000 Center at North Hills St
Suite 200
Raleigh North Carolina 27609
NC License No: C-1554

PROJECT REFERENCE NO.		SHEET NO.
R-5759		EC-10/CONST-10
RW SHEET NO.		
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER

MATCHLINE -L- STA. 86+50.00 SEE SHEET 9

MATCHLINE -L- STA. 99+50.00 SEE SHEET 11

- HPB
- CONCRETE SIDEWALK
- CONCRETE ISLAND

- NOTE:
1. ALL DRIVEWAY RADII ARE 20' UNLESS NOTED ON PLANS.
 2. ALL OUTSIDE CURB & GUTTER ARE 2'-6" UNLESS OTHERWISE NOTED.
 3. ALL ISLANDS ARE KEYED-IN 5" MONOLITHIC CONCRETE ISLANDS UNLESS OTHERWISE NOTED.
 4. FOR ISLAND DIMENSIONS, SEE DETAIL 28-9.

FOR ROW MONUMENT INFORMATION SEE PSH 2B-13
FOR EMERGENCY VEHICLE ACCESS DETAIL SEE SHEET 2B-15
FOR -L- PROFILE, SEE SHEETS 21 & 22
FOR -Y8- PROFILE, SEE SHEET 34
FOR -DRW5- PROFILE, SEE SHEET 34
FOR -DRW6- PROFILE, SEE SHEET 35
FOR -Y9- PROFILE, SEE SHEET 35
FOR RETAINING WALL 3 PLANS, SEE SHEETS W3-1 THRU W3-7