

CONTRACT: C204397

NCDOT CONTACT: NATHAN ADIMA, P.E.

STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS
CONVENTIONAL PLAN SHEET SYMBOLS

BOUNDARIES AND PROPERTY:

State Line	
County Line	
Township Line	
City Line	
Reservation Line	
Property Line	
Existing Iron Pin	
Computed Property Corner	
Property Monument	
Parcel/Sequence Number	
Existing Fence Line	
Proposed Woven Wire Fence	
Proposed Chain Link Fence	
Proposed Barbed Wire Fence	
Existing Wetland Boundary	
Proposed Wetland Boundary	
Existing Endangered Animal Boundary	
Existing Endangered Plant Boundary	
Existing Historic Property Boundary	
Known Contamination Area: Soil	
Potential Contamination Area: Soil	
Known Contamination Area: Water	
Potential Contamination Area: Water	
Contaminated Site: Known or Potential	

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	
Sign	
Well	
Small Mine	
Foundation	
Area Outline	
Cemetery	
Building	
School	
Church	
Dam	

HYDROLOGY:

Stream or Body of Water	
Hydro, Pool or Reservoir	
Jurisdictional Stream	
Buffer Zone 1	
Buffer Zone 2	
Flow Arrow	
Disappearing Stream	
Spring	
Wetland	
Proposed Lateral, Tail, Head Ditch	
False Sump	

RAILROADS:

Standard Gauge	
RR Signal Milepost	
Switch	
RR Abandoned	
RR Dismantled	

RIGHT OF WAY & PROJECT CONTROL:

Secondary Horiz and Vert Control Point	
Primary Horiz Control Point	
Primary Horiz and Vert Control Point	
Exist Permanent Easment Pin and Cap	
New Permanent Easement Pin and Cap	
Vertical Benchmark	
Existing Right of Way Marker	
Existing Right of Way Line	
New Right of Way Line	
New Right of Way Line with Pin and Cap	
New Right of Way Line with Concrete or Granite R/W Marker	
New Control of Access Line with Concrete C/A Marker	
Existing Control of Access	
New Control of Access	
Existing Easement Line	
New Temporary Construction Easement	
New Temporary Drainage Easement	
New Permanent Drainage Easement	
New Permanent Drainage /Utility Easement	
New Permanent Utility Easement	
New Temporary Utility Easement	
New Aerial Utility Easement	

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	
Existing Curb	
Proposed Slope Stakes Cut	
Proposed Slope Stakes Fill	
Proposed Curb Ramp	
Existing Metal Guardrail	
Proposed Guardrail	
Existing Cable Guiderail	
Proposed Cable Guiderail	
Equality Symbol	
Pavement Removal	

VEGETATION:

Single Tree	
Single Shrub	

*S.U.E. = Subsurface Utility Engineering

Hedge	
Woods Line	
Orchard	
Vineyard	

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	
Bridge Wing Wall, Head Wall and End Wall	
MINOR:	
Head and End Wall	
Pipe Culvert	
Footbridge	
Drainage Box: Catch Basin, DI or JB	
Paved Ditch Gutter	
Storm Sewer Manhole	
Storm Sewer	

UTILITIES:

POWER:	
Existing Power Pole	
Proposed Power Pole	
Existing Joint Use Pole	
Proposed Joint Use Pole	
Power Manhole	
Power Line Tower	
Power Transformer	
U/G Power Cable Hand Hole	
H-Frame Pole	
U/G Power Line LOS B (S.U.E.*)	
U/G Power Line LOS C (S.U.E.*)	
U/G Power Line LOS D (S.U.E.*)	

TELEPHONE:

Existing Telephone Pole	
Proposed Telephone Pole	
Telephone Manhole	
Telephone Pedestal	
Telephone Cell Tower	
U/G Telephone Cable Hand Hole	
U/G Telephone Cable LOS B (S.U.E.*)	
U/G Telephone Cable LOS C (S.U.E.*)	
U/G Telephone Cable LOS D (S.U.E.*)	
U/G Telephone Conduit LOS B (S.U.E.*)	
U/G Telephone Conduit LOS C (S.U.E.*)	
U/G Telephone Conduit LOS D (S.U.E.*)	
U/G Fiber Optics Cable LOS B (S.U.E.*)	
U/G Fiber Optics Cable LOS C (S.U.E.*)	
U/G Fiber Optics Cable LOS D (S.U.E.*)	

WATER:

Water Manhole	
Water Meter	
Water Valve	
Water Hydrant	
U/G Water Line LOS B (S.U.E.*)	
U/G Water Line LOS C (S.U.E.*)	
U/G Water Line LOS D (S.U.E.*)	
Above Ground Water Line	

TV:

TV Pedestal	
TV Tower	
U/G TV Cable Hand Hole	
U/G TV Cable LOS B (S.U.E.*)	
U/G TV Cable LOS C (S.U.E.*)	
U/G TV Cable LOS D (S.U.E.*)	
U/G Fiber Optic Cable LOS B (S.U.E.*)	
U/G Fiber Optic Cable LOS C (S.U.E.*)	
U/G Fiber Optic Cable LOS D (S.U.E.*)	

GAS:

Gas Valve	
Gas Meter	
U/G Gas Line LOS B (S.U.E.*)	
U/G Gas Line LOS C (S.U.E.*)	
U/G Gas Line LOS D (S.U.E.*)	
Above Ground Gas Line	

SANITARY SEWER:

Sanitary Sewer Manhole	
Sanitary Sewer Cleanout	
U/G Sanitary Sewer Line	
Above Ground Sanitary Sewer	
SS Forced Main Line LOS B (S.U.E.*)	
SS Forced Main Line LOS C (S.U.E.*)	
SS Forced Main Line LOS D (S.U.E.*)	

MISCELLANEOUS:

Utility Pole	
Utility Pole with Base	
Utility Located Object	
Utility Traffic Signal Box	
Utility Unknown U/G Line LOS B (S.U.E.*)	
U/G Tank; Water, Gas, Oil	
Underground Storage Tank, Approx. Loc.	
A/G Tank; Water, Gas, Oil	
Geoenvironmental Boring	
U/G Test Hole LOS A (S.U.E.*)	
Abandoned According to Utility Records	
End of Information	


6/2/99

8/17/2021 4:23:03 PM
R-2233BB.RDY.TYP.2A-1.DGN
115561-0000


PAVEMENT SCHEDULE (FINAL)							
ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION		
A1	7" CONCRETE TRUCK APRON	E4	PROP. APPROX. 5.0" ASPHALT CONCRETE BASE COURSE,TYPE B25.0C, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YARD.	R4	PROPOSED 2'-0" MODIFIED VALLEY GUTTER		
C1	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YARD.	E5	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YARD PER 1" DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 3" OR GREATER THAN 5.5" IN DEPTH.	R5	PROPOSED 8" x 12" CONCRETE CURB		
C2	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YARD IN EACH OF TWO LAYERS.	J1	PROP. 6" AGGREGATE BASE COURSE	R6	PROPOSED CONCRETE EXPRESSWAY GUTTER		
C3	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YARD PER 1" IN DEPTH TO BE PLACED IN LAYERS NOT TO EXCEED 1.5" IN DEPTH.	J2	PROP. 8" AGGREGATE BASE COURSE	S	4" CONCRETE SIDEWALK		
C4	PROP. APPROX. 3.0" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YARD IN EACH OF TWO LAYERS.	K1	PROP. CHEMICAL STABILIZATION (SOIL-CEMENT BASE/LIME-TREATED SOIL). BASE TREATED WITH CEMENT AT A RATE OF 56 LBS. PER SQ. YARD @ 7" DEPTH OR SOIL TREATED WITH LIME AT A RATE OF 24 LBS. PER SQ. YARD @ 8" DEPTH.	T	EARTH		
C5	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YARD PER 1" IN DEPTH TO BE PLACED IN LAYERS NOT TO EXCEED 2" IN DEPTH.	K2	PROP. 8" CLASS IV SUBGRADE STABILIZATION	U	EXISTING PAVEMENT		
D1	PROP. APPROX. 2.5" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 285 LBS. PER SQ. YARD.	N1	GEOTEXTILE FOR SOIL STABILIZATION	V1	INCIDENTAL MILLING (SEE MILLING DETAIL V1)		
D2	PROP. APPROX. 4.0" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YARD.	N2	GEOTEXTILE FOR PAVEMENT STABILIZATION	V2	INCIDENTAL MILLING (SEE MILLING DETAIL V2)		
D3	PROP. VAR. DEPTH ASPHALT CONC. INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YARD PER 1" DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 2.5" OR GREATER THAN 4" IN DEPTH.	P	PRIME COAT AT THE NORMAL APPLICATION RATE OF 0.35 GAL. PER SQ. YARD	V3	1.5 " PAVEMENT MILLING		
E1	PROP. APPROX. 3.0" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YARD.	R1	2'-6" CONCRETE CURB AND GUTTER	V4	0" TO 3" PAVEMENT MILLING		
E2	PROP. APPROX. 4.0" ASPHALT CONCRETE BASE COURSE,TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YARD.	R2	SHOULDER BERM GUTTER (SBG)	Z	MILLED RUMBLE STRIP		
E3	PROP. APPROX. 4.5" ASPHALT CONCRETE BASE COURSE,TYPE B25.0C, AT AN AVERAGE RATE OF 513 LBS. PER SQ. YARD.	R3	5" MONOLITHIC CONCRETE ISLAND (KEYED IN)	W1	W2	W3	VARIABLE DEPTH ASPHALT (SEE WEDGING DETAILS ON THIS SHEET)

NOTES:


- ALL PAVEMENT EDGE SLOPES ARE 1:1 UNLESS OTHERWISE NOTED.
- USE 4:1 MAX SLOPES ON THE INSIDE OF INTERCHANGE AREAS.
- SEE PLANS FOR LOCATION OF ACCELERATION AND DECELERATION LANES.
- SEE PLANS FOR LOCATION OF TURN LANE AND INTERSECTION TURNOUTS.
- SEE PLANS FOR LOCATION OF ALL PAVEMENT TAPERS.
- ALL DRIVEWAY RADII ARE 10' UNLESS SHOWN OTHERWISE ON PLANS.




WEDGING DETAIL - W1
USE IN CONJUNCTION WITH TS Nos. 5 & 5A




WEDGING DETAIL - W2
USE IN CONJUNCTION WITH TS Nos. 6, 7A, & 19A




WEDGING DETAIL - W3
USE IN CONJUNCTION WITH TS No. 8A, 15 & 20




DETAIL FOR CHEMICAL STABILIZATION-GEOTEXTILE FOR PAVEMENT STABILIZATION WITH ABC
USE IN CONJUNCTION WITH TYPICAL SECTIONS No.1, 5, 13, & 14 WHERE GEOTEXTILE IS REQUIRED. FOR LOCATIONS SEE SHEET 3G-1.



GEOTEXTILE FOR SOIL STABILIZATION PLACEMENT (PLAN VIEW)
(100% COVERAGE REQUIRED)




GEOTEXTILE FOR PAVEMENT STABILIZATION PLACEMENT (PLAN VIEW)
(100% COVERAGE REQUIRED)



DETAIL FOR CHEMICAL STABILIZATION-GEOTEXTILE FOR PAVEMENT STABILIZATION WITH ASPHALT BASE
USE IN CONJUNCTION WITH TYPICAL SECTIONS No. 7, 7A, 8, 9, 9A, 9B, 10, 12, 15, 16, 17, 18 19, 19A, 21, 22 & 23 WHERE GEOTEXTILE IS REQUIRED. FOR LOCATIONS SEE SHEET 3G-1.

PAVEMENT SCHEDULE (FINAL)

ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM				DESCRIPTION		
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8"LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB			(U)	EXIST. PAVEMENT			
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER			(Z)	MILLED RUMBLE STRIP			
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK	(V1)	(V2)	(V3)	(V4)	PAVEMENT MILLING		
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(P)	PRIME COAT	(R4)	2' MODIFIED VALLEY GUTTER	(T)	EARTH		(W1)	(W2)	(W3)	VARIABLE DEPTH PAVEMENT WEDGING



TYPICAL SECTION NO. 1


NOTE: SEE SHEET 2A-9 FOR THE GRADING ONLY
TYPICAL SECTION FROM -L3- 732+00.00 TO -L3- 743+00

SOUTHBOUND LANES

-L3- 744+75.00 TO -L3- 773+94.15 (BRIDGE)
-L3- 774+97.75 (BRIDGE) TO -L3- 948+00.00


NORTHBOUND LANES

-L3- 744+75.00 TO -L3- 773+85.37 (BRIDGE)
-L3- 774+88.77 (BRIDGE) TO -L3- 955+00.00




TYPICAL SECTION NO. 2

-RPA- 14+53.78 TO -RPA- 23+94.24 -RPB- 13+70.55 TO -RPB- 25+50.13
-RPC- 14+56.68 TO -RPC- 23+71.04 -RPD- 13+36.43 TO -RPD- 24+00.00




TYPICAL SECTION NO. 3

-LPA- 11+61.84 TO -LPA- 16+31.16 -LPB- 12+89.84 TO -LPB- 17+01.04
-LPC- 11+83.18 TO -LPC- 16+33.37 -LPD- 15+12.97 TO -LPD- 19+71.53




TYPICAL SECTION NO. 4

-LPB- 17+01.04 TO -LPB- 21+72.55 -LPD- 19+71.53 TO -LPD- 26+53.27
-RPB- 25+50.13 TO -RPB- 30+40.47 -RPD- 24+00.00 TO -RPD- 30+87.27




TYPICAL SECTION NO. 4A

-LPC- 16+33.37 TO	-LPC- 19+61.65	-LPA- 16+31.16 TO	-LPA- 19+53.84
-RPC- 23+71.04 TO	-RPC- 27+03.60	-RPA- 23+94.24 TO	-RPA- 27+23.95



DETAIL FOR SHOULDER BERM GUTTER

USE IN CONJUNCTION WITH -L3- TYPICAL SECTION No.1




DETAIL FOR SHOULDER BERM GUTTER

USE IN CONJUNCTION WITH -RPD- TYPICAL SECTION No. 2

6/2/99

8/17/2021 4:23:08 PM
R2233BB.DWG
TYP. TYP. 2A-3.DGN

PAVEMENT SCHEDULE (FINAL)													
ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8" LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(P)	PRIME COAT	(T)	EARTH
												(U)	EXIST. PAVEMENT
												(Z)	MILLED RUMBLE STRIP
												(V1)	PAVEMENT MILLING
												(W1)	VARIABLE DEPTH PAVEMENT WEDGING
												(W2)	
												(W3)	



△ PAVEMENT WIDTH VARIES FROM 12' TO 30' FOR SUPERSTREET BULB-OUTS.

△ PAVEMENT WIDENING WIDTH VARIES FROM 4' TO 22' FOR SUPERSTREET BULB-OUTS.


TYPICAL SECTION NO. 5

SOUTHBOUND LANES

-L3- 948+00.00 TO -L3- 952+00.00
(PAVEMENT WEDGING FROM 0' TO 24')
-L3- 952+00.00 TO -L3- 996+27.26
(FULL DEPTH PAVEMENT)

NORTHBOUND LANES

-L3- 955+00.00 TO -L3- 996+27.26




SOUTHBOUND LANES

-L3TIE- 10+00.00 TO -L3TIE- 17+29.95


NORTHBOUND LANES

-L3- 996+27.26 TO -L3- 1004+00.00




INCIDENTAL MILLING DETAIL - V1

USE IN CONJUNCTION WITH TYPICAL SECTION No. 5A
-L3- 1003+25.00 TO -L3- 1004+00.00




DETAIL NO. 1 FOR NOISE WALLS

USE IN CONJUNCTION WITH -L3- TYPICAL SECTION No.1



DETAIL NO. 2 FOR NOISE WALLS

USE IN CONJUNCTION WITH -L3- TYPICAL SECTION No.1



DETAIL NO. 3 FOR NOISE WALLS

USE IN CONJUNCTION WITH -L3- TYPICAL SECTION No.1


PROJECT REFERENCE NO. R-2233BB	SHEET NO. 2A-3
ROADWAY DESIGN ENGINEER SEAL 020031 DENNIS J. MORRIS	PAVEMENT DESIGN ENGINEER SEAL 024964 JOSEPH T. HOLLAND
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Dewberry 2610 WYCLIFF ROAD SUITE 410 RALEIGH, NC 27607 PHONE: 919.881.9939 NC CSA No. F-00261	
NC DEPARTMENT OF TRANSPORTATION PAVEMENT MANAGEMENT UNIT 1593 MAIL SERVICE CENTER RALEIGH, NC 27699-1593	

6/2/99

8/17/2023 4:23:41 PM
R2233BB.RDY.TYP.2A-4.DGN
11566.000


PAVEMENT SCHEDULE (FINAL)

ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8" LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB	(U)	EXIST. PAVEMENT
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER	(Z)	MILLED RUMBLE STRIP
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK	(V1)(V2)(V3)(V4)	PAVEMENT MILLING
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(R4)	2' MODIFIED VALLEY GUTTER	(T)	EARTH	(W1)(W2)(W3)	VARIABLE DEPTH PAVEMENT WEDGING
								(P)	PRIME COAT						




TYPICAL SECTION NO. 6

-Y2- 17+25.00 TO -Y2- 42+25.00




PROPOSED RETAINING WALL

-Y2- 27+67+/- TO -Y2- 31+45+/- - EASTBOUND
-Y2- 28+41+/- TO -Y2- 30+91+/- - WESTBOUND
NOTE: SIDEWALK ON WESTBOUND SIDE ONLY.
SEE BRIDGE PLANS FOR WALL LOCATION & DETAILS



TYPICAL SECTION NO. 6A

-Y2- 14+66.70 TO -Y2- 17+25.00
-Y2- 40+49.83 TO -Y2- 42+25.00




TYPICAL SECTION NO. 7

WESTBOUND LANES

-Y3- 14+75.00 TO -Y3- 25+40.52 BRIDGE
-Y3- 27+69.52 BRIDGE TO -Y3- 37+25.00

EASTBOUND LANES

-Y3- 14+75.00 TO -Y3- 25+40.52 BRIDGE
-Y3- 27+69.52 BRIDGE TO -Y3- 32+05.00
(SEE DETAIL FOR OMVT THIS SHEET)




TYPICAL SECTION NO. 7A

WESTBOUND LANES

-Y3- 13+10.00 TO -Y3- 14+75.00
-Y3- 37+25.00 TO -Y3- 41+50.00


EASTBOUND LANES

-Y3- 13+10.00 TO -Y3- 14+75.00
-Y3- 33+96.00 TO -Y3- 39+88.56
-Y3- 40+67.67 TO -Y3- 41+50.00




TYPICAL SECTION NO. 8

-Y19- 12+75.00 TO -Y19- 20+03.44 (BRIDGE)
-Y19- 21+84.94 (BRIDGE) TO -Y19- 28+50.00




TYPICAL SECTION NO. 8A

-Y19- 6+75.00 TO -Y19- 12+75.00 SIDEWALK - RIGHT
-Y19- 28+50.00 TO -Y19- 30+20.73 CURB & GUTTER /NO SIDEWALK - LEFT



OVER MOUNTAIN VICTORY TRAIL (OMVT)

-Y3- 21+60.55 TO -Y3- 25+40.52 BRIDGE
-Y3- 27+69.52 BRIDGE TO -Y3- 32+05.00



INCIDENTAL MILLING DETAIL - V2


USE INCONJUNCTION WITH ALL -Y- LINE TIE-INS
-Y3- 13+10.00 TO -Y3- 13+50.00
-Y3- 41+10.00 TO -Y3- 41+50.00

USE INCONJUNCTION WITH TS No. 7
-Y3- 21+53.59 TO -Y3- 31+35.00 (CONCRETE VERTICAL BARRIER)
-Y3- 22+00.00 TO -Y3- 25+40.52 BRIDGE (BIKE SAFE HANDRAIL-RIGHT)
-Y3- 27+69.52 BRIDGE TO -Y3- 31+35.00 (BIKE SAFE HANDRAIL-RIGHT)
-Y3- 24+50.00 TO -Y3- 25+00.00 WIDTH VARIES FROM 10' TO 8'
-Y3- 28+00.00 TO -Y3- 28+50.00 WIDTH VARIES FROM 8' TO 10'
SIDEWALK WIDTH IS 8' ON THE PROPOSED BRIDGE.
SEE CROSS SECTIONS & BRIDGE PLANS.

6/2/99


8/17/2021 4:23:44 PM
R-2233BB.RDY.TYP_2A-5.DGN
USER:cmo

PAVEMENT SCHEDULE (FINAL)													
ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8" LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(P)	PRIME COAT	(T)	EARTH
												(U)	EXIST. PAVEMENT
												(Z)	MILLED RUMBLE STRIP
												(V1)	(V2)
												(V3)	(V4)
												(W1)	(W2)
												(W3)	




TYPICAL SECTION NO. 9

-Y6- 10+00.00 TO -Y6- 25+92.57
-Y6- 26+12.41 TO -Y6- 33+21.90
-DR4- 12+00.00 TO -DR4- 14+17.87
NOTE - STABILIZATION NOT REQUIRED FOR DRIVEWAY -DR4-




TYPICAL SECTION NO. 9A

-Y6- 26+60.00 TO -Y6- 27+11.00 - RIGHT
-Y6- 26+25.06 TO -Y6- 26+64.31 (FDPS - RIGHT)




TYPICAL SECTION NO. 9B

-Y6- 27+11.00 TO -Y6- 26+60.00 - RIGHT
-DR4 13+14.00 TO 13+97.10 - LEFT
NOTE - STABILIZATION NOT REQUIRED FOR DRIVEWAY -DR4-




TYPICAL SECTION NO. 10

-Y22A- 34+50.00 TO -Y22A- 40+24.15
-Y23- 36+60.00 TO -Y23- 39+33.33




TYPICAL SECTION NO. 11

-Y4- 17+00.00 TO -Y4- 18+50.00 - LEFT (MILL & OVERLAY)
-Y4- 18+50.00 TO -Y4- 23+45.84




INCIDENTAL MILLING DETAIL - V2
USE INCONJUNCTION WITH ALL -Y- LINE TIE-INS
-Y23- 36+60.00 TO -Y23- 37+00.00



TYPICAL SECTION NO. 12

-Y18- 14+30.00 TO -Y18- 18+11.97
-Y18- 15+50.00 TO -Y18- 16+50.00 - RIGHT wHANDRAIL



TYPICAL SECTION NO. 12A

-Y18- 10+30.42 TO -Y18- 14+30.00


PROJECT REFERENCE NO. R-2233BB		SHEET NO. 2A-5	
ROADWAY DESIGN ENGINEER 		PAVEMENT DESIGN ENGINEER 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
		2610 WYCLIFF ROAD SUITE 410 RALEIGH, NC 27607 PHONE: 919.881.9939 NC CSA No. F-00251	
		NC DEPARTMENT OF TRANSPORTATION PAVEMENT MANAGEMENT UNIT 1593 MAIL SERVICE CENTER RALEIGH, NC 27699-1593	

6/2/99

8/17/2021 4:23:47 PM
R2233BB.RDY.TYP_2A-6.DGN
USER: dmcc


PAVEMENT SCHEDULE (FINAL)

ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM				DESCRIPTION		
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8" LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB				(U)	EXIST. PAVEMENT		
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER				(Z)	MILLED RUMBLE STRIP		
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK	(V1)	(V2)	(V3)	(V4)	PAVEMENT MILLING		
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(P)	PRIME COAT	(R4)	2' MODIFIED VALLEY GUTTER	(T)	EARTH		(W1)	(W2)	(W3)	VARIABLE DEPTH PAVEMENT WEDGING




TYPICAL SECTION NO. 13

-DR2- 9+67.72 TO -DR2- 19+44.66
-DR3- 10+25.16 TO -DR3- 16+75.00




TYPICAL SECTION 14

WOVEN WIRE FENCE BERM DETAIL
-L3- 751+20.89 TO -L3- 759+00.00 NORTHBOUND LANES
-DR2- 11+80.00 TO -DR2- 19+44.00




TYPICAL SECTION NO. 15

-Y5- 11+75.00 TO -Y5- 21+01.44
-Y11- 10+47.29 TO -Y11- 28+00.00
-Y12- 11+25.00 TO -Y12- 33+00.00




TYPICAL SECTION NO. 16

-Y10- 20+58.96 TO -Y10- 24+81.26 - LEFT
-Y10- 20+58.96 TO -Y10- 24+81.26 - RIGHT




TYPICAL SECTION NO. 17

-Y10- 26+75.30 TO -Y10- 29+70.35 - RIGHT
-Y10- 26+75.66 TO -Y10- 29+70.35 - LEFT




TYPICAL SECTION NO. 18


ROUNDABOUT -RAB-
-RAB- STA 0+00.00 TO -RAB- STA 3+58.14



INCIDENTAL MILLING DETAIL - V2
USE IN CONJUNCTION WITH ALL -Y- LINE TIE-INS
-Y5- 11+75.00 TO -Y5- 12+15.00
-Y12- 11+25.00 TO -Y12- 11+65.00
-Y12- 32+60.00 TO -Y12- 33+00.00



DETAIL FOR SHOULDER BERM GUTTER
USE IN CONJUNCTION WITH TYPICAL SECTION No. 15



DETAIL FOR MODIFIED VALLEY GUTTER
USE IN CONJUNCTION WITH TYPICAL SECTION No. 18
FOR ROUNDABOUT TRUCK APRON

PROJECT REFERENCE NO. R-2233BB SHEET NO. 2A-6

ROADWAY DESIGN ENGINEER DENNIS J. MORRIS SEAL 020031 NORTH CAROLINA PROFESSIONAL ENGINEER


PAVEMENT DESIGN ENGINEER JOSEPH T. HOLLAND SEAL 024964 NORTH CAROLINA PROFESSIONAL ENGINEER

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Dewberry


2610 WYCLIFF ROAD SUITE 410 RALEIGH, NC 27607 PHONE: 919.881.9939 NC CEA NO. F-00261 NC DEPARTMENT OF TRANSPORTATION PAVEMENT MANAGEMENT UNIT 1593 MAIL SERVICE CENTER RALEIGH, NC 27699-1593

PAVEMENT SCHEDULE (FINAL)													
ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8" LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(P)	PRIME COAT	(T)	EARTH
												(U)	EXIST. PAVEMENT
												(Z)	MILLED RUMBLE STRIP
												(V1)	PAVEMENT MILLING
												(W1)	VARIABLE DEPTH PAVEMENT WEDGING
												(W2)	
												(W3)	




TYPICAL SECTION NO. 19

-Y8- 15+00.00 TO -Y8- 20+57.13
-Y10- 18+30.59 TO -Y10- 20+58.16




TYPICAL SECTION NO. 19A

-Y8- 22+07.13 TO -Y8- 36+60.00




TYPICAL SECTION NO. 20

-Y9- 13+50.00 TO -Y9- 16+53.96




TYPICAL SECTION NO. 21

-Y7- 14+75.00 TO -Y7- 23+08.78
-Y7A- 13+75.00 TO -Y7A- 17+98.84




TYPICAL SECTION NO. 22

-Y25REV- 17+50.00 TO -Y25REV- 33+28.28



TYPICAL SECTION NO. 23

-Y25EXT- 10+12.00 TO -Y25EXT- 13+00.00



INCIDENTAL MILLING DETAIL - V2

USE INCONJUNCTION WITH ALL -Y- LINE TIE-INS

-Y7- 14+75.00 TO -Y7- 15+15.00
-Y7A- 13+75.00 TO -Y7A- 14+15.00
-Y8- 15+00.00 TO -Y8- 15+40.00
-Y8- 36+20.00 TO -Y8- 36+60.00
-Y9- 13+50.00 TO -Y9- 13+90.00
-Y25EXT- 13+00.00 TO -Y25EXT- 13+55.00

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

2A-7

ROADWAY DESIGN ENGINEER



PAVEMENT DESIGN ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

Dewberry



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9939
NC CSA No. F-00251



NC DEPARTMENT OF TRANSPORTATION
PAVEMENT MANAGEMENT UNIT
1593 MAIL SERVICE CENTER
RALEIGH, NC 27699-1593

6/2/99

8/17/2021 4:23:23 PM
R2233BB.RDY.TYP_2A-8.DGN
USER:cmo


PAVEMENT SCHEDULE (FINAL)

ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION	ITEM	DESCRIPTION
(A1)	7" CONCRETE	(C4)	3" S9.5C	(D3)	VAR DEPTH I19.0C	(E4)	5" B25.0C	(K1)	CHEMICAL STABILIZATION: 7" SOIL-CEMENT BASE OR 8" LIME-TREATED SOIL	(R1)	2'-6" CONCRETE CURB & GUTTER	(R5)	8"x12" CONCRETE CURB	(U)	EXIST. PAVEMENT
(C1)	1.5" S9.5B	(C5)	VAR DEPTH S9.5C	(E1)	3" B25.0C	(E5)	VAR DEPTH B25.0C	(K2)	8" CLASS IV SUBGRADE STABILIZATION	(R2)	SHOULDER BERM GUTTER	(R6)	CONCRETE EXPRESSWAY GUTTER	(Z)	MILLED RUMBLE STRIP
(C2)	3" S9.5B	(D1)	2.5" I19.0C	(E2)	4" B25.0C	(J1)	6" ABC	(N1)	GEOTEXTILE FOR SOIL STABILIZATION	(R3)	5" CONC. ISLAND	(S)	4" CONC. SIDEWALK	(V1)(V2)(V3)(V4)	PAVEMENT MILLING
(C3)	VAR DEPTH S9.5B	(D2)	4" I19.0C	(E3)	4.5" B25.0C	(J2)	8" ABC	(N2)	GEOTEXTILE FOR PAVEMENT STABILIZATION	(R4)	2' MODIFIED VALLEY GUTTER	(T)	EARTH	(W1)(W2)(W3)	VARIABLE DEPTH PAVEMENT WEDGING
								(P)	PRIME COAT						




CUL-DE-SACS			
LABEL	STREET	CENTER	PAVING LIMITS
-CUL1-	LAUREL HILL RD.	-Y25- 15+70.10 (20.25' RT.)	-Y25- 15+00.65
-CUL2-	LAUREL HILL RD.	-DR2- 10+34.38 (23.69' RT.)	-Y25- 25+16.69
-CUL3-	EAST 2ND ST.	-Y16- 13+03.91 (20.92' LT.)	-Y16- 12+32.17
-CUL4-	EAST 2ND ST.	-Y16- 17+82.39 (19.25' RT.)	-Y16- 18+55.84
-CUL5-	COLLETT ST.	-Y17- 13+21.98 (20.16' RT.)	-Y17- 12+52.47
-CUL6-	COLLETT ST.	-Y17- 17+78.13 (17.44' LT)	-Y17- 18+50.00
-CUL7-	REESE ST.	-Y20- 11+92.83 (20.91' LT.)	-Y20- 11+23.32
-CUL8-	SOUTHERN ST.	-Y21- 17+36.58 (22.04' RT.)	-Y21- 16+64.63
-CUL9-	LONG ST.	-Y23- 25+93.98 (22.00' RT.)	-Y23- 26+64.82
-CUL10-	ROCK RD.	-Y22A- 34+80.00 (19.00' LT.)	-Y22A- 39+96.06
-CUL13-	GILBOA CHURCH RD.	-Y42- 14+45.32 (21.36' RT.)	-Y42- 15+46.08
-CUL14-	SOUTHERN ST.	-L3- 839+94.99 (150.79' RT.)	-L3- 840+01.33 (211.66' RT)
-CUL11-	OLD US 221	-Y12- 41+97.56 (21.19' LT)	-Y12- 41+28.01
-CUL15-	LONG ST.	-Y23A- 45+53.87 (21.00' RT.)	-Y23A- 46+28.28
-CUL16-	OLD CHARLOTTE RD.	-L3- 779+79.91 (226.59' LT.)	-L3- 779+38.74 (289.42' LT.)

STREET CONNECTIONS		
LABEL	DESCRIPTION	LOCATION
-STCON1-	OAK ST. TO REECE ST.	-Y20- 13+72.71 TO -Y20- 16+56.66
-STCON2-	HILDERBRAND DR. TO HUDGEN'S LAKE DR.	-L3- 871+07.28 (131.42' LT.) TO -L3- 871+55.28 (147.40' LT.)
-STCON3-	SASAFFRAS DR. TO RIDGELAND DR.	-L3- 896+53.63 (129.30' LT.) TO -L3- 896+89.24 (185.15' LT.)
-STCON4-	CHURCH ST. TO SANDY WOODS LN.	-Y23- 21+23.17 TO -Y23- 21+52.30 (43.68' RT.)
-STCON5-	US 221 TO GOLD HILL MISSIONARY BAPTIST CHURCH	-L3- 941+22.37 (127.71' LT.) TO -L3- 944+44.60 (129.15' LT.)



RAILS TO TRAILS PAVEMENT CONNECTIONS			
LOCATION	DESCRIPTION	PAVING LENGTH	BOLLARD LOCATIONS
-Y6- 14+11 LT.	EXISTING TRAIL IS 7' GRAVEL	LENGTH = 30'	PLACE 38' LT.
-Y6- 14+48 RT.	EXISTING TRAIL IS 7' GRAVEL	LENGTH = 24'	PLACE 32' RT.
-Y11- 14+82 RT.	EXISTING TRAIL IS 12' PAVED	LENGTH = 21'	PLACE 35' RT.
-Y11- 14+82 LT.	EXISTING TRAIL IS 12' PAVED	LENGTH = 21'	PLACE 35' LT.
-TR1-	EXISTING TRAIL IS 12' PAVED	LENGTH = 176'	SEE SHEET 11
-TR2-	EXISTING TRAIL IS 7' GRAVEL	LENGTH = 150'	SEE SHEET 11



SHOULDER DRAIN DETAIL B25.0C

NOTE: SEE SHEET 3B-4 FOR STATION LOCATIONS AND QUANTITY SUMMARY.

PROJECT REFERENCE NO.
R-2233BB

SHEET NO.
2A-8

ROADWAY DESIGN ENGINEER

PAVEMENT DESIGN ENGINEER

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9939
NC CSA No. F-00263

NC DEPARTMENT OF TRANSPORTATION
PAVEMENT MANAGEMENT UNIT
1593 MAIL SERVICE CENTER
RALEIGH, NC 27699-1593

SOUTHBOUND LANES

-L3- 733+30.00 TO -L3- 743+21.39



TEMPORARY PAVEMENT FROM
-Y3- 12+50.00 TO 19+50.00



TEMPORARY PAVEMENT FROM
-Y3- 12+50.00 TO 19+50.00



TYPICAL SECTION NO. 29

TEMPORARY PAVEMENT FROM
-Y18DET- 10+76.97 TO 13+80.03



TEMPORARY PAVEMENT FROM
-Y18DET- 10+76.97 TO 13+80.03




GRADING ONLY

NORTHBOUND LANES

-L3- 733+30.00 TO -L3- 743+21.39

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
 Deberry	2610 HWY/CIF ROAD SUITE 410 RALEIGH, NC 27607 PHONE: 919-881-7029 NC COA No. F-0629
	NC DEPARTMENT OF TRANSPORTATION PAYMENT MANAGEMENT UNIT 1593 MAIL SERVICE CENTER RALEIGH, NC 27699-1593

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



5/14/99
8/17/2021 4:24:53 PM
125233338B_Rdy_PSH4A.dgn
LISTED: 000000

CURVE DATA FOR -Y25REV-			CURVE DATA FOR -Y25EXT-		
PI Sta 15+51.99	PI Sta 22+34.65	PI Sta 31+10.35	PI Sta 11+53.14	PI Sta 14+91.68	
$\Delta = 18^{\circ} 50' 34.9" (RT)$	$\Delta = 26^{\circ} 13' 38.7" (RT)$	$\Delta = 15^{\circ} 00' 00.0" (RT)$	$\Delta = 46^{\circ} 01' 04.5" (RT)$	$\Delta = 2^{\circ} 09' 18.4" (RT)$	
$D = 5^{\circ} 27' 24.3"$	$D = 5^{\circ} 27' 24.3"$	$D = 9^{\circ} 32' 57.5"$	$D = 28^{\circ} 38' 52.4"$	$D = 1^{\circ} 48' 47.4"$	
$L = 345.32'$	$L = 480.64'$	$L = 157.08'$	$L = 160.63'$	$L = 118.86'$	
$T = 174.23'$	$T = 244.61'$	$T = 78.99'$	$T = 84.93'$	$T = 59.44'$	
$R = 1,050.00'$	$R = 1,050.00'$	$R = 600.00'$	$R = 200.00'$	$R = 3,160.00'$	
SE = EXIST.	SE = .05	SE = .06	SE = .06	SE = EXIST.	



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27603
PHONE: 919.881.9939
NC CON No. F-29259


PROJECT REFERENCE NO.
R-2233BB

SHEET NO.
4A

ROADWAY DESIGN
ENGINEER
NORTH CAROLINA
PROFESSIONAL
SEAL
020031
DEVINIS J. MORRIS

HYDRAULICS
ENGINEER
NORTH CAROLINA
PROFESSIONAL
SEAL
12786
STEVEN M. BORDOR


DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



SEE SHEET 85 FOR -Y25REV- PROFILE
SEE SHEET 86 FOR -Y25EXT- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99

8/17/2001 4:24:55 PM
JSEB: 3353388.RDY_PSH05.DGN




Dewberry
2010 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27603
PHONE: 919.881.9279
NC CON No. F-2925

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		5
RW SHEET NO.		HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER		SEAL 12786
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

CURVE DATA FOR -RPB-		
Pls Sta 11+20.02 Δs = 3' 0" 59.9" Ls = 180.00' LT = 120.02' ST = 60.02'	Pls Sta 16+29.91 Δ = 29' 38" 50.3" (LT) D = 3' 22" 13.2" L = 879.65' T = 449.91' R = 1,700.00' SE = .06	Pls Sta 21+09.66 Δs = 2' 31' 39.9" Ls = 150.00' LT = 100.01' ST = 50.01'
CURVE DATA FOR -Y74-		
Pls Sta 15+16.42 Δ = 24' 19" 03.7" (RT) D = 2' 33" 11.8" L = 952.41' T = 483.48' R = 2,244.00' SE = EXIST.	Pls Sta 11+75.00 Δ = 5' 59" 12.9" (RT) D = 1' 42" 43.6" L = 349.68' T = 175.00' R = 3,346.50' SE = EXIST.	Pls Sta 17+27.25 Δ = 3' 27' 46.4" (RT) D = 1' 06" 44.8" L = 311.29' T = 155.69' R = 5,150.42' SE = EXIST.

SEE SHEET 34 FOR -L3- PROFILE
SEE SHEET 56 FOR -RPB- PROFILE
SEE SHEET 85 FOR -Y25REV- PROFILE
SEE SHEET 86 FOR -DR2- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS




5/14/99

8/17/2021 4:25:05 PM
JSEB, SBOB
R-2233BB, RDY_PSH07.DGN

MATCH TO SHEET 6 - L3- STA. 782+00.00

MATCH TO SHEET 8 - L3- STA. 794+50.00



CURVE DATA FOR -L3-
PI Sta 774+55.22
 $\Delta = 6^\circ 21' 09.5''$ (LT)
 $D = 0' 14' 56.8''$
 $L = 2,550.11'$
 $T = 1,276.36'$
 $R = 23,000.00'$
SE = NC

CURVE DATA FOR -Y16-


PI Sta 11+74.86 $\Delta = 9^\circ 57' 00.8''$ (LT) $D = 6' 23' 53.3''$ $L = 155.52'$ $T = 77.95'$ $R = 895.51'$	PI Sta 13+58.60 $\Delta = 6' 44' 04.4''$ (LT) $D = 5' 18' 41.4''$ $L = 126.79'$ $T = 63.47'$ $R = 1,078.71'$	PI Sta 17+01.15 $\Delta = 9' 15' 12.4''$ (RT) $D = 13' 55' 20.5''$ $L = 66.46'$ $T = 33.30'$ $R = 411.54'$	PI Sta 18+72.03 $\Delta = 15' 51' 05.9''$ (RT) $D = 5' 47' 31.0''$ $L = 273.68'$ $T = 137.72'$ $R = 989.23'$	PI Sta 20+41.30 $\Delta = 13' 11' 55.6''$ (RT) $D = 19' 54' 11.8''$ $L = 66.31'$ $T = 33.30'$ $R = 287.87'$
--	---	---	---	--

Dewberry

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9939
NC CON No. F-2925


PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		7
RW SHEET NO.		HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER		SEAL 12786
NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 020031 DENNIS J. MORRIS		NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 12786 STEVEN M. BONDOR
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

SEE SHEET 37 FOR -L3- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS



SEE SHEET 38 FOR -L3- PROFILE
SEE SHEETS C1-1 THRU C1-5 FOR CULVERT PLANS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

8/17/2021 4:25:42 PM
JSEB: 3388.RDY_PSH09.DGN



CURVE DATA FOR -L3-				CURVE DATA FOR -Y20A-			
PI Sta 816+54.67	PI Sta 825+28.78	PI Sta 833+82.14		PI Sta 12+36.83	PI Sta 13+32.1	PI Sta 13+86.81	PI Sta 14+9.82
Os = 1° 36' 41.2"	Δ = 22° 35' 44.0" (RT)	Os = 1° 36' 41.2"		Δ = 3° 19' 12.5" (RT)	Δ = 0° 36' 06.8" (LT)	Δ = 27° 06' 40.0" (RT)	Δ = 48° 03' 58.1" (RT)
Ls = 225.00'	D = 1° 25' 56.6"	Ls = 225.00'		D = 7° 57' 27.9"	D = 0° 32' 31.4"	D = 76° 23' 39.7"	D = 163° 42' 08.0"
LT = 150.01'	L = 1,577.47'	LT = 150.01'		L = 41.72'	L = 111.04'	L = 35.49'	L = 29.36'
ST = 75.01'	T = 799.12'	ST = 75.01'		T = 20.87'	T = 55.52'	T = 18.08'	T = 15.61'
	R = 4,000.00'			R = 720.00'	R = 10,570.00'	R = 75.00'	R = 35.00'
	SE = .05						

PI Sta 14+54.40	PI Sta 14+75.16	PI Sta 14+75.16	PI Sta 14+75.16
Δ = 7° 56' 30.6" (RT)	Δ = 19° 05' 54.7"	Δ = 19° 05' 54.7"	Δ = 19° 05' 54.7"
D = 19° 05' 54.7"	D = 19° 05' 54.7"	D = 19° 05' 54.7"	D = 19° 05' 54.7"
L = 41.58'	L = 20.83'	L = 20.83'	L = 20.83'
T = 20.83'	T = 20.83'	T = 20.83'	T = 20.83'
R = 300.00'	R = 300.00'	R = 300.00'	R = 300.00'

SEE SHEET 39 FOR -L3- PROFILE
SEE SHEETS 62 & 63 FOR -Y19- PROFILE
SEE SHEETS 53-1 THRU 53-34 FOR STRUCTURE PLANS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

2810 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27609
PHONE: 919.881.9979
NC CON. NO. F-2925


PROJECT REFERENCE NO.
R-2233BB


SHEET NO.
9


ROADWAY DESIGN ENGINEER
NORTH CAROLINA PROFESSIONAL SEAL
020031
ENGINEER
DENNIS J. MORRIS

HYDRAULICS ENGINEER
NORTH CAROLINA PROFESSIONAL SEAL
12786
ENGINEER
STEVEN M. BORDOWITZ

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED








CURVE DATA FOR -RPD-

Pls Sta 12+00.19	Pls Sta 15+27.21	Pls Sta 18+12.27
$\Delta s = 7' 45'' 00.0''$	$\Delta = 23' 09'' 28.9''$ (LT)	$\Delta s = 4' 57'' 36.0''$
$Ls = 300.00'$	$D = 5' 10'' 00.0''$	$Ls = 192.00'$
$LT = 200.19'$	$L = 448.22'$	$LT = 128.05'$
$ST = 100.17'$	$T = 227.21'$	$ST = 64.05'$
	$R = 1,089.95'$	
	$SE = .08$	


CURVE DATA FOR -L3-

Pls Sta 860+48.88	Pls Sta 872+38.56	Pls Sta 884+21.15
$\Delta s = 0' 29'' 53.6''$	$\Delta = 11' 09'' 17.8''$ (LT)	$\Delta s = 0' 29'' 53.6''$
$Ls = 200.00'$	$D = 0' 29'' 53.6''$	$Ls = 200.00'$
$LT = 133.33'$	$L = 2,238.94'$	$LT = 133.33'$
$ST = 66.67'$	$T = 1,123.02'$	$ST = 66.67'$
	$R = 11,500.00'$	
	$SE = RC$	
	$RUNOFF = 90.00'$	

SEE SHEET 43 FOR -L3 PROFILE
SEE SHEET 67 FOR -RPA- PROFILE
SEE SHEET 72 FOR -RPD- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS




SEE SHEET 44 FOR -L3 PROFILE
SEE SHEET 78 FOR -Y5- PROFILE
SEE SHEETS C3-1 THRU C3-5 FOR CULVERT PLANS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

TRAFFIC DATA



Pls Sta 901+81.18
 $\theta_s = 1^\circ 16' 35.0''$
 $L_s = 180.00'$
 $LT = 120.00'$
 $ST = 60.00'$

CURVE DATA FOR -13-

PI Sta 906+97.73
 $\Delta = 12^\circ 53' 42.4''$ (LT)
 $D = 1^\circ 25' 05.6''$
 $L = 909.25'$
 $T = 456.55'$
 $R = 4,040.00'$
 $SE = .04$

Pls Sta 912+10.43
 $\theta_s = 1^\circ 16' 35.0''$
 $L_s = 180.00'$
 $LT = 120.00'$
 $ST = 60.00'$

Δ $29^{\circ}15'.232''$ (RT)	Δ $41^{\circ}41'.823''$ (LT)	Δ $39^{\circ}11'.558''$ (LT)
$D = 1^{\circ}27'.330''$	$D = 1^{\circ}27'.330''$	$D = 1^{\circ}27'.330''$
$L = 255.31'$	$L = 363.39'$	$L = 342.07'$
$T = 130.50'$	$T = 190.37'$	$T = 178.04'$
$R = 500'$	$R = 500'$	$R = 500'$
$SE = .06$	$SE = .06$	$SE = .06$
$RUNOFF = 126'$	$RUNOFF = 126'$	$RUNOFF = 126'$


SEE SHEET 46 FOR -L3- PROFILE
SEE SHEET 79 FOR -Y10- PROFILE
SEE SHEET 80 FOR -Y12- PROFILE
SEE SHEET 2B-5 FOR CONC. ISLAND DETAILS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99
8/17/2001 4:25:42 PM
R-2233BB.RDY_PSH16.DGN
USER: GADON



2010 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9999
NC CON No. F-29259


PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		16
RW SHEET NO.		HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER		SEAL 12786
		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		



CURVE DATA FOR -Y12-				CURVE DATA FOR -L3-					
PI Sta 25+13.97 $\Delta = 39^\circ 11' 56.8''$ (LT) $D = 11' 27.330''$ $L = 342.07'$ $T = 178.04'$ $R = 500'$ $SE = .06$ RUNOFF = 126'	PI Sta 30+01.85 $\Delta = 34^\circ 37' 23.5''$ (RT) $D = 11' 27.330''$ $L = 302.14'$ $T = 155.84'$ $R = 500'$ $SE = .06$ RUNOFF = 126'	PI Sta 34+26.32 $\Delta = 12^\circ 57' 49.0''$ (RT) $D = 3' 53.516''$ $L = 332.60'$ $T = 167.01'$ $R = 1,470'$ $SE = .04$ RUNOFF = 84'	PI Sta 36+75.27 $\Delta = 2^\circ 20' 38.0''$ (RT) $D = 1' 24.217''$ $L = 166.70'$ $T = 83.36'$ $R = 4,075'$ $SE = EX.$	PIs Sta 901+81.8 $\Delta = 1^\circ 16' 35.0''$ $Ls = 180'$ $LT = 120'$ $ST = 60'$	PI Sta 906+97.73 $\Delta = 12^\circ 53' 42.4''$ (LT) $D = 1' 25.056''$ $L = 909.25'$ $T = 456.55'$ $R = 4,040'$ $SE = .04$	PIs Sta 912+10.43 $\Delta = 1^\circ 16' 35.0''$ $Ls = 180'$ $LT = 120'$ $ST = 60'$	PIs Sta 916+06.01 $\Delta = 1^\circ 13' 48.4''$ $Ls = 180'$ $LT = 120'$ $ST = 60'$	PI Sta 924+88.88 $\Delta = 22^\circ 12' 42.0''$ (RT) $D = 1' 22.004''$ $L = 1,625.10'$ $T = 822.88'$ $R = 4,192'$ $SE = .04$	PIs Sta 933+51.11 $\Delta = 1^\circ 13' 48.4''$ $Ls = 180'$ $LT = 120'$ $ST = 60'$

SEE SHEET 47 FOR -L3- PROFILE
SEE SHEET 80 FOR -Y12- PROFILE
SEE SHEET 28-5 FOR CONC. ISLAND DETAILS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99
8/17/2014 2:45:45 PM
L:\RFB\333333\B.RDY.PSH17.DGN



CURVE DATA FOR -L3-

Pls Sta 916+06.01	Pls Sta 924+88.88	Pls Sta 933+51.11
$\Delta s = 1' 13' 48.4''$	$\Delta = 22' 12' 42.1''$ (RT)	$\Delta s = 1' 13' 48.4''$
$Ls = 180'$	$D = 1' 22' 00.4''$	$Ls = 180'$
$LT = 120'$	$L = 1,625.10'$	$LT = 120'$
$ST = 60'$	$T = 822.88'$	$ST = 60'$
	$R = 4,192'$	
	$SE = .04$	

CURVE DATA FOR -Y12-

Pls Sta 40+50.12
$\Delta = 0' 52' 36.2''$ (LT)
$D = 0' 09' 01.4''$
$L = 583'$
$T = 291.51'$
$R = 38,100'$
$SE = EX.$




2010 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9939
NC CON No. F-2925

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		17
RW SHEET NO.		
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

SEE SHEET 48 FOR -L3- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

SEE SHEET 50 FOR -L3- PROFILE
SEE SHEET 2B-6 FOR BULB-OUT DETAILS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS



5/14/99

8/17/2021 4:25:57 PM
R-2233BB.RDY_PSH20.DGN
JSEB:GROU




2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 719.881.9939
NC CON No. F-2925

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		20
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

MATCH TO SHEET 19 - L3- STA. 965+00.00

MATCH TO SHEET 21 - L3- STA. 976+50.00



SEE SHEET 51 FOR -L3- PROFILE
SEE SHEET 28-7 FOR BULB-OUT DETAILS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99

8/17/2021 4:26:04 PM
JSEB: GDB

WADE D. KING
GISELA B. KING
DB 600 PG 460


WADE D. KING
GISELA B. KING
DB 600 PG 460

CURVE DATA FOR -L3TIE-
PI Sta 11+82.87 PI Sta 15+47.85
 $\Delta = 9^{\circ}07'27.8''$ (RT) $\Delta = 9^{\circ}07'27.8''$ (LT)
 $D = 2^{\circ}30'00.0''$ $D = 2^{\circ}30'00.0''$
 $L = 364.98'$ $L = 364.98'$
 $T = 182.87'$ $T = 182.87'$
 $R = 2,291.83'$ $R = 2,291.83'$
 $SE = .06$ $SE = .06$
 $RUNOFF = 162'$ $RUNOFF = 162'$




2010 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27602
PHONE: 919.881.9939
NC CON No. F-2925

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		22
RW SHEET NO.		HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER		SEAL 12786
NORTH CAROLINA PROFESSIONAL SEAL 020031		SEAL 12786
DENNIS J. MORRIS		STEVEN M. BORDO
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		



SEE SHEET 53 FOR -L3- PROFILE
SEE SHEET 84 FOR -L3TIE- PROFILE
SEE SHEET 2B-7 FOR BULB-OUT DETAILS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS




SEE SHEET 55 FOR -Y2- PROFILE
SEE SHEET 2B-2 FOR CONC. ISLAND DETAILS
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99
8/17/2021 4:26:05 PM
C:\PROJECTS\2021\3388.RD\PSH25.DGN
USER: GPOW



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9929
NC CON No. F-29257

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		25
RW SHEET NO.		HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER		SEAL 12786
		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		



MATCH TO SHEET 9 - -Y19- STA. 17+00.00

CURVE DATA FOR -Y19-		
PI Sta 6+40.01	PI Sta 11+43.16	PI Sta 13+70.68
$\Delta = 2^\circ 22' 07.7''$ (LT)	$\Delta = 2^\circ 20' 35.7''$ (LT)	$\Delta = 10^\circ 06' 04.4''$ (LT)
$D = 0^\circ 45' 50.2''$	$D = 0^\circ 49' 06.6''$	$D = 5^\circ 59' 58.4''$
$L = 310.08'$	$L = 286.28'$	$L = 168.37'$
$T = 155.06'$	$T = 143.16'$	$T = 84.40'$
$R = 7,500.00'$	$R = 7,000.00'$	$R = 955.00'$
SE = EX.	SE = EX.	SE = EX.


SEE SHEET 62 FOR -Y19- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS



CURVE DATA FOR -Y19-

PI Sta 31+55.16
 $\Delta = 1^{\circ}05'41.6''$ (LT)
 $D = 0^{\circ}28'38.9''$
 $L = 229.31'$
 $T = 114.66'$
 $R = 12,000.00'$
 $SE = NC$

SEE SHEET 63 FOR -Y19- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS



5/14/99

8/17/2021 4:26:38 PM
JSEB: G:\PROJECTS\2020\2020-03-30\2020-03-30.DGN



2010 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9929
NC CON No. F-2925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

29

R/W SHEET NO.

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

MATCH TO SHEET 12



CURVE DATA FOR -Y6-

PI Sta 10+55.56 Δ = 0° 45' 51.3" (RT) D = 0° 41' 16.2" L = 111.11' T = 55.56' R = 8,330.00' SE = EX. DS = 35 mph	PI Sta 15+90.64 Δ = 100° 20' 01.8" (LT) D = 14° 19' 26.2" L = 700.46' T = 479.53' R = 400.00' SE = .06 RUNOFF = 108.00' DS = 35 mph	PI Sta 23+39.06 Δ = 74° 45' 15.9" (RT) D = 14° 19' 26.2" L = 521.88' T = 305.57' R = 400.00' SE = .06 RUNOFF = 108.00' DS = 35 mph
---	---	--

CURVE DATA FOR -Y23-

PI Sta 32+45.69 Δ = 4° 29' 38.6" (RT) D = 1° 16' 23.7" L = 352.96' T = 176.57' R = 4,500.00' SE = EX. DS = 35 mph	PI Sta 35+18.06 Δ = 30° 01' 05.5" (RT) D = 16° 00' 15.9" L = 187.56' T = 95.99' R = 358.00' SE = EX. DS = 20 mph	PI Sta 38+60.88 Δ = 33° 58' 51.3" (LT) D = 57° 17' 44.8" L = 59.31' T = 30.55' R = 100.00' SE = .06 RUNOFF = 108.00' DS = 20 mph
--	---	--


CURVE DATA FOR -Y22A-

PI Sta 35+65.41 Δ = 4° 35' 36.2" (RT) D = 1° 40' 13.6" L = 274.98' T = 137.56' R = 3,430.00' SE = EX. DS = 35 mph	PI Sta 38+01.76 Δ = 6° 44' 25.9" (LT) D = 3° 24' 37.7" L = 197.64' T = 98.94' R = 1,680.00' SE = EX. DS = 35 mph	PI Sta 39+46.88 Δ = 49° 47' 48.1" (RT) D = 57° 17' 44.8" L = 86.91' T = 46.41' R = 100.00' SE = .04 RUNOFF = 72.00' DS = 15 mph
--	---	---

CURVE DATA FOR -Y23A-

PI Sta 44+55.25 Δ = 1° 32' 38.7" (RT) D = 1° 09' 35.4" L = 133.13' T = 66.57' R = 4,940.00' SE = EX.	PI Sta 45+75.10 Δ = 6° 33' 34.4" (RT) D = 6° 09' 39.0" L = 106.47' T = 53.29' R = 930.00' SE = EX.	PI Sta 46+84.50 Δ = 19° 55' 51.0" (RT) D = 17° 54' 17.8" L = 111.31' T = 56.23' R = 320.00' SE = EX.	PI Sta 48+15.42 Δ = 35° 04' 00.6" (RT) D = 23° 52' 23.7" L = 146.89' T = 75.83' R = 240.00' SE = EX.
--	--	--	--

SEE SHEETS 75 & 76 FOR -Y6- PROFILE
SEE SHEET 77 FOR -Y22A- PROFILE
SEE SHEET 77 FOR -Y23- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS



CURVE DATA FOR -Y6-

PI Sta 23+39.06
 $\Delta = 74^\circ 45' 15.9''$ (RT)
 $D = 14^\circ 19' 26.2''$
 $L = 521.88'$
 $T = 305.57'$
 $R = 400.00'$
 $SE = .06$
 $RUNOFF = 108.00'$
 $DS = 35$ mph


CURVE DATA FOR -Y3-		
PI Sta 45+64.98	PI Sta 47+53.28	PI Sta 52+83.59
$\Delta = 0^\circ 33' 33.7''$ (LT)	$\Delta = 0^\circ 40' 00.8''$ (RT)	$\Delta = 12^\circ 16' 55.8''$ (RT)
$D = 0^\circ 24' 28.1''$	$D = 0^\circ 16' 42.7''$	$D = 4^\circ 45' 17.4''$
$L = 137.16'$	$L = 239.42'$	$L = 258.31'$
$T = 68.58'$	$T = 119.71'$	$T = 129.65'$
$R = 14,050.00'$	$R = 20,570.00'$	$R = 1,205.00'$
$SE = EX.$	$SE = EX.$	$SE = EX.$

CURVE DATA FOR -Y23A-					
PI Sta 48+15.42	PI Sta 49+11.60	PI Sta 49+70.08	PI Sta 50+29.49	PI Sta 51+06.57	PI Sta 52+99.65
$\Delta = 35^\circ 04' 00.6''$ (RT)	$\Delta = 27^\circ 24' 47.6''$ (RT)	$\Delta = 42^\circ 36' 29.5''$ (RT)	$\Delta = 17^\circ 23' 07.3''$ (RT)	$\Delta = 8^\circ 34' 17.9''$ (RT)	$\Delta = 4^\circ 06' 49.5''$ (RT)
$D = 23^\circ 52' 23.7''$	$D = 55^\circ 37' 37.1''$	$D = 65^\circ 06' 31.8''$	$D = 30^\circ 58' 14.5''$	$D = 8^\circ 43' 14.9''$	$D = 1^\circ 25' 43.8''$
$L = 146.89'$	$L = 49.28'$	$L = 65.44'$	$L = 56.13'$	$L = 98.29'$	$L = 287.91'$
$T = 75.83'$	$T = 25.12'$	$T = 34.32'$	$T = 28.28'$	$T = 49.24'$	$T = 144.02'$
$R = 240.00'$	$R = 103.00'$	$R = 88.00'$	$R = 185.00'$	$R = 657.00'$	$R = 4,010.00'$
$SE = EX.$	$SE = EX.$	$SE = EX.$	$SE = EX.$	$SE = EX.$	$SE = EX.$

SEE SHEET 76 FOR -DR4- PROFILE
 SEE SHEETS 75 & 76 FOR -Y6- PROFILE
 SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS
 SEE SHEETS W-1 THRU W-11 FOR RETAINING WALL PLANS

5/14/99
8/17/2021 4:26:35 PM
USER: G:\BENTLEY\PROJECTS\2021\20210333\B.RDY_PSH31.DGN

CURVE DATA FOR -Y8-			
PI Sta 16+37.55 Δ = 5° 49' 31.0" (RT) D = 2° 17' 30.6" L = 254.18' T = 127.20' R = 2,500.00'	PI Sta 22+89.77 Δ = 18° 14' 44.9" (RT) D = 1° 27' 33.0" L = 159.22' T = 80.29' R = 500.00'	PI Sta 24+86.43 Δ = 0° 26' 26.8" (LT) D = 0° 11' 14.0" L = 235.44' T = 117.72' R = 30,605.00'	PI Sta 28+64.40 Δ = 3° 01' 15.1" (LT) D = 0° 34' 49.8" L = 520.39' T = 260.25' R = 9,870.00'



CURVE DATA FOR -Y10-		CURVE DATA FOR -RAB-	
PI Sta 18+75.18 Δ = 26° 55' 04.1" (LT) D = 1° 27' 32.9" L = 234.90' T = 119.66' R = 500.00'	PI Sta 1+63.96 Δ = 141° 39' 34.3" (RT) D = 100° 31' 08.1" L = 140.93' T = 163.96' R = 57.00'	PI Sta 3+04.88 Δ = 218° 20' 25.7" (RT) D = 100° 31' 08.1" L = 217.21' T = 163.96' R = 57.00'	



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9939
NC CON No. F-2925


PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		31
RW SHEET NO.		
ROADWAY DESIGN ENGINEER 	HYDRAULICS ENGINEER 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

MATCH TO SHEET 31A -Y8- STA. 25+00.00

MATCH TO SHEET 15 -Y10- STA. 22+00.00

SEE SHEET 78 & 79 FOR -Y8- PROFILE
SEE SHEET 79 FOR -Y10- PROFILE
SEE SHEET 79 FOR -RAB- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99
8/17/2021 4:26:39 PM
R-2233BB_R0Y_PSH31A.DGN
USER: chm



CURVE DATA FOR -Y8-

PI Sta 33+03.18	PI Sta 34+94.23	PI Sta 38+76.36
$\Delta = 1^{\circ}26'30.8" (LT)$	$\Delta = 0^{\circ}59'23.9" (LT)$	$\Delta = 0^{\circ}31'48.4" (LT)$
$D = 0^{\circ}49'53.7"$	$D = 0^{\circ}28'27.5"$	$D = 0^{\circ}05'43.5"$
$L = 173.39'$	$L = 208.72'$	$L = 555.54'$
$T = 86.70'$	$T = 104.36'$	$T = 277.77'$
$R = 6,890.00'$	$R = 12,080.00'$	$R = 60,045.00'$

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27603
PHONE: 919.881.9939
NC CON No. F-2925

PROJECT REFERENCE NO. R-2233BB		SHEET NO. 31A
RW SHEET NO.		
ROADWAY DESIGN ENGINEER DENNIS J. MORI	HYDRAULICS ENGINEER STEVEN M. BOUDOR	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

SEE SHEETS 78 & 79 FOR -Y8- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS


5/14/2021 4:26:41 PM
JSEB: SHOWN
8/17/2021 4:26:41 PM
JSEB: SHOWN
R-2233BB.RDY_PSH32.DGN



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9939
NC CON No. F-29259

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		32
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		


CURVE DATA FOR -YII-
PI Sta 18+63.57
 $\Delta = 39^\circ 47' 36.2''$ (RT)
 $D = 9^\circ 32' 57.5''$
 $L = 416.72'$
 $T = 217.16'$
 $R = 600.00'$
 $SE = .06$
 $RUNOFF = 126.00'$
 $DS = 40$ mph



SEE SHEETS 81 & 82 FOR -YII- PROFILE
SEE SHEETS 2D-1 THRU 2D-7 FOR DRAINAGE DETAILS

5/14/99

8/17/2001 4:28:10 PM
R2233BB.RDY_PFL33.DGN
USER: jmorris



Dewberry

2810 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 719.881.9239
NC CON No. F-2925

PROJECT REFERENCE NO.
R-2233BB

ROADWAY DESIGN ENGINEER

SEAL
020031
ENGINEER
JENNIS J. MORRIS

SHEET NO.
33

HYDRAULICS ENGINEER

SEAL
12786
ENGINEER
J. E. BOND

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

DITCH LEGEND

LEFT DITCH - - - - -

RIGHT DITCH - - - - -

5/14/99

8/17/2021 4:28:13 PM
R:\33333333\RDY_PFL34.DGN
USER: jmorris



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27605
PHONE: 919.881.9229
NC CON No. F-29259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

34

ROADWAY DESIGN
ENGINEER

HYDRAULICS
ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DITCH LEGEND

LEFT DITCH - - - - -

-L3-



SEE SHEET 5 FOR -L3-

-L3- STA. 744 + 00.00 TO STA. 756 + 00.00

5/14/99

8/17/2021 4:28:45 PM
R-2233BB.RDY PFL35.DGN
USER: jmoran



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-2925

PROJECT REFERENCE NO.
R-2233BB

SHEET NO.
35


DITCH LEGEND

LEFT DITCH - - - - -


RIGHT DITCH - - - - -

ROADWAY DESIGN
ENGINEER

HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED




SEE SHEET 6 FOR -L3-

PIPE HYDRAULIC DATA		
18" RCP-IV Sta. 767+18.00		
DRAINAGE AREA	= 1.7	AC
DESIGN FREQUENCY	= 50	YRS
DESIGN DISCHARGE	= 5.7	CFS
DESIGN HW ELEVATION	= 1,016.3	FT
100 YEAR DISCHARGE	= 6.1	CFS
100 YEAR HW ELEVATION	= 1,016.4	FT
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING DISCHARGE	= 28	CFS
OVERTOPPING ELEVATION	= 1,024.6	FT

-L3- STA. 756+00.00 TO STA. 769+00.00

5/14/99

8/17/2021 4:28:17 PM
R:\3338B\RDY_PFL36.DGN
USER: jmorris



5/14/99

8/17/2021 4:28:20 PM
R-2233BB.RDY_PFL37.DGN
USER: jmoran



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-29229

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

37

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED


-L3-




SEE SHEET 7 FOR -L3-

-L3- STA. 782 +00.00 TO STA. 794 +50.00







5/14/99

8/17/2021 4:28:30 PM
R:\333883\333883_P01_P01.dgn
USER: jmoran



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9339
NC CON No. F-2925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

41

ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DITCH LEGEND

RIGHT DITCH - - - - -

-L3-

-Y3-

-L3- Sta. 846+53.34=


-LPD- Sta. 10+00.00 - 47.00' RT

-L3- Sta. 845+53.34=

-LPA- Sta. 10+00.00 - 47.00' LT

-L3- Sta. 843+44.48=

-Y3- Sta. 26+65.52



5/14/99

8/17/2021 4:28:32 PM
R-2233BB.RDY_PFL42.DGN
USER: jmoran



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9239
NC CON No. F-29259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

42

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

-L3-



5/14/99
8/17/2021 4:28:35 PM
R:\2233BB_R0Y_PFL43.DGN
USER: jmorris



-L3-

1,005.80'

1,055.36'

-L3- Sta. 861+15.54=
-RPA- Sta. 10+00.00 - 47.00' LT

-L3- Sta. 863+75.00=
-RPD- Sta. 10+00.00 - 47.00' RT

(-14.6400%)

(-14.6400%)

EXIST.
30' CMP

54" RCP-V

EXISTING
GROUND

PIPE HYDRAULIC DATA		
54" RCP-V Sta. 866+00		
DRAINAGE AREA	= 53.0	AC
DESIGN FREQUENCY	= 50	YRS
DESIGN DISCHARGE	= 80.0	CFS
DESIGN HW ELEVATION	= 950.0	FT
100 YEAR DISCHARGE	= 97.0	CFS
100 YEAR HW ELEVATION	= 950.6	FT
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING DISCHARGE	= 286.0	CFS
OVERTOPPING ELEVATION	= 964.0	FT

SEE SHEET 12 FOR -L3-

-L3- STA. 860+50.00 TO STA. 872+50.00



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9239
NC CCA No. F-29259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

43


ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED




Dewberry

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.993
NC COA No. F-0929

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

45


DITCH LEGEND

LEFT DITCH - - - - -

RIGHT DITCH -----



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



5/14/99

8/17/2021 4:28:45 PM
R2233BB.RDY_PFL47.DGN
USER: jmoran



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-29229

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

47

ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

-L3-

BM #18
-L3- STA 916+49.08
685.23' LEFT
ELEV. 1030.87'

PI = 916+00.00
EL = 1,075.52'
VC = 1,100'
K = 255

(+)3.4400% (-)0.8673%

PROPOSED
GRADE


EXISTING
GROUND

SEE SHEET 16 FOR -L3-

-L3- STA. 912+00.00 TO STA. 925+00.00

5/14/99

8/17/2021 4:28:47 PM
R:\3338B.RDY_PFL48.DGN
USER: jmoran



Dewberry

2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-2925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

48

ROADWAY DESIGN
ENGINEER

HYDRAULICS
ENGINEER



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

5/14/99

8/17/2021 4:28:48 PM
R:\333333\333333\RDY_PFL49.DGN
USER: jmoran

**Dewberry**


2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 719.881.9239
NC CON No. F-29259

PROJECT REFERENCE NO.
R-2233BB

ROADWAY DESIGN ENGINEER

SHEET NO.
49

HYDRAULICS ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DITCH LEGEND
LEFT DITCH - - - - -

-L3-

PI = 944+50.00
EL = 1,078.23'
VC = 200'
K = 286

-L3- Sta. 950+76.55=
-Y9- Sta. 17+01.02
-Y11- Sta. 10+00.00





2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9939
NC COA No. F-0929

PROJECT REFERENCE NO.

R-2233BB

ROADWAY DESIGN
ENGINEER

SHEET NO.

50

HYDRAULICS
ENGINEER



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

—L3—

1,088.38'

$$\begin{aligned} PI &= 954+00.00 \\ EL &= 1,091.52' \\ VC &= 650' \\ K &= 229 \end{aligned}$$

PROPOSED
GRADE

EXISTING
GROUND

BEGIN LAT. V DITCH LT.
STA. 961+50
EI = 1,069.4

$$\begin{aligned} P_I &= 962,00 \\ E_I &= 1.058,20 \end{aligned}$$
$$\begin{array}{l} P1 = 962 + 50 \\ E1 = 1052.20 \end{array}$$
$$\frac{P}{E} = \frac{963 + 0}{1,047.70}$$
$$P1 = 963 + 50$$

$$E1 = 1.041,50$$
$$\begin{array}{r} P1 = 964,00 \\ E1 = 1.035,30 \end{array}$$
$$\frac{PI = 964 + 50}{EI = 1.042.30}$$
$$EI = 1.048.40$$

42" WELDED STEEL

$$\frac{P1}{E1} = \frac{1}{17}$$
$$\begin{aligned} P_1 &= 964 + 50 \\ E_1 &= 1,020.30 \end{aligned}$$
$$P1 = 965 + 00$$

PIPE HYDRAULIC DATA

42" WELDED STEEL Sta. 964+30

DRAINAGE AREA	= 16.0	AC
DESIGN FREQUENCY	= 50	YRS
DESIGN DISCHARGE	= 40.0	CFS
DESIGN HW ELEVATION	= 1,034.4	FT
100 YEAR DISCHARGE	= 46.0	CFS
100 YEAR HW ELEVATION	= 1,034.7	FT
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING DISCHARGE	= 180.0	CFS
OVERTOPPING ELEVATION	= 1,057.8	FT

SEE SHEET 19 FOR -L3-

-L3- STA. 952+00.00 TO STA. 965+00.00

.../Proj/R2233BB_RDY_PFL51.DGN
USER: dmoell


Dewberry

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9939
NC COA No. F-0929

PROJECT REFERENCE NO.

SHEET NO.

DITCH LEGEND

RIGHT DITCH - - - - -

BM #21
-L3- STA 971+03.46
501.07' LEFT
ELEV. 1083.30'

$$\begin{aligned} PI &= 966+00.00 \\ EL &= 1,074.26' \\ VC &= 200' \\ K &= 710 \end{aligned}$$
$$\begin{aligned} PI &= 969+00.00 \\ EL &= 1,069.10' \\ VC &= 200' \\ K &= 256 \end{aligned}$$
$$\begin{aligned}PI &= 972+00.00 \\EL &= 1,066.28' \\VC &= 250' \\K &= 543\end{aligned}$$

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

PIPE HYDRAULIC DATA

36" WELDED STEEL Sta. 968+64

DRAINAGE AREA = 14.0

DESIGN FREQUENCY = 50

DESIGN DISCHARGE = 29.0

DESIGN HW ELEVATION = 1031.75

100 YEAR DISCHARGE = 35.0
100 YEAR LWM ELEVATION = 103.9

100 YEAR HW ELEVATION = 1.032
OVERTOPPING FREQUENCY = 500

OVERTOPPING DISCHARGE = 1220

OVERTOPPING ELEVATION = 1.057

OVERTIGHTING ELEVATION		NOSE

SEE SHEET 20 FOR -L3-

-L3- STA. 965+00.00 TO STA. 976+50.00

5/14/99

8/17/2021 4:28:57 PM
R:\3338B.RDY_PFL52.DGN
USER:cmo




2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9339
NC CON No. F-59259


PROJECT REFERENCE NO.
R-2233BB

SHEET NO.
52

ROADWAY DESIGN
ENGINEER


HYDRAULICS
ENGINEER


DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



-L3-

BM #22
-L3- STA 983+16.40
621.23' LEFT
ELEV. 990.41'

PI = 989+00.00
EL = 1,042.48'
VC = 200'
K = 1429

-L3- Sta. 977+95.26=
-Y7A- Sta. 18+45.84

-L3- Sta. 982+79.74=
-Y7- Sta. 18+64.30

PROPOSED
GRADE

EXISTING
GROUND

36" WELDED STEEL

BEGIN LAT.V DITCH RT.
STA. 989+50
EI = 1028.1

END LAT.V DITCH RT.
STA. 989+89
EI = 1023.0


36" WELDED STEEL

PIPE HYDRAULIC DATA		
36" WELDED STEEL Sta. 981+00		
DRAINAGE AREA	= 9.0	AC
DESIGN FREQUENCY	= 50	YRS
DESIGN DISCHARGE	= 26	CFS
DESIGN HW ELEVATION	= 1,037.6	FT
100 YEAR DISCHARGE	= 28.0	CFS
100 YEAR HW ELEVATION	= 1,037.7	FT
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING DISCHARGE	= 102.0	CFS
OVERTOPPING ELEVATION	= 1,050.5	FT


PIPE HYDRAULIC DATA		
36" WELDED STEEL Sta. 990+18		
DRAINAGE AREA	= 10.3	AC
DESIGN FREQUENCY	= 50	YRS
DESIGN DISCHARGE	= 34.0	CFS
DESIGN HW ELEVATION	= 1,026.2	FT
100 YEAR DISCHARGE	= 37.0	CFS
100 YEAR HW ELEVATION	= 1,026.5	FT
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING DISCHARGE	= 100.0	CFS
OVERTOPPING ELEVATION	= 1,037.7	FT

SEE SHEET 21 FOR -L3-

-L3- STA. 976 + 50.00 TO STA. 990 + 50.00



BM #10
-Y2- STA 39+84.95
67.45 LEFT
ELEV. 1067.01'

$$\begin{aligned} PI &= 40 + 25.00 \\ EL &= 1,057.88' \\ VC &= 320' \\ K &= III \end{aligned}$$


5/14/99

8/17/2021 4:29:07 PM
R2233BB.RDY_PFL56.DGN
USER: jmorris



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9239
NC CON No. F-59259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

56

ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

-RPB-


-L3- POT Sta. 755+52.50=
-RPB- TS Sta. 10+00.00 47.00' LT.
BEG. GRADE
EL. 1,050.04'

PI = 11+00.00
EL = 1,049.72'
VC = 170'
K = 206

PI = 14+25.00
EL = 1,046.00'
VC = 480'
K = 99


SEE SHEETS 5 & 6 FOR -RPB-

-RPB- STA. 10+00.00 TO STA. 23+00.00



5/14/99

8/17/2021 4:29:09 PM
R-2233BB.DGN
R-2233BB.DGN



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-29229

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

57


ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

-L3- POC Sta. 772+25.00=
-LPB- CS Sta. 10+00.00 47.00' LT.
BEGIN GRADE
EL. 1,016.71'

$$\begin{aligned} PI &= 12+30.00 \\ EL &= 1,022.00' \\ VC &= 290' \\ K &= 27 \end{aligned}$$

EXISTING
GROUND

PROPOSED
GRADE
$$\begin{aligned} PI &= 20+00.00 \\ EL &= 955.93' \\ VC &= 345' \\ K &= 39 \end{aligned}$$

-Y2- POT Sta. 25+37.01=


END GRADE
-LPB- POT Sta. 21+72.55
EL. 956.50'

SEE SHEET 6 FOR -LPB-

-LPB- STA. 10+00.00 TO STA. 21+72.55



–LPC–



...\\Proj\R2233BB_RDY_PFL60.DGN
USER: dmaru

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.993
NC COA No. E-0030

SHEET NO.

60

HYDRAULICS
ENGINEER



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

-L3- POT Sta.756+50.00=
-RPC- POT Sta.10+00.00 47.00' RT.
BEGIN GRADE
EL.1,049.58'

$PI = 11+50.00$
 $EL = 1,048.40'$
 $VC = 280'$
 $K = 192$


$$\begin{aligned} PI &= 15+50.00 \\ EL &= 1,039.40' \\ VC &= 200' \\ K &= 227 \end{aligned}$$

— EXISTING
GROUND

PROPOSED
GRADE

SEE SHEET 6 FOR -RPC-

-RPC- STA. 10+00.00 TO STA. 23+00.00



5/14/99

8/17/2021 4:29:49 PM
R2233BB.RDY_PFL61.DGN
USER: jmoran



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9339
NC CON No. F-59259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

61

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED


-RPC-




5/14/99

8/17/2021 4:29:21 PM
R2233BB.DWG
USER: jmoran










**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



...\\Proj\R2233BB_RDY_PFL66.DGN
USER: dmaru

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27607
PHONE: 919.881.9999
NC COA No. E-0023


SHEET NO.

66

HYDRAULICS
ENGINEER




**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



5/14/99

8/17/2021 4:29:36 PM
R-2233BB.DGN
R-2233BB.DGN
R-2233BB.DGN



Dewberry

2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-29229

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

67

ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

5/14/99

8/17/2021 4:29:39 PM
R2233BB.RDY_PFL68.DGN
USER: jmoran



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CDR No. F-59259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

68

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

-RPA-





—LPA—



5/14/99

8/17/2021 4:29:44 PM
R:\333333\333333\RDY_PEL_70.DGN
USER: daniel

-LPD-

Dewberry

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-2925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

70


ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED





—LPD—



5/14/99
8/17/2021 4:29:50 PM
R2233BB.RDY_PEL72.DGN
USER: jmorris

-RPD-



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-2925

PROJECT REFERENCE NO.
R-2233BB

ROADWAY DESIGN ENGINEER


SHEET NO.
72

HYDRAULICS ENGINEER

SEAL
020031
ENGINEER
JENNIS J. MORRIS


SEAL
12786
ENGINEER
J. EMMETT BOND

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



5/14/99

8/17/2021 4:29:52 PM
R-2233BB.RDY_PEL73.DGN
USER: jmoran



5/28/99

8/17/2021 4:29:55 PM
R:\333333\333333\RDY_PEL_74.DGN
USER: daniel



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9239
NC CON No. F-59259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

74



ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



5/14/99

8/17/2021 4:29:58 PM
R:\33388_R0Y_PEL_75.DGN
USER: dmoh



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 719.881.9239
NC CON No. F-2925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

75

ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DITCH LEGEND

LEFT DITCH - - - - -

RIGHT DITCH - - - - -

-Y6-

1,060

1,050

1,040

1,030

1,020

1,010

1,000

990

980

970

960

950

940

930

920

910

900

1,060

1,050

1,040

1,030

1,020

1,010

1,000

990

980

970

960

950

940

930

920

910

900

SEE SHEETS 29 & 30 FOR -Y6-

-Y6- STA. 10+00.00 TO STA. 23+00.00

PI = 11+00.00
EL = 972.34'
VC = 200'
K = 24
DS = 20 MPH

BEGIN GRADE
-Y6- POT Sta. 10+00.00
EL. 969.55'

BEG. SPEC. CUT
DITCH LT
STA. 11+39
EL = 975.00

BEG. SPEC. CUT
DITCH LT
STA. 10+00
EL = 966.77

END SPEC. CUT
DITCH LT
STA. 10+90
EL = 966.50

PI = 11+50.00
EL = 975.51

PI = 12+00
EL = 976.01

PI = 13+00.00
EL = 994.69'
VC = 200'
K = 32
DS = 35 MPH

-Y6- POC Sta. 13+55.00 =
-Y22A- POT Sta. 40+35.15

END SPEC. CUT
DITCH LT
STA. 15+55
EL = 985.93

EXISTING
GROUND

PI = 15+00.00
EL = 1,004.69'
VC = 100'
K = 77

-Y6- POC Sta. 16+54.00 =
-Y23- POT Sta. 39+44.33

PI = 17+50.00
EL = 1,020.44'
VC = 200'
K = 33
DS = 35 MPH

PROPOSED
GRADE

BEG. SPEC. GRADE DITCH RT.
STA. 19+50
EL. 1018.39

END SPEC. GRADE DITCH RT.
BEG. SPEC. LAT V DITCH RT.
STA. 20+68
EL. 1016.00


END SPEC. LAT V DITCH RT.
STA. 21+32
EL. 1021.5


PI = 21+25.00
EL = 1,021.64'
VC = 375'
K = 53
DS = 35 MPH


PIPE HYDRAULIC DATA			
18" RCP-IV Sta. 16+90.00			
DRAINAGE AREA	= 2.3	AC	
DESIGN FREQUENCY	= 25	YRS	
DESIGN DISCHARGE	= 8.0	CFS	
DESIGN HW ELEVATION	= 1,016.1	FT	
100 YEAR DISCHARGE	= 9.0	CFS	
100 YEAR HW ELEVATION	= 1016.4	FT	
OVERTOPPING FREQUENCY	= 500+	YRS	
OVERTOPPING DISCHARGE	= 13.0	CFS	
OVERTOPPING ELEVATION	= 1,017.0	FT	

PIPE HYDRAULIC DATA			
24" RCP-III Sta. 20+69			
DRAINAGE AREA	= 5.1	AC	
DESIGN FREQUENCY	= 25	YRS	
DESIGN DISCHARGE	= 17.0	CFS	
DESIGN HW ELEVATION	= 1,020.3	FT	
100 YEAR DISCHARGE	= 21.0	CFS	
100 YEAR HW ELEVATION	= 1,020.7	FT	
OVERTOPPING FREQUENCY	= 50	YRS	
OVERTOPPING DISCHARGE	= 18	CFS	
OVERTOPPING ELEVATION	= 1,020.4	FT	

LEFT DITCH — — — — —








5/28/99

8/17/2023 4:30:10 PM
R2233BB.RDY_PEL 79.DGN
USER: dmo





**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

RIGHT DITCH - - - - -

$$\begin{aligned}PI &= 18+75.00 \\EL &= 1,055.24' \\VC &= 150' \\K &= 87\end{aligned}$$

BEGIN GRADE
-Y12- POT Sta. 11+25.00
EL. 1,027.63'

$$\begin{aligned} PI &= 12+00.00 \\ EL &= 1,030.13' \\ VC &= 150' \\ K &= 388 \end{aligned}$$

-Y12-

PIPF HYDRAULIC DATA

18" RCP-N Sta. 16+85

DRAINAGE AREA	= 2.4	AC
DESIGN FREQUENCY	= 25	YRS
DESIGN DISCHARGE	= 7.0	CFS
DESIGN HW ELEVATION	= 1,035.1	FT
100 YEAR HW DISCHARGE	= 9.0	CFS
100 YEAR HW ELEVATION	= 1,035.3	FT
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING DISCHARGE	= 19.0	CFS
OVERTOPPING ELEVATION	= 1,037.9	FT

SEE SHEET 15 FOR -Y12-

- Y12- STA. 11+25.00 TO STA. 23+00.00

DITCH LEGEND

RIGHT DITCH -----

-Y12-

$$\begin{aligned} PI &= 23+50.00 \\ EL &= 1,064.74' \\ VC &= 125' \\ K &= 89 \end{aligned}$$
$$\begin{aligned} PI &= 32+50.00 \\ EL &= 1,070.14' \\ VC &= 100' \\ K &= 102 \end{aligned}$$

END GRADE
-Y12- POT Sta. 33+00.00
EL. 1,069.95'


PIPE HYDRAULIC DATA

18" RCP-III Sta. 29+20

DRAINAGE AREA	= 2.1	AC
DESIGN FREQUENCY	= 25	YRS
DESIGN DISCHARGE	= 6.0	CFS
DESIGN HW ELEVATION	= 1,064.8	FT
100 YEAR DISCHARGE	= 8.0	CFS
100 YEAR HW ELEVATION	= 1,065.0	FT
OVERTOPPING FREQUENCY	= 100	YRS
OVERTOPPING DISCHARGE	= 7.6	CFS
OVERTOPPING ELEVATION	= 1,065.0	FT

SEE SHEETS 15 & 16 FOR -Y12-

- Y12- STA. 23+00.00 TO STA. 33+00.00



5/14/99

8/17/2021 4:30:48 PM
R2233BB.RDY_PFL82.DGN
USER: jmorris



2610 WYCLIFF ROAD
SUITE 400
RALEIGH, NC 27601
PHONE: 919.881.9229
NC CON No. F-59259

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

82

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

-Y11-



5/28/99

8/17/2001 4:30:21 PM
R2233BB.DWG_PFL83.DGN
USER: dmo



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9939
NC CON No. F-2925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

83

ROADWAY DESIGN
ENGINEER




HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DITCH LEGEND


RIGHT DITCH - - - - -



DITCH LEGEND


LEFT DITCH - - - - -

RIGHT DITCH - - - - -



5/28/99

8/17/2001 4:30:23 PM
R2233BB.DWG
PFL84.DGN
USER: dmo



Dewberry

2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9239
NC CON No. F-5925

PROJECT REFERENCE NO.		SHEET NO.
R-2233BB		84
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

DITCH LEGEND	
LEFT DITCH	- - - - -

5/28/99



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919.881.9939
NC CON No. F-5925

PROJECT REFERENCE NO.
R-2233BB

ROADWAY DESIGN
ENGINEER

HYDRAULICS
ENGINEER



SEAL
020031
DENNIS J. MORI



SEAL
12786
STEPHEN M. BOND

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DITCH LEGEND

LEFT DITCH

-Y25REV-

PI = 20+75.00
EL = 1,073.13'
VC = 460'
K = 29
DS = 35 MPH

BEGIN GRADE
-Y25REV- Sta.17+50.00
EL.1,052.56'

PROPOSED GRADE

EXISTING GROUND

SEE SHEET 4A FOR -Y25REV-

-Y25REV- STA. 14+00.00 TO STA. 25+00.00

Station	Proposed Grade (ft)	Existing Ground (ft)
14	1032	1032
15	1040	1040
16	1048	1048
17	1055	1055
18	1062	1062
19	1068	1068
20	1072	1072
21	1073.13	1073.13
22	1068	1068
23	1055	1055
24	1040	1040
25	1032	1032

8/17/2021 4:30:36 PM
R2233BB.DWG
PFL85.DGN

-Y25REV-

PI = 28+25.00
EL = 1,001.88'
VC = 330'
K = 38
DS = 30 MPH

END GRADE
-Y25REV- Sta.33+28.28
EL.997.50'

FUTURE BRIDGE

EXISTING GROUND

SEE SHEETS 4&4A FOR -Y25REV-

-Y25REV- STA. 25+00.00 TO STA. 33+67.91

Station	Proposed Grade (ft)	Existing Ground (ft)
25	1032	1032
26	1020	1020
27	1010	1010
28	1001.88	1001.88
29	998	998
30	995	995
31	993	993
32	992	992
33	997.50	997.50

5/28/99



2610 WYCLIFF ROAD
SUITE 410
RALEIGH, NC 27601
PHONE: 919-881-9239
NC CON No. F-5925

PROJECT REFERENCE NO.

R-2233BB

SHEET NO.

86



ROADWAY DESIGN
ENGINEER



HYDRAULICS
ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



8/17/2019 4:30:30 PM
R-2233BB_P01_PFL86.DGN
USER: dmor