



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

ROY COOPER
GOVERNOR

JAMES H. TROGDON, III
SECRETARY

November 13, 2019

MEMORANDUM TO: Mr. Michael Pettyjohn, P.E.
Division 11 Engineer

FROM: *MR for* Philip S. Harris, III, P.E., Manager
Environmental Analysis Unit

SUBJECT: 404 Individual Permit and 401 Water Quality Certification for the
improvements to NC 107 from SR 1136 to NC 105 Bypass in Boone,
Watauga County, Division 11; WBS No 37512.1.5, **TIP: R-2566 B/BA**

Enclosed is the US Army Corps of Engineers Permit, NC Division of Water Resources Water Quality Certification, and Project Commitments ("greensheet") for the above-referenced project. All environmental permits have been received for the construction of this project.

The permit package has been posted on the NCDOT website at:
<https://xfer.services.ncdot.gov/pdea/PermIssued/>

cc:

Mr. Ron Davenport, P.E. Contracts Management
Mr. Kevin Hining, Division Environmental Officer
Dr. Majed Al-Ghandour, P.E., Programming and TIP
Mr. Stephen Morgan, P.E., Hydraulics
Mr. Brian Hanks, P.E., Structure Design
Mr. Mark Staley, Roadside Environmental
Mr. Lamar Sylvester, P.E., State Roadway Construction Engineer

PROJECT COMMITMENTS

T.I.P. Project No R-2566B
NC 105 Improvements from Clark's Creek Road (SR 1136) to
NC 105 Bypass (SR 1107) in Boone
Watauga County
Federal Aid Project NHPP-0150(004)
W.B.S. No. 37512.1.5

COMMITMENTS FROM PROJECT DEVELOPMENT AND DESIGN

Due to the high quality waters and trout waters throughout the project corridor, Design Standards in Sensitive Watersheds will be implemented.

Based on a recommendation from the North Carolina Wildlife Resources Commission (NCWRC), a moratorium will be placed on in-stream work and land disturbance to the 25-foot trout buffer from October 15th to April 15th for the entire corridor, to protect reproducing trout.

Coordination between NCDOT and NCWRC established a moratorium from April 1 to November 1 for the Watauga River and Laurel Fork. A trout moratorium from October 15 to April 15 will be in effect for all other streams on the project. See Commitments From Permitting.

The NCDOT Biological Surveys Group will be notified thirty days prior to demolition in order to perform a pre-demolition bridge check for listed bat species.

COMMITMENTS FROM PERMITTING

Division 11 Construction, Roadside Environmental Unit

404 Special Condition #16: In-Water Work Moratoria: To avoid adverse impacts to the Eastern Hellbender in the project area, no in-water work shall be conducted from April 1 to November 1, within the Watauga River and Laurel Fork, and adjacent wetlands that have an active connection to these tributaries during periods of inundation. To avoid adverse impacts to reproducing trout in the project area, no in-water work shall be conducted from October 15 to April 15, within perennial tributaries, other than the Watauga River and Laurel Fork, and their adjacent wetlands that have an active connection to these tributaries during periods of inundation.

DEPARTMENT OF THE ARMY PERMIT

Permittee **North Carolina Department of Transportation**

Permit No. **SAW-2010-00653**

Issuing Office **CESAW-RG**

NOTE: The term "you" and its derivatives, as used in this permit, means the permittee or any future transferee. The term "this office" refers to the appropriate district or division office of the Corps of Engineers having jurisdiction over the permitted activity or the appropriate official of that office acting under the authority of the commanding officer.

You are authorized to perform work in accordance with the terms and conditions specified below.

Project Description: **TIP R-2566 B and BA; NC 105 improvements, impacting 0.47 acre of wetlands, 4,499 linear feet of tributaries, and 0.01 acre of open water pond.**

Project Location: **Existing NC 105 from Clark's Creek Road (SR 1136) to NC 105 Bypass (SR 1107), near Boone, Watauga County, NC, in the Watauga watershed (HUC 06010103); Latitude and Longitude (at Watauga River bridge): 36.194 N, -81.745 W.**

Permit Conditions:

General Conditions:

1. The time limit for completing the work authorized ends on **December 31, 2024**. If you find that you need more time to complete the authorized activity, submit your request for a time extension to this office for consideration at least one month before the above date is reached.
2. You must maintain the activity authorized by this permit in good condition and in conformance with the terms and conditions of this permit. You are not relieved of this requirement if you abandon the permitted activity, although you may make a good faith transfer to a third party in compliance with General Condition 4 below. Should you wish to cease to maintain the authorized activity or should you desire to abandon it without a good faith transfer, you must obtain a modification of this permit from this office, which may require restoration of the area.
3. If you discover any previously unknown historic or archeological remains while accomplishing the activity authorized by this permit, you must immediately notify this office of what you have found. We will initiate the Federal and state coordination required to determine if the remains warrant a recovery effort or if the site is eligible for listing in the National Register of Historic Places.
4. If you sell the property associated with this permit, you must obtain the signature of the new owner in the space provided and forward a copy of the permit to this office to validate the transfer of this authorization.
5. If a conditioned water quality certification has been issued for your project, you must comply with the conditions specified in the certification as special conditions to this permit. For your convenience, a copy of the certification is attached if it contains such conditions.
6. You must allow representatives from this office to inspect the authorized activity at any time deemed necessary to ensure that it is being or has been accomplished in accordance with the terms and conditions of your permit.

Special Conditions:

SEE ATTACHED SPECIAL CONDITIONS

Further Information:

1. Congressional Authorities: You have been authorized to undertake the activity described above pursuant to:
 - Section 10 of the Rivers and Harbors Act of 1899 (33 U.S.C. 403).
 - Section 404 of the Clean Water Act (33 U.S.C. 1344).
 - Section 103 of the Marine Protection, Research and Sanctuaries Act of 1972 (33 U.S.C. 1413).
2. Limits of this authorization.
 - a. This permit does not obviate the need to obtain other Federal, state, or local authorizations required by law.
 - b. This permit does not grant any property rights or exclusive privileges.
 - c. This permit does not authorize any injury to the property or rights of others.
 - d. This permit does not authorize interference with any existing or proposed Federal project.
3. Limits of Federal Liability. In issuing this permit, the Federal Government does not assume any liability for the following:
 - a. Damages to the permitted project or uses thereof as a result of other permitted or unpermitted activities or from natural causes.
 - b. Damages to the permitted project or uses thereof as a result of current or future activities undertaken by or on behalf of the United States in the public interest.
 - c. Damages to persons, property, or to other permitted or unpermitted activities or structures caused by the activity authorized by this permit.
 - d. Design or construction deficiencies associated with the permitted work.
 - e. Damage claims associated with any future modification, suspension, or revocation of this permit.
4. Reliance on Applicant's Data: The determination of this office that issuance of this permit is not contrary to the public interest was made in reliance on the information you provided.

5. Reevaluation of Permit Decision. This office may reevaluate its decision on this permit at any time the circumstances warrant. Circumstances that could require a reevaluation include, but are not limited to, the following:

- a. You fail to comply with the terms and conditions of this permit.
- b. The information provided by you in support of your permit application proves to have been false, incomplete, or inaccurate (See 4 above).
- c. Significant new information surfaces which this office did not consider in reaching the original public interest decision.

Such a reevaluation may result in a determination that it is appropriate to use the suspension, modification, and revocation procedures contained in 33 CFR 325.7 or enforcement procedures such as those contained in 33 CFR 326.4 and 326.5. The referenced enforcement procedures provide for the issuance of an administrative order requiring you to comply with the terms and conditions of your permit and for the initiation of legal action where appropriate. You will be required to pay for any corrective measures ordered by this office, and if you fail to comply with such directive, this office may in certain situations (such as those specified in 33 CFR 209.170) accomplish the corrective measures by contract or otherwise and bill you for the cost.

6. Extensions. General condition 1 establishes a time limit for the completion of the activity authorized by this permit. Unless there are circumstances requiring either a prompt completion of the authorized activity or a reevaluation of the public interest decision, the Corps will normally give favorable consideration to a request for an extension of this time limit.

Your signature below, as permittee, indicates that you accept and agree to comply with the terms and conditions of this permit.

for Carla Drew
(PERMITTEE) PHILLIP S. HARRIS, (NCDOT) November 6, 2019
(DATE)

This permit becomes effective when the Federal official, designated to act for the Secretary of the Army, has signed below.

Mark Matthews for
(DISTRICT COMMANDER) ROBERT J. CLARK, COLONEL 06 Nov 2019
(DATE)

When the structures or work authorized by this permit are still in existence at the time the property is transferred, the terms and conditions of this permit will continue to be binding on the new owner(s) of the property. To validate the transfer of this permit and the associated liabilities associated with compliance with its terms and conditions, have the transferee sign and date below.

 (TRANSFeree) (DATE)

SPECIAL CONDITIONS
Action ID SAW-2010-00653
NCDOT TIPs R-2566B and R-2566BA; NC 105

1. CONSTRUCTION PLANS: All work authorized by this permit shall be performed in strict compliance with the attached permit plans, which were submitted on March 29, 2019 (Section BA), and July 2, 2019 (Section B), which are a part of this permit. The Permittee shall ensure that the construction design plans for this project do not deviate from the permit plans attached to this authorization. Any modification to the attached permit plans must be approved by the U.S. Army Corps of Engineers (Corps) prior to any active construction in waters or wetlands.

2. PHASED PERMIT: This permit only authorizes work on Section BA of TIP R-2566. Construction on Section B of TIP R-2566 shall not commence until: (a) final design has been completed for those sections and submitted to the U.S. Army Corps of Engineers (Corps); (b) the Permittee has minimized impacts to waters and wetlands to the maximum extent practicable and the Corps concurs with this assessment through standard Merger 4B and 4C meetings; (c) any modification to the plans have been approved by the Corps in writing; and (d) a final compensatory mitigation plan has been submitted by the Permittee and approved by the Corps.

3. BORROW AND WASTE: To ensure that all borrow and waste activities occur on high ground and do not result in the degradation of adjacent waters and wetlands, except as authorized by this permit, the Permittee shall require its contractors and/or agents to identify all areas to be used as borrow and/or waste sites associated with this project. The Permittee shall provide the U.S. Army Corps of Engineers with appropriate maps indicating the locations of proposed borrow and/or waste sites as soon as such information is available. The Permittee shall submit to the Corps site-specific information needed to ensure that borrow and/or waste sites comply with all applicable Federal requirements, to include compliance with the Endangered Species Act and the National Historic Preservation Act, such as surveys or correspondence with agencies (e.g., the USFWS, the NC-HPO, etc.). The required information shall also include the location of all aquatic features, if any, out to a distance of 400 feet beyond the nearest boundary of the site. The Permittee shall not approve any borrow and/or waste sites before receiving written confirmation from the Corps that the proposed site meets all Federal requirements, whether or not waters of the U.S., including wetlands, are located in the proposed borrow and/or waste site. All delineations of aquatic sites on borrow and/or waste sites shall be verified by the U.S. Army Corps of Engineers and shown on the approved reclamation plans. The Permittee shall ensure that all borrow and/or waste sites comply with Special Condition 4 of this permit.

Additionally, the Permittee shall produce and maintain documentation of all borrow and waste sites associated with this project. This documentation will include data regarding soils, vegetation, hydrology, any delineation(s) of aquatic sites, and any jurisdictional determinations made by the Corps to clearly demonstrate compliance with Special Condition 4. All information will be available to the U.S. Army Corps of Engineers upon request. The Permittee shall require its contractors to complete and execute reclamation plans for each borrow and/or waste site and provide written documentation that the reclamation plans have been implemented and all work is completed. This documentation will be provided to the U.S. Army Corps of Engineers within 30 days of the completion of the reclamation work.

SPECIAL CONDITIONS
Action ID SAW-2010-00653
NCDOT; TIPs R-2566B and R-2566BA; NC 105

4. UNAUTHORIZED DREDGE OR FILL: Except as authorized by this permit or any U.S. Army Corps of Engineers approved modification to this permit, no excavation, fill, or mechanized land-clearing activities shall take place at any time in the construction or maintenance of this project, within waters or wetlands, or shall any activities take place that cause the degradation of waters or wetlands. There shall be no excavation from, waste disposal into, or degradation of, jurisdictional wetlands or waters associated with this permit without appropriate modification of this permit, including appropriate compensatory mitigation. This prohibition applies to all borrow and waste activities connected with this project. In addition, except as specified in the plans attached to this permit, no excavation, fill or mechanized land-clearing activities shall take place at any time in the construction or maintenance of this project, in such a manner as to impair normal flows and circulation patterns within, into, or out of waters or wetlands or to reduce the reach of waters or wetlands.

5. PERMIT DISTRIBUTION: The Permittee shall require its contractors and/or agents to comply with the terms and conditions of this permit in the construction and maintenance of this project, and shall provide each of its contractors and/or agents associated with the construction or maintenance of this project with a copy of this permit. A copy of this permit, including all conditions and drawings shall be available at the project site during construction and maintenance of this project.

6. PRECONSTRUCTION MEETING: The Permittee shall conduct an onsite preconstruction meeting between its representatives, the contractor's representatives and the appropriate U.S. Army Corps of Engineers Project Manager prior to undertaking any work within jurisdictional waters and wetlands to ensure that there is a mutual understanding of all terms and conditions contained within the Department of the Army permit. The Permittee shall schedule the preconstruction meeting for a time frame when the Corps and NCDWR Project Managers can attend. The Permittee shall invite the Corps and NCDWR Project Managers a minimum of thirty (30) days in advance of the scheduled meeting in order to provide those individuals with ample opportunity to schedule and participate in the required meeting. The thirty (30) day requirement can be waived with the concurrence of the Corps.

7. NOTIFICATION OF CONSTRUCTION COMMENCEMENT AND COMPLETION: The Permittee shall notify the U.S. Army Corps of Engineers in writing prior to beginning the work authorized by this permit and again upon completion of the work authorized by this permit.

8. REPORTING ADDRESS: All reports, documentation, and correspondence required by the conditions of this permit shall be submitted to the following: U.S. Army Corps of Engineers, Wilmington District; Raleigh Regulatory Field Office, Attn: Eric Alsmeyer; 3331 Heritage Trade Drive, Suite 105; Wake Forest, NC 27587, or eric.c.alsmeyer@usace.army.mil The Permittee shall reference the following permit number, SAW-2010-00653, on all submittals.

9. PERMIT REVOCATION: The Permittee, upon receipt of a notice of revocation of this permit or upon its expiration before completion of the work will, without expense to the United States and in such time and manner as the Secretary of the Army or his authorized representative may direct, restore the water or wetland to its pre-project condition.

SPECIAL CONDITIONS
Action ID SAW-2010-00653
NCDOT; TIPs R-2566B and R-2566BA; NC 105

10. REPORTING VIOLATIONS: Violation of these permit conditions or violation of Section 404 of the Clean Water Act shall be reported to the Corps in writing and by telephone at: 919.554.4884, extension 23, within 24 hours of the Permittee's discovery of the violation.

11. ENDANGERED SPECIES ACT: The Permittee shall implement all necessary measures to ensure the authorized activity does not kill, injure, capture, harass, or otherwise harm any federally-listed threatened or endangered species. While accomplishing the authorized work, if the Permittee discovers or observes an injured or dead threatened or endangered species, the U.S. Army Corps of Engineers, Wilmington District; Raleigh Regulatory Field Office, Attn: Eric Alsmeyer; 3331 Heritage Trade Drive, Suite 105; Wake Forest, NC 27587, at 919.554.4884, extension 23, or eric.c.alsmeyer@usace.army.mil will be immediately notified to initiate the required Federal coordination.

The U.S. Fish and Wildlife Service's (USFWS's) Programmatic Biological Opinion (BO) titled "Northern Long-eared Bat (NLEB) Programmatic Biological Opinion for North Carolina Department of Transportation (NCDOT) Activities in Eastern North Carolina (Divisions 1-8)," dated March 25, 2015, and adopted on April 10, 2015, contains mandatory terms and conditions to implement the reasonable and prudent measures that are associated with "incidental take" that are specified in the BO.

Your authorization under this Department of the Army permit is conditional upon your compliance with all the mandatory terms and conditions associated with incidental take of the BO, which terms and conditions are incorporated by reference in this permit.

Failure to comply with the terms and conditions associated with incidental take of the BO, where a take of the listed species occurs, would constitute an unauthorized take, and it would also constitute non-compliance with your Department of the Army permit. The USFWS is the appropriate authority to determine compliance with the terms and conditions of its BO, and with the ESA.

12. MAINTAIN FLOWS AND CIRCULATION PATTERNS OF WATERS: Except as specified in the plans attached to this permit, no excavation, fill or mechanized land-clearing activities shall take place at any time in the construction or maintenance of this project, in such a manner as to impair normal flows and circulation patterns within waters or wetlands or to reduce the reach of waters and/or wetlands.

13. SEDIMENT AND EROSION CONTROL:

1) During the clearing phase of the project, heavy equipment shall not be operated in surface waters or stream channels. Temporary stream crossings will be used to access the opposite sides of stream channels.

All temporary diversion channels and stream crossings will be constructed of non-erodible materials. Grubbing of riparian vegetation will not occur until immediately before construction begins on a given segment of stream channel.

SPECIAL CONDITIONS
Action ID SAW-2010-00653
NCDOT; TIPs R-2566B and R-2566BA; NC 105

2) No fill or excavation impacts for the purposes of sedimentation and erosion control shall occur within jurisdictional waters, including wetlands, unless the impacts are included on the plan drawings and specifically authorized by this permit. This includes, but is not limited to, sediment control fences and other barriers intended to catch sediment losses.

3) The Permittee shall remove all sediment and erosion control measures placed in waters and/or wetlands, and shall restore natural grades on those areas, prior to project completion.

4) The Permittee shall use appropriate sediment and erosion control practices which equal or exceed those outlined in the most recent version of the “North Carolina Sediment and Erosion Control Planning and Design Manual” to ensure compliance with the appropriate turbidity water quality standard. Erosion and sediment control practices shall be in full compliance with all specifications governing the proper design, installation and operation and maintenance of such Best Management Practices in order to ensure compliance with the appropriate turbidity water quality standards. This shall include, but is not limited to, the immediate installation of silt fencing or similar appropriate devices around all areas subject to soil disturbance or the movement of earthen fill, and the immediate stabilization of all disturbed areas. Additionally, the project shall remain in full compliance with all aspects of the Sedimentation Pollution Control Act of 1973 (North Carolina General Statutes Chapter 113A Article 4). Adequate sedimentation and erosion control measures shall be implemented prior to any ground disturbing activities to minimize impacts to downstream aquatic resources. These measures shall be inspected and maintained regularly, especially following rainfall events. All fill material shall be adequately stabilized at the earliest practicable date to prevent sediment from entering into adjacent waters or wetlands.

14. CLEAN FILL: The Permittee shall use only clean fill material for this project. The fill material shall be free of items such as trash, construction debris, metal and plastic products, and concrete block with exposed metal reinforcement bars. Soils used for fill shall not be contaminated with any toxic substance in concentrations governed by Section 307 of the Clean Water Act. Unless otherwise authorized by this permit, all fill material placed in waters or wetlands shall be generated from an upland source.

15. WATER CONTAMINATION: All mechanized equipment shall be regularly inspected and maintained to prevent contamination of waters and wetlands from fuels, lubricants, hydraulic fluids, or other toxic materials. In the event of a spill of petroleum products or any other hazardous waste, the Permittee shall immediately report it to the N.C. Division of Water Resources at (919) 733-3300 or (800) 858-0368 and provisions of the North Carolina Oil Pollution and Hazardous Substances Control Act shall be followed.

SPECIAL CONDITIONS
Action ID SAW-2010-00653
NCDOT; TIPs R-2566B and R-2566BA; NC 105

16. IN-WATER WORK MORATORIA: To avoid adverse impacts to the Eastern Hellbender in the project area, no in-water work shall be conducted from April 1 to November 1, within the Watauga River and Laurel Fork, and adjacent wetlands that have an active connection to these tributaries during periods of inundation. To avoid adverse impacts to reproducing trout in the project area, no in-water work shall be conducted from October 15 to April 15, within perennial tributaries, other than the Watauga River and Laurel Fork, and their adjacent wetlands that have an active connection to these tributaries during periods of inundation.

17. AQUATIC LIFE MOVEMENT: No activity may substantially disrupt the necessary life cycle movements of those species of aquatic life indigenous to the waterbody, including those species that normally migrate through the area. All discharges of dredged or fill material within waters of the United States shall be designed and constructed to maintain low flows to sustain the movement of aquatic species.

18. PROHIBITIONS ON CONCRETE: The Permittee shall take measures necessary to prevent live or fresh concrete, including bags of uncured concrete, from coming into contact with any water in or entering into waters of the United States. Water inside coffer dams or casings that has been in contact with concrete shall only be returned to waters of the United States when it no longer poses a threat to aquatic organisms (concrete is set and cured).

19. COMPENSATORY MITIGATION: In order to compensate for impacts associated with this permit, mitigation shall be provided in accordance with the provisions outlined on the most recent version of the attached Compensatory Mitigation Responsibility Transfer Form. The requirements of this form, including any special conditions listed on this form, are hereby incorporated as special conditions of this permit.

20. CULVERTS:

1) Unless otherwise requested in the application and depicted on the approved permit plans, culverts greater than 48 inches in diameter shall be buried at least one foot below the bed of the stream. Culverts 48 inches in diameter and less shall be buried or placed on the stream bed as practicable and appropriate to maintain aquatic passage, and every effort shall be made to maintain existing channel slope. The bottom of the culvert shall be placed at a depth below the natural stream bottom to provide for passage during drought or low flow conditions. Culverts shall be designed and constructed in a manner that minimizes destabilization and head cutting.

2) Measures shall be included in the culvert construction/installation that will promote the safe passage of fish and other aquatic organisms. The dimension, pattern, and profile of the stream above and below a culvert or pipe shall not be modified by widening the stream channel or by reducing the depth of the stream in connection with the construction activity. The width, height, and gradient of a proposed opening shall be such as to pass the average historical low flow and spring flow without adversely altering flow velocity. Spring flow should be determined from gauge data, if available. In the absence of such data, bankfull flow can be used as a comparable level.

SPECIAL CONDITIONS
Action ID SAW-2010-00653
NCDOT; TIPs R-2566B and R-2566BA; NC 105

3) The Permittee shall implement all reasonable and practicable measures to ensure that equipment, structures, fill pads, work, and operations associated with this project do not adversely affect upstream and/or downstream reaches. Adverse effects include, but are not limited to, channel instability, flooding, and/or stream bank erosion. The Permittee shall routinely monitor for these effects, cease all work when detected, take initial corrective measures to correct actively eroding areas, and notify this office immediately. Permanent corrective measures may require additional authorization by the U.S. Army Corps of Engineers.

4) Culverts placed within wetlands must be installed in a manner that does not restrict the flows and circulation patterns of waters of the United States. Culverts placed across wetland fills purely for the purposes of equalizing surface water shall not be buried, but the culverts must be of adequate size and/or number to ensure unrestricted transmission of water.

21. TEMPORARY FILLS: Within thirty (30) days of the date of completing the authorized work, the Permittee shall remove all temporary fills in waters of the United States and restore the affected areas to pre-construction contours and elevations. The affected areas shall be re-vegetated with native, non-invasive vegetation as necessary to minimize erosion and ensure site stability.

End Special Conditions – SAW-2010-00653

U.S. ARMY CORPS OF ENGINEERS
Wilmington District
Compensatory Mitigation Responsibility Transfer Form

Permittee: NCDOT

Project Name: TIP R-2566; Section BA/NC105/DIV11

Action ID: SAW-2010-00653

County: Watauga

Instructions to Permittee: The Permittee must provide a copy of this form to the Mitigation Sponsor, either an approved Mitigation Bank or the North Carolina Division of Mitigation Services (NCDMS), who will then sign the form to verify the transfer of the mitigation responsibility. Once the Sponsor has signed this form, it is the Permittee's responsibility to ensure that to the U.S. Army Corps of Engineers (USACE) Project Manager identified on page two is in receipt of a signed copy of this form before conducting authorized impacts, unless otherwise specified below. If more than one mitigation Sponsor will be used to provide the mitigation associated with the permit, or if the impacts and/or the mitigation will occur in more than one 8-digit Hydrologic Unit Code (HUC), multiple forms will be attached to the permit, and the separate forms for each Sponsor and/or HUC must be provided to the appropriate mitigation Sponsors.

Instructions to Sponsor: The Sponsor must verify that the mitigation requirements (credits) shown below are available at the identified site. By signing below, the Sponsor is accepting full responsibility for the identified mitigation, regardless of whether or not they have received payment from the Permittee. Once the form is signed, the Sponsor must update the bank ledger and provide a copy of the signed form and the updated bank ledger to the Permittee, the USACE Project Manager, and the Wilmington District Mitigation Office (see contact information on page 2). The Sponsor must also comply with all reporting requirements established in their authorizing instrument.

Permitted Impacts and Compensatory Mitigation Requirements

Permitted Impacts Requiring Mitigation*:

8-digit HUC and Basin: 06010103, Watauga River Basin

Stream Impacts (linear feet)			Wetland Impacts (acres)			
Warm	Cool	Cold	Riparian Riverine	Riparian Non-Riverine	Non-Riparian	Coastal
		203				

*If more than one mitigation sponsor will be used for the permit, only include impacts to be mitigated by this sponsor.

Compensatory Mitigation Requirements:

8-digit HUC and Basin: 06010103, Watauga River Basin

Stream Mitigation (credits)			Wetland Mitigation (credits)			
Warm	Cool	Cold	Riparian Riverine	Riparian Non-Riverine	Non-Riparian	Coastal
		406				

Mitigation Site Debited: NCDMS

(List the name of the bank to be debited. For umbrella banks, also list the specific site. For NCDMS, list NCDMS. If the NCDMS acceptance letter identifies a specific site, also list the specific site to be debited).

Section to be completed by the Mitigation Sponsor

Statement of Mitigation Liability Acceptance: I, the undersigned, verify that I am authorized to approve mitigation transactions for the Mitigation Sponsor shown below, and I certify that the Sponsor agrees to accept full responsibility for providing the mitigation identified in this document (see the table above), associated with the USACE Permittee and Action ID number shown. I also verify that released credits (and/or advance credits for NCDMS), as approved by the USACE, are currently available at the mitigation site identified above. Further, I understand that if the Sponsor fails to provide the required compensatory mitigation, the USACE Wilmington District Engineer may pursue measures against the Sponsor to ensure compliance associated with the mitigation requirements.

Mitigation Sponsor Name: _____

Name of Sponsor's Authorized Representative: _____

Signature of Sponsor's Authorized Representative

Date of Signature

USACE Wilmington District
Compensatory Mitigation Responsibility Transfer Form, Page 2

Conditions for Transfer of Compensatory Mitigation Credit:

- Once this document has been signed by the Mitigation Sponsor and the USACE is in receipt of the signed form, the Permittee is no longer responsible for providing the mitigation identified in this form, though the Permittee remains responsible for any other mitigation requirements stated in the permit conditions.
- Construction within jurisdictional areas authorized by the permit identified on page one of this form can begin only after the USACE is in receipt of a copy of this document signed by the Sponsor, confirming that the Sponsor has accepted responsibility for providing the mitigation requirements listed herein. For authorized impacts conducted by the North Carolina Department of Transportation (NCDOT), construction within jurisdictional areas may proceed upon permit issuance; however, a copy of this form signed by the Sponsor must be provided to the USACE within 30 days of permit issuance. NCDOT remains fully responsible for the mitigation until the USACE has received this form, confirming that the Sponsor has accepted responsibility for providing the mitigation requirements listed herein.
- Signed copies of this document must be retained by the Permittee, Mitigation Sponsor, and in the USACE administrative records for both the permit and the Bank/ILF Instrument. It is the Permittee's responsibility to ensure that the USACE Project Manager (address below) is provided with a signed copy of this form.
- If changes are proposed to the type, amount, or location of mitigation after this form has been signed and returned to the USACE, the Sponsor must obtain case-by-case approval from the USACE Project Manager and/or North Carolina Interagency Review Team (NCIRT). If approved, higher mitigation ratios may be applied, as per current District guidance and a new version of this form must be completed and included in the USACE administrative records for both the permit and the Bank/ILF Instrument.

Comments/Additional Conditions:

This form is not valid unless signed below by the USACE Project Manager and by the Mitigation Sponsor on Page 1. *Once signed, the Sponsor should provide copies of this form along with an updated bank ledger to: 1) the Permittee, 2) the USACE Project Manager at the address below, and 3) the Wilmington District Mitigation Office, Attn: Todd Tugwell, 3331 Heritage Trade Drive, Suite 105, Wake Forest, NC 27587 (email: todd.tugwell@usace.army.mil).* Questions regarding this form or any of the permit conditions may be directed to the USACE Project Manager below.

USACE Project Manager: Eric Alsmeyer

USACE Field Office: Raleigh Regulatory Field Office
US Army Corps of Engineers
3331 Heritage Trade Drive, Suite 105
Wake Forest, NC 27587

Email: eric.c.alsmeyer@usace.army.mil


USACE Project Manager Signature

November 6, 2019

Date of Signature

Current Wilmington District mitigation guidance, including information on mitigation ratios, functional assessments, and mitigation bank location and availability, and credit classifications (including stream temperature and wetland groupings) is available at <http://ribits.usace.army.mil>.

Page 2 of 2

The Wilmington District is committed to providing the highest level of support to the public. To help us ensure we continue to do so, please complete the Customer Satisfaction Survey located at our website at <http://regulatory.usacesurvey.com/> to complete the survey online.

ROY COOPER
Governor

MICHAEL S. REGAN
Secretary

LINDA CULPEPPER
Director



June 19, 2019

Mr. Philip S. Harris, III, P.E., CPM
Natural Environment Section Head
Project Development and Environmental Analysis
North Carolina Department of Transportation
1598 Mail Service Center
Raleigh, North Carolina, 27699-1598

Subject: 401 Water Quality Certification Pursuant to Section 401 of the Federal Clean Water Act with
ADDITIONAL CONDITIONS for proposed improvements to NC 105 and Bridge No. 5 replacement over
the Watauga River in Watauga County; WBS 37512.1.1; TIPs R-2566BA and R-2566B.
NCDWR Project No. 20190397

Dear Mr. Harris:

Attached hereto is a copy of Certification No.004194 issued to The North Carolina Department of Transportation (NCDOT) dated June 19, 2019.

If we can be of further assistance, do not hesitate to contact us.

Sincerely,

DocuSigned by:

Amy Chapman

9C9886312DCD474...
Linda Culpepper, Director
Division of Water Resources

Attachments

Electronic copy only distribution:

Steve Kichefsky, US Army Corps of Engineers, Asheville Field Office
Kevin Hining, Division 11 Environmental Officer
Carla Dagnino, NC Department of Transportation
Chris Militscher, US Environmental Protection Agency
Claire Ellwanger, US Fish and Wildlife Service
Marla Chambers, NC Wildlife Resources Commission
Beth Harmon, Division of Mitigation Services
File Copy



North Carolina Department of Environmental Quality | Division of Water Resources
512 North Salisbury Street | 1617 Mail Service Center | Raleigh, North Carolina 27699-1617
919.707.9000

401 Water Quality Certification Pursuant to Section 401 of the Federal Clean Water Act with ADDITIONAL CONDITIONS

THIS CERTIFICATION is issued in conformity with the requirements of Section 401 Public Laws 92-500 and 95-217 of the United States and subject to the North Carolina Division of Water Resources (NCDWR) Regulations in 15 NCAC 2H. This certification authorizes the NCDOT to impact 0.57 acres (preliminary for B-Section; no wetland impacts for BA Section) of jurisdictional wetlands; 4,099 linear feet of jurisdictional streams (preliminary for B-Section); and, 600 linear feet of jurisdictional streams for BA Section (203 permanent and 397 temporary) in Watauga County. The project shall be constructed pursuant to the application dated received March 29, 2019 (revised April 17, 2019). The authorized impacts are as described below:

Stream Impacts in the Watauga River Basin R-2566BA; Final

Site	Permanent Fill in Perennial Stream (linear ft)	Temporary Fill in Perennial Stream (linear ft)	Total Stream Impact (linear ft)	Stream Impacts Requiring Mitigation (linear ft)
	Culvert			
1	100	10	110	-
2	-	274	274	-
3	-	70	70	-
4	73	22	95	-
5	30	21	51	-
Total	203	397	600	-

Total Stream Impact for Section BA: 600 linear feet

Stream Impacts in the Watauga River Basin R-2566B; Preliminary

Site	Permanent Fill in Perennial Stream (linear ft)	Temporary Fill in Perennial Stream (linear ft)	Total Stream Impact (linear ft)	Stream Impacts Requiring Mitigation (linear ft)
1A, B	300	-	300	300
1	163	-	163	-
4, 6, 8	479	-	479	479
5, 7	169	-	169	-
9	163	-	163	-
10	77	-	77	-
11	132	-	132	-

Stream Impacts in the Watauga River Basin R-2566B; Preliminary

Site	Permanent Fill in Perennial Stream (linear ft)	Temporary Fill in Perennial Stream (linear ft)	Total Stream Impact (linear ft)	Stream Impacts Requiring Mitigation (linear ft)
12	93	-	93	-
14, 15	66	-	66	-
16	135	-	135	-
18	42	-	42	-
19	90	-	90	-
20	42	-	42	-
21	242	-	242	-
25	217	-	217	-
26	152	-	152	-
28	50	-	50	-
29	54	-	54	-
30	73	-	73	-
31	52	-	52	-
32	130	-	130	-
34	115	-	115	-
35	268	-	268	-
36, 37	150	-	150	-
38	59	-	59	-
39	40	-	40	-
42	98	-	98	-
Additional	200	-	200	-
Total	4,099	-	4,099	779

Total Preliminary Stream Impacts for Project: 4,099 linear feet

Wetland Impacts in the Watauga River Basin (Riverine) Preliminary; B Section

Site	Fill (ac)	Excavation (ac)	Mechanized Clearing (ac)	Hand Clearing (ac)	Total Wetland Impact (ac)
1A	0.09	-	-	-	0.09
1B	<0.01	-	-	-	<0.01
2	0.02	-	-	-	0.02
3	0.04	-	-	-	0.04
7	0.02	-	-	-	0.02
10	0.01	-	-	-	0.01
11	0.02	-	-	-	0.02
13	0.03	-	-	-	0.03
17	0.08	-	-	-	0.08
20	0.06	-	-	-	0.06
27	0.03	-	-	-	0.03
32	0.03	-	-	-	0.03
33	<0.01	-	-	-	<0.01
35	0.02	-	-	-	0.02
40	<0.01	-	-	-	<0.01
Additional	0.10	-	-	-	0.10
Total	0.57	-	-	-	0.57

Total Preliminary Wetland Impact for Project: 0.57 acres.

The application provides adequate assurance that the discharge of fill material into the waters of the Watauga River Basin in conjunction with the proposed development will not result in a violation of applicable Water Quality Standards and discharge guidelines. Therefore, the State of North Carolina certifies that this activity will not violate the applicable portions of Sections 301, 302, 303, 306, 307 of PL 92-500 and PL 95-217 if conducted in accordance with the application and conditions hereinafter set forth.

This approval is only valid for the purpose and design that you submitted in your application dated received March 29, 2019 (revised April 17, 2019). Should your project change, you are required to notify the NCDWR and submit a new application. If the property is sold, the new owner must be given a copy of this Certification and approval letter and is thereby responsible for complying with all the conditions. If any additional wetland impacts, or stream impacts, for this project (now or in the future) exceed one acre or 300 linear feet, respectively, additional compensatory mitigation may be required as described in 15A NCAC 2H .0506 (h) (6) and (7). For this approval to remain valid, you are required to comply with all the conditions listed below. In addition, you should obtain all

other federal, state or local permits before proceeding with your project including (but not limited to) Sediment and Erosion control, Coastal Stormwater, Non-discharge and Water Supply watershed regulations. This Certification shall expire on the same day as the expiration date of the corresponding Corps of Engineers Permit.

Condition(s) of Certification:

Specific Conditions

1. When final design plans are completed for R-2566B, a modification to the 401 Water Quality Certification shall be submitted with five copies and fees to the NC Division of Water Resources. Final designs shall reflect all appropriate avoidance, minimization, and mitigation for impacts to wetlands, streams, and other surface waters. No construction activities that impact any wetlands, streams, surface waters located in R-2566B shall begin until after the permittee applies for and receives a written modification of the 401 Water Quality Certification from the NC Division of Water Resources. [15A NCAC 02H. 0506(b)]
2. Compensatory mitigation for 779 linear feet of impact to streams for the B Section is required. We understand that you have chosen to perform compensatory mitigation for impacts to streams through the North Carolina Division of Mitigation Service (DMS) (formerly NCEEP), and that the DMS has agreed to implement the mitigation for the project. The DMS has indicated in a letter dated April 12, 2019 that they will assume responsibility for satisfying the federal Clean Water Act compensatory mitigation requirements for the above-referenced project, in accordance with the DMS Mitigation Banking Instrument signed July 28, 2010.
3. NCDOT shall be in compliance with the NCS000250 issued to the NCDOT, including the applicable requirements of NCG010000. Please note the extra protections for the sensitive watersheds. [15A NCAC 02B.0224 and 0225]
4. NCDOT will adhere to a trout moratorium for tributaries to the Watauga River and Laurel Fork during October 15 through April 15 prohibiting in-water work and land disturbance within 25 feet of the stream. [15A NCAC 02H .0506(b)(2) and 15A NCAC 04B.0125]
5. NCDOT will coordinate with NCWRC regarding rescue and relocation of the eastern hellbender prior to causeway installation to determine if river conditions will facilitate the task. NCDOT will adhere to an in-water moratorium from April 1 through November 1 to protect early life stages and spawning activities of the hellbender. [15A NCAC 02H .0506(b)(2) and 15A NCAC 04B.0125]
6. Bridge demolition and construction must be accomplished in strict compliance with the most recent version of NCDOT's Best Management Practices for Construction and Maintenance Activities. [15A NCAC 02H .0507(d)(2) and 15A NCAC 02H .0506(b)(5)]
7. No drill slurry or water that has been in contact with uncured concrete shall be allowed to enter surface waters. This water shall be captured, treated, and disposed of properly. [15A NCAC 02H .0506(b)(3)]
8. Post-construction removal of any temporary bridge structures/workpads must return the project site to its preconstruction contours and elevations. The impacted areas shall be revegetated with appropriate native species. [15A NCAC 02H .0506(b)(2)]
9. Placement of culverts and other structures in open waters and streams, shall be placed below the elevation of the streambed by one foot for all culverts with a diameter greater than 48 inches, and 20 percent of the culvert diameter for culverts having a diameter less than 48 inches, to allow low flow passage of water and aquatic life. This requirement is waived if noted/shown on permit plans that burial will not occur. Design and placement of culverts and other structures including temporary erosion control measures shall not be conducted in a manner that may result in dis-equilibrium of wetlands or streambeds or banks, adjacent to or upstream and downstream of the above structures. The applicant is required to provide evidence that the equilibrium is being maintained if requested by the NCDWR. If this condition is unable to be met due to bedrock or other limiting features encountered during construction, please contact the NCDWR for guidance on how to proceed and to determine whether or not a permit modification will be required. [15A NCAC 02H.0506(b)(2)]

10. If concrete is used during construction, a dry work area shall be maintained to prevent direct contact between curing concrete and stream water. Water that inadvertently contacts uncured concrete shall not be discharged to surface waters due to the potential for elevated pH and possible aquatic life and fish kills. [15A NCAC 02B.0200]

General Conditions

1. The use of rip-rap above the Normal High Water Mark shall be minimized. Any rip-rap placed for stream stabilization shall be placed in stream channels in such a manner that it does not impede aquatic life passage. [15A NCAC 02H.0506(b)(2)]
2. The Permittee shall ensure that the final design drawings adhere to the permit and to the permit drawings submitted for approval. [15A NCAC 02H .0507(c) and 15A NCAC 02H .0506 (b)(2) and (c)(2)]
3. No rock, sand or other materials shall be dredged from the stream channel except where authorized by this certification. [15A NCAC 02H.0506(b)(3)]
4. Discharging hydroseed mixtures and washing out hydroseeders and other equipment in or adjacent to surface waters is prohibited. [15A NCAC 02H.0506(b)(3)]
5. The permittee and its authorized agents shall conduct its activities in a manner consistent with State water quality standards (including any requirements resulting from compliance with §303(d) of the Clean Water Act) and any other appropriate requirements of State and Federal law. If the NCDWR determines that such standards or laws are not being met (including the failure to sustain a designated or achieved use) or that State or federal law is being violated, or that further conditions are necessary to assure compliance, the NCDWR may reevaluate and modify this certification. [15A NCAC 02B.0200]
6. All fill slopes located in jurisdictional wetlands shall be placed at slopes no flatter than 3:1, unless otherwise authorized by this certification. [15A NCAC 02H.0506(b)(2)]
7. A copy of this Water Quality Certification shall be maintained on the construction site at all times. In addition, the Water Quality Certification and all subsequent modifications, if any, shall be maintained with the Division Engineer and the on-site project manager. [15A NCAC 02H .0507(c) and 15A NCAC 02H .0506 (b)(2) and (c)(2)]
8. The outside buffer, wetland or water boundary located within the construction corridor approved by this authorization shall be clearly marked by highly visible fencing or flagging prior to any land disturbing activities. Impacts to areas within the fencing are prohibited unless otherwise authorized by this certification. [15A NCAC 02H.0501 and .0502]
9. The issuance of this certification does not exempt the Permittee from complying with any and all statutes, rules, regulations, or ordinances that may be imposed by other government agencies (i.e. local, state, and federal) having jurisdiction, including but not limited to applicable buffer rules, stormwater management rules, soil erosion and sedimentation control requirements, etc.
10. The Permittee shall report any violations of this certification to the Division of Water Resources within 24 hours of discovery. [15A NCAC 02B.0506(b)(2)]
11. Upon completion of the project (including any impacts at associated borrow or waste sites), the NCDOT Division Engineer (or appointee) shall complete and return the enclosed "Certification of Completion Form" to notify the NCDWR when all work included in the 401 Certification has been completed. [15A NCAC 02H.0502(f)]
12. Native riparian vegetation must be reestablished in the riparian areas within the construction limits of the project by the end of the growing season following completion of construction. [15A NCAC 02H.0506(b)(3) and (c)(3)]
13. There shall be no excavation from, or waste disposal into, jurisdictional wetlands or waters associated with this permit without appropriate modification. Should waste or borrow sites, or access roads to waste or borrow sites,

be located in wetlands or streams, compensatory mitigation will be required since that is a direct impact from road construction activities. [15A NCAC 02H.0506(b)(3) and (c)(3)]

14. Where placement of sediment and erosion control devices in wetlands and/or waters is unavoidable, they shall be removed, and the natural grade restored upon completion of the project. [15A NCAC 02H.0506(b)(3) and (c)(3)].
15. Erosion and sediment control practices must be in full compliance with all specifications governing the proper design, installation and operation and maintenance of such Best Management Practices in order to protect surface waters standards [15A NCAC 02H.0506(b)(3) and (c)(3)]:
 - a. The erosion and sediment control measures for the project must be designed, installed, operated, and maintained in accordance with the most recent version of the *North Carolina Sediment and Erosion Control Planning and Design Manual*.
 - b. The design, installation, operation, and maintenance of the sediment and erosion control measures must be such that they equal, or exceed, the requirements specified in the most recent version of the *North Carolina Sediment and Erosion Control Manual*. The devices shall be maintained on all construction sites, borrow sites, and waste pile (spoil) projects, including contractor-owned or leased borrow pits associated with the project.
 - c. For borrow pit sites, the erosion and sediment control measures must be designed, installed, operated, and maintained in accordance with the most recent version of the *North Carolina Surface Mining Manual*.
 - d. The reclamation measures and implementation must comply with the reclamation in accordance with the requirements of the Sedimentation Pollution Control Act.

Violations of any condition herein set forth may result in revocation of this Certification and may result in criminal and/or civil penalties. This Certification shall become null and void unless the above conditions are made conditions of the Federal 404 and/or Coastal Area Management Act Permit. This Certification shall expire upon the expiration of the 404 or CAMA permit.

If you wish to contest any statement in the attached Certification you must file a petition for an administrative hearing. You may obtain the petition form from the office of Administrative hearings. You must file the petition with the office of Administrative Hearings within sixty (60) days of receipt of this notice. A petition is considered filed when it is received in the office of Administrative Hearings during normal office hours. The Office of Administrative Hearings accepts filings Monday through Friday between the hours of 8:00am and 5:00pm, except for official state holidays. The original and one (1) copy of the petition must be filed with the Office of Administrative Hearings.

The petition may be faxed-providing the original and one copy of the document is received by the Office of Administrative Hearings within five (5) business days following the faxed transmission.

The mailing address for the Office of Administrative Hearings is:

Office of Administrative Hearings
6714 Mail Service Center
Raleigh, NC 27699-6714
Telephone: (919) 431-3000, Facsimile: (919) 431-3100

A copy of the petition must also be served on DEQ as follows:

Mr. Bill F. Lane, General Counsel
Department of Environmental Quality
1601 Mail Service Center

This the 19th day of June, 2019

DIVISION OF WATER RESOURCES

DocuSigned by:

Amy Chapman

9C9886312DCD474...

Linda Culpepper, Director

WQC No. 004194

ROY COOPER
Governor

MICHAEL S. REGAN
Secretary

LINDA CULPEPPER
Director



NORTH CAROLINA
Environmental Quality

NCDWR Project No.: _____ **County:** _____

Applicant: _____

Project Name: _____

Date of Issuance of 401 Water Quality Certification: _____

Certificate of Completion

Upon completion of all work approved within the 401 Water Quality Certification or applicable Buffer Rules, and any subsequent modifications, the applicant is required to return this certificate to the 401 Transportation Permitting Unit, North Carolina Division of Water Resources, 1617 Mail Service Center, Raleigh, NC, 27699-1617. This form may be returned to NCDWR by the applicant, the applicant's authorized agent, **or** the project engineer. It is not necessary to send certificates from all of these.

Applicant's Certification

I, _____, hereby state that, to the best of my abilities, due care and diligence was used in the observation of the construction such that the construction was observed to be built within substantial compliance and intent of the 401 Water Quality Certification and Buffer Rules, the approved plans and specifications, and other supporting materials.

Signature: _____ Date: _____

Agent's Certification

I, _____, hereby state that, to the best of my abilities, due care and diligence was used in the observation of the construction such that the construction was observed to be built within substantial compliance and intent of the 401 Water Quality Certification and Buffer Rules, the approved plans and specifications, and other supporting materials.

Signature: _____ Date: _____

Engineer's Certification

_____ Partial _____ Final

I, _____, as a duly registered Professional Engineer in the State of North Carolina, having been authorized to observe (periodically, weekly, full time) the construction of the project for the Permittee hereby state that, to the best of my abilities, due care and diligence was used in the observation of the construction such that the construction was observed to be built within substantial compliance and intent of the 401 Water Quality Certification and Buffer Rules, the approved plans and specifications, and other supporting materials.

Signature _____ Registration No. _____

Date _____



North Carolina Department of Environmental Quality | Division of Water Resources
512 North Salisbury Street | 1617 Mail Service Center | Raleigh, North Carolina 27699-1617
919.707.9000

JOHN F. AYERS, TRUST

JOHN F. AYERS, TRUST

THOMAS S. & FRANCES WHITE

DENNIS M. MCLURIN

BOBBY R. BROWN

BETTY P. COLEMAN

RETAIN & CLEAN OUT

CLASS B RIP RAP 2 TONS, 7 SY GEO

TEMPORARY WORKER

REMOVAL

MAXIMUM LIMITS OF BIOFILTRATION CONVEYANCE (NOT TO BE DESIGNED)

SHEET 4

SANDRA J. HIGGIN

The logo for Wether Engineering features a stylized 'W' composed of a solid black bar and a dashed black bar, positioned above the company name 'WETHER ENGINEERING' in a bold, sans-serif font. The entire logo is set against a dark grey background.

TRANSPORTATION PLANNING/DESIGN - BRIDGE/STRUCTURE DESIGN
CIVIL/SITE DESIGN - GIS/GPS - CONSTRUCTION OBSERVATION

PERMIT DRAWING SHEET 5 OF 9

**DENOTES IMPACTS IN
SURFACE WATER**

**DENOTES TEMPORARY
IMPACTS IN SURFACE WATER**

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

For more information, contact the Office of the Vice President for Research and the Office of the Vice President for Student Affairs.

SS

TEMPORARY WORKPA

The diagram shows a bridge structure with a central span of 150'. On each side, there is a 100' approach. The total length of the bridge is 180'. The diagram is labeled with 'L- (NC 105)' at the top left and '150' at the top right.


EXISTING TRAFFIC SIGNAL TO BE RETROFITTED

SEE SHT. 7 FOR -L- PROFILE
SEE SHT. 8 FOR -Y4- PROFILE
SEE SHT. 8 FOR -Y5- PROFILE
SEE SHTS. S-1 THRU S-2 FOR STRUCTURE PLANS
SEE SHT. 2A-4 FOR RETAINING WALL

PERMIT DRAWING SHEET 6 OF 9


S S

TS TS

DENOTES IMPACTS IN
SURFACE WATERDENOTES TEMPORARY
IMPACTS IN SURFACE WATER

PROJECT REFERENCE NO. R-2566BA
SHEET NO. 6
RW SHEET NO.
ROADWAY DESIGN ENGINEER

HYDRAULICS ENGINEER
CHARLES W. CONNOR, JR.

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

DOCUMENT NOT CONSIDERED FINAL
LESS ALL SIGNATURES COMPLETED

CHARLES W. CONNOR, JR.

DETAIL 6A
STANDARD 'V' DITCH
 (Not to Scale)

Natural ground

D

Natural ground

Min. D. = 1.5 Ft.

DETAIL 6B
STANDARD BASE DITCH
 (Not to Scale)

Natural Ground

Geotextile

Min. D. = 3 Ft.
 Min. d. = 3 Ft.
 B = 8 Ft.

When B is < 6.0'

of Liner = Class II Rip-Rap

—L— STA 171 +41@104 LT TO 171 +41@96 LT
 —L— STA 171 +99@113 LT TO 172 +03@95 LT

DETAIL 6C
TOE PROTECTION
(Not to Scale)

NATURAL GROUND

d

2:1 OR
FLATTER

FILL SLOPE

GEOTEXTILE

1 Ft.

Type of Liner = Class B Rip-Rap

\$ \$ D
S U

DENOTES IMPACTS IN
SURFACE WATER

**DENOTES TEMPORARY
IMPACTS IN SURFACE WATER**

Franklin Rd.
C. 27606
F. F-0377
351 8077
351 8107

PROJECT R
R-2


ROADWAY

ENGIN

DOCUMENT NOT CONSIDERED FINAL
LESS ALL SIGNATURES COMPLETED

CHARLES W. CONNOR, JR.

EE SHT. 8 FOR -L- PROFILE



WETLAND AND SURACE WATER IMPACTS SUMMARY

Site No.	Station (From/To)	Structure Size / Type	WETLAND IMPACTS					SURFACE WATER IMPACTS				
			Permanent Fill In Wetlands (ac)	Temp. Fill In Wetlands (ac)	Excavation in Wetlands (ac)	Mechanized Clearing in Wetlands (ac)	Hand Clearing in Wetlands (ac)	Permanent SW impacts (ac)	Temp. SW impacts (ac)	Existing Channel Impacts Permanent (ft)	Existing Channel Impacts Temp. (ft)	Natural Stream Design (ft)
1	158+60/158+72 LT	24" CSP						< 0.01	< 0.01	100	10	
2	162+93/165+13	Temporary Workpad							0.12		274	
2	164+12/164+70 RT	Biofiltration conveyance							0.01			
3	171+33/172+10	60" SSP							< 0.01		70	
4	171+39/171+72	60" SSP						0.01	< 0.01	73	22	
5	172+30/172+63 RT	60" SSP						< 0.01	< 0.01	30	21	
TOTALS*:								0.02	0.15	203	397	0

*Rounded totals are sum of actual impacts

NOTES:

<0.01 acres of Permanent SW impacts for bridge interior bent (drilled shafts) at 164+14.

Site2: Limit streamflow blockage to 50% at one time; Biofiltration conveyance linear impacts accounted for in workpad impacts

NC DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

3/25/2019

WATAUGA COUNTY

R-2566BA

37512.1.4

5/14/99

<i>-L-</i>		
PI Sta 69+03JII	PI Sta 77+25.46	PIs Sta 82+29.57
$\Delta = 15^{\circ}12' 35.3''$ (LT)	$\Delta = 15^{\circ}23' 55.6''$ (LT)	$\Theta_S = 1^{\circ}27' 13.6''$
$D = 2^{\circ}02' 46.6''$	$D = 1^{\circ}42' 37.2''$	$L_S = 170.00'$
$L = 743.29'$	$L = 900.34'$	$L_I = 113.34'$
$T = 373.84'$	$T = 456.20'$	$ST = 56.67'$
$R = 2,800.00'$	$R = 3,350.00'$	
$SE = 5\%$ (EXIST.)	$SE = 5\%$	
$DS = 65 MPH$	$DS = 70 MPH$	
$RO = 135'$	$RO = 170'$	

-YI-	
PI Sta II+55.36	PI Sta 2I+27.42
$\Delta = 92^\circ 59' 28.6''$ (LT)	$\Delta = 15^\circ 10' 18.8''$ (RT)
$D = 57^\circ 17' 44.8''$	$D = 2^\circ 51' 53.2''$
$L = 162.30'$	$L = 529.60'$
$T = 105.36'$	$T = 266.36'$
$R = 100.00'$	$R = 2,000.00'$
$SE = 4\%$	$SE = 3\%$
$DS = 20$ MPH	$DS = 30$ MPH
$RO = 20'$	$RO = 42'$

SEE SHEET 23 FOR -L- PROFILE
SEE SHEET 35 FOR -YI- PROFILE

A graphic scale bar consisting of a black horizontal line with a white checkered pattern on its left side. The pattern has 10 squares, with the first 5 being white and the next 5 being black. To the left of the pattern, the text '50'' is written above the line. To the right of the pattern, the text '0'' is written above the line. To the far right of the line, the text '100' is partially visible.


Kimley » Horn


PROJECT REFERENCE NO.		SHEET NO.
R-2566B		4
R/W SHEET NO.		
Roadway Design Engineer	Hydraulics Engineer	
<div style="border: 1px solid black; padding: 10px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>		
<hr/> DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED <hr/>		

REVISIONS

K:\CHL\PRJ\01036212 - (R-25666)Hydrolics PERMITS Environment\CADNR-25666B.rpt - psh-04900

4/11/2019





K:\CHL_PRJ\01036212 - (R-2566\Hydraulics\PERMITS_Environmental\CAD\VR-2566B_rdy_psh_06.dgn

REVISIONS


4/11/2019

5/14/99

<i>-L-</i>			
PI Sta 98+46.09	PIs Sta 103+27.02	PIs Sta 106+42.97	PI Sta 110+79.92
$\Delta = 44^\circ 18' 56.6''$ (LT)	$\theta_5 = 6^\circ 05' 39''$	$\theta_5 = 3^\circ 39' 25.8''$	$\Delta = 2^\circ 30' 12.6''$ (RT)
$D = 5^\circ 12' 31.3''$	$Ls = 234.00'$	$Ls = 240.00'$	$D = 3^\circ 02' 51.5''$
$L = 850.80'$	$LT = 156.09'$	$LT = 160.03'$	$L = 705.58'$
$T = 447.96'$	$ST = 78.08'$	$ST = 80.03'$	$T = 356.99'$
$R = 1,000.00'$			$R = 1,880.00'$
$SE = 6\%$			$SE = 6\%$
$DS = 55$			$DS = 65$
$RO = 234'$			$RO = 240'$

SEE SHEET 24 FOR -L- PROFILE

PROJECT REFERENCE NO.		SHEET NO.
R-2566B		6
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
<div style="border: 1px solid black; padding: 10px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		



5/14/99

SEE SHEET 24 FOR -L- PROFILE

PI Sta 110+79.92	PIs Sta 115+08.54
$\Delta = 21^{\circ}30'12.6''$ (RT)	$\Theta S = 3^{\circ}39'25.8''$
$D = 3^{\circ}02'51.5''$	$Ls = 24000'$
$L = 705.58'$	$LT = 160.03'$
$T = 356.99'$	$ST = 80.03'$
$R = 1880.00'$	
$SE = 6\%$	
$DS = 65$	
$RO = 240'$	

A graphic scale bar consisting of a black horizontal line with a white checkered pattern on its left side. The pattern is divided into two sections: the top section is labeled '50\' and the bottom section is labeled '0\' above the line. Below the line, the words 'GRAPHIC SCALE' are printed in capital letters.

PROJECT REFERENCE NO.		SHEET NO.
R-2566B		7
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
<div style="border: 1px solid black; padding: 5px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		



NAD 83/NSRS 2007

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

REVISIONS

CHL_PR\00\0362\2 - (R-2566)\Hydraulics\PERMITS_Environmental\CA\DR-2566B_rdy_dsh_07.dgn

4/11/2019



SEE SHEET 25 FOR -L- PROFILE

A graphic scale bar consisting of a black horizontal line with a white checkered pattern on its left side. The text '50\' is at the far left, '0\' is in the center, and '10\' is at the far right.


Kimley Horn

PROJECT REFERENCE NO.		SHEET NO.
R-2566B		8
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
<div style="border: 1px solid black; padding: 5px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>		
<hr/> DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED <hr/>		

REVISIONS


MATCHLINE -L- STA 122+00 (SEE SHEET 7)

28
28
30



K:\CHL_PRJ\01\036212 - (R-2566)\Hydraulics\PERMITS_Environmental\ADDR-2566B_rdy_psh_dgn

4/11/2019



5/14/99

<i>Pls Sta 140+52.37</i>	<i>Pls Sta 141+90.52</i>	<i>Pls Sta 143+28.71</i>	<i>Pls Sta 148+10.22</i>	<i>Pls Sta 150+76.47</i>
$\Theta_S = 3^{\circ} 49' 11.0''$	$\Delta = 3^{\circ} 42' 12.1'' (RT)$	$\Theta_S = 3^{\circ} 49' 11.0''$	$\Theta_S = 4^{\circ} 17' 49.9''$	$\Delta = 13^{\circ} 16' 58.0'' (LT)$
$L_S = 240.00'$	$D = 3^{\circ} 10' 59.2''$	$L_S = 240.00'$	$L_S = 240.00'$	$D = 3^{\circ} 34' 51.5''$
$LT = 160.04'$	$L = 116.34'$	$LT = 160.04'$	$LT = 160.05'$	$L = 370.93'$
$ST = 80.03'$	$T = 58.9'$	$ST = 80.03'$	$ST = 80.04'$	$T = 186.30'$
	$R = 1,800.00'$			$R = 1,600.00'$
	$SE = 6\%$			$SE = 6\%$
	$DS = 65$			$DS = 60$
	$RO = 240'$			$RO = 240'$

SEE SHEET 25 FOR -L- PROFILE

A graphic scale bar consisting of a black horizontal line with a white checkered pattern on its left side. The pattern has 10 squares, with the first 5 on the left labeled '50'' and the next 5 on the right labeled '0''. The total length of the scale bar is 100'.

Kimley Horn ©2018
200 SOUTH TRYON, SUITE 200
CHARLOTTE, N.C. 28202

PROJECT REFERENCE NO.		SHEET NO.
<i>R-2566B</i>		9
R/W SHEET NO.		
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER
<div style="border: 1px solid black; padding: 10px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>		
<hr/> <hr/> <hr/>		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		


MCLEAN INNOVATIVE HOMES, LLC

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

REVISIONS


K:\CHL_PRJ\01036212 - (R-2566)\H\drawings\PERMITS_Environmental\CADDR-2566B_dy_psh_0B.dgn

4/11/2019



- STREAM IMPACTS WITHIN SLOPE STAKES +25'•
- WETLAND IMPACTS WITHIN SLOPE STAKES +25'*
- POND IMPACTS WITHIN SLOPE STAKES +25'•
- SLOPE STAKES +25'

RELIMINARY IMPACTS



-L-


PI Sta 165+98.50
 $\Delta = 5^{\circ} 31' 45.6''$ (RT)
 $D = 4^{\circ} 14' 38.9''$
 $L = 1,214.13'$
 $T = 651.59'$
 $R = 1,350.00'$
 $SE = 6\%$
 $DS = 60$
 $RO = 324'$

SEE SHEET 26 FOR -L- PROFILE

REVISIONS

KACHL_PR\0010\036212 - (R-2566)Hydrolics\PERMITS\Environment\ADDYR-2566B_rdy_dsh_lndgn

4/11/2019



Kimley-Horn ©2011

200 SOUTH TRYON, SUITE 200
 CHARLOTTE, NC 28202

PROJECT REFERENCE NO.	SHEET NO.
R-2566B	11
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

K:\CHL_PR\0036212 - (R-2566)Hydraulics\PERMITS_Environmental\CA\DR-2566B_rdy_psh_18.dgn

4/11/2019

5/14/99

-L-			
Pl Sta 165+98.50	Pls Sta 172+69.20	Pls Sta 180+43.89	Pl Sta 182+60.47
$\Delta = 5^{\circ} 31' 45.6''$ (RT)	$\Theta s = 6^{\circ} 52' 31.8''$	$\Theta s = 6^{\circ} 37' 47.8''$	$\Delta = 8^{\circ} 52' 54.5''$ (LT)
$D = 4^{\circ} 14' 38.9''$	$Ls = 324.00'$	$Ls = 324.00'$	$D = 4^{\circ} 05' 33.2''$
$L = 1214.13'$	$LT = 216.16'$	$LT = 216.15'$	$L = 217.02'$
$T = 651.59'$	$ST = 1081.5'$	$ST = 1081.4'$	$T = 1087.3'$
$R = 1,350.00'$			$R = 1,400.00'$
$SE = 6\%$			$SE = 6\%$
$DS = 60$			$DS = 60$
$RO = 324'$			$RO = 324'$

SEE SHEET 27 FOR -L- PROFILE

NOTE:
THE PROPOSED ROW SHOWN BETWEEN STA. 158 + 59.82 TO STA. 171 + 63.75
IS ANTICIPATED TO BE ACQUIRED AS A PART OF THE R-2566BA PROJECT.

The logo for Kimley Horn. It features the word "Kimley" in a large, bold, black serif font. To the right of "Kimley" is a black square containing a white right-pointing arrowhead. To the right of the arrow is the word "Horn" in a bold, black sans-serif font. Below the main name is the address "200 SOUTH TRYON, SUITE 200" and "CHARLOTTE, N.C. 28202" in a smaller, black sans-serif font. In the bottom right corner of the logo, there is a small circular copyright symbol followed by the year "©2018".

PROJECT REFERENCE NO.	SHEET NO.
R-2566B	12
RW SHEET NO.	
Roadway Design Engineer	Hydraulics Engineer
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

RO = 324'

GRAPHIC SCALE

1' R = 1400'
SE = 6%
DS = 60

DO NOT USE FOR R/W ACC

DOCUMENT NOT CONSIDERED UNLESS ALL SIGNATURES

NAD 83 NSRS

110

100

90

80

70

60

50

40

30

20

10

0

100

200

300

400

500

600

700

800

900

1000

1100

1200

1300

1400

1500

1600

1700

1800

1900

2000

2100

2200

2300

2400

2500

2600

2700

2800

2900

3000

3100

3200

3300

3400

3500

3600

3700

3800

3900

4000

4100

4200

4300

4400

4500

4600

4700

4800

4900

5000

5100

5200

5300

5400

5500

5600

5700

5800

5900

6000

6100

6200

6300

6400

6500

6600

6700

6800

6900

7000

7100

7200

7300

7400

7500

7600

7700

7800

7900

8000

8100

8200

8300

8400

8500

8600

8700

8800

8900

9000

9100

9200

9300

9400

9500

9600

9700

9800

9900

10000

10100

10200

10300

10400

10500

10600

10700

10800

10900

11000

11100

11200

11300

11400

11500

11600

11700

11800

11900

12000

12100

12200

12300

12400

12500

12600

12700

12800

12900

13000

13100

13200

13300

13400

13500

13600

13700

13800

13900

14000

14100

14200

14300

14400

14500

14600

14700

14800

14900

15000

15100

15200

15300

15400

15500

15600

15700

15800

15900

16000

16100

16200

16300

16400

16500

16600

16700

16800

16900

17000

17100

17200

17300

17400

17500

17600

17700

17800

17900

18000

18100

18200

18300

18400

18500

18600

18700

18800

18900

19000

19100

19200

19300

19400

19500

19600

19700

19800

19900

20000

20100

20200

20300

20400

20500

20600

20700

20800

20900

21000

21100

21200

21300

21400

21500

21600

21700

21800

21900

22000

22100

22200

22300

22400

22500

22600

22700

22800

22900

23000

23100

23200

23300

23400

23500

23600

23700

23800

23900

24000

24100

24200

24300

24400

24500

24600

24700

24800

24900

25000

25100

25200

25300

25400

25500

25600

25700

25800

25900

26000

26100

26200

26300

26400

26500

26600

26700

26800

26900

27000

27100

27200

27300

27400

27500

27600

27700

27800

27900

28000

28100

28200

28300

28400

28500

28600

28700

28800

28900

29000

29100

29200

29300

29400

29500

29600

29700

29800

29900

30000

30100

30200

30300

30400

30500

30600

30700

30800

30900

31000

31100

31200

31300

31400

31500

31600

31700

31800

31900

32000

32100

32200

32300

32400

32500

32600

32700

32800

32900

33000

33100

33200

33300

33400

33500

33600

33700

33800

33900

34000

34100

34200

34300

34400

34500

34600

34700

34800

34900

35000

35100

35200

35300

35400

35500

35600

35700

35800

35900

36000

36100

36200

36300

36400

36500

36600

36700

36800

36900

37000

37100

37200

37300

37400

37500

37600

37700

37800

37900

38000

38100

38200

38300

38400

38500

38600

38700

38800

38900

39000

39100

39200

39300

39400

39500

39600

39700

39800

39900

40000

40100

40200

40300

40400

40500

40600

40700

40800

40900

41000

41100

41200

41300

41400

41500

41600

41700

41800

41900

42000

42100

42200

42300

42400

42500

42600

42700

42800

42900

43000

43100

43200

43300

43400

43500

43600

43700

43800

43900

44000

44100

44200

44300

44400

44500

44600

44700

44800

44900

45000

45100

45200

45300

45400

45500

45600

45700

45800

45900

46000

46100

46200

46300

46400

46500

46600

46700

46800

46900

47000

47100

47200

47300

47400

47500

47600

47700

47800

47900

48000

48100

48200

48300

48400

48500

48600

48700

48800

48900

49000

49100

49200

49300

49400

49500

49600

49700

49800

49900

50000

50100

50200

50300

50400

50500

50600

50700

50800

50900

51000

51100

51200

51300

51400

51500

51600

51700

51800

51900

52000

52100

52200

52300

52400

52500

52600

52700

52800

52900

53000

53100

53200

53300

53400

53500

53600

53700

53800

53900

54000

54100

54200

54300

54400

54500

54600

54700

54800

54900

55000

55100

55200

55300

55400

55500

55600

55700

55800

55900

56000

56100

56200

56300

56400

56500

56600

56700

56800

56900

57000

57100

57200

57300

57400

57500

57600

57700

57800

57900

58000

58100

58200

58300

58400

58500

58600

58700

58800

58900

59000

59100

59200

59300

59400

59500

59600

59700

59800

59900

60000

60100

60200

60300

60400

60500

60600

60700

60800

60900

61000

61100

61200

61300

61400

61500

61600

61700

61800

61900

62000

62100

62200

62300

62400

62500

62600

62700

62800

62900

63000

63100

63200

63300

63400

63500

63600

63700

63800

63900

64000

64100

64200

64300

64400

64500

64600

64700

64800

64900

65000

65100

65200

65300

65400

65500

65600

65700

65800

65900

66000

66100

66200

66300

66400

66500

66600

66700

66800

66900

67000

67100

67200

67300

67400

67500

67600

67700

67800

67900

68000

68100

68200

68300

68400

68500

68600

68700

68800

68900

69000

69100

69200

69300

69400

69500

69600

69700

69800

69900

70000

70100

70200

70300

70400

70500

70600

70700

70800

70900

71000

71100

71200

71300

71400

71500

71600

71700

71800

71900

72000

72100

72200

72300

72400

72500

72600

72700

72800

72900

73000

73100

73200

73300

73400

73500

73600

73700

73800

73900

74000

74100

74200

74300

74400

74500

74600


74700

74800

- STREAM IMPACTS WITHIN SLOPE STAKES +25'*
- WETLAND IMPACTS WITHIN SLOPE STAKES +25'*
- POND IMPACTS WITHIN SLOPE STAKES +25'*
- SLOPE STAKES +25'

RELIMINARY IMPACTS

<p style="text-align: center;">-L-</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33.33%;">PI Sta 182+60.47</td> <td style="width: 33.33%;">PIs Sta 184+76.90</td> </tr> <tr> <td>$\Delta = 8^{\circ} 52' 54.5'' (LT)$</td> <td>$\Theta_S = 6^{\circ} 37' 47.8''$</td> </tr> <tr> <td>$D = 4^{\circ} 05' 33.2''$</td> <td>$LS = 324.00'$</td> </tr> <tr> <td>$L = 217.02'$</td> <td>$LT = 216.55'$</td> </tr> <tr> <td>$T = 108.73'$</td> <td>$ST = 108.14'$</td> </tr> <tr> <td>$R = 1400.00'$</td> <td></td> </tr> <tr> <td>$SE = 6\%$</td> <td></td> </tr> <tr> <td>$DS = 60$</td> <td></td> </tr> <tr> <td>$RO = 324'$</td> <td></td> </tr> </table>	PI Sta 182+60.47	PIs Sta 184+76.90	$\Delta = 8^{\circ} 52' 54.5'' (LT)$	$\Theta_S = 6^{\circ} 37' 47.8''$	$D = 4^{\circ} 05' 33.2''$	$LS = 324.00'$	$L = 217.02'$	$LT = 216.55'$	$T = 108.73'$	$ST = 108.14'$	$R = 1400.00'$		$SE = 6\%$		$DS = 60$		$RO = 324'$		<p style="text-align: center;">-Y3-</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33.33%;">PI Sta 10+71.40</td> <td style="width: 33.33%;">PI Sta 11+47.94</td> <td style="width: 33.33%;">PI Sta 12+23.00</td> </tr> <tr> <td>$\Delta = 60^{\circ} 06' 59.4'' (LT)$</td> <td>$\Delta = 9^{\circ} 19' 55.6'' (RT)$</td> <td>$\Delta = 17^{\circ} 59' 12.5'' (RT)$</td> </tr> <tr> <td>$D = 133^{\circ} 14' 45.6''$</td> <td>$D = 8^{\circ} 18' 13.5''$</td> <td>$D = 47^{\circ} 44' 47.3''$</td> </tr> <tr> <td>$L = 451.2'$</td> <td>$L = 112.38'$</td> <td>$L = 37.67'$</td> </tr> <tr> <td>$T = 24.88'$</td> <td>$T = 56.32'$</td> <td>$T = 18.99'$</td> </tr> <tr> <td>$R = 43.00'$</td> <td>$R = 690.00'$</td> <td>$R = 120.00'$</td> </tr> <tr> <td>$SE = 3\%$</td> <td>$SE = EXIST$</td> <td>$SE = EXIST$</td> </tr> <tr> <td>$DS = 15$</td> <td>$DS = 15$</td> <td>$DS = EXIST$</td> </tr> <tr> <td>$RO = 39'$</td> <td>$RO = 39'$</td> <td>$RO = EXIST$</td> </tr> </table>	PI Sta 10+71.40	PI Sta 11+47.94	PI Sta 12+23.00	$\Delta = 60^{\circ} 06' 59.4'' (LT)$	$\Delta = 9^{\circ} 19' 55.6'' (RT)$	$\Delta = 17^{\circ} 59' 12.5'' (RT)$	$D = 133^{\circ} 14' 45.6''$	$D = 8^{\circ} 18' 13.5''$	$D = 47^{\circ} 44' 47.3''$	$L = 451.2'$	$L = 112.38'$	$L = 37.67'$	$T = 24.88'$	$T = 56.32'$	$T = 18.99'$	$R = 43.00'$	$R = 690.00'$	$R = 120.00'$	$SE = 3\%$	$SE = EXIST$	$SE = EXIST$	$DS = 15$	$DS = 15$	$DS = EXIST$	$RO = 39'$	$RO = 39'$	$RO = EXIST$	<p style="text-align: center;">SEE SHEET 27 FOR -L- PROFILE SEE SHEET 36 FOR -Y3- PROFILE</p>
PI Sta 182+60.47	PIs Sta 184+76.90																																														
$\Delta = 8^{\circ} 52' 54.5'' (LT)$	$\Theta_S = 6^{\circ} 37' 47.8''$																																														
$D = 4^{\circ} 05' 33.2''$	$LS = 324.00'$																																														
$L = 217.02'$	$LT = 216.55'$																																														
$T = 108.73'$	$ST = 108.14'$																																														
$R = 1400.00'$																																															
$SE = 6\%$																																															
$DS = 60$																																															
$RO = 324'$																																															
PI Sta 10+71.40	PI Sta 11+47.94	PI Sta 12+23.00																																													
$\Delta = 60^{\circ} 06' 59.4'' (LT)$	$\Delta = 9^{\circ} 19' 55.6'' (RT)$	$\Delta = 17^{\circ} 59' 12.5'' (RT)$																																													
$D = 133^{\circ} 14' 45.6''$	$D = 8^{\circ} 18' 13.5''$	$D = 47^{\circ} 44' 47.3''$																																													
$L = 451.2'$	$L = 112.38'$	$L = 37.67'$																																													
$T = 24.88'$	$T = 56.32'$	$T = 18.99'$																																													
$R = 43.00'$	$R = 690.00'$	$R = 120.00'$																																													
$SE = 3\%$	$SE = EXIST$	$SE = EXIST$																																													
$DS = 15$	$DS = 15$	$DS = EXIST$																																													
$RO = 39'$	$RO = 39'$	$RO = EXIST$																																													




Kimley Horn

200 SOUTH TRYON, SUITE 200

CHARLOTTE, N.C. 28202

PROJECT REFERENCE NO. R-2566B	SHEET NO. 13
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	




- STREAM IMPACTS WITHIN SLOPE STAKES +25'
- WETLAND IMPACTS WITHIN SLOPE STAKES +25'
- POND IMPACTS WITHIN SLOPE STAKES +25'
- SLOPE STAKES +25'
- PRELIMINARY IMPACTS

REVISIONS

CHL_PR\00\0362\2 - (R-2566)Hydraulics PERMITS Environmental\CA\DR-2566B_rdy_psh_4.dgn

4/11/2019



CHL_PRN/0103622 - (R-2566)HydraulicsPERMIT_S-Environmental CADDNR-2566B-rdy-psn/13.dwg

REVISIONS



4/11/2019

-L-		
Pls Sta 207+78.43	Pls Sta 212+59.36	Pls Sta 216+98.97
$\Theta_S = 9^{\circ} 21' 29.9''$	$\Delta = 46^{\circ} 07' 37.8''$ (RT)	$\Theta_S = 9^{\circ} 21' 29.9''$
$L_S = 294.00'$	$D = 6^{\circ} 21' 58.3''$	$L_S = 294.00'$
$L_T = 196.27'$	$L = 724.56'$	$L_T = 196.27'$
$ST = 98.25'$	$T = 383.21'$	$ST = 98.25'$
	$R = 900.00'$	
	$SE = 6\%$	
	$DS = 50$	
	$RO = 294'$	

-Y4-			
PI Sta 10+64.41	PI Sta 11+57.44	PI Sta 12+92.36	PI Sta 14+43.76
$\Delta = 63^{\circ} 03' 17.2''$ (RT)	$\Delta = 10^{\circ} 08' 30.7''$ (RT)	$\Delta = 3^{\circ} 02' 38.0''$ (RT)	$\Delta = 4^{\circ} 45' 11.9''$ (RT)
$D = 54^{\circ} 34' 02.7''$	$D = 12^{\circ} 08' 19.9''$	$D = 1^{\circ} 37' 56.5''$	$D = 28^{\circ} 38' 52.4''$
$L = 115.55'$	$L = 83.55'$	$L = 186.47'$	$L = 16.59'$
$T = 64.41'$	$T = 41.88'$	$T = 93.26'$	$T = 8.30'$
$R = 105.00'$	$R = 472.00'$	$R = 3,510.01'$	$R = 200,000'$ MOLL AND SCHEL
$SE = 4\%$	$SE = 4\%$	$SE = 4\%$	$SE = EXIST$
$DS = 30$	$DS = 30$	$DS = 30$	$DS = EXIST$
$RO = 52'$	$RO = 52'$	$RO = 52'$	$RO = EXIST$

SEE SHEET 28 FOR -L-50 PROFILE
SEE SHEET 37 FOR -Y4- P.E. [REDACTED]
GRAPHIC SCALE

PROJECT REFERENCE NO.		SHEET NO.
R-2566B		15
R/W SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
<div style="border: 1px solid black; padding: 10px; text-align: center;"> INCOMPLETE DO NOT USE FOR R/W ACQUISITION </div>		
<hr/> DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED <hr/>		



K:\CHL_PR\NOI036212 - (R-2566)\Hydraulics\PERMITS Environmental\CA001\R-2566B_rdy_psh_6.dgn

4/11/2019



-L-		
Pls Sta 223+68.86	Pls Sta 226+29J8	Pls Sta 228+87.83
$\Theta s = 7^{\circ} 01' 07.4''$	$\Delta = 15^{\circ} 25' 16.0'' (RT)$	$\Theta s = 7^{\circ} 01' 07.4''$
$Ls = 294.00'$	$D = 4^{\circ} 46' 28.7''$	$Ls = 294.00'$
$LT = 196J5'$	$L = 322.98'$	$LT = 196J5'$
$ST = 98J4'$	$T = 162.47'$	$ST = 98J4'$
	$R = 1,200.00'$	
	$SE = 6\%$	
	$DS = 55$	
	$RO = 294'$	


SEE SHEET 29 FOR -L- PROFILE

A graphic scale bar consisting of a black horizontal line with a white checkered pattern on its left side. The pattern has 10 squares, with the first 5 being white and the next 5 being black. Above the bar, the text "50'" is positioned above the first white square, and "0'" is positioned above the first black square. Below the bar, the words "GRAPHIC SCALE" are printed in capital letters.

The logo for Kimley Horn features the company name in a large, bold, sans-serif font. A stylized double arrow graphic is positioned between the two words. Below the logo, the company's address and phone number are listed in a smaller, bold, sans-serif font.

PROJECT REFERENCE NO.		SHEET NO.
<i>R-2566B</i>		<i>16</i>
R/W SHEET NO.		
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER
<div style="border: 1px solid black; padding: 10px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>		
<hr/> <hr/> <hr/>		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		





-L-

SEE SHEET 30 FOR -L- PROFILE

PI Sta 247+33.03 PI Sta 260+56.06
 $\Delta = 38^\circ 22' 19.3''$ (LT) $\Delta = 17^\circ 42' 28.3''$ (LT)
 $D = 1' 56' 32.0''$ $D = 2' 23' 14.4''$
 $L = 1,975.67'$ $L = 741.75'$
 $T = 1,026.49'$ $T = 373.85'$
 $R = 2,950.00'$ $R = 2,400.00'$
 $SE = 4\%$ $SE = 4\%$
 $DS = 55'$ $DS = 50'$
 $RO = 196'$ $RO = 196'$


50' 0' 100'
 GRAPHIC SCALE

Kimley-Horn ©2011
 200 SOUTH TRYON, SUITE 200
 CHARLOTTE, NC 28202

PROJECT REFERENCE NO.	HEET NO.
R-2566B	18
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

NAD 83 / NSRS 2007

REVISIONS



STREAM IMPACTS WITHIN SLOPE STAKES +25''
 WETLAND IMPACTS WITHIN SLOPE STAKES +25''
 POND IMPACTS WITHIN SLOPE STAKES +25''
 SLOPE STAKES +25'
 ■ PRELIMINARY IMPACTS

-L-

SEE SHEET 31 FOR -L- PROFILE

PI Sta 260+56.06 Pls Sta 264+89.30 Pls Sta 268+16.08 PI Sta 272+63.32
 $\Delta = 17^{\circ} 42' 28.3''$ (LT) $\Theta_S = 2^{\circ} 20' 22.5''$ $\Theta_S = 8^{\circ} 25' 20.9''$ $\Delta = 38^{\circ} 50' 53.3''$ (RT)
 D = 2' 23" 14.4" LS = 196.00' LS = 294.00' D = 5' 43" 46.5"
 L = 741.75' LT = 130.68' LT = 196.22' L = 672.21'
 T = 373.85' ST = 65.34' T = 349.36' T = 1,000.00'
 R = 2,400.00' SE = 6% DS = 50' RO = 294'
 SE = 4% DS = 50' RO = 196'

50' 0' 100'


GRAPHIC SCALE

Kimley-Horn ©2011
200 SOUTH TRYON, SUITE 200
CHARLOTTE, NC 28202

PROJECT REFERENCE NO.	HEET NO.
R-2566B	19
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

REVISIONS

MATCHLINE -L- STA 258+00 (SEE SHEET 18)



KACHL_PR_N01036212 - R-2566Hydro/PermitS_EnvironmentAddR-2566B_rdy_dsh_9.dwg

4/11/2019

- STREAM IMPACTS WITHIN SLOPE STAKES +25'
- WETLAND IMPACTS WITHIN SLOPE STAKES +25'
- POUND IMPACTS WITHIN SLOPE STAKES +25'
- SLOPE STAKES +25'
- PRELIMINARY IMPACTS

1

SEE SHEET 32 FOR -L- PROFILE

<i>PI Sta</i>	<i>272°+63.32'</i>	<i>PIs Sta</i>	<i>276°+84.37'</i>
Δ	$38^{\circ} 30' 53.3''$ (RT)	θ_S	$8^{\circ} 25' 20.9''$
<i>D</i>	$5^{\circ} 43' 46.5''$	<i>Ls</i>	$294.00'$
<i>L</i>	$672.2'$	<i>LT</i>	$196.22'$
<i>T</i>	$349.36'$	<i>ST</i>	$98.20'$
<i>R</i>	$1,000.00'$		
<i>SE</i>	6%		
<i>DS</i>	50		
<i>RO</i>	$294'$		


A graphic scale bar consisting of a black horizontal line with a white checkerboard pattern at its left end. The pattern is composed of four squares in a 2x2 grid. Above the bar, the text '50\' is on the left and '0\' is on the right, indicating a distance of 50 feet.

PROJECT REFERENCE NO.		SHEET NO.	
R-2566B		20	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
<div style="border: 1px solid black; padding: 5px; text-align: center;"> INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION </div>			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			

REVISIONS

K:\CHL_PRJ\01036212 - (R-2566\Hydraulics\PERMITS_Environmental\CAD\VR-2566B_rdy_psh_20.dgn

4/11/2019



R-2566B Preliminary Permit Impact Summary Table

Plan Sheet Number	Station (To/From)	Site Identifier	Wetland Impacts Within Slope Stakes +25' (Acres)	Stream Impacts Within Slope Stakes +25' (Linear Feet)	Pond Impacts Within Slope Stakes +25' (Acres)
4	68+74/70+81 -L- RT	1A	0.09		
4	68+74/70+81 -L- RT	1A		235	
4	71+87/72+15 -L- LT	1B	< 0.01		
4	71+27/71+51 -L- LT	1B		25	
4	71+78/72+36 -L- LT	1B		40	
4	13+48 RT/13+97 LT-Y1-	1		134	
4	76+68/76+83 -L- RT	1		29	
4	17+78/19+54 -Y1- RT	2	0.02		
4	17+78 LT/19+54 RT-Y1-	3	0.04		
5	86+77/87+09 -L- LT	4		62	
5	85+79/86+50 -L- RT	4		81	
5	88+84/89+09 -L- LT	5		51	
5	89+09/89+39 -L- RT	5		43	
5	17+97/18+08 -Y1- LT	6		38	
5	17+99/18+48 -Y1- RT	6		57	
5	10+95/11+16 -Y2- LT	7		47	
5	10+74/11+43 -Y2- RT	7	0.02	28	
5	26+37/28+99 -Y1- RT	8		241	
6	105+88/106+72 -L- LT	9		101	
6	106+69/107+23 -L- RT	9		62	
6	108+13/108+34 -L- LT	10		50	
7	110+43/111+03 -L- RT	10	0.01	27	
7	117+20/118+98 -L- LT	11	0.02		
7	118+51/119+34 -L- LT	11		132	
8	124+80/124+97 -L- LT	12		46	
8	124+48/124+85 -L- RT	12		47	
8	125+03/127+06 -L- LT	13	0.03		
8	126+68/126+87 -L- LT	14		26	
8	127+02/127+22 -L- LT	15		40	
8	129+76/130+23 -L- LT	16		76	
8	129+98/130+23 -L- RT	16		59	
8	130+64/130+97 -L- LT	17	< 0.01		
8	131+23/133+13 -L- LT	17	0.08		
8	131+90/132+08 -L- RT	18		42	
8	133+78/133+97 -L- LT	19		16	
8	133+88/134+02 -L- LT	19		19	
8	134+01/134+49 -L- RT	19		55	
9	144+93/146+67 -L- LT	20	0.06	42	
9	147+75/148+53 -L- LT	21		130	
9	147+65/148+31 -L- RT	21		112	
10	158+28/158+76 -L- LT	22		Impacts Previously Accounted for on R-2566BA Project	
12	171+33/171+72 -L- LT	23		Impacts Previously Accounted for on R-2566BA Project	
12	171+39/171+66 -L- RT	23		Impacts Previously Accounted for on R-2566BA Project	
12	171+84/172+10 -L- LT	24		Impacts Previously Accounted for on R-2566BA Project	
12	172+30/172+63 -L- RT	24		Impacts Previously Accounted for on R-2566BA Project	
13	190+05/190+36 -L- LT	25		72	
13	190+49/190+99 -L- RT	25		145	
14	197+08/197+23 -L- LT	26		50	
14	197+11/197+27 -L- RT	26		102	
14	200+98/202+38 -L- RT	27		190	
14	201+14/202+51 -L- RT	27	0.03		
14	201+94/202+50 -L- LT	27		58	
14	202+93/203+47 -L- LT	28		50	
15	218+97/219+00 -L- RT	29		9	
15	218+80/218+86 -L- LT	29		3	
15	218+93/218+99 -L- LT	29		42	
16	222+43/222+55 -L- LT	30		51	
16	222+81/222+91 -L- RT	30		22	
16	228+09/228+50 -L- LT	31		52	
17	239+13/239+81 -L- LT	32	0.03		
17	240+31/241+00 -L- RT	32		110	
17	240+48/240+94 -L- RT	32	< 0.01		
17	241+12/241+31 -L- RT	32		20	
17	242+69/243+37 -L- RT	33	< 0.01		
17/18	244+91/245+12 -L- LT	34		50	
18	244+99/245+63 -L- RT	34		65	
18	248+96/251+04 -L- RT	35		268	
18	249+79/250+59 -L- RT	35	0.02		
18	253+30/253+54 -L- LT	36		45	
18	254+09/254+25 -L- RT	37		105	
19	260+62/260+78 -L- LT	38		59	
19	263+85/263+97 -L- LT	39		40	
20	271+85/271+97 -L- LT	40	< 0.01		
20	274+19/274+63 -L- LT	41			< 0.01
21	287+86/288+13 -L- RT	42		60	
21	287+89/288+09 -L- LT	42		38	
TOTAL			0.47	3899	0.01